

STN	Elektromagnetická kompatibilita a záležitosti rádiového spektra (ERM). Pozemná pohyblivá služba. Rádiové zariadenia s integrálnou anténou určené prednostne na analógový prenos hovoru. Časť 1: Technické charakteristiky a meracie metódy.	STN EN 300 296-1 V1.4.1 87 0296
------------	--	---

Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech; Part 1: Technical characteristics and methods of measurement

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 12/13

Obsahuje: EN 300 296-1 V1.4.1:2013

ETSI EN 300 296-1 V1.4.1 (2013-08)



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Land Mobile Service;
Radio equipment using integral antennas
intended primarily for analogue speech;
Part 1: Technical characteristics and
methods of measurement**

Reference

REN/ERM-TGDMR-302

Keywords

analogue, mobile, PMR, radio, speech

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations	9
4 General	10
4.1 Selection of equipment for testing purposes.....	10
4.2 Mechanical and electrical design.....	10
4.2.1 General.....	10
4.2.2 Controls	10
4.2.3 Transmitter shut-off facility	10
4.2.4 Push-to-talk facility.....	10
5 Test conditions, power sources and ambient temperatures	10
5.1 Normal and extreme test conditions	10
5.2 Test power source.....	11
5.3 Normal test conditions.....	11
5.3.1 Normal temperature and humidity	11
5.3.2 Normal test power source	11
5.3.2.1 Mains voltage	11
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	11
5.3.2.3 Other power sources.....	11
5.4 Extreme test conditions	12
5.4.1 Extreme temperatures	12
5.4.2 Extreme test source voltages.....	12
5.4.2.1 Mains voltage	12
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	12
5.4.2.3 Power sources using other types of batteries.....	12
5.4.2.4 Other power sources.....	12
5.5 Procedure for tests at extreme temperatures	13
5.5.1 Procedure for equipment designed for continuous transmission.....	13
5.5.2 Procedure for equipment designed for intermittent transmission	13
6 General test conditions	13
6.1 Test signals.....	13
6.2 Receiver mute or squelch facility	14
6.3 Artificial antenna.....	14
6.4 Test sites and general arrangements for radiated measurements	14
6.5 Arrangement for test signals at the input of the transmitter	14
6.6 Receiver rated audio output power	14
6.7 Reference for degradation measurements.....	14
6.7.1 Definition.....	14
6.7.2 Procedures for measurements using the test fixture.....	15
6.7.3 Procedures for measurements using the test site.....	15
7 Technical characteristics of the transmitter	15
7.1 Frequency error	15
7.1.1 Definition.....	15
7.1.2 Method of measurement	16
7.1.3 Limits.....	16

7.2	Effective radiated power	16
7.2.1	Definition	16
7.2.2	Method of measurement	17
7.2.2.1	Maximum effective radiated power under normal test conditions	17
7.2.2.2	Average effective radiated power under normal test conditions	18
7.2.2.3	Method of measurements of maximum and average effective radiated power under extreme test conditions	19
7.2.3	Limits	19
7.3	Maximum permissible frequency deviation	20
7.3.1	Definition	20
7.3.2	Method of measurement	20
7.3.2.1	Maximum permissible frequency deviation	21
7.3.2.2	Response of the transmitter to modulation frequencies above 3 kHz	21
7.3.3	Limits	21
7.3.3.1	Maximum permissible frequency deviation	21
7.3.3.2	Response of the transmitter to modulation frequencies above 3 kHz	21
7.4	Adjacent and alternate channel power	22
7.4.1	Definition	22
7.4.2	Method of measurement	22
7.4.3	Limits	24
7.5	Radiated unwanted emissions in the spurious domain	24
7.5.1	Definition	24
7.5.2	Method of measurement	25
7.5.3	Limits	26
7.6	Voice Operated Transmitter	27
7.6.1	Definition	27
7.6.2	Method of measurement	27
7.6.3	Limits	27
7.7	Maximum transmission time	28
7.7.1	Definition	28
7.7.2	Method of measurement	28
7.7.3	Limits	28
8	Technical characteristics of the receiver	28
8.1	Average usable sensitivity (field strength, speech)	28
8.1.1	Definition	28
8.1.2	Methods of measurement	28
8.1.2.1	Method of measurement under normal test conditions	28
8.1.2.2	Method of measurement under extreme test conditions	30
8.1.3	Limits	30
8.2	Spurious radiations	31
8.2.1	Definition	31
8.2.2	Method of measurement	32
8.2.3	Limits	33
8.3	Co-channel rejection	34
8.3.1	Definition	34
8.3.2	Method of measurement	34
8.3.3	Limits	35
8.4	Adjacent channel selectivity	35
8.4.1	Definition	35
8.4.2	Method of measurement	35
8.4.3	Limits	36
8.5	Spurious response rejection	36
8.5.1	Definition	36
8.5.2	Method of measurement	37
8.5.2.1	Introduction to the method of measurement	37
8.5.2.2	Measurement arrangement	38
8.5.2.3	Method of the search	38
8.5.2.4	Measurement	39
8.5.3	Limits	40
8.6	Intermodulation response rejection	40
8.6.1	Definition	40

8.6.2	Method of measurement	40
8.6.3	Limits.....	41
8.6.3.1	Limits for low power equipment	41
8.6.3.2	Limits for other equipment.....	42
8.7	Blocking or desensitization	42
8.7.1	Definition.....	42
8.7.2	Method of measurement	42
8.7.3	Limits.....	43
9	Measurement uncertainty	44
Annex A (normative):	Radiated measurement.....	45
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	45
A.1.1	Anechoic chamber	45
A.1.2	Anechoic chamber with a conductive ground plane	46
A.1.3	Open Area Test Site (OATS)	47
A.1.4	Test antenna.....	48
A.1.5	Substitution antenna	48
A.1.6	Measuring antenna	49
A.2	Guidance on the use of radiation test sites	49
A.2.1	Verification of the test site	49
A.2.2	Preparation of the EUT.....	49
A.2.3	Power supplies to the EUT	49
A.2.4	Volume control setting for analogue speech tests	49
A.2.5	Range length.....	50
A.2.6	Site preparation	50
A.3	Coupling of signals.....	51
A.3.1	General	51
A.3.2	Data Signals.....	51
A.3.3	Speech and analogue signals	51
A.3.3.1	Acoustic coupler description.....	51
A.3.3.2	Calibration	52
A.4	Test fixture	52
A.4.1	Description	52
A.4.2	Calibration.....	53
A.4.3	Mode of use.....	53
Annex B (normative):	Specifications for adjacent channel power measurement arrangements.....	54
B.1	Power measuring receiver specification.....	54
B.1.1	General	54
B.1.2	IF filter	54
B.1.3	Oscillator and amplifier.....	56
B.1.4	Attenuation indicator.....	56
B.1.5	Level indicators	56
B.1.5.1	Rms level indicator	56
B.1.5.2	Peak level indicator.....	56
B.2	Spectrum analyzer for adjacent channel power measurement.....	56
Annex C (normative):	Spectrum Analyzer	58
C.1	Adjacent Channel Power Measurement	58
C.2	Unwanted Emissions Measurement	58
Annex D (normative):	Band-stop filter (for SINAD meter)	59
Annex E (informative):	Bibliography.....	60
History		61

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 1 of a multi-part deliverable covering the Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates	
Date of adoption of this EN:	13 August 2013
Date of latest announcement of this EN (doa):	30 November 2013
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2014
Date of withdrawal of any conflicting National Standard (dow):	31 May 2014

1 Scope

The present document covers the minimum characteristics considered necessary in order to avoid harmful interference and to make acceptable use of the available frequencies.

The present document applies to equipment with integral antennas, used in angle modulation systems in the land mobile service, operating on radio frequencies between 30 MHz and 1 000 MHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, and is intended primarily for analogue speech.

In the present document different requirements are given for the different radio frequency bands, channel separations, environmental conditions and types of equipment, where appropriate.

The present document is complementary to EN 300 086 [i.7], which covers radio equipment with an internal or external RF connector, for use in the land mobile service.

The present document may apply to PMR446 equipment as defined in [i.8]. Note that PMR446 equipment has a requirement to incorporate a receiver and may have requirements for 180 s maximum transmission time and VOX.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/REC 74-01E: "Unwanted emissions in the spurious domain" (Siófok 1998, Nice 1999, Sesimbra 2002; Hradec Kralove 2005).
- [i.2] ETSI EN 300 793 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Presentation of equipment for type testing".
- [i.3] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.4] IEC 60489-3 (1988): "Methods of measurement for radio equipment used in the mobile services; Part 3: Receivers for A3E or F3E emissions".
- [i.5] Recommendation ITU-T O.41 (1994): "Psophometer for use on telephone-type circuits".

- [i.6] Void.
 - [i.7] ETSI EN 300 086 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech".
 - [i.8] CEPT/ERC/DEC(98)25: "The Harmonised frequency band designated for analogue PMR446".
-

koniec náhľadu – text ďalej pokračuje v platenej verzii STN