

STN	Elektromagnetická kompatibilita a záležitosti rádiového spektra (ERM). Plavebné pohyblivé vysielače a prijímače prevádzkované v pásmach MF a HF. Časť 1: Technické charakteristiky a meracie metódy.	STN EN 300 373-1 V1.4.1
		87 0373

Electromagnetic compatibility and Radio spectrum Matters (ERM); Maritime mobile transmitters and receivers for use in the MF and HF bands; Part 1: Technical characteristics and methods of measurement

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 01/14

Obsahuje: EN 300 373-1 V1.4.1:2013

118582

www.sutn.sk

Slovenský ústav technickej normalizácie, 2014

Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy rozmnožovať a rozširovať iba so súhlasom Slovenského ústavu technickej normalizácie.

SUTN

ETSI EN 300 373-1 V1.4.1 (2013-09)



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Maritime mobile transmitters and receivers
for use in the MF and HF bands;
Part 1: Technical characteristics and
methods of measurement**

Reference

REN/ERM-TG26-097-1

Keywords

maritime, radio, telephony

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	13
3.1 Definitions	13
3.2 Symbols.....	13
3.3 Abbreviations	14
4 General requirements	15
4.1 Construction	15
4.1.1 Design.....	15
4.1.2 Inspection and maintenance	15
4.1.3 Illumination.....	15
4.1.4 Antenna static protection	15
4.1.5 Digital input panels.....	15
4.1.6 DSC operation	15
4.1.7 NBDP operation.....	16
4.1.8 Interfaces.....	16
4.1.8.1 Audio frequency.....	16
4.1.8.2 Digital interfaces	16
4.1.9 Antenna matching	16
4.2 Controls and indicators.....	16
4.2.1 General.....	16
4.2.2 Ease of use	17
4.2.3 Loudspeaker switching	17
4.2.4 Noise reducer	17
4.2.5 Frequency indication and class of emission.....	17
4.2.6 Synthesizer lock.....	17
4.2.7 Channel switching	17
4.2.8 Distress controls.....	17
4.2.9 Telephony transmit control	17
4.2.10 Misuse.....	18
4.2.11 Control panel priority.....	18
4.2.12 Manual gain control and Automatic Gain Control (AGC).....	18
4.2.13 Output indication	18
4.2.14 Audio Processing.....	18
4.3 Labels	18
4.3.1 General.....	18
4.3.2 Power supplies	18
4.3.3 Distress frequencies	18
4.3.4 Manufacturer.....	19
4.3.5 Compass safe distance	19
4.4 Safety precautions	19
4.4.1 Protection.....	19
4.4.2 Earthing	19
4.4.3 Access	19
4.4.4 Memories	19
4.5 Classes of emission	20
4.6 Frequency bands.....	20
4.6.1 Requirement.....	20
4.6.2 MF band.....	20
4.6.3 HF bands.....	20

4.7	Warming up period.....	20
4.7.1	Time.....	20
4.7.2	Heaters.....	20
4.7.3	Heating circuits.....	20
4.7.4	Delay.....	20
4.8	Instructions	21
4.8.1	Repair instructions	21
4.8.2	Accessibility	21
5	Test conditions	21
5.1	General	21
5.2	Test power source.....	21
5.3	Internally generated signals.....	21
5.4	Normal test conditions.....	22
5.4.1	Normal temperature and humidity.....	22
5.4.2	Normal test power source	22
5.4.2.1	Mains voltage and frequency	22
5.4.2.2	Secondary battery power sources	22
5.4.2.3	Other power sources.....	22
5.5	Extreme test conditions	22
5.5.1	Extreme temperature tests.....	22
5.5.2	Extreme values of test power source	22
5.5.2.1	Mains voltage and mains frequency	22
5.5.2.2	Secondary battery power sources	22
5.5.2.3	Other power sources.....	23
5.6	Artificial antennas	23
5.6.1	Transmitters	23
5.6.2	Receivers	23
5.7	Standard test signals	23
5.7.1	Test signals applied to the receiver input.....	23
5.7.1.1	Sources	23
5.7.1.2	Levels.....	23
5.7.2	Normal test signals.....	24
5.7.2.1	Class of emission J3E.....	24
5.7.3	Test signals for equipment with integrated DSC decoder.....	24
5.7.3.1	Reference to standard DSC signals	24
5.7.3.2	Standard DSC test signal 1.....	24
5.7.3.3	Standard DSC test signal 2.....	24
5.7.4	Symbol error rate at the DSC receiving part.....	24
5.7.5	Choice of testing frequencies.....	24
5.7.6	Exclusion bands for emissions testing	25
5.7.6.1	Receiver exclusion bands	25
5.7.6.2	Transmitter exclusion bands.....	25
5.7.7	Reference bandwidths for spurious measurements	25
5.8	Measurement uncertainty and interpretation of the measuring results	25
5.8.1	Measurement uncertainty.....	25
5.8.2	Interpretation of measurement results.....	26
6	General conditions of measurement	26
6.1	Sequence of testing.....	26
7	Environmental tests	26
7.1	Introduction	26
7.2	Procedure.....	27
7.3	Performance check	27
7.4	Performance check of DSC with encoder/decoder.....	27
7.5	Vibration test	28
7.5.1	Method of measurement	28
7.5.2	Requirement.....	28
7.6	Temperature tests	28
7.6.1	General.....	28
7.6.2	Dry heat	28
7.6.2.1	Internally mounted equipment	28

7.6.2.1.1	Method of measurement	28
7.6.2.1.2	Requirement	29
7.6.2.2	Externally mounted equipment	29
7.6.2.2.1	Method of measurement	29
7.6.2.2.2	Requirement	29
7.6.3	Damp heat	29
7.6.3.1	Method of measurement	29
7.6.3.2	Requirement	29
7.6.4	Low temperature cycle	30
7.6.4.1	Internally mounted equipment	30
7.6.4.1.1	Method of measurement	30
7.6.4.1.2	Requirement	30
7.6.4.2	Externally mounted equipment	30
7.6.4.2.1	Method of measurement	30
7.6.4.2.2	Requirement	30
7.7	Corrosion test	30
7.7.1	General	30
7.7.2	Method of measurement	31
7.7.3	Requirements	31
7.8	Rain test	31
7.8.1	General	31
7.8.2	Method of measurement	32
7.8.3	Requirements	32
8	Transmitter	32
8.1	General	32
8.1.1	Output power reduction	32
8.1.2	Class of emission	32
8.1.3	Minimum number of operating frequencies	32
8.1.3.1	Transmitters operating between 1 606,5 kHz to 4 000 kHz only	32
8.1.3.2	Transmitters operating between 1 606,5 kHz to 27 500 kHz	33
8.2	Frequency error	33
8.2.1	Definition	33
8.2.2	Method of measurement	33
8.2.3	Limits	33
8.3	Output power and intermodulation products	33
8.3.1	Definitions	33
8.3.2	Method of measurement	34
8.3.3	Limits	34
8.3.3.1	Output power in the range 1 606,5 kHz to 4 000 kHz for all modulation modes	34
8.3.3.2	Output power in the range 4 MHz to 27,5 MHz for all modulation modes	34
8.3.3.3	Intermodulation products for SSB telephony modes	34
8.4	Unwanted frequency modulation	34
8.4.1	Definition	34
8.4.2	Method of measurement	34
8.4.3	Limits	35
8.5	Sensitivity of the microphone	35
8.5.1	Definition	35
8.5.2	Method of measurement	35
8.5.3	Limits	35
8.6	Sensitivity of the 600 Ω line input for SSB telephony	35
8.6.1	Definition	35
8.6.2	Method of measurement	35
8.6.3	Limits	35
8.7	Automatic level control and/or limiter for SSB telephony	35
8.7.1	Method of measurement	36
8.7.2	Limits	36
8.8	Audio frequency response of SSB telephony	36
8.8.1	Definition	36
8.8.2	Method of measurement	37
8.8.3	Limits	37
8.9	Power of out-of-band emissions of SSB telephony	37

8.9.1	Definition.....	37
8.9.2	Method of measurement	38
8.9.3	Limits.....	38
8.10	Power of conducted spurious emissions of SSB telephony.....	38
8.10.1	Definition.....	38
8.10.2	Method of measurement	38
8.10.3	Limits.....	39
8.11	Residual hum and noise power for telephony.....	39
8.11.1	Definition.....	39
8.11.2	Method of measurement	39
8.11.3	Limits.....	39
8.12	Carrier suppression.....	39
8.12.1	Definition.....	39
8.12.2	Method of measurement	39
8.12.3	Limits.....	40
8.13	Continuous operation on telephony.....	40
8.13.1	Definition.....	40
8.13.2	Method of measurement	40
8.13.3	Limits.....	40
8.14	Protection of transmitter	40
8.14.1	Definition.....	40
8.14.2	Method of measurement	40
8.14.3	Limits.....	40
8.15	Radiated spurious emissions.....	40
8.15.1	Definition.....	40
8.15.2	Method of measurement	41
8.15.3	Limits.....	42
9	Transmitter with DSC encoder.....	42
9.1	Frequency error	42
9.1.1	Definition.....	42
9.1.2	Method of measurement	42
9.1.3	Limits.....	42
9.2	Output power.....	42
9.2.1	Definitions	42
9.2.2	Method of measurement	43
9.2.3	Limits.....	43
9.2.3.1	Output power in the range 1 606,5 kHz to 4 000 kHz.....	43
9.2.3.2	Output power in the range 4 MHz to 27,5 MHz for all modulation modes.....	43
9.2.3.3	Difference of power of B-state frequency and Y-state frequency	43
9.3	Out-of-band emission of DSC	43
9.3.1	Definition.....	43
9.3.2	Method of measurement	43
9.3.3	Limits.....	43
9.4	Spurious emission of DSC	44
9.4.1	Definition.....	44
9.4.2	Method of measurement	44
9.4.3	Limits.....	45
9.5	Residual frequency modulation of DSC.....	45
9.5.1	Definition.....	45
9.5.2	Method of measurement	45
9.5.3	Limits.....	45
9.6	Modulation rate of DSC	45
9.6.1	Definition.....	45
9.6.2	Method of measurement	45
9.6.3	Limits.....	46
9.7	Testing of call sequences of DSC.....	46
9.8	Transmitter tuning of DSC equipment	46
9.9	Testing of free channel transmission on DSC frequencies	46
9.9.1	Definition.....	46
9.9.2	Method of measurement	46
9.9.2.1	Distress frequency.....	46

9.9.2.2	Ship-ship routine frequency	47
9.9.3	Requirement.....	47
10	Receiver.....	47
10.1	Receiver output powers	47
10.1.1	Standard output power.....	47
10.1.2	Rated output power.....	47
10.2	Frequency error	48
10.2.1	Definition.....	48
10.2.2	Method of measurement	48
10.2.3	Limits.....	48
10.3	Unwanted frequency modulation	48
10.3.1	Definition.....	48
10.3.2	Method of measurement	48
10.3.3	Limits.....	48
10.4	Pass band	49
10.4.1	Definition.....	49
10.4.2	Method of measurement	49
10.4.2.1	Class of emission J3E.....	49
10.4.3	Limits.....	49
10.5	Maximum usable sensitivity	49
10.5.1	Definition.....	49
10.5.2	Methods of measurement.....	49
10.5.3	Limits.....	50
10.6	Adjacent signal selectivity.....	50
10.6.1	Definition.....	50
10.6.2	Method of measurement	50
10.6.3	Limits.....	50
10.7	Blocking or desensitization	50
10.7.1	Definition.....	50
10.7.2	Method of measurement	51
10.7.3	Limits.....	51
10.8	Intermodulation response	51
10.8.1	Definition.....	51
10.8.2	Method of measurement	51
10.8.2.1	Class of emission J3E.....	51
10.8.3	Limits.....	52
10.9	Reciprocal mixing	52
10.9.1	Definition.....	52
10.9.2	Method of measurement	52
10.9.3	Results	52
10.10	Spurious response rejection ratio.....	52
10.10.1	Definition.....	52
10.10.2	Method of measurement	53
10.10.3	Limits.....	53
10.11	Harmonic content in output	54
10.11.1	Definition.....	54
10.11.2	Method of measurement	54
10.11.3	Limits.....	54
10.12	Audio frequency intermodulation.....	54
10.12.1	Definition.....	54
10.12.2	Method of measurement	54
10.12.3	Limits.....	54
10.13	Conducted spurious emissions	54
10.13.1	Definition.....	54
10.13.2	Methods of measurement.....	55
10.13.3	Limits.....	55
10.14	Internally generated spurious signals	55
10.14.1	Definition.....	55
10.14.2	Method of measurement	55
10.14.3	Limits.....	55
10.15	AGC efficiency	55

10.15.1	Definition.....	55
10.15.2	Method of measurement and limits.....	56
10.15.2.1	Settings.....	56
10.15.2.2	Increase in Signal-to-Noise Ratio (SNR)	56
10.15.2.3	Range	56
10.16	AGC time constants (attack and recovery time).....	56
10.16.1	Definitions	56
10.16.2	Method of measurement	56
10.16.3	Limits.....	56
10.17	Protection of input circuits.....	57
10.17.1	Definition.....	57
10.17.2	Method of measurement	57
10.17.3	Limit	57
10.18	Radiated spurious emission.....	57
10.18.1	Definition.....	57
10.18.2	Method of measurement	57
10.18.3	Limits.....	58
11	Receiver with DSC decoder	58
11.1	Calling sensitivity.....	58
11.1.1	Definition.....	58
11.1.2	Method of measurement	58
11.1.3	Limits.....	59
11.2	Adjacent channel selectivity.....	59
11.2.1	Definition.....	59
11.2.2	Method of measurement	59
11.2.3	Limits.....	59
11.3	Co-channel rejection.....	60
11.3.1	Definition.....	60
11.3.2	Method of measurement	60
11.3.3	Limits.....	60
11.4	Intermodulation response	60
11.4.1	Definition.....	60
11.4.2	Method of measurement	60
11.4.3	Limits.....	61
11.5	Spurious response rejection.....	61
11.5.1	Definition.....	61
11.5.2	Method of measurement	61
11.5.3	Limits.....	62
11.6	Blocking immunity.....	62
11.6.1	Definition.....	62
11.6.2	Method of measurement	62
11.6.3	Limits.....	62
11.7	Dynamic range	62
11.7.1	Definition.....	62
11.7.2	Method of measurements	62
11.7.3	Limits.....	63
11.8	Verification of correct decoding of various types of DSC signals	63
A	Annex A (normative): Radiated measurement.....	64
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	64
A.1.1	Anechoic chamber.....	64
A.1.2	Anechoic chamber with a ground plane	65
A.1.3	OATS	66
A.1.4	Test antenna.....	67
A.1.5	Substitution antenna	67
A.1.6	Measuring antenna	68
A.2	Guidance on the use of radiation test sites	68
A.2.1	Verification of the test site	68
A.2.2	Preparation of the EUT.....	68
A.2.3	Power supplies to the EUT	68

A.2.4	Volume control setting for analogue speech tests	68
A.2.5	Range length.....	69
A.2.6	Site preparation	69
A.3	Coupling of signals.....	70
A.3.1	General	70
A.3.2	Data signals	70
A.3.3	Speech and analogue signals	70
A.3.3.1	Acoustic coupler description.....	70
A.3.3.2	Calibration	71
Annex B (normative):	Spectrum analyser specification	72
Annex C (normative):	Protocol for the EN 61162-1 Commands Frequency Set Information (FSI)	73
C.1	Frequency Set Information (FSI)	73
Annex D (informative):	DSC test calls.....	74
D.1	Interoperability tests	74
Annex E (informative):	Bibliography.....	75
	History	76

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 1 of a multi-part deliverable covering Maritime mobile transmitters and receivers for use in the MF and HF bands, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive";

Part 3: "Harmonized EN covering essential requirements under article 3.3(e) of the R&TTE Directive;
Equipment with integrated or associated equipment for Class E Digital Selective Calling (DSC)".

The present document sets out the minimum requirements for Medium Frequency (MF) and Medium and High Frequency (MF/HF) equipment on board ships, operating in the maritime mobile MF and HF radio services.

National transposition dates	
Date of adoption of this EN:	13 September 2013
Date of latest announcement of this EN (doa):	31 December 2013
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2014
Date of withdrawal of any conflicting National Standard (dow):	30 June 2014

1 Scope

The present document states the minimum requirements for radio transmitters and receivers, for use on ships, operating in either the Medium Frequency (MF) only or in the Medium and High Frequency (MF/HF) bands allocated in the International Telecommunications Union (ITU) Radio Regulations [6], to the Maritime Mobile Service (MMS).

The present document includes the International Maritime Organization (IMO) and ITU requirements included in the relevant provisions of the Radio Regulations [6], the International Convention for the Safety Of Life At Sea (SOLAS) [i.1], the IMO Resolutions A.694(17) [i.3] and A806 (19) [i.2] and is primarily intended to specify equipment suitable for fitting to ships subject to the SOLAS convention and complying with the European Marine Equipment Directive [i.12].

The present document refers to equipment for one or more of the following:

- Single SideBand (SSB) modulation for telephony transmission and reception (J3E);
- Frequency Shift Keying (FSK) or SSB modulation of a keyed sub-carrier to transmit and receive Digital Selective Calling (DSC) signals in accordance with Recommendation M.493-13 ITU-R [i.4].

The present document also refers to radio equipment, which is not integrated with the DSC encoder or decoder, but defines the interfaces with such equipment.

NOTE 1: The requirements for integrated equipment may be found in other relevant ENs.

NOTE 2: The requirements for other modes of operation may be found in other relevant ENs.

The tests in the present document are applicable to equipment operating on all frequencies in the bands 1 606,5 kHz to 4 000 kHz or 1 606,5 kHz to 27,5 MHz as allocated in the Radio Regulations [6], to the MMS.

The present document does not address the testing of ancillary equipment on a stand-alone basis, i.e. separately from the radio equipment with which it is to be used.

NOTE 3: The EMC requirements and requirements for cabinet radiation for ancillary equipment are found in EN 301 843-5 [i.5], clause 7.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 033: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for shipborne watchkeeping receivers for reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and VHF bands".
- [2] Recommendation ITU-T E.161 (2001): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [3] CENELEC EN 61162-1 (2011): "Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners".

- [4] ISO 3791 (1976): "Office machines and data processing equipment -- Keyboard layouts for numeric applications".
- [5] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [6] ITU Radio Regulations (2012).
- [7] ANSI C63.5-2006: "American National Standard for Electromagnetic Compatibility - Radiated Emission Measurements in Electromagnetic Interference (EMI) Control - Calibration of Antennas (9 kHz to 40 GHz)".
- [8] IEC 60489-3 Second edition (1999) appendix F: "Methods of measurement for radio equipment used in the mobile services. Part 3: Receivers for A3E or F3E emissions".
- [9] ETSI EN 300 338-2 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 2: Class A/B DSC".
- [10] CISPR 16-1-1 ed. 3.1 (2010) "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] International Convention for the Safety of Life at Sea, (SOLAS), as amended.
- [i.2] IMO Resolutions A.806 (19): "Performance Standards for Shipborne MF/HF Radio Installations Capable of Voice Communication, Narrow-Band Direct Printing and Digital Selective Calling".
- [i.3] IMO Resolutions A.694(17): "General Requirements for Shipborne Radio Equipment Forming Part of the Global Maritime Distress and Safety System and for Electronic Navigational Aids".
- [i.4] Recommendation ITU-R M.493-13: "Digital selective-calling system for use in the maritime mobile service".
- [i.5] ETSI EN 301 843-5: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for marine radio equipment and services; Part 5: Specific conditions for MF/HF radiotelephone transmitters and receivers".
- [i.6] ETSI ETS 300 019-1-6: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-6: Classification of environmental conditions; Ship environments".
- [i.7] Recommendation ITU-R SM.326-6: "Determination and measurement of the power of radio transmitters".
- [i.8] Recommendation ITU-R SM.332-4: "Selectivity of receivers".
- [i.9] ETSI TR 102 273 (parts 2, 3 and 4): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.10] ETSI TS 101 570-2 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Interoperability Testing for Maritime Digital Selective Calling (DSC) Radios; Part 2: Class A/B Test Descriptions".
- [i.11] ETSI ETS 300 067 (Edition 1) (1990): "Radio Equipment and Systems (RES); Radiotelex equipment operating in the maritime MF/HF service; Technical Characteristics and methods of measurement".

[i.12] Council Directive 96/98/EC of 20 December 1996 on marine equipment (Marine Equipment Directive).

koniec náhľadu – text d'alej pokračuje v platenej verzii STN