STN	Káblové siete pre televízne signály, rozhlasové signály a interaktívne služby. Časť 8: Elektromagnetická kompatibilita sietí.	STN EN 50083-8
		36 7211

Táto norma obsahuje anglickú verziu európskej normy. This standard includes the English version of the European Standard.

Obsahuje: EN 50083-8:2013

Oznámením tejto normy sa od 8.11.2016 ruší STN EN 50083-8 (36 7211) z augusta 2003

#### 118993

## **EUROPEAN STANDARD**

## EN 50083-8

December 2013

# NORME EUROPÉENNE

## **EUROPÄISCHE NORM**

ICS 33.060.40; 33.100.01

des réseaux

Supersedes EN 50083-8:2002 + A11:2008

English version

## Cable networks for television signals, sound signals and interactive services -

Part 8: Electromagnetic compatibility for networks

Réseaux de distribution par câbles pour signaux de télévision, signaux de radiodiffusion sonore et services interactifs Partie 8: Compatibilité électromagnétique

Kabelnetze für Fernsehsignale, Tonsignale und interaktive Dienste -Teil 8: Elektromagnetische Verträglichkeit von Kabelnetzen

This European Standard was approved by CENELEC on 2013-11-11. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## **CENELEC**

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

## **Contents**

Forew	ord	4
1	Scope	5
1.1	General	5
1.2	Specific scope of EN 50083-8	5
2	Normative references	6
	Terms, definitions, symbols and abbreviations	
3 3.1	Terms and definitions	
3.2	Symbols	
3.3	Abbreviations	
	Methods of measurement	_
4 4.1	Basic principles	
4.2	Radiation from cable networks	
4.2.1	General	
4.2.2	Field strength method	
4.2.3	Subcarrier measurement procedure	
4.2.4	GPS based leakage detection system	
4.3	Immunity of cable networks	
4.3.1	General	
4.3.2	Measurement procedure for interference caused by high-power local transmitter	
_	,	
5 5.1	Performance requirements	
5.1 5.2	General conditions	
5.2.1	General	
5.2.1 5.2.2	Measurement of the total radiation	
5.2.2 5.2.3	Measurement of the total radiation	
5.2.3 5.3	Immunity of cable networks	
	•	
	A (informative) A-deviations	
A.1	United Kingdom	
A.1.1	Regulation	
A.1.2	Principle	
A.1.3	Equipment	
A.1.4 A.1.5	Measurement frequencies  Procedure	
A.1.5 A.1.6	Expression of results	
A.1.6 A.1.7	Permitted limits	
A.1.7 A.1.8	Interpretation	_
A.1.9	Bibliography of A.1	
A.1.3 A.2	United Kingdom	
A.2.1	Regulation	
A.2.2	Principle	
A.2.3	Equipment	
A.2.4	Measurement frequencies	
A.2.5	Procedure	
A.2.6	Permitted limits	
A.2.7	Interpretation	
A.2.8	Bibliography of A.2	
A.3	Finland	
A.4	Germany	25

Annex	B (informative) Frequency ranges of typical safety of life services	.28
Annex	C (informative) Interdependence between the maximum allowable field strength and the minimum signal level at system outlet	.29
Annex	D (informative) Measurements in other distances than the standard distance of 3 m	
D.1	Measurement at a reduced distance below 3 m	
D.2	Measurement at measurement distances above 3 m	.31
	E (informative) GPS based leakage detection system for cable networks	
E.1 E.2	General	
E.2 E.3	Automated data collection by driving through the HFC network	
E.4	Post processing the collected data and visualisation of leakages	
E.5	On site location of the leak	
Biblioa	raphy	.33
	A.1 – Arrangement of test equipment for the measurement of radiation from complete stems	.20
Table 1	- Limits of total radiation	.15
Table 2	? – Narrowband radiation limits	.15
Table 3	B – Maximum expected field strength	.16
Table 4	- Required carrier-to-interference ratio	.17
Table A	A.1 – Radiation from complete systems: maximum permitted field strengths	.21
Table A	A.2 – Distance correction factor	.22
Table A	A.3 – Radiation from complete systems: maximum permitted field strengths	.24
Table A	A.4 – Distance correction factor	.24
Table A	A.5 – Protection of particular frequency ranges according to § 3 of the Order	.25
	A.6 – Field strength limit values at 3 m distance from line-bound telecommunications cilities and networks	.27
Table E	3.1 – Frequency ranges of typical safety of life services	28

## **Foreword**

This document (EN 50083-8:2013) has been prepared by CLC/TC 209 "Cable networks for television signals, sound signals and interactive services".

The following dates are fixed:

•	latest date by which this document has to be implemented at national level by publication of an identical national	(dop)	2014-11-08
•	standard or by endorsement latest date by which the national standards conflicting with this document have to be withdrawn	(dow)	2016-11-08

This document supersedes EN 50083-8:2002 + A11:2008.

EN 50083-8:2013 includes the following significant technical changes with respect to EN 50083-8:2002 and EN 50083-8/A11:2008.

- EN 50083-8 with its methods of measurement and EMC performance requirements is explicitly dedicated to "under operating conditions (in situ)" to ensure the ongoing EMC integrity of cable networks.
- The harmonized standard EN 50529-2 is dedicated for the provision of presumption of conformance to the EMC Directive.
- The first intermediate frequency range (1<sup>st</sup> IF range) for satellite signal transmission was extended to cover now frequencies from 950 MHz up to 3 500 MHz.
- The method of measurement and the requirements for in-band immunity were extended taking into account the new EMC environment due to the allocation of broadband wireless services in the frequency band 790 MHz to 862 MHz. As a consequence, the limits of in-band immunity were specified for analogue and additionally for digital signals in this frequency range.
- The substitution method of measurement (power method) was deleted.
- EMC measurements below 30 MHz were deleted
- New Annex D "Measurement in other distances than the standard distance of 3 m"
- New Annex E "GPS based leakage detection system for cable networks"

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

#### 1 Scope

#### 1.1 General

Standards of the EN 50083 and EN 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes for instance

- regional and local broadband cable networks,
- extended satellite and terrestrial television distribution systems,
- individual satellite and terrestrial television receiving systems,

and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

## 1.2 Specific scope of EN 50083-8

This European Standard applies to the radiation characteristics and immunity to electromagnetic disturbance of cable networks for television signals, sound signals and interactive services and covers the frequency range 0,15 MHz to 3,5 GHz. It should be noted that measurements below 30 MHz are not generally considered useful in the context of cable networks and are difficult to perform in practice.

Application of the harmonized standard EN 50529-2 provides presumption of conformance to the EMC Directive. Therefore, to fulfil the requirements of EN 50529-2, it is necessary to use cable network equipment that satisfies the requirements of EN 50083-2 regarding limits of radiation and of immunity to external fields.

This European Standard specifies methods of measurement and EMC performance requirements under operating conditions (in situ) to ensure the ongoing EMC integrity of cable networks.

Cable networks beyond the system outlets (e.g. the receiver lead, in simplest terms) which begin at the system outlet and end at the input to the subscriber's terminal equipment are not covered by the standard EN 50083-8. Requirements for the electromagnetic compatibility of receiver leads are laid down in EN 60966-2-4, EN 60966-2-5 and EN 60966-2-6.

Cable networks and a wide range of radio services have to coexist. These include for example the emergency services, safety of life, broadcasting, aeronautical, radio navigation services and also land mobile, amateur and cellular radio services. Frequency ranges of typical safety of life services are listed in Annex B. Additional protection for certain services may be required by national regulations.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50083 (all parts), Cable networks for television signals, sound signals and interactive services

EN 50083-2, Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment

EN 50117 (all parts), Coaxial cables

EN 50529-2, EMC Network Standard - Part 2: Wire-line telecommunications networks using coaxial cables

EN 55016-1-1, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus (CISPR 16-1-1)

EN 55016-1-4, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements (CISPR 16-1-4)

EN 60728 (all parts), Cable networks for television signals, sound signals and interactive services (IEC 60728, all parts)

EN 60728-1, Cable networks for television signals, sound signals and interactive services – Part 1: System performance of forward paths (IEC 60728-1)

IEC 60050-161, International Electrotechnical Vocabulary – Chapter 161: Electromagnetic compatibility

koniec náhľadu – text ďalej pokračuje v platenej verzii STN