

| | | |
|------------|---|----------------------------|
| STN | Výbušné atmosféry. Časť 14: Návrh, výber a montáž elektrických inštalácií. | STN EN 60079-14 |
| | | 33 2320 |

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola označená vo Vestníku ÚNMS SR č. 10/14

Obsahuje: EN 60079-14:2014, IEC 60079-14:2013

Oznámením tejto normy sa od 02.01.2017 ruší
STN EN 60079-14 (33 2320) z júna 2009

119639

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, odbor SÚTN, 2014
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy
rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

**EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM**

EN 60079-14

March 2014

ICS 29.260.20

Supersedes EN 60079-14:2008, EN 60079-14:2008/AC:2011

English version

**Explosive atmospheres -
Part 14: Electrical installations design, selection and erection
(IEC 60079-14:2013)**

Atmosphères explosives -
Partie 14: Conception, sélection et
construction des installations électriques
(CEI 60079-14:2013)

Explosionsgefährdete Bereiche -
Teil 14: Projektierung, Auswahl und
Errichtung elektrischer Anlagen
(IEC 60079-14:2013)

This European Standard was approved by CENELEC on 2014-01-02. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 31J/225/FDIS, future edition 5 of IEC 60079-14, prepared by SC 31J "Classification of hazardous areas and installation requirements" of IEC/TC 31 "Equipment for explosive atmospheres" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60079-14:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-10-02
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-01-02

This document supersedes EN 60079-14:2008.

EN 60079-14:2014 includes the following significant technical changes with respect to EN 60079-14:2008:

| | | Type | | |
|---|---------|-----------------------------|-----------|-------------------------|
| Explanation of the significance of the changes | Clause | Minor and editorial changes | Extension | Major technical changes |
| Introduction of initial inspection | Scope | | X | |
| Introduction of definition "electrical equipment" | 3.1.3 | X | | |
| Introduction of definition "hybrid mixture" | 3.2.4 | | X | |
| Note added to the definition "associated apparatus" | 3.5.2 | X | | |
| Introduction of definition "radio frequency identification" | 3.15 | X | | |
| List for documents improved and extended: site, equipment, installation and personnel | 4.2 | X | | |
| New clause for initial inspection | 4.3 | | X | |
| Specific requirements given in this standard based on the current edition of the EN standards in the EN 60079 series. | 4.4.1.2 | X | | |
| New selection criteria for radiating equipment according to EN 60079-0 | 5.7 | | X | |
| New selection criteria for ultrasonic equipment according to EN 60079-0 | 5.8 | | X | |
| Specific requirements for cells and batteries used in transportable, portable and personal equipment aligned with EN 60079-11 | 5.10 | | | C1 |
| New structure for the selection of rotating electrical machines | 5.11 | X | | |
| New selection criteria for cells and batteries | 5.14 | | X | |
| New selection criteria for radio frequency identification tags | 5.15 | | X | |
| New selection criteria for gas detection equipment | 5.16 | | X | |
| The requirements for material composition of metallic installation material aligned with the requirements for light metal according to EN 60079-0 | 6.1 | | X | |
| Above hazardous area, the restriction of 3,5 m deleted | 6.3.7 | X | | |

| | | Type | | |
|--|--|-----------------------------|-----------|-------------------------|
| Explanation of the significance of the changes | Clause | Minor and editorial changes | Extension | Major technical changes |
| New structure of the requirements for static electricity according to EN 60079-0 added | 6.5 | | X | |
| New requirements for electromagnetic radiation in accordance with EN 60079-0 | 6.7 | | X | |
| Improvement of the text for cables, cables for fixed and flexible cables for fixed installation for easier reading | 9.3.1 9.3.2 9.3.3 | X | | |
| New structure of the requirements for cable entry system and blanking elements with subclauses - General - Connections of cables to equipment - Selection of cable glands with the new Table 10 - Additional requirements for cable glands other than Ex "d", Ex "t" or Ex "nR" - Additional requirements for Ex "d" - Additional requirements for Ex "t" - Additional requirements for Ex "nR" | 10 10.1 10.2 10.3 10.4 10.5 10.6 10.7 10.8 | | X | |
| New structure for the requirements for rotating electrical machines for all types of protections | 11 | | X | |
| New structure for the requirements for electric heating systems including temperature monitoring, limiting temperature, safety device and additional requirements for electrical heat tracing system | 13 | | X | |
| New clause to limit the dissipation power of terminal boxes as a function of the numbers of wire in relation to the cross-section and the permissible continuous current with an example. | 15.4 | | X | |
| Improvement of the text for simple apparatus with its definition, limits and the variation in maximum power dissipation based on the ambient temperature and an alternative equation to calculate the max. surface temperature. | 16.4 | | X | |
| New requirements for terminal boxes if containing more than one intrinsically safe circuits to avoid short circuits between independent intrinsically safe circuits. | 16.5 | | | C2 |
| Improvement of the text for terminal boxes with non-intrinsically and intrinsically safe circuits | 16.5.4 | X | | |
| New subclause for pressurized rooms and analyser houses | 17.4 | | X | |
| New clause for optical radiation | 22 | | X | |
| New annex for initial inspection with the equipment specific inspection schedule for all type of protections | Annex C | | X | |
| New annex for electrical installations in extremely low ambient temperature | Annex D | | X | |
| New annex for the restricted migration of gas through cables | Annex E | | X | |
| New annex for installation of electrical trace heating systems | Annex F | | X | |
| New annex for the requirements for type of protection "op" – Optical radiation | Annex K | | X | |
| New annex for hybrid mixtures | Annex M | | X | |

| Explanation of the types of significant changes: | |
|---|--|
| A) Definitions | |
| 1 Minor and editorial changes: | <ul style="list-style-type: none"> - Clarification - Decrease of technical requirements - Minor technical change - Editorial corrections |
| These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in level of existing requirement. | |
| 2 Extension: | - Addition of technical options |
| These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing the requirements for the design, selection and erection of existing installations that are fully compliant with the previous standard. Therefore, these will not have to be considered for existing installations in conformity with the preceding edition. | |
| 3 Major technical changes: | <ul style="list-style-type: none"> - addition of technical requirements - increase of technical requirements |
| These are changes to technical requirements (addition, increase of the level or removal) made in a way that an existing installation in conformity with the preceding edition will not always be able to fulfil the requirements given in the later edition. These changes have to be considered for existing installations in conformity with the preceding edition, for which additional information is provided in B) below. | |
| These changes represent the latest state-of-the-art technology. However, these changes should not normally have an influence on existing installations. | |
| B) Information about the background of "major technical changes" | |
| C1 | Due to the risk of gassing producing hydrogen from all cell types, adequate provision for venting is required as the gassing can create an explosive condition in small enclosures. This condition would apply to torches, multi meters, pocket gas sensors and similar items. Alternatively, where the equipment meets the requirements for Equipment Group IIC, the requirement of degassing apertures or limitation of hydrogen concentration does not apply. |
| C2 | An individual intrinsically safe circuit is also safe under short-circuit conditions. The short-circuit between two independent intrinsically safe circuits is not considered. Therefore the terminal boxes have to meet additional requirements for IP rating as well for the mechanical impact to make sure that the integrity of the enclosure is given also under worst case conditions. |

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60079-14:2013 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

| | | |
|--------------------|------|--|
| IEC 60034-5 | NOTE | Harmonized as EN 60034-5. |
| IEC/TS 60034-17 | NOTE | Harmonized as CLC/TS 60034-17. |
| IEC/TS 60034-25 | NOTE | Harmonized as CLC/TS 60034-25. |
| IEC 60079-2 | NOTE | Harmonized as EN 60079-2. |
| IEC 60079-5 | NOTE | Harmonized as EN 60079-5. |
| IEC 60079-29-2 | NOTE | Harmonized as EN 60079-29-2. |
| IEC 60079-30-2 | NOTE | Harmonized as EN 60079-30-2. |
| IEC 60079-31 | NOTE | Harmonized as EN 60079-31. |
| IEC 60332-2-2 | NOTE | Harmonized as EN 60332-2-2. |
| IEC 60332-3 Series | NOTE | Harmonized as EN 60332-3 Series (partly modified). |
| IEC 60529 | NOTE | Harmonized as EN 60529. |
| IEC 60742 | NOTE | Harmonized as EN 60742. |

| | | |
|------------------|------|---|
| IEC 61008-1 | NOTE | Harmonized as EN 61008-1. |
| IEC 61010-1 | NOTE | Harmonized as EN 61010-1. |
| IEC 61241 Series | NOTE | Harmonized as EN 61241 Series (not modified). |
| IEC 61241-1 | NOTE | Harmonized as EN 61241-1 ¹⁾ . |
| IEC 61241-4 | NOTE | Harmonized as EN 61241-4. |
| IEC 61241-11 | NOTE | Harmonized as EN 61241-11. |
| IEC 61439-1 | NOTE | Harmonized as EN 61439-1. |
| ISO 10807 | NOTE | Harmonized as EN ISO 10807. |

¹⁾ Superseded by EN 60079-31.

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|--------------------|-------------|--|---------------|-------------|
| IEC 60034-1 | - | Rotating electrical machines - Part 1: Rating and performance | EN 60034-1 | - |
| IEC 60060-1 | - | High-voltage test techniques - Part 1: General definitions and test requirements | EN 60060-1 | - |
| IEC 60079 | Series | Explosive atmospheres | EN 60079 | Series |
| IEC 60079-0 | - | Explosive atmospheres - Part 0: Equipment - General requirements | EN 60079-0 | - |
| IEC 60079-1 | - | Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d" | EN 60079-1 | - |
| IEC 60079-6 | - | Explosive atmospheres - Part 6: Equipment protection by oil immersion "o" | EN 60079-6 | - |
| IEC 60079-7 | - | Explosive atmospheres - Part 7: Equipment protection by increased safety "e" | EN 60079-7 | - |
| IEC 60079-10-1 | - | Explosive atmospheres - Part 10-1: Classification of areas - Explosive gas atmospheres | EN 60079-10-1 | - |
| IEC 60079-10-2 | - | Explosive atmospheres - Part 10-2: Classification of areas - Combustible dust atmospheres | EN 60079-10-2 | - |
| IEC 60079-11 | - | Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i" | EN 60079-11 | - |
| IEC 60079-13 | - | Explosive atmospheres - Part 13: Equipment protection by pressurized room "p" | EN 60079-13 | - |
| IEC 60079-15 | - | Explosive atmospheres - Part 15: Equipment protection by type of protection "n" | EN 60079-15 | - |
| IEC/TR 60079-16 | - | Electrical apparatus for explosive gas atmospheres - Part 16: Artificial ventilation for the protection of analyzer(s) houses | - | - |
| IEC 60079-17 | - | Explosive atmospheres - Part 17: Electrical installations inspection and maintenance | EN 60079-17 | - |
| IEC 60079-18 | - | Explosive atmospheres - Part 18: Equipment protection by encapsulation "m" | EN 60079-18 | - |

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|----------------------|-------------|--|----------------------------|--------------|
| IEC 60079-19 | - | Explosive atmospheres - Part 19: Equipment repair, overhaul and reclamation | EN 60079-19 | - |
| IEC 60079-26 | - | Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga | EN 60079-26 | - |
| IEC 60079-28 | - | Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation | EN 60079-28 | - |
| IEC 60079-29-1 | - | Explosive atmospheres - Part 29-1: Gas detectors - Performance requirements of detectors for flammable gases | EN 60079-29-1 | - |
| IEC 60079-29-4 | - | Explosive atmospheres - Part 29-4: Gas detectors - Performance requirements of open path detectors for flammable gases | EN 60079-29-4 | - |
| IEC 60079-30-1 | - | Explosive atmospheres - Part 30-1: Electrical resistance trace heating - General and testing requirements | EN 60079-30-1 | - |
| IEC 60243-1 | - | Electric strength of insulating materials - Test methods - Part 1: Tests at power frequencies | EN 60243-1 | - |
| IEC 60332-1-2 | - | Tests on electric and optical fibre cables under fire conditions - Part 1-2: Test for vertical flame propagation for a single insulated wire or cable - Procedure for 1 kW pre-mixed flame | EN 60332-1-2 | - |
| IEC 60364 | Series | Low voltage electrical installations | HD 60364 | Series |
| IEC 60364-4-41 (mod) | 2005 | Low-voltage electrical installations - Part 4-41: Protection for safety - Protection against electric shock | HD 60364-4-41 + corr. July | 2007 2007 |
| IEC 60950 | Series | Information technology equipment - Safety | EN 60950 | Series |
| IEC 61010-1 | - | Safety requirements for electrical equipment for measurement, control and laboratory use - Part 1: General requirements | EN 61010-1 | - |
| IEC 61285 | - | Industrial-process control - Safety of analyser houses | EN 61285 | - |
| IEC 61558-2-6 | - | Safety of transformers, reactors, power supply units and similar products for supply voltages up to 1 100 V - Part 2-6: Particular requirements and tests for safety isolating transformers and power supply units incorporating safety isolating transformers | EN 61558-2-6 | - |
| IEC 62305-3 (mod) | 2010 | Protection against lightning - Part 3: Physical damage to structures and life hazard | EN 62305-3 | 2011 |



IEC 60079-14

Edition 5.0 2013-11

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Explosive atmospheres –
Part 14: Electrical installations design, selection and erection**

**Atmosphères explosives –
Partie 14: Conception, sélection et construction des installations électriques**





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalelement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



INTERNATIONAL STANDARD

NORME INTERNATIONALE



Explosive atmospheres –

Part 14: Electrical installations design, selection and erection

Atmosphères explosives –

Partie 14: Conception, sélection et construction des installations électriques

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX **XG**

ICS 26.260.20

ISBN 978-2-8322-1276-9

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

| | |
|--|----|
| FOREWORD | 11 |
| INTRODUCTION | 16 |
| 1 Scope | 18 |
| 2 Normative references | 19 |
| 3 Terms and definitions | 20 |
| 3.1 General | 20 |
| 3.2 Hazardous areas | 21 |
| 3.3 Flameproof enclosure | 22 |
| 3.4 Increased safety | 22 |
| 3.5 Intrinsic safety | 23 |
| 3.6 Intrinsic safety parameters | 24 |
| 3.7 Pressurization | 24 |
| 3.8 Type of protection "n" | 24 |
| 3.9 oil-immersion "o" | 25 |
| 3.10 powder filling "q" | 25 |
| 3.11 encapsulation "m" | 25 |
| 3.12 protection by enclosure "t" | 25 |
| 3.13 Electrical supply systems | 25 |
| 3.14 Equipment | 25 |
| 3.15 radio frequency identification RFID | 26 |
| 4 General | 26 |
| 4.1 General requirements | 26 |
| 4.2 Documentation | 27 |
| 4.3 Initial inspection | 28 |
| 4.4 Assurance of conformity of equipment | 28 |
| 4.4.1 Equipment with certificates according to IEC standards | 28 |
| 4.4.2 Equipment without certificates according to IEC standards | 28 |
| 4.4.3 Selection of repaired, second hand or existing equipment | 29 |
| 4.5 Qualifications of personnel | 29 |
| 5 Selection of equipment | 29 |
| 5.1 Information requirements | 29 |
| 5.2 Zones | 30 |
| 5.3 Relationship between equipment protection levels (EPLs) and zones | 30 |
| 5.4 Selection of equipment according to EPLs | 30 |
| 5.4.1 General | 30 |
| 5.4.2 Relationship between EPLs and types of protection | 30 |
| 5.4.3 Equipment for use in locations requiring EPL "Ga" or "Da" | 32 |
| 5.4.4 Equipment for use in locations requiring EPL "Gb" or "Db" | 32 |
| 5.4.5 Equipment for use in locations requiring EPL "Gc" or "Dc" | 32 |
| 5.5 Selection according to equipment grouping | 32 |
| 5.6 Selection according to the ignition temperature of the gas, vapour or dust and ambient temperature | 33 |
| 5.6.1 General | 33 |
| 5.6.2 Gas or vapour | 33 |
| 5.6.3 Dust | 34 |
| 5.7 Selection of radiating equipment | 36 |
| 5.7.1 General | 36 |

| | | | |
|------|--------|--|----|
| | 5.7.2 | Ignition process | 36 |
| 5.8 | | Selection of ultrasonic equipment | 36 |
| | 5.8.1 | General | 36 |
| | 5.8.2 | Ignition process | 37 |
| 5.9 | | Selection to cover external influences | 37 |
| 5.10 | | Selection of transportable, portable and personal equipment | 38 |
| | 5.10.1 | General | 38 |
| | 5.10.2 | Transportable and portable equipment..... | 39 |
| | 5.10.3 | Personal equipment..... | 39 |
| 5.11 | | Rotating electrical machines | 39 |
| | 5.11.1 | General | 39 |
| | 5.11.2 | Environmental Factors for “Ex” machine installation..... | 40 |
| | 5.11.3 | Power and accessory connections, grounding..... | 40 |
| | 5.11.4 | Motors fed from a converter supply..... | 41 |
| | 5.11.5 | Switching motors above 1kV..... | 41 |
| 5.12 | | Luminaires | 42 |
| 5.13 | | Plugs and socket outlets | 42 |
| | 5.13.1 | General | 42 |
| | 5.13.2 | Specific requirements for explosive dust atmospheres | 42 |
| | 5.13.3 | Location..... | 42 |
| 5.14 | | Cells and batteries | 42 |
| | 5.14.1 | Charging of secondary cells and batteries | 42 |
| | 5.14.2 | Ventilation | 43 |
| 5.15 | | RFID tags | 43 |
| | 5.15.1 | General | 43 |
| | 5.15.2 | Passive RFID tags | 43 |
| | 5.15.3 | Mounting RFID tags | 43 |
| 5.16 | | Gas detection equipment | 43 |
| 6 | | Protection from dangerous (incendive) sparking | 44 |
| 6.1 | | Light metals as construction materials | 44 |
| 6.2 | | Danger from live parts..... | 44 |
| 6.3 | | Danger from exposed and extraneous conductive parts | 44 |
| | 6.3.1 | General | 44 |
| | 6.3.2 | TN type of system earthing | 45 |
| | 6.3.3 | TT type of system earthing | 45 |
| | 6.3.4 | IT type of system earthing | 45 |
| | 6.3.5 | SELV and PELV systems..... | 45 |
| | 6.3.6 | Electrical separation | 45 |
| | 6.3.7 | Non Ex electrical equipment above hazardous areas | 45 |
| 6.4 | | Potential equalization..... | 46 |
| | 6.4.1 | General | 46 |
| | 6.4.2 | Temporary bonding..... | 47 |
| 6.5 | | Static electricity | 47 |
| | 6.5.1 | General | 47 |
| | 6.5.2 | Avoidance of a build-up of electrostatic charge on construction and protecting parts for locations requiring EPL “Ga”, “Gb” and “Gc” | 47 |
| | 6.5.3 | Avoidance of a build-up of electrostatic charge on construction and protecting parts for locations requiring EPL “Da”, “Db” and “Dc” | 49 |

| | | |
|--------|--|----|
| 6.6 | Lightning protection | 49 |
| 6.7 | Electromagnetic radiation..... | 49 |
| 6.7.1 | General | 49 |
| 6.7.2 | Radio frequency received in hazardous areas..... | 49 |
| 6.8 | Cathodically protected metallic parts..... | 50 |
| 6.9 | Ignition by optical radiation | 50 |
| 7 | Electrical protection | 51 |
| 8 | Switch-off and electrical isolation..... | 51 |
| 8.1 | General..... | 51 |
| 8.2 | Switch-off..... | 51 |
| 8.3 | Electrical isolation..... | 51 |
| 9 | Cables and wiring systems | 52 |
| 9.1 | General..... | 52 |
| 9.2 | Aluminium conductors..... | 52 |
| 9.3 | Cables | 52 |
| 9.3.1 | General | 52 |
| 9.3.2 | Cables for fixed installations | 52 |
| 9.3.3 | Flexible cables for fixed installations (excluding intrinsically safe circuits) | 53 |
| 9.3.4 | Flexible cables supplying transportable and portable equipment (excluding intrinsically safe circuits) | 53 |
| 9.3.5 | Single insulated wires (excluding intrinsically safe circuits)..... | 54 |
| 9.3.6 | Overhead lines | 54 |
| 9.3.7 | Avoidance of damage | 54 |
| 9.3.8 | Cable surface temperature..... | 54 |
| 9.3.9 | Resistance to flame propagation..... | 54 |
| 9.4 | Conduit systems | 55 |
| 9.5 | Additional requirements | 56 |
| 9.6 | Installation requirements | 56 |
| 9.6.1 | Circuits traversing a hazardous area..... | 56 |
| 9.6.2 | Terminations..... | 56 |
| 9.6.3 | Unused cores | 56 |
| 9.6.4 | Openings in walls | 56 |
| 9.6.5 | Passage and collection of flammables | 56 |
| 9.6.6 | Accumulation of dust | 57 |
| 10 | Cable entry systems and blanking elements | 57 |
| 10.1 | General..... | 57 |
| 10.2 | Selection of cable glands | 57 |
| 10.3 | Connections of cables to equipment..... | 58 |
| 10.4 | Additional requirements for entries other than Ex “d”, Ex “t” or Ex “nR” | 59 |
| 10.5 | Unused openings | 59 |
| 10.6 | Additional requirements for type of protection “d” – Flameproof enclosures | 59 |
| 10.6.1 | General | 59 |
| 10.6.2 | Selection of cable glands | 60 |
| 10.7 | Additional requirements for type of protection “t” – Protection by enclosure | 60 |
| 10.8 | Additional requirements for type of protection “nR” – Restricted breathing enclosure | 61 |

| | | |
|--------|---|----|
| 11 | Rotating electrical machines | 61 |
| 11.1 | General..... | 61 |
| 11.2 | Motors with type of protection “d” – Flameproof enclosures | 61 |
| 11.2.1 | Motors with a converter supply | 61 |
| 11.2.2 | Reduced-voltage starting (soft starting) | 62 |
| 11.3 | Motors with type of protection “e” – Increased safety | 62 |
| 11.3.1 | Mains-operated..... | 62 |
| 11.3.2 | Winding temperature sensors | 63 |
| 11.3.3 | Machines with rated voltage greater than 1 kV..... | 64 |
| 11.3.4 | Motors with converter supply | 64 |
| 11.3.5 | Reduced-voltage starting (soft starting) | 64 |
| 11.4 | Motors with type of protection “p” and “pD” – Pressurized enclosures | 64 |
| 11.4.1 | Motors with a converter supply | 64 |
| 11.4.2 | Reduced-voltage starting (soft starting) | 65 |
| 11.5 | Motors with type of protection “t” – Protection by enclosures supplied at varying frequency and voltage | 65 |
| 11.5.1 | Motors with a converter supply | 65 |
| 11.5.2 | Reduced-voltage starting (soft starting) | 66 |
| 11.6 | Motors with type of protection “nA” – Non-sparking | 66 |
| 11.6.1 | Motors with converter supply | 66 |
| 11.6.2 | Reduced-voltage starting (soft starting) | 66 |
| 11.6.3 | Machines with rated voltage greater than 1 kV..... | 66 |
| 12 | Luminaires..... | 67 |
| 13 | Electric heating systems | 67 |
| 13.1 | General..... | 67 |
| 13.2 | Temperature monitoring | 67 |
| 13.3 | Limiting temperature | 68 |
| 13.4 | Safety device | 68 |
| 13.5 | Electrical trace heating systems..... | 69 |
| 14 | Additional requirements for type of protection “d” – Flameproof enclosures | 69 |
| 14.1 | General..... | 69 |
| 14.2 | Solid obstacles | 70 |
| 14.3 | Protection of flameproof joints..... | 70 |
| 14.4 | Conduit systems | 71 |
| 15 | Additional requirements for type of protection “e” – Increased safety | 71 |
| 15.1 | General..... | 71 |
| 15.2 | Maximum dissipated power of terminal box enclosures | 72 |
| 15.3 | Conductor terminations | 72 |
| 15.4 | Maximum number of conductors in relation to the cross-section and the permissible continuous current..... | 73 |
| 16 | Additional requirements for types of protection “i” – Intrinsic safety | 73 |
| 16.1 | General..... | 73 |
| 16.2 | Installations to meet the requirements of EPL “Gb” or “Gc” and “Db” or “Dc” | 74 |
| 16.2.1 | Equipment | 74 |
| 16.2.2 | Cables | 75 |
| 16.2.3 | Earthing of intrinsically safe circuits | 79 |
| 16.2.4 | Verification of intrinsically safe circuits | 80 |
| 16.3 | Installations to meet the requirements of EPL “Ga” or “Da” | 81 |

| | | |
|---------------------|--|----|
| 16.4 | Simple apparatus | 82 |
| 16.5 | Terminal boxes | 84 |
| 16.5.1 | General | 84 |
| 16.5.2 | Terminal boxes with only one intrinsically safe circuit | 84 |
| 16.5.3 | Terminal boxes with more than one intrinsically safe circuit | 84 |
| 16.5.4 | Terminal boxes with non-intrinsically safe and intrinsically safe circuits | 85 |
| 16.5.5 | Plugs and sockets used for external connections | 85 |
| 16.6 | Special applications | 85 |
| 17 | Additional requirements for pressurized enclosures | 85 |
| 17.1 | General..... | 85 |
| 17.2 | Type of protection “p”..... | 86 |
| 17.2.1 | General | 86 |
| 17.2.2 | Ducting | 86 |
| 17.2.3 | Action to be taken on failure of pressurization..... | 87 |
| 17.2.4 | Multiple pressurized enclosures with a common safety device | 89 |
| 17.2.5 | Purging..... | 89 |
| 17.2.6 | Protective gas..... | 90 |
| 17.3 | Type of protection “pD” | 90 |
| 17.3.1 | Sources of protective gas | 90 |
| 17.3.2 | Automatic switch-off | 91 |
| 17.3.3 | Alarm..... | 91 |
| 17.3.4 | Common source of protective gas..... | 91 |
| 17.3.5 | Switching on electrical supply..... | 91 |
| 17.4 | Rooms for explosive gas atmosphere..... | 91 |
| 17.4.1 | Pressurized rooms..... | 91 |
| 17.4.2 | Analyser houses | 92 |
| 18 | Additional requirements for type of protection “n”..... | 92 |
| 18.1 | General..... | 92 |
| 18.2 | “nR” equipment | 92 |
| 18.3 | Combinations of terminals and conductors for general connection and junction boxes..... | 93 |
| 18.4 | Conductor terminations | 93 |
| 19 | Additional requirements for type of protection “o”– Oil immersion | 93 |
| 19.1 | General..... | 93 |
| 19.2 | External connections..... | 94 |
| 20 | Additional requirements for type of protection “q” – Powder filling..... | 94 |
| 21 | Additional requirements for type of protection “m” – Encapsulation | 94 |
| 22 | Additional requirements for type of protection “op” – Optical radiation | 94 |
| 23 | Additional requirements for type of protection “t” – Protection by enclosure | 95 |
| Annex A (normative) | Knowledge, skills and competencies of responsible persons, operatives/technicians and designers | 96 |
| A.1 | Scope | 96 |
| A.2 | Knowledge and skills | 96 |
| A.2.1 | Responsible persons | 96 |
| A.2.2 | Operatives/technicians (selection and erection) | 96 |
| A.2.3 | Designers (design and selection) | 96 |
| A.3 | Competencies | 97 |

| | | |
|-----------------------|---|-----|
| A.3.1 | General | 97 |
| A.3.2 | Responsible persons | 97 |
| A.3.3 | Operatives/technicians | 97 |
| A.3.4 | Designers | 97 |
| A.4 | Assessment | 98 |
| Annex B (informative) | Safe work procedure guidelines for explosive gas atmospheres | 99 |
| Annex C (normative) | Initial inspection – Equipment-specific inspection schedules | 100 |
| Annex D (informative) | Electrical installations in extremely low ambient temperature | 105 |
| D.1 | General..... | 105 |
| D.2 | Cables | 105 |
| D.3 | Electrical trace heating systems..... | 105 |
| D.4 | Lighting systems | 105 |
| D.4.1 | General | 105 |
| D.4.2 | Emergency lights | 105 |
| D.5 | Electrical rotating machines | 105 |
| Annex E (informative) | Restricted breathing test for cables | 106 |
| E.1 | Test procedure..... | 106 |
| Annex F (informative) | Installation of electrical trace heating systems..... | 107 |
| F.1 | General..... | 107 |
| F.2 | Definitions..... | 107 |
| F.2.1 | Electrical trace heating system | 107 |
| F.2.2 | System components | 107 |
| F.2.3 | Site-fabricated trace heaters..... | 107 |
| F.2.4 | Location of sensors | 108 |
| F.2.5 | Thermal insulation | 108 |
| F.2.6 | Personnel aspects | 108 |
| F.3 | General requirements | 108 |
| F.4 | Requirements for EPL “Gb”, “Gc”, “Db” and “Dc” | 109 |
| F.4.1 | General | 109 |
| F.4.2 | Stabilized design | 109 |
| F.4.3 | Controlled design..... | 109 |
| F.5 | Design information | 110 |
| F.5.1 | Design information drawings and documents | 110 |
| F.5.2 | Isometric or heater configuration line lists and load charts | 110 |
| F.6 | Incoming inspections | 111 |
| F.6.1 | Receiving materials | 111 |
| F.6.2 | Pre-installation testing | 112 |
| F.6.3 | Visual examination | 112 |
| F.6.4 | Insulation resistance test | 112 |
| F.6.5 | Component substitution | 112 |
| F.6.6 | Location of power supply | 112 |
| F.7 | Installation of trace heaters..... | 113 |
| F.7.1 | General | 113 |
| F.7.2 | Connections and terminations | 114 |
| F.7.3 | Conductor terminations..... | 115 |
| F.8 | Installation of control and monitoring equipment | 115 |
| F.8.1 | Verification of equipment suitability..... | 115 |
| F.8.2 | Sensor considerations | 115 |

| | | |
|-----------------------|--|-----|
| F.8.3 | Controller operation, calibration, and access | 119 |
| F.9 | Installation of thermal insulation system..... | 120 |
| F.9.1 | General | 120 |
| F.9.2 | Preparatory work | 120 |
| F.10 | Installation of distribution wiring and coordination with branch circuits | 120 |
| F.10.1 | General | 120 |
| F.10.2 | Tagging/identification..... | 120 |
| F.11 | Final installation review..... | 120 |
| F.11.1 | Necessary modifications | 120 |
| F.11.2 | Field (site work) circuit insulation resistance test | 121 |
| F.11.3 | Visual inspection | 121 |
| F.12 | Commissioning | 121 |
| F.12.1 | Pre-commissioning check | 121 |
| F.12.2 | Functional check and final documentation..... | 121 |
| Annex G (normative) | Potential stator winding discharge risk assessment – Ignition risk factors | 124 |
| Annex H (normative) | Verification of intrinsically safe circuits with more than one associated apparatus with linear current/voltage characteristics | 125 |
| H.1 | General..... | 125 |
| H.2 | Intrinsic safety with level of protection “ib” | 125 |
| H.3 | Intrinsic safety with level of protection “ic”..... | 125 |
| Annex I (informative) | Methods of determining the maximum system voltages and currents in intrinsically safe circuits with more than one associated apparatus with linear current/voltage characteristics (as required by Annex H)..... | 126 |
| I.1 | Intrinsically safe circuits with linear current/voltage characteristics | 126 |
| I.2 | Intrinsically safe circuits with non-linear current/voltage characteristics | 128 |
| Annex J (informative) | Determination of cable parameters | 129 |
| J.1 | Measurements | 129 |
| J.2 | Cables carrying more than one intrinsically safe circuit | 129 |
| J.2.1 | General | 129 |
| J.2.2 | Type A cables..... | 129 |
| J.2.3 | Type B cables..... | 130 |
| J.2.4 | Type C cables..... | 130 |
| J.3 | FISCO..... | 130 |
| Annex K (normative) | Additional requirements for type of protection “op” – Optical radiation | 131 |
| K.1 | General..... | 131 |
| K.2 | Inherently safe optical radiation “op is” | 131 |
| K.2.1 | General | 131 |
| K.2.2 | Change of cross sections..... | 131 |
| K.2.3 | Coupler..... | 131 |
| K.3 | Protected optical radiation “op pr” | 131 |
| K.3.1 | General | 131 |
| K.3.2 | Radiation inside enclosures | 132 |
| K.4 | Optical radiation interlocked with optical breakage “op sh” | 132 |
| Annex L (informative) | Examples of dust layers of excessive thickness | 133 |
| Annex M (informative) | Hybrid mixtures..... | 134 |
| M.1 | General..... | 134 |
| M.2 | Concentration limits | 134 |

| | | |
|--|-----------------------------------|-----|
| M.3 | Energy/temperature limits | 134 |
| M.4 | Selection of equipment..... | 134 |
| M.5 | Use of flameproof equipment | 134 |
| M.6 | Electrostatic hazard | 134 |
| M.7 | Installation requirements | 135 |
| Bibliography..... | | 136 |
| Figure 1 – Correlation between the maximum permissible surface temperature and depth of dust layers | | 35 |
| Figure 2 – Earthing of conducting screens | | 76 |
| Figure F.1 – Typical installation of control sensor and sensor for temperature limiting control | | 117 |
| Figure F.2 – Limiting device sensor on sheath of trace heater..... | | 118 |
| Figure F.3 – Limiting device sensor as artificial hot spot | | 119 |
| Figure I.1 – Series connection – Summation of voltage | | 127 |
| Figure I.2 – Parallel connection – Summation of currents..... | | 127 |
| Figure I.3 – Series and parallel connections – Summations of voltages and summations of currents..... | | 128 |
| Figure L.1 – Examples for dust layers of excessive thickness with the requirement of laboratory investigation | | 133 |
| Table 1 – Equipment protection levels (EPLs) where only zones are assigned | | 30 |
| Table 2 – Default relationship between types of protection and EPLs..... | | 31 |
| Table 3 – Relationship between gas/vapour or dust subdivision and equipment group | | 33 |
| Table 4 – Relationship between gas or vapour ignition temperature and temperature class of equipment..... | | 34 |
| Table 5 – Limitation of surface areas | | 48 |
| Table 6 – Maximum diameter or width..... | | 48 |
| Table 7 – Limitation of thickness of non-metallic layer | | 48 |
| Table 8 – Radio frequency power thresholds..... | | 50 |
| Table 9 – Radio-frequency energy thresholds | | 50 |
| Table 10 – Selection of glands, adapters and blanking elements type of protection according to the enclosure type of protection | | 58 |
| Table 11 – Level of protection, equipment group and ingress protection relationship | | 61 |
| Table 12 – Requirements for the temperature monitoring systems | | 68 |
| Table 13 – Minimum distance of obstruction from the flameproof flange joints related to the gas group of the hazardous area..... | | 70 |
| Table 14 – Example of defined terminal/conductor arrangement – Maximum number of wires in relation to the cross-section and the permissible continuous current | | 73 |
| Table 15 – Variation in maximum power dissipation with ambient temperature for Equipment Group II..... | | 83 |
| Table 16 – Determination of type of protection (with no flammable release within the enclosure)..... | | 86 |
| Table 17 – Use of spark and particle barriers | | 87 |
| Table 18 – Summary of protection requirements for enclosures without an internal source of release | | 88 |
| Table 19 – Summary of protection requirements for enclosures | | 90 |

| | |
|--|-----|
| Table C.1 – Inspection schedule for Ex “d”, Ex “e”, Ex “n” and Ex “t”..... | 100 |
| Table C.2 – Initial inspection schedule for Ex “I” installations | 102 |
| Table C.3 – Inspection schedule for Ex “p” and “pD” installations..... | 103 |
| Table F.1 – Pre-installation checks | 113 |
| Table F.2 – Electrical trace heating systems installation record – Example | 123 |
| Table G.1 – Ignition risk factors | 124 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

EXPLOSIVE ATMOSPHERES –**Part 14: Electrical installations design, selection and erection****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60079-14 has been prepared by subcommittee 31J: Classification of hazardous areas and installation requirements, of IEC technical committee 31: Equipment for explosive atmospheres.

This fifth edition cancels and replaces the fourth edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

| Explanation of the significance of the changes | Clause | Type | | |
|--|--|------------------------------------|------------------|--------------------------------|
| | | Minor and editorial changes | Extension | Major technical changes |
| Introduction of initial inspection | Scope | | X | |
| Introduction of definition “electrical equipment” | 3.1.3 | X | | |
| Introduction of definition “hybrid mixture” | 3.2.4 | | X | |
| Note added to the definition “associated apparatus” | 3.5.2 | X | | |
| Introduction of definition “radio frequency identification” | 3.15 | X | | |
| List for documents improved and extended: site, equipment, installation and personnel | 4.2 | X | | |
| New subclause for initial inspection | 4.3 | | X | |
| Specific requirements given in this standard based on the current edition of the IEC standards in the IEC 60079 series. | 4.4.1.2 | X | | |
| New selection criteria for radiating equipment according to IEC 60079-0 | 5.7 | | X | |
| New selection criteria for ultrasonic equipment according to IEC 60079-0 | 5.8 | | X | |
| Specific requirements for cells and batteries used in transportable, portable and personal equipment aligned with IEC 60079-11 | 5.10 | | | C1 |
| New structure for the selection of rotating electrical machines | 5.11 | X | | |
| New selection criteria for cells and batteries | 5.14 | | X | |
| New selection criteria for radio frequency identification tags | 5.15 | | X | |
| New selection criteria for gas detection equipment | 5.16 | | X | |
| The requirements for material composition of metallic installation material aligned with the requirements for light metal according to IEC 60079-0 | 6.1 | | X | |
| Above hazardous area, the restriction of 3,5 m deleted | 6.3.7 | X | | |
| New structure of the requirements for static electricity according to IEC 60079-0 added | 6.5 | | X | |
| New requirements for electromagnetic radiation in accordance with IEC 60079-0 | 6.7 | | X | |
| Improvement of the text for cables, cables for fixed and flexible cables for fixed installation for easier reading | 9.3.1 9.3.2 9.3.3 | X | | |
| New structure of the requirements for cable entry system and blanking elements with subclauses – General – Connections of cables to equipment – Selection of cable glands with the new Table 10 – Additional requirements for cable glands other than Ex “d”, Ex “t” or Ex “nR” – Additional requirements for Ex “d” – Additional requirements for Ex “t” – Additional requirements for Ex “nR” | 10 10.1 10.2 10.3 10.4 10.5 10.6 10.7 10.8 | | X | |
| New structure for the requirements for rotating electrical machines for all types of protections | 11 | | X | |

| Explanation of the significance of the changes | Clause | Type | | |
|---|---------------|------------------------------------|------------------|--------------------------------|
| | | Minor and editorial changes | Extension | Major technical changes |
| New structure for the requirements for electric heating systems including temperature monitoring, limiting temperature, safety device and additional requirements for electrical heat tracing system | 13 | | X | |
| New subclause to limit the dissipation power of terminal boxes as a function of the numbers of wire in relation to the cross-section and the permissible continuous current with an example | 15.4 | | X | |
| Improvement of the text for simple apparatus with its definition, limits and the variation in maximum power dissipation based on the ambient temperature and an alternative equation to calculate the max. surface temperature. | 16.4 | | X | |
| New requirements for terminal boxes if containing more than one intrinsically safe circuit to avoid short-circuits between independent intrinsically safe circuits | 16.5 | | | C2 |
| Improvement of the text for terminal boxes with non-intrinsically and intrinsically safe circuits | 16.5.4 | X | | |
| New subclause for pressurized rooms and analyser houses | 17.4 | | X | |
| New clause for optical radiation | 22 | | X | |
| New annex for initial inspection with the equipment specific inspection schedule for all types of protections | Annex C | | X | |
| New annex for electrical installations in extremely low ambient temperature | Annex D | | X | |
| New annex for the restricted migration of gas through cables | Annex E | | X | |
| New annex for installation of electrical trace heating systems | Annex F | | X | |
| New annex for the requirements for type of protection "op" – Optical radiation | Annex K | | X | |
| New annex for hybrid mixtures | Annex M | | X | |

| Explanation of the types of significant changes: | |
|---|--|
| A) Definitions | |
| 1. Minor and editorial changes: | <ul style="list-style-type: none"> – Clarification – Decrease of technical requirements – Minor technical change – Editorial corrections |
| These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in the level of existing requirement. | |
| 2. Extension: | <ul style="list-style-type: none"> – Addition of technical options |
| These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing the requirements for the design, selection and erection of existing installations that are fully compliant with the previous standard. Therefore, these will not have to be considered for existing installations in conformity with the preceding edition. | |
| 3. Major technical changes: | <ul style="list-style-type: none"> – Addition of technical requirements – Increase of technical requirements |
| These are changes to technical requirements (addition, increase of the level or removal) made in a way that an existing installation in conformity with the preceding edition will not always be able to fulfil the requirements given in the later edition. These changes have to be considered for existing installations in conformity with the preceding edition, for which additional information is provided in B) below. | |
| These changes represent the latest state-of-the-art technology. However, these changes should not normally have an influence on existing installations. | |
| B) Information about the background of “major technical changes” | |
| <p>C1 Due to the risk of gassing producing hydrogen from all cell types, adequate provision for venting is required as the gassing can create an explosive condition in small enclosures. This condition would apply to torches, multi meters, pocket gas sensors and similar items. Alternatively, where the equipment meets the requirements for Equipment Group IIC, the requirement of degassing apertures or limitation of hydrogen concentration does not apply.</p> <p>C2 An individual intrinsically safe circuit is also safe under short-circuit conditions. The short-circuit between two independent intrinsically safe circuits is not considered. Therefore the terminal boxes have to meet additional requirements for IP rating as well for the mechanical impact to make sure that the integrity of the enclosure is given also under worst case conditions.</p> | |

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|--------------|------------------|
| 31J/225/FDIS | 31J/230/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60079 series, under the general title *Explosive atmospheres*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Preventive measures to reduce the explosion risk from flammable materials are based on three principles, which are normally applied in the following order:

- 1) substitution
- 2) control
- 3) mitigation

Substitution involves, for example, replacing a flammable material by one which is either not flammable or less flammable.

Control involves, for example:

- a) reducing the quantity of flammables;
- b) avoiding or minimising releases;
- c) controlling the release;
- d) preventing the formation of an explosive atmosphere;
- e) collecting and containing releases; and
- f) avoiding ignition sources.

NOTE 1 With the exception of item f), all of the above are part of the process of hazardous area classification.

Mitigation involves, for example:

- 1) reducing the number of people exposed;
- 2) providing measures to avoid the propagation of an explosion;
- 3) providing explosion pressure relief;
- 4) providing explosion pressure suppression; and
- 5) providing suitable personal protective equipment.

NOTE 2 The above items are part of consequence management when considering risk.

Once the principles of substitution and control (items a) to e)) have been applied, the remaining hazardous areas should be classified into zones according to the likelihood of an explosive atmosphere being present (see IEC 60079-10-1 or IEC 60079-10-2). Such classification, which may be used in conjunction with an assessment of the consequences of an ignition, allows equipment protection levels to be determined and hence appropriate types of protection to be specified for each location.

For an explosion to occur, an explosive atmosphere and a source of ignition need to co-exist. Protective measures aim to reduce, to an acceptable level, the likelihood that the electrical installation could become a source of ignition.

By careful design of the electrical installation, it is frequently possible to locate much of the electrical equipment in less hazardous or non-hazardous areas.

When electrical equipment is installed in areas where explosive concentrations and quantities of flammable gases vapours or dusts may be present in the atmosphere, protective measures are applied to reduce the likelihood of explosion due to ignition by arcs, sparks or hot surfaces, produced either in normal operation or under specified fault conditions.

Many types of dust that are generated, processed, handled and stored, are combustible. When ignited they can burn rapidly and with considerable explosive force if mixed with air in the appropriate proportions. It is often necessary to use electrical equipment in locations where such materials are present, and suitable precautions should therefore be taken to

ensure that all such equipment is adequately protected so as to reduce the likelihood of ignition of the external explosive atmosphere. In electrical equipment, potential ignition sources include electrical arcs and sparks, hot surfaces and frictional sparks.

Dust can be ignited by equipment in several ways:

- by surfaces of the equipment that are above the minimum ignition temperature of the dust concerned. The temperature at which a type of dust ignites is a function of the properties of the dust, whether the dust is in a cloud or layer, the thickness of the layer and the geometry of the heat source;
- by arcing or sparking of electrical parts such as switches, contacts, commutators, brushes, or the like;
- by discharge of an accumulated electrostatic charge;
- by radiated energy (e.g. electromagnetic radiation);
- by mechanical sparking or frictional sparking associated with the equipment.

In order to avoid dust ignition hazards it is important that:

- the temperature of surfaces on which dust can be deposited, or which would be in contact with a dust cloud, is kept below the temperature limitation specified in this standard;
- any electrical sparking parts, or parts having a temperature above the temperature limit specified in this standard:
 - are contained in an enclosure which adequately prevents the ingress of dust, or
 - the energy of electrical circuits is limited so as to avoid arcs, sparks or temperatures capable of igniting dust;
- any other ignition sources are avoided.

Several types of protection are available for electrical equipment in hazardous areas (see IEC 60079-0), and this standard gives the specific requirements for design, selection and erection of electrical installations in explosive atmospheres.

This part of the IEC 60079 series is supplementary to other relevant IEC standards, for example IEC 60364 series as regards electrical installation requirements. This part also refers to IEC 60079-0 and its associated standards for the construction, testing and marking requirements of suitable electrical equipment.

This standard provides the specific requirements for the design, selection, erection and the required initial inspection of electrical equipment in hazardous areas. This standard is also based on manufacturer's instructions being followed. On-going inspection, maintenance and repair aspects also play an important role in control of hazardous area installations and the user's attention is drawn to IEC 60079-17, IEC 60079-19 and manufacturer's instructions for further information concerning these aspects.

In any industrial installation, irrespective of size, there may be numerous sources of ignition apart from those associated with electrical equipment. Precautions may be necessary to ensure safety from other possible ignition sources, but guidance on this aspect is outside the scope of this standard.

EXPLOSIVE ATMOSPHERES –

Part 14: Electrical installations design, selection and erection

1 Scope

This part of the IEC 60079 series contains the specific requirements for the design, selection, erection and initial inspection of electrical installations in, or associated with, explosive atmospheres.

Where the equipment is required to meet other environmental conditions, for example, protection against ingress of water and resistance to corrosion, additional protection requirements may be necessary.

The requirements of this standard apply only to the use of equipment under standard atmospheric conditions as defined in IEC 60079-0. For other conditions, additional precautions may be necessary, and the equipment should be certified for these other conditions. For example, most flammable materials and many materials which are normally regarded as non-flammable might burn vigorously under conditions of oxygen enrichment.

NOTE 1 The standard atmospheric conditions defined in IEC 60079-0 relate to the explosion characteristics of the atmosphere and not the operating range of the equipment i.e.

- Temperature: –20 °C to 60 °C;
- Pressure: 80 kPa (0,8 bar) to 110 kPa (1,1 bar); and
- air with normal oxygen content, typically 21 % v/v.

These requirements are in addition to the requirements for installations in non-hazardous areas.

NOTE 2 For voltages up to 1 000 V a.c. or 1 500 V d.c. requirements of this standard are based on installation requirements in the IEC 60364 series, but other relevant national requirements can apply.

This standard applies to all electrical equipment including fixed, portable, transportable and personal, and installations, permanent or temporary.

This standard does not apply to

- electrical installations in mines susceptible to firedamp;

NOTE 3 This standard can apply to electrical installations in mines where explosive gas atmospheres other than firedamp can be formed and to electrical installations in the surface installation of mines.

- inherently explosive situations and dust from explosives or pyrophoric substances (for example explosives manufacturing and processing);
- rooms used for medical purposes;
- electrical installations in areas where the hazard is due to flammable mist.

NOTE 4 Additional guidance on the requirements for hazards due to hybrid mixtures of dust or flyings and flammable gas or vapour is provided in Annex M.

No account is taken in this Standard of the toxic risks that are associated with flammable gases, liquids and dusts in concentrations that are usually very much less than the lower explosive limit. In locations where personnel may be exposed to potentially toxic concentrations of flammable material, appropriate precautions should be taken. Such precautions are outside the scope of this Standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-1, *Rotating electrical machines – Part 1: Rating and performance*

IEC 60060-1, *High-voltage test techniques - Part 1: General definitions and test requirements*

IEC 60079 (all parts), *Explosive atmospheres*

IEC 60079-0, *Explosive atmospheres – Part 0: Equipment – General requirements*

IEC 60079-1, *Explosive atmospheres – Part 1: Equipment protection by flameproof enclosures "d"*

IEC 60079-6, *Explosive atmospheres – Part 6: Equipment protection by oil immersion "o"*

IEC 60079-7, *Explosive atmospheres – Part 7: Equipment protection by increased safety "e"*

IEC 60079-10-1, *Explosive atmospheres – Part 10-1: Classification of areas - Explosive gas atmospheres*

IEC 60079-10-2, *Explosive atmospheres – Part 10-2: Classification of areas – Combustible dust atmospheres*

IEC 60079-11, *Explosive atmospheres – Part 11: Equipment protection by intrinsic safety "i"*

IEC 60079-13, *Explosive atmospheres – Part 13: Equipment protection by pressurized room "p"*

IEC 60079-15, *Explosive atmospheres – Part 15: Equipment protection by type of protection "n"*

IEC/TR 60079-16, *Electrical apparatus for explosive gas atmospheres – Part 16: Artificial ventilation for the protection of analyzer(s) houses*

IEC 60079-17, *Explosive atmospheres – Part 17: Electrical installations inspection and maintenance*

IEC 60079-18, *Explosive atmospheres – Part 18: Equipment protection by encapsulation "m"*

IEC 60079-19, *Explosive atmospheres – Part 19: Equipment repair, overhaul and reclamation*

IEC 60079-26, *Explosive atmospheres – Part 26: Equipment with equipment protection level (EPL) "Ga"*

IEC 60079-28, *Explosive atmospheres – Part 28: Protection of equipment and transmission systems using optical radiation*

IEC 60079-29-1, *Explosive atmospheres – Part 29-1: Gas detectors – Performance requirements of detectors for flammable gases*

IEC 60079-29-4, *Explosive atmospheres – Part 29-4: Gas detectors – Performance requirements of open path detectors for flammable gases*

IEC 60079-30-1, *Explosive atmospheres – Part 30-1: Electrical resistance trace heating – General and testing requirements*

IEC 60243-1, *Electrical strength of insulating materials – Test methods – Part 1: Tests at power frequencies*

IEC 60332-1-2, *Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW pre-mixed flame*

IEC 60364 (all parts), *Low-voltage electrical installations*

IEC 60364-4-41:2005, *Low-voltage electrical installations – Part 4-41: Protection for safety – Protection against electric shock*

IEC 60950 (all parts), *Information technology equipment – Safety*

IEC 61010-1, *Safety requirements for electrical equipment for measurement, control, and laboratory use – Part 1: General requirements*

IEC 61285, *Industrial process control – Safety of analyser houses*

IEC 61558-2-6, *Safety of transformers, reactors, power supply units and similar products for supply voltages up to 1 100 V – Part 2-6: Particular requirements and tests for safety isolating transformers and power supply units incorporating safety isolating transformers*

IEC 62305-3:2010, *Protection against lightning – Part 3: Physical damage to structures and life hazard*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN