

	Káblové siete pre televízne signály, rozhlasové signály a interaktívne služby. Časť 10-1: Usmernenia na zavádzanie spätných kanálov v káblových sieťach.	TNI CLC/TR 50083-10-1 36 7211
--	---	---

Táto technická normalizačná informácia obsahuje anglickú verziu CLC/TR 50083-10-1:2014.
This Technical standard information includes the English version of CLC/TR 50083-10-1:2014.

Táto technická normalizačná informácia bola oznámená vo Vestníku ÚNMS SR č. 11/14

Oznámením tohto dokumentu sa ruší
TNI CLC/TR 50083-10-1 (36 7211) z mája 2009

119861

TECHNICAL REPORT

CLC/TR 50083-10-1

RAPPORT TECHNIQUE

TECHNISCHER BERICHT

June 2014

ICS 33.060.40

Supersedes CLC/TR 50083-10-1:2009

English Version

Cable networks for television signals, sound signals and interactive services - Part 10-1: Guidelines for the implementation of return paths in cable networks

Réseaux de distribution par câbles pour signaux de télévision, signaux de radiodiffusion sonore et services interactifs - Partie 10-1: Lignes directrices relatives à la mise en oeuvre de la voie de retour dans les réseaux câblés

Kabelnetze für Fernsehsignale, Tonsignale und interaktive Dienste - Teil 10-1: Leitfaden für die Einrichtung von Rückkanälen in Kabelnetzen

This Technical Report was approved by CENELEC on 2014-06-02.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Foreword	5
1 Scope	6
1.1 General	6
1.2 Specific scope of this Technical Report.....	6
2 Normative references.....	6
3 Terms, definitions, symbols and abbreviations.....	7
3.1 Terms and definitions.....	7
3.2 Symbols	10
3.3 Abbreviations	11
4 Network architecture.....	13
4.1 HFC architecture.....	13
4.2 Upgrade alternatives.....	15
4.3 Active or passive return path	25
4.4 In building network	25
4.5 In home network	25
5 Network design.....	26
5.1 Considerations	26
5.2 Return path loss, path loss difference and return path slope	26
5.3 Noise and nonlinearity, optimizing signal levels	31
5.4 Isolation between outlets	33
5.5 Equalization and filtering in return paths.....	33
6 Channel planning	36
6.1 Purpose of this section.....	36
6.2 Introduction	36
6.3 Summary.....	36
6.4 Considerations for channel planning	37
6.5 Common path distortion products.....	41
6.6 European upstream bandwidths	41
6.7 Channel width	41
6.8 QPSK/16QAM operation and channel widths.....	41
6.9 Available return path spectrum (Table 8).....	42
6.10 Channel plans	43
6.11 Network radiation	45
7 Equipment for return path implementation	45
7.1 General	45
7.2 Return path amplifiers.....	45
8 Installation and maintenance.....	48

8.1	Signal level adjustment	48
8.2	Monitoring and measurements	52
Annex A	(informative) Interference on return path.....	54
A.1	Multiple interference.....	54
A.2	Impulse interference	63
A.3	Interference from home terminals — EMC standards of home terminals	65
A.4	Hum modulation.....	66
A.5	Common path distortion (CPD).....	66
Annex B	(informative) Null packet and PRBS definitions.....	74
B.1	Null packet definition.....	74
B.2	PRBS definition.....	74
Annex C	(informative) ITU DWDM grid.....	75
Bibliography		77
Figures		
Figure 1	— Typical HFC topology	14
Figure 2	— Regional network.....	15
Figure 3	— Trunk-and-distribution architecture using only coaxial equipment	15
Figure 4	— HFC system	16
Figure 5	— Generic diagram showing the mapping of nodes and CMTS(s) to segments.....	17
Figure 6	— Segment comprising a single CMTS to N optical nodes	17
Figure 7	— Spectrum allocation bandwidth.....	18
Figure 8	— Basic node architecture	19
Figure 9	— Re-arranged feeds (two CMTS serving four nodes).....	20
Figure 10	— Optical node with frequency stacking	21
Figure 11	— Divided node.....	21
Figure 12	— Return path segmentation	22
Figure 13	— Division of the node areas using additional fibres	22
Figure 14	— DWDM (CWDM) return path transmission	23
Figure 15	— Digital return technology basic concept.....	23
Figure 16	— Two return paths multiplexed to the transmission stream	24
Figure 17	— Optical node segmentation.....	25
Figure 18	— In house structures for transparent return path transmission.....	26
Figure 19	— Example of forward (862 MHz) and return path (65 MHz) network with operating levels for the drop and in home parts of the network	28
Figure 20	— Example of a block diagram of return path amplifier	46
Figure 21	— Commissioning of the forward path	48
Figure 22	— Commissioning of the return path amplifiers using the same method as on the forward path.....	49
Figure 23	— Problem when commissioning return path amplifiers following the method used for downstream amplifiers (standard output levels).....	49
Figure 24	— Unity gain method.....	50
Figure 25	— Optical reverse path	50

Figure 26 — Optical node with reverse transmitter	51
Figures in annexes	
Figure A.1 — Typical spectrum of a return path.....	54
Figure A.2 — Noise funnelling.....	55
Figure A.3 — Average noise level vs. the number of subscribers and the return path frequency [19].....	56
Figure A.4 — Simplified equivalent circuit of a drop cable	56
Figure A.5 — Screening effectiveness of a coaxial cable vs. frequency	58
Figure A.6 — Spectrogram of noise level vs. frequency and time (example).....	60
Figure A.7 — Maximum, minimum and average noise levels vs. frequency (example)	61
Figure A.8 — Centile analysis of noise levels vs. frequency (example)	62
Figure A.9 — Temporal evolution of the -10 dB(mV) threshold crossing occurrence (example).....	63
Figure A.10 — Frequency evolution of the -10 dB(mV) threshold crossing occurrence (example).....	63
Figure A.11 — Illustration of impulse noise measurement according to the method described in EN 60728-10	65
Figure A.12 — Example for the use of the return path frequency range	66
Figure A.13 — Test set-up for CPD simulation	68
Figure A.14 — Intermodulation products with 8 MHz spacing	68
Figure A.15 — Contact resistance as function of contact pressure	69
Figure A.16 — Upstream pass-band characterization	70
Figure A.17 — Set-up of test signals.....	71
Figure A.18 — Test set-up for passive devices.....	71
Figure A.19 — Test set-up for power passing devices	72
Figure A.20 — Thermal cycle profile	72
Figure A.21 — Spectral response with CPD in the return path.....	73
Tables	
Table 1 — Summary of in home return path losses.....	30
Table 2 — Calculation of return path versus temperature	31
Table 3 — Broadcasting allocations between 5 MHz and 42 MHz	38
Table 4 — Amateur and Citizens Band allocations between 5 MHz and 42 MHz	39
Table 5 — DOCSIS/EuroDOCSIS symbol rates and channel widths	39
Table 6 — Data carriers in the gaps between broadcasting bands	40
Table 7 — Data carriers in the gaps between broadcasting, amateur and CB bands.....	40
Table 8 — Available spectrum between 5 MHz and 65 MHz.....	42
Table 9 — Example of a 1,6 MHz wide channel plan up to 65 MHz (avoiding CPD products)	43
Table 10 — Example of a 3,2 MHz wide channel plan up to 65 MHz.....	44
Table 11 — Permitted radiation 0,3 MHz to 30 MHz (A-Deviation for Great Britain).....	45
Table 12 — Permitted radiation 30 MHz to 68 MHz (A-Deviation for Great Britain).....	45
Table 13 — Split frequencies used in Europe	47
Table 14 — Alarm thresholds for upstream monitoring (example).....	53
Tables in Annexes	
Table A.1 — European EMC standards applicable to home terminals.....	65
Table B.1 — Null transport stream packet definition.....	74
Table C.1 — ITU DWDM grid	75

Foreword

This document (CLC/TR 50083-10-1:2014) has been prepared by CLC/TC 209 "Cable networks for television signals, sound signals and interactive services".

This document supersedes CLC/TR 50083-10-1:2009.

CLC/TR 50083-10-1:2014 includes the following significant technical changes with respect to CLC/TR 50083 10-1:2009:

- a) the introduction of a new "General Scope";
- b) the introduction of new upper frequency limit 85 MHz for return path as an option;
- c) the introduction of some new "Terms and definitions" due to the new general scope and due to the introduction of the extended return path frequency range to 85 MHz;
- d) the deletion of Clause B.1 on "Noise power ratio";
- e) the deletion of Clause B.2 on "10-tone measurement";
- f) the deletion of Clause B.3 on "MER measurement".

EN 50083 is currently composed of the following parts:

- EN 50083-2, *Cable networks for television signals, sound signals and interactive services — Part 2: Electromagnetic compatibility for equipment*;
- CLC/TR 50083-5-1, *Cable networks for television signals, sound signals and interactive services — Part 5-1: IP gateways and interfaces for headends*;
- EN 50083-8, *Cable networks for television signals, sound signals and interactive services — Part 8: Electromagnetic compatibility for networks*;
- EN 50083-9, *Cable networks for television signals, sound signals and interactive services — Part 9: Interfaces for CATV/SMATV headends and similar professional equipment for DVB/MPEG-2 transport streams*;
- EN 50083-10, *Cable networks for television signals, sound signals and interactive services — Part 10: System performance for return paths*;
- CLC/TR 50083-10-1, *Cable networks for television signals, sound signals and interactive services — Part 10-1: Guidelines for the implementation of return paths in cable networks* [the present document].

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

1 Scope

1.1 General

Standards and other deliverables of the EN 50083 and EN 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes for instance:

- regional and local broadband cable networks,
- extended satellite and terrestrial television distribution networks and systems,
- individual satellite and terrestrial television receiving systems
- and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

1.2 Specific scope of this Technical Report

This document is intended to provide guidance to network designers on the issues which should be addressed when considering the design of return paths for regional or local broadband networks.

Items such as return path architecture & design, channel performance, channel planning and sources of interference, measurements, segmentation and re-segmentation, in home networks, distortion and commissioning are included. This document is not intended as a design reference but provides details which need to be addressed on individual issues relating to the design of the return path for a regional or local broadband network.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60728-1:2008, *Cable networks for television signals, sound signals and interactive services — Part 1: System performance of forward paths (IEC 60728-1:2007)*

EN 60728-3, *Cable networks for television signals, sound signals and interactive services — Part 3: Active wideband equipment for cable networks (IEC 60728-3)*

EN 60728-4, *Cable networks for television signals, sound signals and interactive services — Part 4: Passive wideband equipment for coaxial cable networks (IEC 60728-4)*

EN 60728-5, *Cable networks for television signals, sound signals and interactive services — Part 5: Headend equipment (IEC 60728-5)*

EN 60728-6, *Cable networks for television signals, sound signals and interactive services — Part 6: Optical equipment (IEC 60728-6)*

EN 60728-10:2014, *Cable networks for television signals, sound signals and interactive services — Part 10: System performance for return paths (IEC 60728-10:2014)*

ETSI EN 302 878 series, *Access, Terminals, Transmission and Multiplexing (ATTM); Third Generation Transmission Systems for Interactive Cable Television Services — IP Cable Modems*

ETSI ES 201 488 series, *Access and Terminals (AT); Data Over Cable Systems*

ETSI ES 202 488 series, *Access and Terminals (AT); Second Generation Transmission Systems for Interactive Cable Television Services — IP Cable Modems*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN