

STN	Káblové siete pre televízne signály, rozhlasové signály a interaktívne služby. Časť 1: Systémové vlastnosti vzostupnej cesty.	STN EN 60728-1 36 7211
------------	--	--

Cable networks for television signals, sound signals and interactive services - Part 1: System performance of forward paths

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 01/15

Obsahuje: EN 60728-1:2014, IEC 60728-1:2014

Oznámením tejto normy sa od 27.06.2017 ruší
STN EN 60728-1 (36 7211) z januára 2009

119942

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, odbor SÚTN, 2015
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy
rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

EUROPEAN STANDARD

EN 60728-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 2014

ICS 33.060.40

Supersedes EN 60728-1:2008

English Version

**Cable networks for television signals, sound signals and
interactive services - Part 1: System performance of forward
paths
(IEC 60728-1:2014)**

Réseaux de distribution par câbles pour signaux de
télévision, signaux de radiodiffusion sonore et services
interactifs - Partie 1: Caractéristiques des systèmes de voie
directe
(CEI 60728-1:2014)

Kabelnetze für Fernsehsignale, Tonsignale und interaktive
Dienste - Teil 1: Systemanforderungen in Vorwärtsrichtung
(IEC 60728-1:2014)

This European Standard was approved by CENELEC on 2014-06-27. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 100/2269/FDIS, future edition 5 of IEC 60728-1, prepared by Technical Area 5 "Cable networks for television signals, sound signals and interactive services" of IEC/TC 100 "Audio, video and multimedia systems and equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60728-1:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-03-27
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-06-27

This document supersedes EN 60728-1:2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

For this European Standard the informative Annex K of IEC 60728-1:2014 shall be disregarded and has been replaced by the informative Annex ZB "A-deviations".

Annexes ZA and ZB have been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60728-1:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60728 Series	NOTE	Harmonized as EN 60728 Series (not modified).
IEC 61169-2	NOTE	Harmonized as EN 61169-2 (not modified).
IEC 61169-24	NOTE	Harmonized as EN 61169-24 (not modified).
CISPR 16-1 Series	NOTE	Harmonized as EN 55016-1 Series (not modified).
ISO/IEC 13818 Series	NOTE	Harmonized as EN ISO/IEC 13818 Series ¹⁾ (not modified).
ISO/IEC 13818-3	NOTE	Harmonized as EN ISO/IEC 13818-3 ¹⁾ (not modified).

¹⁾ Withdrawn.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
		Characteristics of DAB receivers	EN 50248	2001
IEC 60050-705	-	International Electrotechnical Vocabulary (IEV) - Chapter 705: Radio wave propagation	-	-
IEC 60050-712	1992	International Electrotechnical Vocabulary (IEV) - Chapter 712: Antennas	-	-
IEC 60050-725	-	International Electrotechnical Vocabulary (IEV) - Chapter 725: Space radiocommunications	-	-
IEC 60728-1-1	-	Cable networks for television signals, sound signals and interactive services - Part 1-1: RF cabling for two way home networks	EN 60728-1-1	-
IEC 60728-1-2	-	Cable networks for television signals, sound signals and interactive services - Part 1-2: Performance requirements or signals delivered at the system outlet in operation	EN 60728-1-2	-
IEC 60728-2	-	Cable networks for television signals, sound signals and interactive services - Part 2: Electromagnetic compatibility for equipment	EN 50083-2	-
IEC 60728-3	2010	Cable networks for television signals, sound signals and interactive services - Part 3: Active wideband equipment for cable networks	EN 60728-3	2011
IEC 60728-5	-	Cable networks for television signals, sound signals and interactive services - Part 5: Headend equipment	EN 60728-5	-
IEC 60728-10	-	Cable networks for television signals, sound signals and interactive services - Part 10: System performance of return paths	EN 60728-10	-

EN 60728-1:2014

IEC 60728-11	-	Cable networks for television signals, sound signals and interactive services - Part 11: Safety	EN 60728-11	-
IEC 60728-12	-	Cabled distribution systems for television and sound signals - Part 12: Electromagnetic compatibility of systems	EN 50083-8	-
IEC 60966-2-4	-	Radio frequency and coaxial cable assemblies - Part 2-4: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 MHz to 3 000 MHz, IEC 61169-2 connectors	EN 60966-2-4	-
IEC 60966-2-5	-	Radio frequency and coaxial cable assemblies - Part 2-5: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 MHz to 1 000 MHz, IEC 61169-2 connectors	EN 60966-2-5	-
IEC 60966-2-6	-	Radio frequency and coaxial cable assemblies - Part 2-6: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors	EN 60966-2-6	-
ISO/IEC 13818-1	2007	Information technology - Generic coding of moving pictures and associated audio information: Systems		-
ISO/IEC 13818-4		Information technology - Generic coding of moving pictures and associated audio information - Part 4: Conformance testing		-
ISO/IEC 14496-1	-	Information technology - Coding of audio-visual objects - Part 1: Systems		-
ITU-R Recommendation BS.412-9	-	Planning standards for terrestrial FM sound-broadcasting at VHF		-
ITU-R Recommendation BT.417-4		Minimum field strengths for which protection may be sought in planning an analogue terrestrial television service		-
ITU-R Recommendation BT.470-7	-	Conventional analogue television systems		-
ITU-R Recommendation BT.500-11	-	Methodology for the subjective assessment-of the quality of television pictures		-
ITU-T Recommendation J.61	-	Transmission performance of television circuits designed for use in international connections		-

ETSI EN 300 421	-	Digital Video Broadcasting (DVB): Framing - structure, channel coding and modulation for 11/12 GHz satellite services	-
ETSI EN 300 429	-	Digital Video Broadcasting (DVB): Framing - structure, channel coding and modulation for cable systems	-
ETSI EN 300 468	-	Digital Video Broadcasting (DVB); - Specification for Service Information (SI) in DVB systems	-
ETSI EN 300 473	-	Digital Video Broadcasting (DVB): Satellite - Master Antenna Television (SMATV) distribution systems	-
ETSI EN 300 744	-	Digital Video Broadcasting (DVB): Framing - structure, channel coding and modulation for digital terrestrial television	-
ETSI EN 302 307/V1.3.1	2013	Digital Video Broadcasting (DVB); Second - generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications (DVB-S2)	-
ETSI ETS 300 784	-	Satellite Earth Stations and Systems (SES);Television Receive-Only (TVRO) satellite earth stations operating in the 11/12 GHz frequency bands	-
ETSI TS 101 211	-	Digital Video Broadcasting (DVB); - Guidelines on implementation and usage of Service Information (SI)	-
ETSI TS 102 831 V1.2.1	2012	Digital Video Broadcasting (DVB); - Implementation guidelines for a second generation digital terrestrial television broadcasting system (DVB-T2)	-

Annex ZB (informative)

A-deviations

A-deviation: National deviation due to regulations, the alteration of which is for the time being outside the competence of the CENELEC national member.

This European Standard does not fall under any Directive of the EC.

In the relevant CENELEC countries these A-deviations are valid instead of the provisions of the European Standard until they have been removed.

Clause Deviation

3.1.58 Norway

According to Regulations on Electronic Communications Networks and Services (Ecom Regulations) laid down by the Norwegian Ministry of Transport and Communications on 16 February 2004, the following applies:

When installing coaxial cable-based networks, the part of the network to which the end-user is connected shall be placed in a star structure. It is not permitted to insert receiver connections into the connection between the star points.

5.4.1 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Replace by/add the following “minimum and maximum carrier levels” regulation as indicated in Table ZB.1.

Table ZB.1 – Carrier signal levels at any system outlet

FM sound mono:	80 dB(μ V) _{max}
----------------	--------------------------------

(measured in accordance with CISPR 16-1 [4] (quasi-peak measurement within 120 kHz bandwidth))

5.6.2 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Add the group delay response curve valid for PAL with FM-FM sound (Clause 5.4.1), as shown in Figure ZB.1.




Figure ZB.1 – Mask group delay characteristic for PAL signals with FM-FM sound

5.9.1 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Replace by/add the following “single-frequency interference” regulation as indicated in Table ZB.2.


Table ZB.2 – Single-frequency interference

AM-VSB-PAL-signals:	$C/I \geq 60$ dB	(measured in a bandwidth of 300 kHz)
For signals outside used TV channels:	$C/I \geq 40$ dB	

5.10.2 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Replace the requirements for “echoes in television channels, PAL-SECAM standards” by the “requirement for echo loss in relation to the time delay of the reflected signal for AM-PAL-TV and FM-radio” (Figure ZB.2).



IEC 1466

Figure ZB.2 – Requirement for echo loss in relation to the time delay of the reflected signal

5.12.1 Denmark

(Danish technical regulations for CATV-networks, which are applicable to those networks in accordance with national legislation act. nr; 277 of June 1995, given by the Ministry of Research)

Add the requirement for “decoding margin” being “the decoding margin must be 40 %, when the margin is a minimum of 70 % at the receiving antenna”.

5.14.3 Netherlands

(Dutch Technical Regulations for CATV networks (Technische Voorschriften voor Centrale Antenne Inrichtingen, 3e uitgave), 21 December 1977, which are valid for CATV networks in accordance with Article 21 of the Dutch Telecommunications law (Stb. 1988, 520))

Add the requirement for “adjacent channel spacing” by ≥ 400 kHz.



INTERNATIONAL STANDARD

**Cable networks for television signals, sound signals and interactive services –
Part 1: System performance of forward paths**





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC 60728-1

Edition 5.0 2014-05

INTERNATIONAL STANDARD

**Cable networks for television signals, sound signals and interactive services –
Part 1: System performance of forward paths**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XG**

ICS 33.060.40

ISBN 978-2-8322-1619-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	10
INTRODUCTION.....	12
1 Scope.....	13
2 Normative references	13
3 Terms, definitions, symbols and abbreviations.....	15
3.1 Terms and definitions.....	15
3.2 Symbols.....	27
3.3 Abbreviations.....	29
4 Methods of measurement at system outlet.....	31
4.1 Performance limits	31
4.2 Mutual isolation between system outlets	33
4.2.1 Overview	33
4.2.2 Equipment required	33
4.2.3 Connection of the equipment	34
4.2.4 Measurement procedure	34
4.2.5 Presentation of the results	35
4.3 Amplitude response within a channel	35
4.3.1 Overview	35
4.3.2 Equipment required	35
4.3.3 Connection of the equipment	35
4.3.4 Measurement procedure	36
4.3.5 Presentation of the results	37
4.4 Chrominance-luminance gain and delay inequalities	38
4.4.1 Overview	38
4.4.2 Equipment required	39
4.4.3 Connection of the equipment	39
4.4.4 Measurement procedure	39
4.4.5 Presentation of the results	40
4.5 Non-linear distortion.....	41
4.5.1 General	41
4.5.2 Intermodulation.....	41
4.5.3 Composite beat	41
4.5.4 Composite crossmodulation	45
4.5.5 Intermodulation noise	46
4.5.6 Hum modulation of carriers.....	46
4.5.7 Differential gain and phase	51
4.6 Carrier-to-noise ratio.....	56
4.6.1 Overview	56
4.6.2 Equipment required	56
4.6.3 Connection of the equipment	56
4.6.4 Measurement set-up.....	57
4.6.5 Measurement procedure	57
4.6.6 Presentation of the results	58
4.7 Echoes	58
4.7.1 Overview	58
4.7.2 Equipment required	59

4.7.3	Connection of the equipment	59
4.7.4	Measurement procedure	59
4.7.5	Presentation of the results	60
4.8	AM-VSB television, FM radio and FM television signal level	60
4.8.1	General	60
4.8.2	Definitions for NTSC, PAL and SECAM systems	60
4.8.3	Equipment required	60
4.8.4	Measurement procedure	60
4.8.5	Presentation of the results	61
4.9	Data echo rating and data delay inequality	61
4.10	Interference in FM sound radio channels	61
4.11	Methods of measurement for digitally modulated signals	61
4.11.1	Overview	61
4.11.2	Basic assumptions and measurement interfaces	62
4.11.3	Signal level for digitally modulated signals	65
4.11.4	RF signal-to-noise ratio $S_{D,RF}/N$ for digitally modulated signals	66
4.11.5	Bit error ratio (BER)	68
4.11.6	BER versus E_b/N_0 or C/N	69
4.11.7	Noise margin	73
4.11.8	Modulation error ratio (MER)	74
4.11.9	Phase jitter	76
4.11.10	Phase noise of an RF carrier	79
5	Performance requirements at system outlet	82
5.1	General	82
5.2	Impedance	82
5.3	Requirements at the terminal input	82
5.3.1	General	82
5.3.2	Signal level	83
5.3.3	Other parameters	83
5.4	Carrier levels at system outlets	83
5.4.1	Minimum and maximum carrier levels	83
5.4.2	Carrier level differences	85
5.5	Mutual isolation between system outlets	86
5.5.1	Isolation between two subscribers	86
5.5.2	Isolation between individual outlets in one household	86
5.5.3	Isolation between forward and return path	86
5.6	Frequency response within a television channel at any system outlet	87
5.6.1	Amplitude response	87
5.6.2	Group delay	87
5.7	Long-term frequency stability of distributed carrier signals at any system outlet	88
5.8	Random noise	89
5.9	Interference to television channels	91
5.9.1	Single-frequency interference	91
5.9.2	Single-channel intermodulation interference	92
5.9.3	Multiple frequency intermodulation interference	92
5.9.4	Intermodulation noise	92
5.9.5	Cross-modulation	93

5.10	Video baseband requirements.....	93
5.10.1	Differential gain and phase in any television channel.....	93
5.10.2	Echoes.....	93
5.11	Hum modulation of carriers in television channels.....	93
5.12	Requirements for data signal transmission.....	94
5.12.1	Data signals carried in the structure of a television signal.....	94
5.12.2	Data signals other than those carried within the structure of a television signal.....	94
5.13	Digitally modulated signals – Additional performance requirements.....	94
5.13.1	DVB (PSK, QAM, OFDM) performance.....	94
5.13.2	NICAM performance.....	96
5.13.3	DAB performance.....	96
5.14	FM sound radio – Additional performance requirements.....	97
5.14.1	Amplitude response within an FM channel.....	97
5.14.2	Phase response within an FM channel.....	97
5.14.3	Interference within an FM channel.....	97
5.14.4	AM hum modulation on FM sound carriers.....	97
5.14.5	Echoes within an FM channel.....	97
6	Performance requirements at receiving antennas.....	97
6.1	General.....	97
6.2	Method of measurement of field strength.....	98
6.2.1	Overview.....	98
6.2.2	Equipment required.....	98
6.2.3	Connection of the equipment.....	98
6.2.4	Measurement procedure.....	98
6.2.5	Presentation of the results.....	100
6.3	Requirements.....	100
6.3.1	General.....	100
6.3.2	Field strength requirements.....	100
6.3.3	Quality of received signals.....	102
6.3.4	Safety.....	106
6.3.5	Electromagnetic compatibility (EMC).....	107
6.4	Interference reduction.....	107
6.4.1	General.....	107
6.4.2	Active antennas.....	107
7	Performance requirements at home network interfaces of cable networks.....	107
7.1	General.....	107
7.2	Requirements at HNI1 for passive coaxial home networks.....	108
7.2.1	General.....	108
7.2.2	Carrier levels at the HNI1.....	109
7.2.3	Mutual isolation between two HNI1.....	112
7.2.4	Frequency response within any television channel at HNI1.....	112
7.2.5	Long-term frequency stability of distributed carrier signals at HNI1.....	113
7.2.6	Random noise at the HNI1.....	113
7.2.7	Interference to television channels at HNI1.....	113
7.2.8	Return path requirements at HNI1.....	114
7.3	Requirements at HNI2 for active coaxial home networks.....	114
7.3.1	General.....	114

7.3.2	Carrier levels at the HNI2	114
7.3.3	Mutual isolation between two HNI2	117
7.3.4	Frequency response within any television channel at HNI2	117
7.3.5	Long-term frequency stability of distributed carrier signals at HNI2	117
7.3.6	Random noise at HNI2	118
7.3.7	Interference to television channels at the HNI2	121
7.3.8	Return path requirements at HNI2	122
7.4	Requirements at HNI3 and at system outlet or terminal input when the home network is mainly of balanced type	122
7.4.1	Overview	122
7.4.2	Requirements at HNI3	122
7.4.3	Requirements at system output	123
7.4.4	Additional requirements at HNI3 for upstream transmission	123
7.5	Requirements at HNI3 (Case C)	124
7.6	Requirements at HNI3 (Case D)	124
Annex A (informative) Reception of television signals		125
Annex B (normative) Calibration of modulation depth		130
B.1	Equipment required	130
B.2	Connection of the equipment	130
B.3	Calibration procedure	130
Annex C (normative) Equipment required – Additional items		131
C.1	Measuring receiver preamplifier	131
C.2	Measuring receiver input filter	131
Annex D (normative) Preliminary checks on the measuring equipment for carrier-to-noise ratio		132
D.1	Noise	132
D.2	Intermodulation	132
D.3	Overload	132
Annex E (normative) Correction factors		133
E.1	Level correction factor C_m	133
E.2	Bandwidth correction factor C_b	133
Annex F (normative) Calibration of the measuring receiver		134
Annex G (normative) Correction factors for noise		135
G.1	Signal level measurement	135
G.2	Noise level measurement	135
Annex H (normative) Null packet and PRBS definitions		137
H.1	Null packet definition	137
H.2	PRBS definition	138
Annex I (normative) Digital signal level and bandwidth		139
I.1	RF/IF power (carrier)	139
I.2	Bandwidth of a digital signal	139
I.2.1	Occupied bandwidth	139
I.2.2	Noise bandwidth	140
I.2.3	Equivalent signal bandwidth	140
I.3	Examples	141
Annex J (normative) Correction factor for a spectrum analyser		142
Annex K (informative) Differences in some countries		143

K.1	Subclause 3.1.58, Norway	143
K.2	Subclause 5.4.1, Japan, Netherlands	143
	K.2.1 Japan	143
	K.2.2 Netherlands	143
K.3	Subclause 5.4.2, Japan	143
K.4	Subclause 5.5.1, Japan	144
K.5	Subclause 5.6.1, Japan	145
K.6	Subclause 5.6.2, Netherlands	145
K.7	Subclause 5.7, Japan	146
K.8	Subclause 5.8, Japan	146
K.9	Subclause 5.9.1, Japan, Netherlands	147
	K.9.1 Japan	147
	K.9.2 Netherlands	148
K.10	Subclause 5.9.5, Japan	149
K.11	Subclause 5.10.2, Netherlands, Japan	149
	K.11.1 Netherlands	149
	K.11.2 Japan	149
K.12	Subclause 5.11, Japan	150
K.13	Subclause 5.12.1, Denmark	151
K.14	Subclause 5.13.1.5, Japan	151
K.15	Subclause 5.14.3, Netherlands	151
K.16	Clause 7, Japan	151
	Bibliography	152
	Figure 1 – Arrangement of test equipment for measurement of mutual isolation between system outlets	34
	Figure 2 – Arrangement of test equipment for measurement of frequency response within a channel	36
	Figure 3 – Interpretation of displays for measurement of frequency response within a channel	37
	Figure 4 – Test signal (signal <i>F</i> for 625-line systems) employed for chrominance/luminance gain and delay inequality	38
	Figure 5 – Test signal (signal B2 for 625-line systems) employed for chrominance/luminance gain and delay inequality	38
	Figure 6 – Arrangement of test equipment for measurement of chrominance/luminance gain and delay inequality	39
	Figure 7 – Displayed pulses: chrominance low and lagging	40
	Figure 8 – Displayed pulses: chrominance high and leading	40
	Figure 9 – Connection of test equipment for the measurement of non-linear distortion by composite beat	42
	Figure 10 – Weighting curve for 625-line system B, G and D1 (PAL): CW interference with no special (frequency offset) control	44
	Figure 11 – Weighting curve for 625-line system I (PAL): CW interference with no special (frequency offset) control	44
	Figure 12 – Weighting curve for 625-line systems D and K (PAL): CW interference with no special (frequency offset) control	45
	Figure 13 – Weighting curve for 625-line system L (SECAM): CW interference with no special (frequency offset) control	45
	Figure 14 – Hum modulation envelope	46

Figure 15 – Calibrated potential divider.....	47
Figure 16 – Stable variable DC source.....	47
Figure 17 – Connection of equipment for measurement of hum modulation (DC method).....	48
Figure 18 – Oscilloscope display.....	49
Figure 19 – Connection of equipment for hum modulation measurement (AC method).....	50
Figure 20 – Signal D2.....	52
Figure 21 – Example of the modified staircase waveform.....	53
Figure 22 – Arrangement of test equipment for measurement of differential gain and phase.....	54
Figure 23 – Arrangement of test equipment for carrier-to-noise ratio measurement.....	56
Figure 24 – Echo rating graticule.....	58
Figure 25 – Arrangement of test equipment for measurement of echo rating.....	59
Figure 26 – PSK modulation (QPSK, BPSK or TC8PSK).....	62
Figure 27 – DVB-S2 modulation (QPSK, 8PSK, 16APSK, 32APSK).....	62
Figure 28 – DVB-C QAM modulation.....	62
Figure 29 – DVB-T OFDM modulation.....	63
Figure 30 – DVB-T2 OFDM modulation.....	63
Figure 31 – Reference receiver for PSK demodulation (QPSK, BPSK or TC8PSK).....	63
Figure 32 – Reference receiver for DVB-S2 demodulation (QPSK, 8PSK, 16APSK, 32APSK).....	64
Figure 33 – Reference receiver for QAM demodulation.....	64
Figure 34 – Reference receiver for DVB-T OFDM demodulation.....	64
Figure 35 – Reference receiver (buffer model) for DVB-T2 OFDM demodulation.....	64
Figure 36 – Test set-up for BER measurement.....	69
Figure 37 – Test set-up for BER measurement versus E_b/N_0 or C/N and noise margin measurement.....	70
Figure 38 – Example of <i>BER</i> measurement versus E_b/N_0	72
Figure 39 – Example of <i>BER</i> measurement versus C/N	72
Figure 40 – Test set-up for modulation error ratio (MER) measurement and phase jitter measurement.....	75
Figure 41 – Example of constellation diagram for a 64 QAM modulation format.....	76
Figure 42 – Example of constellation diagram for a 64 QAM modulation format with arc sections due to phase jitter.....	78
Figure 43 – Test set-up for phase noise measurement.....	79
Figure 44 – Example of mask for phase noise measurements: PSK, APSK and QAM formats.....	81
Figure 45 – Example of mask for phase noise measurements: OFDM format.....	81
Figure 46 – Home network types used to define the requirements at HNI1 (coaxial).....	108
Figure A.1 – Example of a master antenna television system (MATV) for terrestrial reception.....	126
Figure A.2 – Example of the headend of a master antenna television system for satellite (SMATV) reception.....	127
Figure A.3 – Example of a master antenna television system for terrestrial and satellite (SMATV) reception.....	127
Figure A.4 – Example of a cabled distribution system for television and sound signals.....	128

Figure A.5 – System model for downstream direction of a cable network for television and sound signals (CATV)	129
Figure B.1 – Calibration of modulation depth	130
Figure G.1 – Noise correction factor CF versus measured level difference D	136
Figure K.1 – Mask group delay characteristic for PAL signals with FM-FM sound (Netherlands).....	145
Figure K.2 – Single-frequency interference (VSB-AM NTSC) (Japan).....	147
Figure K.3 – Single-frequency interference (64 QAM digital) (Japan)	148
Figure K.4 – Single-frequency interference (256 QAM digital) (Japan)	148
Figure K.5 – Requirement for echo loss in relation to the time delay of the reflected signal (Netherlands).....	149
Figure K.6 – Echoes (VSB-AM NTSC) (Japan).....	150
Figure K.7 – Echoes (FM NTSC) (Japan).....	150
Table 1 – Application of the methods of measurement	32
Table 2 – Residual carrier reduction factors	49
Table 3 – Frequency distance f_m	81
Table 4 – Carrier signal levels at any system outlet (analogue signals).....	83
Table 5 – RF signal levels at any system outlet (digital signals).....	84
Table 6 – Maximum level differences at any system outlet between distributed television channels	85
Table 7 – Mutual isolation	86
Table 8 – Residual carrier level at television or FM radio output within the same outlet or between two different outlets	87
Table 9 – Amplitude response variation	87
Table 10 – Group delay variation	88
Table 11 – Maximum deviation of the conversion frequency for digitally modulated DVB signals	89
Table 12 – Carrier-to-noise ratios at system outlet (analogue television).....	89
Table 13 – RF signal-to noise ratio at system outlet (digital television)	90
Table 14 – Carrier-to-noise ratios at the system outlet (sound radio)	91
Table 15 – Differential gain and phase in television channels	93
Table 16 – Modulation error ratio MER of DVB signals.....	95
Table 17 – Phase jitter of a DVB signal.....	95
Table 18 – Phase noise of a DVB signal (PSK, APSK and QAM)	96
Table 19 – Phase noise of a DVB-T signal (COFDM)	96
Table 20 – Minimum field strength levels recommended by ITU-R.....	101
Table 21 – Minimum field strength levels recommended by CEPT:1997	101
Table 22 – Minimum signal level at the headend input for the reception of analogue sound broadcasting.....	102
Table 23 – Minimum signal level at the headend input for the reception of analogue television broadcasting	102
Table 24 – Minimum signal level at the headend input for the reception of DAB signals at an error ratio of 1×10^{-4} and code rate 1/2	103
Table 25 – Minimum signal level and RF signal-to-noise ratio at the headend input for stationary reception of DVB-T signals	103

Table 26 – Minimum signal-to-noise ratio $S_{D,RF}/N$ at the headend input for DVB-T2 signals (LDPC block length 64 800 bit)	104
Table 27 – Minimum signal level and carrier-to-noise ratio at the headend input for the reception of FM modulated satellite signals.....	104
Table 28 – Minimum RF signal-to-noise ratio at the headend input for the reception of DVB-S or DVB-S2 satellite signals (AWGN channel and FECFRAME length of 64 800)	105
Table 29 – Minimum values for signal-to-disturbance ratio	105
Table 30 – Minimum values for signal-to-echo ratio	106
Table 31 – Signal level at HNI1 (analogue signals)	109
Table 32 – Signal level at HNI1 (digital signals)	110
Table 33 – Maximum level differences at HNI1	111
Table 34 – Mutual isolation between two HNI1	112
Table 35 – Amplitude response variation at HNI1	112
Table 36 – Group delay variation at HNI1	113
Table 37 – Signal level at HNI2 (analogue signals)	114
Table 38 – Signal level at HNI2 (digital signals)	115
Table 39 – Maximum level differences at HNI2	116
Table 40 – Amplitude response variation at HNI2.....	117
Table 41 – Group delay variation at HNI2	117
Table 42 – Carrier-to-noise ratios at HNI2 (analogue television)	118
Table 43 – RF signal-to-noise ratios at HNI2 (digital television)	119
Table 44 – Carrier-to-noise ratios at HNI2 (sound radio)	120
Table 45 – Minimum signal level at coaxial terminal input (case A) or at coaxial system outlet (case B)	123
Table G.1 – Noise correction factor.....	135
Table H.1 – Null transport stream packet definition	138
Table I.1 – Examples of bandwidths for digital modulation techniques	141
Table K.1 – Carrier signal levels at any system outlet (Japan)	143
Table K.2 – Carrier signal levels at any system outlet (Netherlands).....	143
Table K.3 – Maximum level differences at any system outlet between distributed television channels (Japan)	144
Table K.4 – Mutual isolation (Japan).....	144
Table K.5 – Amplitude response variation (Japan)	145
Table K.6 – Frequency stability requirements (Japan).....	146
Table K.7 – Carrier-to-noise ratios at system outlet (Japan).....	146
Table K.8 – Single-frequency interference (Japan).....	147
Table K.9 – Single-frequency interference (Netherlands)	148
Table K.10 – Cross-modulation (Japan)	149
Table K.11 – Echoes requirements (Japan).....	149
Table K.12 – Hum modulation of carriers in television channels (Japan)	150
Table K.13 – Phase noise of an RF carrier (Japan).....	151

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CABLE NETWORKS FOR TELEVISION SIGNALS,
SOUND SIGNALS AND INTERACTIVE SERVICES –****Part 1: System performance of forward paths**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-1 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This fifth edition cancels and replaces the fourth edition published in 2007 and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- redrafting of measurement procedure to include DVB-T2 signals;
- updating of performance requirements in Clause 5 to include those for DVB-T2 signals;
- updating of performance requirements in Clause 6 to include those for DVB-T2 signals;
- updating of performance requirements in Clause 7 to include those for DVB-T2 signals;

- reference to IEC 60728-1-1 for home networks;
- reference to IEC 60728-1-2 for performance requirements at system outlet in operation.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/2269/FDIS	100/2335/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60728 series, under the general title *Cable networks for television signals, sound signals and interactive services*, can be found on the IEC website.

For the differences in some countries, see Annex K.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Standards and deliverables of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes for instance

- regional and local broadband cable networks,
- extended satellite and terrestrial television distribution systems,
- individual satellite and terrestrial television receiving systems,

and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

IEC 60728-1 includes the following clauses:

Clause 5 defines the system performance limits which will, with an unimpaired input, (headend input signal), produce picture and sound signals (at system outlets) where the impairment to any single parameter will not be worse, in normal operating conditions for any analogue channel, than grade four on the five-grade impairment scale contained in ITU- R Recommendation BT.500-10. For digitally modulated signals, the quality requirement is a quasi-error-free (QEF) reception.

Appropriate performance requirements for the signals at the receiving antennas site are given in Clause 6 in order to provide at the input of the headend of the cable network both analogue and digital television signals with suitable quality.

Clause 7 is applicable to home networks (including those of individual receiving systems) using coaxial cables, balanced cables or optical cables and primarily intended for television signals, sound signals and interactive services, operating between about 30 MHz and 3 000 MHz.

This clause (Clause 7), considering the basic operational characteristics of a home network, specifies the requirements with respect to the home network interface (HNI) taking into account the performance requirements given at the system outlet or at the terminal input.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 1: System performance of forward paths

1 Scope

This part of IEC 60728 is applicable to any cable network (including individual receiving systems) having in the forward path a coaxial cable output and primarily intended for television and sound signals operating between about 30 MHz and 3 000 MHz.

This part of IEC 60728 specifies the basic methods of measurement of the operational characteristics of cable network having coaxial cable outputs in order to assess the performance of these systems and their performance limits.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-705, *International Electrotechnical Vocabulary – Chapter 705: Radio wave propagation*

IEC 60050-712:1992, *International Electrotechnical Vocabulary – Chapter 712: Antennas*

IEC 60050-725, *International Electrotechnical Vocabulary (IEV) – Chapter 725: Space radiocommunications*

IEC 60728-1-1, *Cable networks for television signals, sound signals and interactive services – Part 1-1: RF cabling for two way home networks*

IEC 60728-1-2, *Cable networks for television signals sound signals and interactive services – Part 1-2: Performance requirements for signals delivered at the system outlet in operation*

IEC 60728-2, *Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment*

IEC 60728-3:2010, *Cable networks for television signals, sound signals and interactive services – Part 3: Active wideband equipment for cable networks*

IEC 60728-5, *Cable networks for television signals, sound signals and interactive services – Part 5: Headend equipment*

IEC 60728-10, *Cable networks for television signals, sound signals and interactive services – Part 10: System performance of return paths*

IEC 60728-11, *Cable networks for television signals, sound signals and interactive services – Part 11: Safety*

IEC 60728-12, *Cabled distribution systems for television and sound signals – Part 12: Electromagnetic compatibility of systems*

IEC 60966-2-4, *Radio frequency and coaxial cable assemblies – Part 2-4: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-2 connectors*

IEC 60966-2-5, *Radio frequency and coaxial cable assemblies – Part 2-5: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 1 000 MHz, IEC 61169-2 connectors*

IEC 60966-2-6, *Radio frequency and coaxial cable assemblies – Part 2-6: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors*

ISO/IEC 13818-1:2007, *Information technology – Generic coding of moving pictures and associated audio information: Systems*

ISO/IEC 13818-4, *Information technology – Generic coding of moving pictures and associated audio information – Part 4: Conformance testing*

ISO/IEC 14496-1, *Information technology – Coding of audio-visual objects – Part 1: Systems*

ITU-R Recommendation BS.412-9, *Planning standards for terrestrial FM sound broadcasting at VHF*

ITU-R Recommendation BT.417-4, *Minimum field strengths for which protection may be sought in planning an analogue terrestrial television service*

ITU-R Recommendation BT.470-7, *Conventional analogue television systems*

ITU-R Recommendation BT.500-11, *Methodology for the subjective assessment of the quality of television pictures*

ITU-T Recommendation J.61, *Transmission performance of television circuits designed for use in international connections*

EN 50248, *Characteristics of DAB receivers*

ETSI EN 300 421, *Digital Video Broadcasting (DVB) – Framing structure, channel coding and modulation for 11/12 GHz satellite services*

ETSI EN 300 429, *Digital Video Broadcasting (DVB) – Framing structure, channel coding and modulation for cable systems*

ETSI EN 300 468, *Digital Video Broadcasting (DVB) – Specification for Service Information (SI) in DVB systems*

ETSI EN 300 473, *Digital Video Broadcasting (DVB) – Satellite Master Antenna Television (SMATV) distribution systems*

ETSI EN 300 744, *Digital Video Broadcasting (DVB) – Framing structure, channel coding and modulation for digital terrestrial television*

ETSI EN 302 307/V1.3.1:2012, *Digital Video Broadcasting (DVB) – Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications*

ETSI ETS 300 784, *Satellite Earth Stations and Systems (SES) – TeleVision Receive-Only (TVRO) satellite earth stations operating in the 11/12 GHz frequency bands*

ETSI TR 101 211, *Digital Video Broadcasting (DVB) – Guidelines on implementation and usage of Service Information (SI)*

ETSI TS 102 831/V1.2.1:2012, *Digital Video Broadcasting (DVB) – Implementation guidelines for a second generation digital terrestrial television broadcasting system (DVB-T2)*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN