

STN	Špecifikácia metód a meracích prístrojov na meranie rádiového rušenia a odolnosti proti nemu. Časť 1-6: Meracie prístroje na meranie rádiového rušenia a odolnosti proti nemu. Kalibrácia antény EMC.	STN EN 55016-1-6 33 4216
------------	--	--

Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-6: Radio disturbance and immunity measuring apparatus - EMC antenna calibration

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 07/15

Obsahuje: CISPR 16-1-6:2014, EN 55016-1-6:2015

121087

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, 2015
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 55016-1-6

February 2015

ICS 33.100.10; 33.100.20

English Version

Specification for radio disturbance and immunity measuring
apparatus and methods -
Part 1-6: Radio disturbance and immunity measuring apparatus -
EMC antenna calibration
(CISPR 16-1-6:2014)

Spécifications des méthodes et des appareils de mesure
des perturbations radioélectriques et de l'immunité aux
perturbations radioélectriques -
Partie 1-6: Appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations
radioélectriques - Étalonnage des antennes CEM
(CISPR 16-1-6:2014)

Anforderungen an Geräte und Einrichtungen sowie
Festlegung der Verfahren zur Messung der hochfrequenten
Störaussendung (Funkstörungen) und Störfestigkeit -
Teil 1-6: Geräte und Einrichtungen zur Messung der
hochfrequenten Störaussendung (Funkstörungen) und
Störfestigkeit - Kalibrierung von Antennen für EMV-
Messungen
(CISPR 16-1-6:2014)

This European Standard was approved by CENELEC on 2015-01-21. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document CISPR/A/1087/FDIS, future edition 1 of CISPR 16-1-6, prepared by CISPR SC A "Radiointerference measurements and statistical methods" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 55016-1-6:2015.

The following dates are fixed:

- latest date by which the document has to be (dop) 2015-10-21
implemented at national level by
publication of an identical national
standard or by endorsement
- latest date by which the national (dow) 2018-01-21
standards conflicting with the
document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard CISPR 16-1-6:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

CISPR 16-1-1:2010	NOTE	Harmonized as EN 55016-1-1:2010 (not modified).
CISPR 16-2-3:2010	NOTE	Harmonized as EN 55016-2-3:2010 (not modified).
CISPR 16-4-2:2011	NOTE	Harmonized as EN 55016-4-2:2011 (not modified).
CISPR 25:2008	NOTE	Harmonized as EN 55025:2008 (not modified).
IEC 61000-4-22:2010	NOTE	Harmonized as EN 61000-4-22:2010 (not modified).
IEC 61169-16:2006	NOTE	Harmonized as EN 61169-16:2007 (not modified).
ISO/IEC 17043:2010	NOTE	Harmonized as EN ISO/IEC 17043:2010 (not modified).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
CISPR 16-1-4	2010	Specification for radio disturbance and immunity measuring apparatus and methods -	EN 55016-1-4	2010
+A1	2012	Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements	+A1	2012
CISPR 16-1-5	2014	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration sites and reference test sites for 5 MHz to 18 GHz	EN 55016-1-5	2015
IEC 60050-161	-	International Electrotechnical Vocabulary (IEV) - Chapter 161: Electromagnetic compatibility	-	-
ISO/IEC Guide 98-3 2008		Uncertainty of measurement - Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)	-	-



CISPR 16-1-6

Edition 1.0 2014-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

Specification for radio disturbance and immunity measuring apparatus and methods –

Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques –

Partie 1-6: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Étalonnage des antennes CEM



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



CISPR 16-1-6

Edition 1.0 2014-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

Specification for radio disturbance and immunity measuring apparatus and methods –

Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques –

Partie 1-6: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Étalonnage des antennes CEM

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

XH

ICS 33.100.10; 33.100.20

ISBN 978-2-8322-1931-7

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD	10
1 Scope	12
2 Normative references	12
3 Terms, definitions and abbreviations	13
3.1 Terms and definitions	13
3.1.1 Antenna terms	13
3.1.2 Antenna factor terms	16
3.1.3 Measurement site terms	17
3.1.4 Other terms	18
3.2 Abbreviations	19
4 Fundamental concepts	20
4.1 General	20
4.2 The concept of antenna factor	20
4.3 Calibration methods for 30 MHz and above	21
4.3.1 General	21
4.3.2 Antenna minimum separation distances	21
4.3.3 General considerations for the TAM	21
4.3.4 General considerations for the SSM	21
4.3.5 General considerations for the SAM	22
4.4 Measurement uncertainties for antenna calibration measurement results	22
4.5 Summary of methods of measurement to obtain AF	23
5 Calibration methods for the frequency range 9 kHz to 30 MHz	25
5.1 Calibration of monopole antennas	25
5.1.1 General	25
5.1.2 Calibration by the ECSM	26
5.2 Calibration of loop antennas	32
5.2.1 General	32
5.2.2 TEM (Crawford) cell method	32
6 Frequencies, equipment and functional checks for calibrations at or above 30 MHz	35
6.1 Calibration frequencies	35
6.1.1 Calibration frequency ranges and increments	35
6.1.2 Transition frequency for hybrid antennas	36
6.2 Measurement instrumentation requirements for antenna calibrations	37
6.2.1 Equipment types	37
6.2.2 Mismatch	38
6.2.3 Dynamic range and reproducibility of SIL measurement	40
6.2.4 Signal-to-noise ratio	40
6.2.5 Antenna masts and cables	41
6.3 Functional checks of an AUC	41
6.3.1 General	41
6.3.2 Balance of an antenna	41
6.3.3 Cross-polar performance of an antenna	41
6.3.4 Radiation patterns of an antenna	42
7 Basic parameters and equations common to antenna calibration methods for frequencies above 30 MHz	43
7.1 Summary of methods for measurements to obtain AF	43

7.2	Site insertion loss measurements.....	43
7.2.1	General	43
7.2.2	SIL and SA measurement procedure.....	43
7.2.3	Common uncertainty components of a SIL measurement.....	44
7.3	Basic equations for the calculation of AF from SIL and SA measurements	46
7.3.1	Antenna factor from SIL measurements	46
7.3.2	Relationship of AF and SIL for a free-space calibration site	46
7.3.3	Relationship of AF and SIL for a calibration site with a metal ground plane	47
7.4	Equations for AF and measurement uncertainties using the TAM, SSM, and SAM.....	48
7.4.1	TAM	48
7.4.2	SSM	53
7.4.3	SAM	55
7.5	Parameters for specifying antenna phase centre and position	57
7.5.1	General	57
7.5.2	Reference position and phase centres of LPDA and hybrid antennas.....	58
7.5.3	Phase centres of horn antennas	61
8	Details for TAM, SAM, and SSM calibration methods for frequencies of 30 MHz and above	63
8.1	General.....	63
8.2	Considerations for F_a calibrations using TAM	63
8.2.1	General considerations	63
8.2.2	Calibration site and antenna set-up considerations for use with the TAM	63
8.2.3	Antenna parameters for a free-space environment or a ground plane site	65
8.2.4	Validation of calibration method.....	66
8.3	Considerations for F_a calibrations using the SAM	66
8.3.1	General considerations and calibration site for use of the SAM.....	66
8.3.2	Calibration procedures and antenna set-ups for F_a by the SAM.....	67
8.3.3	Parameters of the STA	67
8.4	SSM calibrations at a ground-plane site, 30 MHz to 1 GHz	68
8.4.1	General considerations and calibration site for SSM	68
8.4.2	Calibration procedure for SSM.....	69
8.4.3	Calculation of F_a	69
8.4.4	Uncertainties of F_a obtained using SSM	70
9	Calibration procedures for specific antenna types for frequencies of 30 MHz and above	71
9.1	General.....	71
9.2	Calibrations for biconical and hybrid antennas in a free-space environment for 30 MHz to 300 MHz, and tuned dipoles for 60 MHz to 1 000 MHz	71
9.2.1	General considerations and calibration site requirements	71
9.2.2	Calibration procedure and antenna set-up for use with the SAM	71
9.2.3	Uncertainties of F_a determined by the SAM	72
9.2.4	Antenna set-up for use with the TAM (alternative)	74
9.3	Calibration of biconical (30 MHz to 300 MHz) and hybrid antennas, using the SAM and VP at a ground plane site.....	74
9.3.1	General considerations and calibration site requirements	74
9.3.2	Calibration procedure and antenna set-up	75
9.3.3	Uncertainties of F_a determined with the SAM.....	76

9.4	Calibration of LPDA, hybrid, and horn antennas in a free-space environment, 200 MHz to 18 GHz.....	77
9.4.1	General considerations and calibration site for a free-space environment.....	77
9.4.2	Calibrations using the TAM.....	79
9.4.3	Antenna set-up for use with the SAM.....	80
9.4.4	Alternative antenna set-up for site with absorber on the ground.....	80
9.5	Calibration of horn and LPDA antennas in a FAR, 1 GHz to 18 GHz.....	81
9.5.1	Calibration using the TAM.....	81
9.5.2	Calibration and antenna set-up for the SAM.....	84
Annex A (informative) Background information and rationale for the methods of antenna calibration		85
A.1	Rationale for the need for several calibration methods and for use of a ground plane site	85
A.2	Special measures for calibration of omnidirectional antennas.....	86
A.2.1	General	86
A.2.2	Difficulties with calibration of omnidirectional antennas.....	87
A.2.3	Minimizing reflections from antenna supports and radiation from cables	87
A.2.4	Field taper and monocone set-up for VP biconical calibration	88
A.2.5	Use of HP or VP in a FAR.....	89
A.2.6	Substitution where the STA is the same model as the AUC.....	89
A.3	Calibrations using broadband calculable dipole antennas	89
A.3.1	Disadvantages of tuned dipole antennas.....	89
A.3.2	Advantages of broadband calculable dipole antennas.....	90
A.3.3	Disadvantages of calculable dipole antennas.....	90
A.4	Rationale for F_a and biconical/LPDA antenna cross-over frequency.....	90
A.4.1	Rationale for F_a	90
A.4.2	Cross-over frequency from biconical to LPDA antennas.....	91
A.4.3	Biconical element designs	91
A.5	Sources of increased uncertainty in measurement of F_a by the SSM.....	92
A.6	Calibration of LPDA antennas using smaller separation distances.....	94
A.6.1	Calibration of LPDA antennas using smaller separation distances	94
A.6.2	Correction of electric field strength to account for phase centre of LPDA antennas	95
A.7	Cross-polar discrimination of LPDA antennas	96
A.8	Tips for measurement instrumentation	97
A.8.1	Signal-to-noise ratio	97
A.8.2	Connector pin depth	99
A.8.3	Effect of added adaptor in a “cable-through” measurement	99
A.8.4	Compression level	100
A.8.5	Source power slope function above 6 GHz.....	100
A.8.6	Frequency increment for detection of resonances	100
A.8.7	Return loss or VSWR.....	100
A.9	Uncertainty considerations	101
A.9.1	General	101
A.9.2	Achievable uncertainties for F_a	101
A.9.3	Uncertainties of dipoles above a ground plane.....	101
A.9.4	Verification of uncertainty by comparison of methods	102
Annex B (normative) Calibration of biconical antennas and tuned dipole antennas above a ground plane using the TAM and the SAM		103

B.1	General.....	103
B.2	Characteristics of biconical antennas and dipole antennas.....	103
B.3	Frequencies	103
B.4	Measurement of $F_a(h,p)$ of biconical and tuned dipole antennas and derivation of F_a by averaging $F_a(h,p)$, 30 MHz to 300 MHz	104
B.4.1	General	104
B.4.2	Measurement of $F_a(h,H)$ by the SAM and derivation of F_a	104
B.4.3	Measurement of $F_a(h,H)$ by the TAM and derivation of F_a	107
B.5	Measurement of F_a of tuned dipoles placed high above a ground plane in the frequency range 30 MHz to 1 000 MHz.....	109
B.5.1	General	109
B.5.2	Measurement of F_a by the SAM.....	109
B.5.3	Measurement of F_a by the TAM	111
Annex C (informative) Rationale for the equations used in antenna calibration and relevant information about antenna characteristics for uncertainty analysis in the frequency range 30 MHz to 1 GHz		113
C.1	General.....	113
C.2	Antenna factor and antenna gain	113
C.2.1	Relationship between AF and gain for antennas in a free-space environment.....	113
C.2.2	Relationship between AF and gain for monopole antennas on a large ground plane	115
C.3	Equations for the insertion loss between antennas.....	115
C.3.1	Site insertion loss measured at a free-space calibration site	115
C.3.2	Site insertion loss measured at a metal ground plane site.....	117
C.3.3	Site attenuation measured at a metal ground plane site.....	119
C.4	Uncertainty contribution caused by near-field effects	120
C.5	Uncertainty contribution due to the antenna proximity coupling	121
C.6	Uncertainty contribution due to the ground plane reflection	123
C.6.1	Coupling to image in ground plane.....	123
C.6.2	Correction factors $\Delta F_{a,SSM}$ for F_a of biconical antenna	127
C.7	Uncertainty contribution due to the antenna radiation pattern.....	128
C.7.1	General	128
C.7.2	Biconical antennas	129
C.7.3	LPDA antennas.....	129
C.7.4	Hybrid antennas	130
C.7.5	Horn and LPDA antennas from 1 GHz to 18 GHz	131
Annex D (informative) Background information and rationale for calibration of antennas at frequencies above 1 GHz.....		134
D.1	Mismatch uncertainty	134
D.2	Mutual coupling between antennas and chamber reflection	134
D.3	Antenna separation distance and phase centre	134
D.4	Example gain of DRH at 1 m distance	136
Annex E (informative) Notes for measurement uncertainty budgets.....		138
E.1	General.....	138
E.2	Notes for measurement uncertainty budgets	138
Annex F (informative) Mismatch uncertainties from a two-port device connected between a transmit port and a receive port		147
Annex G (informative) Verification method for calibration of monopole antennas and uncertainty analysis of the ECSM.....		149

G.1	Verification method for calibration of monopole antennas by the plane wave method from 5 MHz to 30 MHz	149
G.1.1	Calibration procedure	149
G.1.2	Uncertainty evaluation for the calibration of monopole antennas by the plane wave method	150
G.2	Uncertainty analysis of the ECSM	150
G.2.1	Effect of rod length longer than $\lambda/8$	150
G.2.2	Effect on AF of monopole antenna mounted on a tripod	152
G.2.3	Monopole antenna receiving an electric field	153
G.2.4	Equivalent capacitance substitution method (ECSM)	153
G.2.5	Uncertainties associated with the ECSM	155
G.2.6	An alternative to the dummy antenna, for which $F_{ac} = V_D - V_L$	157
Annex H (informative)	Helmholtz coil method for calibration of loop antennas up to 150 kHz	158
H.1	Measurement procedure	158
H.2	Uncertainties	160
Bibliography		162
Figure 1	– Set-up for AF determination using a network analyzer	29
Figure 2	– Set-up for AF determination using a measuring receiver and signal generator	29
Figure 3	– Example of mounting a capacitor in the dummy antenna	30
Figure 4	– Block diagram of TEM cell set-up for passive loop antennas	34
Figure 5	– Block diagram of TEM cell set-up for active loop antennas	34
Figure 6	– Example of resonant spike due to poor biconical element connections, using 2 MHz increment	36
Figure 7	– Antenna set-up for SIL measurement at a free-space calibration site	44
Figure 8	– Antenna set-up for SIL and SA measurement at a ground-plane calibration site ..	44
Figure 9	– Antenna set-up for the TAM at a free-space calibration site	49
Figure 10	– Antenna set-up for the TAM at a calibration site with a metal ground plane	52
Figure 11	– Antenna set-up for the SSM	54
Figure 12	– Antenna set-up for the SAM at a calibration site with a metal ground plane	56
Figure 13	– Separation distance relative to the phase centre of an LPDA antenna	59
Figure 14	– LPDA antenna with a tapered curved geometry	61
Figure 15	– Separation distance with respect to the phase centre of horn antennas (see [49] for details)	62
Figure 16	– Schematic of a DRH showing relative locations of field point and phase centre of the DRH	63
Figure 17	– Biconical antenna set-up for SAM using vertical polarization, showing the paired monocone antenna and an example collapsible-element biconical AUC	76
Figure 18	– Test set-up for the calibration of LPDA and hybrid antennas positioned at a large height	79
Figure 19	– Set-up for LPDA antennas above absorber	81
Figure 20	– Set-up for transmission measurements using a network analyzer	82
Figure A.1	– Illustration of the angles of the electromagnetic rays subtended from the scanned LPDA antenna to the fixed height LPDA antenna and to the ground plane	93
Figure A.2	– F_a of biconical antenna with 200 Ω balun measured by the VP method of 9.3, and by the SSM method of 8.4 without correction	94

Figure A.3 – F_a of biconical antenna with 200 Ω balun measured by the VP method of 9.3, and by the SSM method of 8.4 with correction	94
Figure A.4 – Separation distance relative to the phase centre of an LPDA antenna.....	96
Figure A.5 – Statistical properties of multiple S_{21} sweeps (minimum, maximum, and mean value).....	98
Figure A.6 – Standard deviation of S_{21}	98
Figure A.7 – Normalized standard deviation of S_{21}	99
Figure C.1 – Simplified model of a receive antenna	114
Figure C.2 – Insertion loss measurement for antenna calibration at a free-space calibration site	116
Figure C.3 – Insertion loss measurement for antenna calibration at a calibration site with a metal ground plane	118
Figure C.4 – Comparison of field strength given by Equation (C.17) versus in near-field region given by Equation (C.31).....	121
Figure C.5 – Theoretical calculations of proximity coupling effects on the AF from the TAM (free-space conditions)	123
Figure C.6 – Deviation of AF from free-space value, F_a , caused by mutual coupling to the image in a metal ground plane (theoretical results)	124
Figure C.7 – Variation of $F_a(h,H)$ of biconical antenna with 50 Ω balun, 30 MHz to 320 MHz at heights every 0,5 m above a ground plane from 1 m to 4 m.....	125
Figure C.8 – AF of Figure C.7 normalized to free-space AF	125
Figure C.9 – Variation of $F_a(h,H)$ of biconical antenna with 200 Ω balun, 30 MHz to 320 MHz at heights every 0,5 m above a ground plane from 1 m to 4 m.....	126
Figure C.10 – Diagram of one triangular section of a biconical antenna element.....	128
Figure C.11 – Examples of radiation patterns (relative realized gain) of two example biconical antennas compared to ideal half-wave tuned dipole antenna.....	129
Figure C.12 – Examples of radiation patterns (relative realized gain) of three example LPDA antennas, compared to ideal half-wave tuned dipole antenna.....	130
Figure C.13 – Examples of radiation patterns (relative realized gain) of an example hybrid antenna, compared to ideal half-wave tuned dipole antenna.....	131
Figure C.14 – Example radiation patterns for classical DRH antenna	132
Figure C.15 – Example radiation patterns for novel DRH antenna	132
Figure C.16 – Example radiation patterns for classical LPDA antenna	133
Figure C.17 – Example radiation patterns for V-type LPDA antenna.....	133
Figure D.1 – Relative phase centres of a DRH antenna and an LPDA antenna	135
Figure D.2 – A transmission system between a horn antenna and an LPDA antenna	136
Figure D.3 – Measured AFs of a DRH antenna at 4,5 GHz.....	136
Figure D.4 – Graph showing the realized gain at 1 m for a DRH antenna	137
Figure E.1 – Comparison of measured and predicted SIL for calculable dipole antenna – 60 MHz element.....	141
Figure E.2 – Comparison of measured and predicted SIL for calculable dipole antenna – 180 MHz element.....	141
Figure E.3 – Reflectivity of chamber absorbing materials	145
Figure E.4 – Laser alignment system	146
Figure F.1 – Flow graph representation of a two-port device between a transmit port and a receiver port.....	147
Figure F.2 – Signal flow reduction.....	147

Figure G.1 – Diagram showing how the brass rod connects to the type N male bulkhead connector.....	150
Figure G.2 – Graph of the magnitude of the $\tan(\dots)$ ratio term in Equation (4) of 5.1.2.2	151
Figure G.3 – Graphical presentation of Equation (4) of 5.1.2.2 self-capacitance C_a of a 1 m monopole	151
Figure G.4 – Graphical presentation of Equation (5) of 5.1.2.2 height correction factor L_h	152
Figure G.5 – Calibration set-up consisting of a biconical and a loop antenna, and an elevated monopole antenna with vertical feed wires.....	153
Figure G.6 – Equivalent circuit representation for a monopole antenna system	153
Figure G.7 – Monopole antenna calibration using the ECSM.....	154
Figure G.8 – Equivalent circuit representation for the ECSM	154
Figure G.9 – Simplified circuit representation for Figure G.8	155
Figure G.10 – Circuit for dummy antenna simulating the effects of the antenna effective height, h_e	157
Figure H.1 – Diagram of Helmholtz coil method set-up.....	158
Figure H.2 – Variation of H/I across the central plane between the coils	160
Table 1 – Summary of calibration methods above 30 MHz for F_a	24
Table 2 – Calibration methods above 30 MHz by subclause number	25
Table 3 – Frequency increments for monopole antenna calibration	26
Table 4 – Example measurement uncertainty budget for F_{ac} of a monopole antenna calibrated by the ECSM using Equation (9)	32
Table 5 –Example measurement uncertainty budget for F_{aH} of a loop antenna measured in a TEM cell	35
Table 6 – Frequency increments for broadband antenna calibration.....	35
Table 7 – Example measurement uncertainty budget for common components of a SIL measurement result evaluated from Equation (20)	46
Table 8 – Parameters used to determine phase centres of segments A and B.....	61
Table 9 – Example measurement uncertainty budget for F_a of a horizontally-polarized biconical antenna measured by the SSM.....	70
Table 10 – Example measurement uncertainty budget for F_a of a biconical antenna measured by the SAM in a FAR over the frequency range 30 MHz to 300 MHz	73
Table 11 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the SAM in a FAR at a free-space calibration site, using a calculable tuned dipole as the STA in the frequency range above 60 MHz	74
Table 12 – Example measurement uncertainty budget for F_a of a biconical antenna measured using the SAM for vertical polarization over the frequency range 30 MHz to 300 MHz	77
Table 13 – Example measurement uncertainty budget for F_a of LPDA and hybrid antennas measured by the TAM at 4 m height for the frequency range 200 MHz to 3 GHz	80
Table 14 – Example measurement uncertainty budget for F_a of a horn antenna measured by the TAM above 1 GHz for 3 m separation in free space.....	84
Table A.1 – Example type N male and female connector pin depths and tolerances using a type N pin-depth gauge	99
Table A.2 – Typical type N adaptor characteristics.....	100
Table B.1 – Antenna set-up for the SAM for tuned dipole antennas with averaging of $F_a(h, H)$	104

Table B.2 – Antenna set-up for the SAM for biconical antennas with averaging of $F_a(h,H)$	105
Table B.3 – Example measurement uncertainty budget for $F_a(h,H)$ of a biconical antenna measured by the SAM over the frequency range 30 MHz to 300 MHz	105
Table B.4 – Example measurement uncertainty budget for F_a of a biconical antenna obtained by the SAM with averaging of $F_a(h,H)$ in the frequency range below 300 MHz	107
Table B.5 – Example measurement uncertainty budget for $F_a(h,H)$ of a biconical antenna obtained by the TAM with the antenna set-up specified in Table B.2.....	108
Table B.6 – Example measurement uncertainty budget for F_a of a biconical antenna obtained by the TAM with averaging of $F_a(h,H)$ in the frequency range below 300 MHz	108
Table B.7 – Antenna set-ups for the SAM for determining F_a of tuned dipole antennas at specific frequencies in the range 30 MHz to 1 000 MHz	110
Table B.8 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the SAM using the antenna set-ups specified in Table B.7	111
Table B.9 – Example measurement uncertainty budget for F_a of a tuned dipole antenna obtained by the TAM using the antenna set-ups specified in Table B.7	112
Table C.1 – Examples of the antenna height range h for horizontal polarization for an error $\leq 0,3$ dB	126
Table C.2 – Correction factors $\Delta F_{a,SSM}$ to convert AF measured by SSM to F_a	127
Table C.3 – Mechanical dimensions for the biconical antenna [52].....	128
Table G.1 – Example measurement uncertainty budget for F_a of a monopole antenna measured by the SAM.....	150
Table H.1 – Example measurement uncertainty budget for F_{aH} of a loop antenna measured by the Helmholtz coil method for the frequency range 50 kHz to 150 kHz	161

INTERNATIONAL ELECTROTECHNICAL COMMISSION
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY
MEASURING APPARATUS AND METHODS –**

**Part 1-6: Radio disturbance and immunity measuring apparatus –
EMC antenna calibration**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard CISPR 16-1-6 has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

It has the status of a basic EMC Standard in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*.

The text of this standard is based on the following documents:

FDIS	Report on voting
CISPR/A/1087/FDIS	CISPR/A/1098/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of CISPR 16 series, under the general title *Specification for radio disturbance and immunity measuring apparatus and methods*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration

1 Scope

This part of CISPR 16 provides procedures and supporting information for the calibration of antennas for determining antenna factors (AF) that are applicable to antennas intended for use in radiated disturbance measurements.

It has the status of a basic EMC Standard in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*.

The AF of an antenna is influenced by nearby surroundings and by its position in space relative to the radiating source. This standard focuses on antenna calibrations that provide the AF in a free-space environment in the direction of the boresight of the antenna. The frequency range addressed is 9 kHz to 18 GHz. The relevant antenna types covered in this standard are monopole, loop, dipole, biconical, log-periodic dipole-array (LPDA), hybrid and horn antennas.

Guidance is also provided on measurement uncertainties associated with each calibration method and configuration, and the test instrumentation used.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 16-1-4:2010, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements*

CISPR 16-1-4:2010/AMD 1:2012

CISPR 16-1-5:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-5: Radio disturbance and immunity measuring apparatus – Antenna calibration sites and reference test sites for 5 MHz to 18 GHz*

IEC 60050-161, *International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility*

ISO/IEC Guide 98-3:2008, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN