

STN	Elektromagnetická kompatibilita a záležitosti rádiového spektra (ERM). Zariadenia s krátkym dosahom (SRD). Rádiové zariadenia vo frekvenčnom rozsahu od 9 kHz do 25 MHz a systémy s indukčnou slučkou vo frekvenčnom rozsahu od 9 kHz do 30 MHz. Časť 1: Technické charakteristiky a skúšobné metódy.	STN EN 300 330-1 V1.8.1 87 0330
------------	--	---

Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz; Part 1: Technical characteristics and test methods

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 07/15

Obsahuje: EN 300 330-1 V1.8.1:2015

121147

ETSI EN 300 330-1 V1.8.1 (2015-03)



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment in the frequency range
9 kHz to 25 MHz and inductive loop systems
in the frequency range 9 kHz to 30 MHz;
Part 1: Technical characteristics and test methods**

Reference

REN/ERM-TG28-0436

Keywords

radio, RFID, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	8
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions.....	12
3.2 Symbols.....	13
3.3 Abbreviations	14
4 Technical requirements specifications	15
4.1 General requirements	15
4.1.1 Receiver categorization.....	15
4.1.2 General performance criteria	15
4.1.3 General performance criteria for wireless power transfer (WPT) systems	15
4.2 Presentation of equipment for testing purposes.....	17
4.2.1 Choice of model for testing	17
4.2.2 Testing of equipment with alternative radiated H-field strengths	18
4.2.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	18
4.2.3.1 Equipment with an internal permanent or temporary antenna connector	18
4.2.3.2 Equipment with a temporary antenna connector	18
4.2.3.3 Wireless Power Transfer systems	18
4.2.4 On-site testing.....	18
4.3 Mechanical and electrical design.....	18
4.3.1 General.....	18
4.3.1.1 WPT	18
4.3.2 Controls	18
4.3.3 Transmitter shut-off facility	19
4.3.4 Receiver mute or squelch.....	19
4.3.5 Marking (equipment identification)	19
4.3.5.1 Equipment identification	19
4.3.5.2 Equipment marking	19
4.4 Declarations by the provider	19
4.5 Auxiliary test equipment	19
4.6 Interpretation of the measurement results	19
5 Test conditions, power sources and ambient temperatures	20
5.1 Normal and extreme test conditions	20
5.2 Test power source.....	20
5.2.1 External test power source	20
5.2.2 Internal test power source	20
5.3 Normal test conditions.....	20
5.3.1 Normal temperature and humidity	20
5.3.2 Normal test power source	21
5.3.2.1 Mains voltage	21
5.3.2.2 Regulated lead-acid battery power sources	21
5.3.2.3 Other power sources.....	21
5.4 Extreme test conditions	21
5.4.1 Extreme temperatures	21
5.4.1.1 Procedure for tests at extreme temperatures.....	21
5.4.1.1.1 Procedure for equipment designed for continuous operation	21
5.4.1.1.2 Procedure for equipment designed for intermittent operation	21

5.4.1.2	Extreme temperature ranges.....	22
5.4.2	Extreme test source voltages.....	22
5.4.2.1	Mains voltage.....	22
5.4.2.2	Regulated lead-acid battery power sources.....	22
5.4.2.3	Power sources using other types of batteries.....	22
5.4.2.4	Other power sources.....	23
6	General conditions.....	23
6.1	Normal test signals and test modulation.....	23
6.1.1	Normal test signals for analogue speech.....	23
6.1.2	Normal test signals for data.....	23
6.2	Artificial antenna.....	23
6.2.1	Artificial antenna for inductive transmitters (non 50 Ω).....	23
6.2.2	Artificial antenna for transmitters with 50 Ω impedance connector.....	24
6.3	Test fixture.....	24
6.4	Test sites and general arrangements for radiated measurements.....	25
6.5	Modes of operation of the transmitter.....	25
6.6	Measuring receiver.....	25
7	Transmitter requirements.....	25
7.1	Transmitter definitions.....	26
7.1.1	The inductive loop coil transmitters.....	26
7.1.2	The large size loop transmitters.....	26
7.1.3	Other transmitters.....	26
7.1.4	Product Classes.....	26
7.2	Transmitter carrier output levels.....	30
7.2.1	H-field (radiated).....	30
7.2.1.1	Definition.....	30
7.2.1.2	Methods of measurement.....	30
7.2.1.3	Limits.....	30
7.2.2	RF carrier current (Product Class 3 only).....	32
7.2.2.1	Definition.....	32
7.2.2.2	Methods of measurement.....	32
7.2.2.3	Limits.....	32
7.2.3	Radiated E-field (Product Class 4 only).....	32
7.2.3.1	Definition.....	32
7.2.3.2	Methods of measurement.....	32
7.2.3.3	Limits.....	33
7.3	Permitted range of operating frequencies.....	33
7.3.1	Definition.....	33
7.3.2	Method of measurement.....	33
7.3.3	Limits.....	33
7.4	Permitted frequency range of the modulation bandwidth.....	33
7.4.1	Definition.....	34
7.4.2	Method of measurement.....	34
7.4.3	Limits.....	34
7.5	Spurious domain emission limits.....	35
7.5.1	Definition.....	35
7.5.2	Conducted spurious emissions (Product class 3 only).....	35
7.5.2.1	Methods of measurement (< 30 MHz).....	35
7.5.2.2	Limits.....	35
7.5.2.3	Methods of measurement ($\geq$ 30 MHz).....	35
7.5.2.4	Limits.....	36
7.5.3	Radiated field strength.....	36
7.5.3.1	Methods of measurement (< 30 MHz).....	36
7.5.3.2	Limits.....	36
7.5.4	Effective radiated power.....	36
7.5.4.1	Methods of measurement ($\geq$ 30 MHz).....	37
7.5.4.2	Limits.....	37
8	Receiver requirement.....	38
8.1	Adjacent channel selectivity - in band.....	38
8.1.1	Definition.....	38

8.1.2	Method of measurement	38
8.1.3	Limits.....	39
8.2	Blocking or desensitization (Receiver category 1 and 2 only)	39
8.2.1	Definition.....	39
8.2.2	Methods of measurement.....	39
8.2.3	Limits.....	40
8.3	Receiver spurious radiation	40
8.3.1	Definition.....	41
8.3.2	Methods of measurement.....	41
8.3.3	Limits.....	41
8.3.3.1	Radiated emissions below 30 MHz	41
8.3.3.2	Radiated emissions above 30 MHz	41
9	Measurement uncertainty	41
10	Interpretation of results	42
10.1	Measurement uncertainty is equal to or less than maximum acceptable uncertainty	42
Annex A (normative):	Radiated measurement.....	43
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	43
A.1.1	Anechoic chamber.....	43
A.1.2	Anechoic chamber with a conductive ground plane	44
A.1.3	Open Area Test Site (OATS)	45
A.1.3.1	Measurements below 30 MHz	46
A.1.3.2	Measurements above 30 MHz	46
A.1.4	Test antenna.....	47
A.1.5	Substitution antenna	48
A.1.6	Measuring antenna	48
A.2	Guidance on the use of radiation test sites	48
A.2.1	Verification of the test site	48
A.2.2	Preparation of the EUT.....	48
A.2.3	Power supplies to the EUT	48
A.2.4	Range length.....	49
A.2.4.1	Far-field length above 30 MHz.....	49
A.2.4.2	Near-field and Far-field length below 30 MHz.....	49
A.2.5	Site preparation	50
A.3	Coupling of signals.....	50
A.3.1	General	50
A.3.2	Data signals	50
A.4	Standard test position	50
A.5	Test fixture	51
A.5.1	Description	51
A.5.2	Calibration.....	52
A.5.3	Mode of use	52
A.6	Technical performance of the spectrum analyser	53
Annex B (normative):	H-field limit correction factor for generated E-fields.....	54
Annex C (normative):	Customized loop antennas.....	55
C.1	Product classes related to the antenna loop	55
C.1.1	Antenna loops below 1 MHz	55
C.1.2	Antenna loops above 1 MHz	56
Annex D (informative):	Test fixture for measuring inductive transmitter carrier and harmonic currents by use of an artificial antenna (Product Class 3 only).....	58
Annex E (informative):	E-fields in the near field at low frequencies.....	60

Annex F (normative):	H-field measurements and limits at 3 m and 30 m	61
F.1	Limits for measurements at 30 m distance	61
F.2	Limits for measurements at 3 m distance	62
Annex G (normative):	Transmitter emission levels and spectrum mask measurements.....	63
Annex H (normative):	Generic inductive loop limits in the frequency range 148,5 kHz to 30 MHz	66
H.1	Introduction	66
H.2	Radiated H-field strength	66
H.2.1	Methods of measurements	66
H.2.2	Radiated H-field strength limit	66
H.2.2.1	Radiated total H-field and H-field density limits according to the measurements in clause H.2.1 indent a)	66
H.2.2.2	Radiated bandwidth and H-field density limits according to the measurements in clause H.2.1 indent b)	67
H.3	Other requirements	67
Annex I (informative):	Determination and use of the measurement bandwidth.....	68
Annex J (informative):	Other limits.....	69
Annex K (informative):	Bibliography.....	70
History		71

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document includes improvements to the previous version of the standard that take advantage of technical developments within the SRD industry.

The present document is part 1 of a multi-part deliverable covering Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates	
Date of adoption of this EN:	20 February 2015
Date of latest announcement of this EN (doa):	31 May 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2015
Date of withdrawal of any conflicting National Standard (dow):	30 November 2015

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document has been prepared to:

- Enhance operating conditions for RFIDs in the 13,56 MHz Band with regard to high datarate wideband low level systems up to ± 7 MHz for ISO 14443 [i.9] type applications including NFC and secondly for higher operating range, narrowband high level modulation for ISO 15693 [i.10] and ISO 18000-3 [i.11] type systems.
- Include wireless inductive power transfer (WPT) systems.

1 Scope

The present document applies to the following Short Range Device major equipment types:

- 1) Generic Short range Devices including transmitters operating in the range from 9 kHz to 25 MHz; and
- 2) inductive loop transmitters operating from 9 kHz to 30 MHz including Radio Frequency Identification (RFID) and EAS operating in LF and HF ranges and for radio equipment including wireless power transfer (WPT) function in the same frequency range;
- 3) receivers of systems as defined by bullets 1 and 2.

These radio equipment types are capable of operating in the permitted frequency bands within the 9 kHz to 30 MHz range as specified in table 1:

- either with a Radio Frequency (RF) output connection and dedicated antenna or with an integral antenna;
- for all types of modulation;
- receivers of systems as defined by bullets 1 and 2.

Table 1 shows a list of the frequency bands as designated to Short Range Devices and the CEPT/ERC/REC 70-03 [i.1] as known at the date of publication of the present document.

When selecting parameters for new SRDs, which may have inherent safety of human life implications, manufacturers and users should pay particular attention to the potential for interference from other systems operating in the same or adjacent bands.

The present document covers fixed stations, mobile stations and portable stations. If a system includes transponders, these are measured together with the transmitter.

All types of modulation for radio devices are covered by the present document, provided the requirements of clause 7.3 are met.

The radio equipment, covered by the classification SRD is divided into several classes based on the maximum radiated magnetic field strength. The field strength designation in the present document is based on CEPT/ERC/REC 70-03 [i.1] and National SRD-frequency designations.

Three types of measuring methods are defined in the present document due to the varied nature of the antenna types for equipment used in this band. One method measures the RF carrier current, another measures the radiated H-field and the third conducted power.

The present document covers requirements for radiated emissions below as well as above 30 MHz.

Additional standards or specifications may be required for equipment such as that intended for connection to the Public Switched Telephone Network (PSTN).

Table 1: Short Range Devices within the 9 kHz to 30 MHz permitted frequency bands

	Frequency Bands/frequencies	Applications
Transmit and Receive	9 kHz to 90 kHz	Inductive devices, Generic use
Transmit and Receive	90 kHz to 119 kHz	Inductive devices, Generic use
Transmit and Receive	119 kHz to 140 kHz	Inductive devices, Generic use
Transmit and Receive	140 kHz to 148,5 kHz	Inductive devices, Generic use
Transmit and Receive	148,5 kHz to 5 MHz	Inductive devices, Generic use
Transmit and Receive	400 kHz to 600 kHz	RFID only
Transmit and Receive	5 kHz to 30 MHz	Inductive devices, Generic use
Transmit and Receive	3 155 kHz to 3 400 kHz	Inductive devices, Generic use
Transmit and Receive	4 234 kHz	Inductive devices, Railway applications
Transmit and Receive	4 516 kHz	Inductive devices, Railway applications
Transmit and Receive	6 765 kHz to 6 795 kHz	Inductive devices, Generic use
Transmit and Receive	7 400 kHz to 8 800 kHz	Inductive devices, Generic use
Transmit and Receive	10 200 kHz to 11,000 MHz	Inductive devices, Generic use
Transmit and Receive	11,810 MHz to 15,310 MHz	RFID only
Transmit and Receive	12,5 MHz to 20 MHz	Inductive devices, Wireless healthcare

	Frequency Bands/frequencies	Applications
Transmit and Receive	13,553 MHz to 13,567 MHz	Inductive devices, Generic use
Transmit and Receive	26,957 MHz to 27,283 MHz	Inductive devices, Generic use
Transmit and Receive	27,095 MHz	Inductive devices, Railway applications

NOTE 1: It should be noted that table 1 represents the most widely implemented position within the European Union and the CEPT countries, but it should not be assumed that all designated bands are available in all countries.

NOTE 2: In addition, it should be noted that other frequency bands may be available in a country within the frequency range 9 kHz to 30 MHz covered by the present document.

NOTE 3: On non-harmonized parameters, national administrations may impose certain conditions such as the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated power, duty cycle, and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of an Individual Rights for use of spectrum or General Authorization, or as a condition for use under "licence exemption" as it is in most cases for Short Range Devices.

The present document covers fixed stations, mobile stations and portable stations.

Applications using Ultra-WideBand (UWB) technology are not covered by the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] CISPR 16-1-4: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.2] Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".

- [i.3] ANSI C63.5: "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [i.4] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.5] ETSI TR 102 273-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.6] ETSI TR 102 273-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.7] ETSI TR 102 273-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.8] ECC report 208: "Impact of RFID devices on radio services in the band 13.56 MHz".
- [i.9] ISO 14443: "Identification cards -- Contactless integrated circuit cards -- Proximity cards".
- [i.10] ISO 15693: "Information technology -- Radio frequency identification for item management -- Unique identification for RF tags".
- [i.11] ISO 18000-3: "Information technology -- Radio frequency identification for item management -- Part 3: Parameters for air interface communications at 13,56 MHz".
- [i.12] Void.
- [i.13] CENELEC EN 62311: "Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)".
- [i.14] CENELEC EN 62479: "Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)".
- [i.15] CENELEC EN 55011: "Industrial, scientific and medical equipment - Radio-frequency disturbance characteristics - Limits and methods of measurement".
- [i.16] Void.
- [i.17] ETSI EN 300 220 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW".
- [i.18] ETSI EN 300 440 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range".
- [i.19] ETSI EN 301 489-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements".
- [i.20] ETSI EN 301 489-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 246 GHz".
- [i.21] ETSI EN 301 489-17: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment; Part 17: Specific conditions for Broadband Data Transmission Systems".

- [i.22] ETSI EN 300 328: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
- [i.23] ETSI EN 300 330: "ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz".
- [i.24] Recommendation ITU-T O.41: "Psophometer for use on telephone-type circuits".
- [i.25] Directive 2006/95/EC of the European Parliament and of the Council of 12 December 2006 on the harmonisation of the laws of Member States relating to Electrical Equipment designed for use within certain voltage limits (LVD).
- [i.26] ITU Radio Regulations.
- [i.27] Directive 2004/108/EC of the European Parliament and of the Council of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC Text with EEA relevance (EMCD).

koniec náhľadu – text ďalej pokračuje v platenej verzii STN