

STN	Pozemská hromadná rádiová sieť (TETRA). Špecifikácia skúšania zhody. Časť 1: Rádiová sieť.	STN EN 300 394-1 V3.3.1 87 0394
------------	---	---

Terrestrial Trunked Radio (TETRA); Conformance testing specification; Part 1: Radio

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 10/15

Obsahuje: EN 300 394-1 V3.3.1:2015

121651

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, 2015
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy
rozmnžovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

ETSI EN 300 394-1 V3.3.1 (2015-04)



Terrestrial Trunked Radio (TETRA); Conformance testing specification; Part 1: Radio

Reference

REN/TCCE-03233

Keywords

DMO, testing, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
Modal verbs terminology.....	10
Introduction	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	12
3.1 Definitions.....	12
3.2 Symbols.....	12
3.3 Abbreviations	13
4 General	13
4.1 Presentation of equipment for testing purposes.....	13
4.1.1 Facilities and information required for testing.....	14
4.1.2 Choice of radio frequency channels to be tested.....	14
4.1.3 Interpretation of the measurement results.....	15
4.2 Mechanical and electrical design.....	15
4.2.1 General.....	15
4.2.2 Controls	15
4.2.3 Marking	15
5 Radio test configuration, test signals and test modes	15
5.1 General functional radio test configuration.....	15
5.2 Radio test modes	16
5.2.1 Test receive mode	16
5.2.1.1 MS test receive mode for phase modulation	16
5.2.1.2 BS test receive mode for phase modulation	17
5.2.1.3 MS test receive mode for QAM (where supported).....	17
5.2.1.4 BS test receive mode for QAM (where supported).....	18
5.2.2 Test transmit mode.....	19
5.2.2.1 MS testing for phase modulation	19
5.2.2.2 Void.....	19
5.2.2.3 BS testing for phase modulation	19
5.2.2.4 MS testing for QAM (where supported)	19
5.2.2.5 BS testing for QAM (where supported)	20
5.3 Radio test signals.....	21
5.3.1 General.....	21
5.3.2 Test signal T1 (TETRA wanted signal, phase modulation)	21
5.3.2.1 MS testing	21
5.3.2.2 BS testing.....	22
5.3.2.3 Void.....	23
5.3.2.4 Void.....	23
5.3.3 Test signal T2 (TETRA interferer)	23
5.3.4 Test signal T3 (unmodulated interferer)	23
5.3.5 Test signal T4 (TETRA wanted signal, QAM).....	23
5.3.5.1 MS testing	23
5.3.5.1.1 Use of synchronization burst in frame 18 when testing CA MSs.....	25
5.3.5.1.1a Use of frequency correction burst in frame 18 when testing DA MSs	26
5.3.5.2 BS testing.....	28
6 Test conditions	29
6.1 General	29
6.2 Power sources and ambient conditions.....	29
6.2.1 Normal test conditions	29

6.2.2	Extreme test conditions.....	30
6.3	Procedure for tests at extreme temperatures.....	31
6.3.1	Equipment designed for continuous operation.....	31
6.3.2	Equipment designed for intermittent operation.....	31
7	Technical characteristics	31
7.1	Transmitter parameter definitions and limits.....	31
7.1.1	Transmitter output power.....	31
7.1.1.1	Definition	31
7.1.1.2	Limit values for phase modulation and QAM.....	32
7.1.2	Unwanted output power in non-active transmit state.....	32
7.1.2.1	Definition	32
7.1.2.2	Limit values.....	32
7.1.3	Adjacent channel power due to modulation.....	32
7.1.3.1	Definition	32
7.1.3.2	Limit values for phase modulation.....	32
7.1.3.3	Limit values for QAM.....	33
7.1.4	Adjacent channel power due to switching transients	34
7.1.4.1	Definition	34
7.1.4.2	Limit values for phase modulation.....	34
7.1.4.3	Limit values for QAM.....	34
7.1.5	Unwanted emissions far from the carrier	34
7.1.5.1	Definition	34
7.1.5.2	Limit values for phase modulation.....	35
7.1.5.3	Limit values for QAM.....	35
7.1.6	Unwanted radiated emissions	37
7.1.6.1	Definition	37
7.1.6.2	Limit values.....	37
7.1.7	Unwanted emissions during the BLCH/CLCH (linearization)	37
7.1.7.1	Definition	37
7.1.7.2	Limit values for phase modulation.....	37
7.1.7.3	Limit values for QAM.....	37
7.1.8	Transmitter intermodulation attenuation.....	37
7.1.8.1	Definition	37
7.1.8.2	Limit values for phase modulation and QAM.....	38
7.1.8.2.1	MS Limit values	38
7.1.8.2.2	Limit values for single BS transmitter.....	38
7.1.8.2.3	Limit values for intra BS intermodulation.....	38
7.2	Receiver parameter definitions and limits	38
7.2.1	General.....	38
7.2.2	Nominal error rates	39
7.2.2.1	Definition	39
7.2.2.2	Limit values for phase modulation.....	39
7.2.2.3	Limit values for QAM.....	39
7.2.3	Reference sensitivity performance.....	39
7.2.3.1	Definition	39
7.2.3.2	Limit values for phase modulation.....	39
7.2.3.3	Limit values for QAM.....	40
7.2.4	Reference interference performance	41
7.2.4.1	Definition	41
7.2.4.2	Limit values for phase modulation.....	42
7.2.4.3	Limit values for QAM.....	42
7.2.4.3.1	Adjacent channel interference	42
7.2.4.3.2	Co-channel interference.....	43
7.2.5	Blocking characteristics	43
7.2.5.1	Definition	43
7.2.5.2	Limit values for phase modulation.....	43
7.2.5.3	Limit values for QAM.....	44
7.2.6	Spurious response rejection	44
7.2.6.1	Definition	44
7.2.6.2	Limit values for phase modulation.....	45
7.2.6.3	Limit values for QAM.....	45

7.2.7	Intermodulation response rejection.....	45
7.2.7.1	Definition	45
7.2.7.2	Limit values.....	45
7.2.8	Unwanted conducted emissions.....	46
7.2.8.1	Definition	46
7.2.8.2	Limit values.....	46
7.2.9	Unwanted radiated emissions	46
7.2.9.1	Definition	46
7.2.9.2	Limit values.....	46
7.3	Transmitter/receiver parameter definitions and limits.....	46
7.3.1	Modulation accuracy.....	46
7.3.1.1	Definition	46
7.3.1.2	Limit values for phase modulation.....	47
7.3.1.3	Limit values for QAM.....	47
7.3.2	Carrier frequency accuracy.....	47
7.3.2.1	Definition	47
7.3.2.2	Limit values.....	47
7.3.3	MS receiver performance for synchronization burst acquisition	47
7.3.3.1	Definition for phase modulation	47
7.3.3.2	Limit values for phase modulation.....	47
7.3.3.3	Definition for QAM modulation	48
7.3.3.4	Limit values for QAM modulation.....	48
7.3.4	MS Frame alignment performance	48
7.3.4.1	Definition	48
7.3.4.2	Limit values.....	48
7.3.5	MS link control.....	48
7.3.5.1	Definition	48
7.3.5.2	Limit values.....	48
8	Methods of measurement for transmitter parameters.....	49
8.1	Transmitter output power	49
8.1.1	Transmitter output power for phase modulation.....	49
8.1.1.1	MS transmitter output power for phase modulation.....	49
8.1.1.2	BS transmitter output power for phase modulation.....	50
8.1.2	Transmitter output power for QAM.....	51
8.1.2.1	MS transmitter output power for QAM.....	51
8.1.2.2	BS transmitter output power for QAM.....	52
8.2	Unwanted output power in non active transmit state.....	52
8.3	Adjacent channel power due to modulation	52
8.4	Adjacent channel power due to switching transients.....	53
8.5	Unwanted emissions far from the carrier	53
8.6	Unwanted radiated emissions.....	55
8.7	Unwanted emissions during the BLCH/CLCH and BLCH-Q/CLCH-Q (linearization)	55
8.7.1	MS unwanted emissions during the CLCH (linearization)	55
8.7.2	BS unwanted emissions during the BLCH (linearization).....	56
8.7.3	MS unwanted emissions during the CLCH-Q (linearization).....	56
8.7.4	BS unwanted emissions during the BLCH-Q (linearization).....	56
8.8	Transmitter intermodulation attenuation	57
8.8.1	MS Transmitter intermodulation attenuation	57
8.8.2	BS Transmitter intermodulation attenuation.....	57
8.8.3	Intra BS transmitter intermodulation attenuation.....	57
9	Methods of measurement for receiver parameters	57
9.1	General	57
9.2	Nominal error rates for phase modulation.....	57
9.2.1	MS nominal error rate.....	57
9.2.2	BS nominal error rate.....	58
9.3	Reference sensitivity performance	58
9.3.1	MS reference sensitivity performance for phase modulation.....	58
9.3.2	BS reference sensitivity performance for phase modulation	58
9.3.3	MS reference sensitivity performance for QAM	59
9.3.4	BS reference sensitivity performance for QAM	59

9.3.5	PUEM performance	59
9.4	Reference interference performance	59
9.4.1	MS reference interference performance for phase modulation	59
9.4.2	BS reference interference performance for phase modulation	60
9.4.3	MS reference interference performance for QAM	60
9.4.4	BS reference interference performance for QAM	60
9.5	Blocking characteristics	61
9.5.1	MS blocking for phase modulation	61
9.5.2	BS blocking for phase modulation	61
9.5.3	MS blocking for QAM	61
9.5.4	BS blocking for QAM	62
9.6	Spurious response rejection	62
9.6.1	Phase Modulation	62
9.6.2	QAM	62
9.7	Intermodulation response rejection	62
9.7.1	MS intermodulation response rejection for phase modulation	62
9.7.2	BS intermodulation response rejection for phase modulation	63
9.7.3	MS intermodulation response rejection for QAM	63
9.7.4	BS intermodulation response rejection for QAM	63
9.8	Unwanted emissions	64
9.9	Unwanted radiated emissions	64
10	Methods of measurement for transmitter/receiver parameters	64
10.1	Modulation accuracy	64
10.1.1	MS modulation accuracy for phase modulation	65
10.1.2	BS modulation accuracy for phase modulation	65
10.1.3	Vector error magnitude at symbol time for phase modulation	65
10.1.4	MS modulation accuracy for QAM	65
10.1.5	BS modulation accuracy for QAM	65
10.1.6	Vector error magnitude at symbol time for QAM	66
10.2	Carrier frequency accuracy	66
10.2.1	MS carrier frequency accuracy for phase modulation	66
10.2.2	BS carrier frequency accuracy for phase modulation	67
10.2.3	MS carrier frequency accuracy for QAM	67
10.2.4	BS carrier frequency accuracy for QAM	68
10.3	MS receiver performance for synchronization acquisition	68
10.3.1	CA MS receiver performance for synchronization burst acquisition	68
10.3.2	DA MS receiver performance for frequency correction burst acquisition	69
10.4	MS Frame alignment performance	69
10.5	MS link control	69
11	Measurement uncertainty	70
11.1	Transmitter	71
11.2	Receiver	74
11.3	Transmitter/receiver parameter definitions and limits	76
11.4	Interpretation of measurement results	77
Annex A (normative): TETRA receiver testing		78
A.1	Frequencies of spurious response	78
A.2	Test cases and test conditions for BS and MS receivers	78
A.3	Test signal T1/T4, content of BSCH, BSCH-Q/T, BNCH/T and BNCH-Q/T	103
Annex B (normative): Radio test system functions		109
B.1	Test transmitter and receiver	109
B.1.1	General	109
B.1.2	Sampling system	109
B.1.2.1	General	109
B.1.2.2	TETRA filter	109
B.1.2.3	Adjacent channel power measurements	110
B.1.2.4	Modulation accuracy measurements	110

B.1.2.5	Measurement of unwanted output power in the non-active transmit state.....	110
B.1.3	Spectrum analyser	110
B.1.4	Error rate tester	110
B.1.5	Test signal requirements.....	111
B.1.5.1	On channel test signal T1.....	111
B.1.5.2	Interfering test signal T2.....	111
B.1.5.2.1	Phase Modulated	111
B.1.5.2.2	QAM Modulated	111
B.1.5.3	Interfering test signal T3.....	111
B.1.5.4	On channel test signal T4.....	112
B.1.6	Propagation simulators	112
B.1.7	Timing measurement unit.....	112
B.1.8	Passive test system components	112
B.1.9	Test system controller	112

Annex C (normative): TETRA Test Connector Interface (TTCI)..... 113

C.1	General	113
C.2	Formal aspects.....	113
C.3	TTCI, layer 1	114
C.3.1	Mechanical and electrical characteristics	114
C.3.2	Transmission and reception characteristics	114
C.4	TTCI, Layer 2.....	114
C.4.1	General structure	114
C.4.2	Frame structure.....	114
C.4.3	Flow of I-frames on layer 2	115
C.4.3.1	Transmission of frames.....	115
C.4.3.2	Reception of frames	115
C.4.3.3	Parameters on layer 2.....	116
C.5	TTCI, Layer 3.....	116
C.5.1	Message structure	116
C.5.2	Definitions of the messages.....	116
C.5.2.1	DATO	116
C.5.2.1.1	Test equipment error handling	118
C.5.2.2	Bi-directional operation of the TTCI	118
C.5.2.3	Codec conformance testing.....	119
C.5.2.4	ST indicator	119
C.6	Control of MS/BS.....	119
C.6.1	Manual intervention of MS/BS	119
C.6.2	Bi-directional operation of the test interface	119
C.6.3	MS controlled by T1.....	120
C.7	Characteristics of the interface	120
C.7.1	Mechanical characteristics of the interface.....	120
C.7.2	Electric characteristics of the interface.....	120
C.8	Codec conformance testing using the TTCI.....	120
C.8.1	Codec conformance test methodology using the TTCI	121

Annex D (normative): RF test facility using RF loop back..... 122

D.1	Introduction to the TETRA Test (TT) protocol for RF loop back test	123
D.1.1	Outline requirements	123
D.1.2	Test modes.....	124
D.1.3	Switching for loop back test mode	125
D.2	TETRA test entity	125
D.3	TETRA RF loop back test protocol.....	126
D.3.1	Setting the TETRA MS into TETRA test mode.....	126
D.3.2	TETRA test protocol	127

D.3.2.1	Confirming that TETRA test mode is set.....	127
D.3.2.2	Operating TETRA loop back.....	128
D.3.2.3	Ending TETRA test mode.....	128
D.3.3	Bad frame indication	128
D.3.4	Channels required to be looped back.....	129
D.3.5	TETRA loop back test scenarios	129
D.4	TETRA Test (TT) PDU descriptions	129
D.4.1	TT PDU description tables downlink.....	130
D.4.1.1	D-LOOP COMMAND	130
D.4.1.2	D-OPEN LOOP COMMAND	130
D.4.1.3	D-TEST MODE CONFIRM COMMAND.....	130
D.4.1.4	D-TEST MODE END COMMAND	130
D.4.2	TT PDU description tables uplink.....	131
D.4.2.1	U-LOOP CONFIRM.....	131
D.4.2.2	U-OPEN LOOP CONFIRM	131
D.4.2.3	U-TEST MODE CONFIRM.....	131
D.4.2.4	U-TEST MODE END CONFIRM.....	132
D.4.3	Information elements coding.....	132
D.4.3.1	Loopback type	132
D.4.3.2	Confirm.....	132
D.4.3.3	MS power class.....	133
D.4.3.4	PDU	133
D.4.3.5	Receiver class	133
D.5	TT use of MLE, LLC and MAC.....	134
D.6	Message sequence charts and operation of TETRA loop back	134
D.7	Introduction to the T1 and T4 test modes for RF loop back test	134
D.7.1	Outline requirements	134
D.7.2	T1/T4 Test Modes	135
D.7.3	Switching for loop back test mode	135
D.8	TETRA RF loop back T1 test mode (phase modulation).....	137
D.8.1	Setting TETRA equipment into T1 test mode	137
D.8.2	T1 loop back test mode operation.....	137
D.8.3	Logical channels to be looped back.....	138
D.8.4	Return channel for logical channel loop back	138
D.8.4.1	Type 1: TCH/7,2 + AACH	139
D.8.4.2	Type 2: SCH/F + AACH	139
D.8.4.3	Type 3: BSCH + SCH/HD + AACH	139
D.8.4.4	Type 4: TCH/2,4 N = 1 + AACH	140
D.8.4.5	Type 7: TCH/7,2 (uplink).....	140
D.8.4.6	Type 8: SCH/F (uplink)	140
D.8.4.7	Type 9: STCH + STCH (uplink).....	140
D.8.4.8	Type 10: TCH/2,4 N = 1 (uplink)	141
D.8.4.9	Type 11: SCH/HU + SCH/HU.....	141
D.8.4.10	Type 15: TCH/S + TCH/S + AACH.....	141
D.8.4.11	Type 16: TCH/S + TCH/S (uplink)	141
D.8.4.12	Type 17: TCH/4,8 N = 1 + AACH	142
D.8.4.13	Type 18: TCH/4,8 N = 1 (uplink)	142
D.8.4.14	Type 19: TCH/S speech codec test (downlink).....	142
D.8.4.15	Type 20: TCH/S speech codec test (uplink)	142
D.8.4.16	Type 21: TCH-P8/10,8 (downlink).....	143
D.8.4.17	Type 22: SCH-P8/HD + SCH-P8/HD.....	143
D.8.4.18	Type 24: SCH-P8/F (downlink).....	143
D.8.4.19	Type 21: TCH-P8/10,8 (uplink).....	143
D.8.4.20	Type 24: SCH-P8/F (uplink).....	144
D.8.4.21	Type 23: SCH-P8/HU + SCH-P8/HU.....	144
D.8.5	Loop back test scenarios.....	144
D.9	TETRA RF loop back T4 test mode (QAM).....	146
D.9.1	Setting TETRA equipment into T4 test mode	146

D.9.2	T4 loop back test mode operation.....	147
D.9.3	Logical channels to be looped back.....	147
D.9.4	Return channel for logical channel loop back	147
D.9.4.1	Type 27: SCH-Q/D with coding rates of 1/2 or 2/3 and error correction enabled	148
D.9.4.2	Type 27: SCH-Q/D with error correction disabled or when the coding rate is 1	149
D.9.4.3	Type 26: SCH-Q/U with coding rates of 1/2 or 2/3 and error correction enabled	150
D.9.4.4	Type 26: SCH-Q/U with coding rate of 1 or error correction disabled.....	150
D.9.4.5	Type 25: SCH-Q/HU with coding rates of 1/2 or 2/3 and error correction enabled	151
D.9.4.6	Type 25: SCH-Q/HU with coding rate of 1 or error correction disabled.....	151
D.9.4.7	Type 28: SCH-Q/RA with error correction enabled	152
D.10	Direct Mode Operation (DMO).....	152
D.10.1	Direct mode only mobile station (DO-MS).....	153
D.10.2	Dual mode switchable mobile station (DU-MS)	153
D.10.3	Dual watch mobile station (DW-MS).....	153
D.10.4	Direct mode repeater (DM-REP).....	153
D.10.5	Direct mode gateway (DM-GATE).....	153
D.10.6	Direct mode repeater/gateway combination (DM-REP/GATE).....	153
D.10.7	DMO summary.....	153
Annex E (normative): Using RF loop back to test a TETRA MS		154
E.1	Introduction	154
E.2	Expected mode of operation for testing a MS	155
E.3	Recognition of TETRA Test mode by MS.....	158
E.4	Using loop back to test traffic channels	159
E.4.1	TCH/7,2.....	161
E.4.2	TCH/S	162
E.4.3	TCH/2,4, N = 8.....	162
E.4.4	Control messages during loop back of traffic channels	163
Annex F (normative): Direct Mode (DM) Conformance Testing.....		164
F.1	Scope	164
F.2	Definitions, symbols and abbreviations	164
F.3	General	164
F.4	Radio test modes	164
F.5	Test conditions	165
F.6	Additional tests for equipment which is capable of Direct Mode Operation	166
F.6.1	DMO test transmit mode	166
F.6.2	DMO transmitter output power profile.....	166
F.6.2.1	DMO transmitter output power profile, limit values	166
F.6.2.2	DMO transmitter output power profile, method of measurement.....	166
F.6.3	DMO Carrier frequency accuracy	167
F.6.3.1	DMO Carrier frequency accuracy, limit values	167
F.6.3.2	DMO Carrier frequency accuracy, method of measurement	167
F.6.4	DM-MS Slave synchronization accuracy	167
F.6.4.1	DM-MS Slave synchronization accuracy, definition	167
F.6.4.2	DM-MS Slave synchronization accuracy, limit values	167
F.6.4.3	DM-MS Slave synchronization accuracy, method of measurement	167
Annex G (informative): Change requests.....		168
History		169

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

The present document contains text concerning conformance testing of the equipment to which it relates. This text should be considered only as guidance and does not make the present document mandatory.

The present document is part 1 of a multi-part deliverable covering the conformance testing specification, as identified below:

Part 1: "Radio";

Part 2: "Protocol testing specification for Voice plus Data (V+D)";

Part 4: "Protocol testing specification for Direct Mode Operation (DMO)";

Part 5: "Security".

NOTE: Part 2, part 4 and part 5 of this multi-part deliverable are in status "historical" and are not maintained.

National transposition dates	
Date of adoption of this EN:	15 April 2015
Date of latest announcement of this EN (doa):	31 July 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2016
Date of withdrawal of any conflicting National Standard (dow):	31 January 2016

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document includes Direct Access and multislot receiver testing in addition to the earlier Release 2 tests and is aligned with ETSI EN 300 392-2 [1].

1 Scope

The present document specifies the minimum technical characteristics of TETRA Voice plus Data (V+D) Base Stations (BS) and Mobile Station (MS) equipment, and TETRA Direct Mode Operation (DMO) equipment, and the radio test methods used for type testing. Specific test methods for DMO equipment are defined in annex F of the present document. The purpose of these specifications is to provide a sufficient quality of radio transmission and reception for equipment operating in a TETRA system and to minimize harmful interference to other equipment. The present document is applicable to TETRA systems operating at radio frequencies in the range of 300 MHz to 1 GHz.

These specifications do not necessarily include all the characteristics which may be required by a user of equipment, nor do they necessarily represent the optimum performance achievable.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)" / ETSI TS 100 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".

NOTE: The references EN 300 392-2 and TS 100 392-2 are two instances of the same document and the latest version of those is used as the normative reference. For a shorter presentation only EN 300 392-2 [1] is used as the reference in the present document.

- [2] Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [3] ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- [4] Recommendation ITU-T V.1: "Equivalence between binary notation symbols and the significant conditions of a two-condition code".
- [5] ISO 2110:1989: "Information technology - Data communication - 25-pole DTE/DCE interface connector and contact number assignments".
- [6] ETSI EN 300 395-4: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 4: Codec conformance testing".
- [7] ETSI EN 300 396-2: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 2: Radio aspects".
- [8] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General Network Design".
- [9] ETSI EN 300 392-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".

- [10] ETSI ETS 300 392-11-22: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 22: Dynamic Group Number Assignment (DGNA)".
- [11] ETSI EN 300 392-12-22: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 22: Dynamic Group Number Assignment (DGNA)".
- [12] ETSI EN 300 395-2: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 2: TETRA codec".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.2] ETSI EN 300 396-1: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 1: General network design".
- [i.3] ETSI TS 101 293: "Digital cellular telecommunications system (Phase 2+); Individual equipment type requirements and interworking; Special conformance testing functions (3GPP TS 04.14)".

koniec náhľadu – text ďalej pokračuje v platenej verzii STN