

<b>STN</b>	<b>Digitálne bezšnúrové telekomunikácie (DECT). Spoločné rozhranie (CI). Časť 2: Fyzická vrstva (PHL).</b>	<b>STN EN 300 175-2 V2.6.1</b>  87 0175
------------	--	---

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 12/15

Obsahuje: EN 300 175-2 V2.6.1:2015

**122017**

# ETSI EN 300 175-2 V2.6.1 (2015-07)



**Digital Enhanced Cordless Telecommunications (DECT);  
Common Interface (CI);  
Part 2: Physical Layer (PHL)**

---

**Reference**

REN/DECT-000304-2

---

**Keywords**

DECT, IMT-2000, mobility, radio, TDD, TDMA

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope .....	8
2 References .....	8
2.1 Normative references .....	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	10
3.1 Definitions.....	10
3.2 Abbreviations .....	11
4 PHL services .....	12
4.0 General .....	12
4.1 RF channels (access in frequency) .....	13
4.1.1 Nominal position of RF carriers .....	13
4.1.2 Accuracy and stability of RF carriers .....	14
4.2 Time Division Multiple Access (TDMA) structure (access in time).....	14
4.2.1 Frame, full-slot, double-slot, half-slot and variable capacity slot structure (including long slot).....	14
4.2.2 Reference timer accuracy and stability .....	15
4.2.3 RFP transmission jitter.....	16
4.2.4 PP reference timer synchronization .....	16
4.2.5 System synchronization .....	16
4.2.6 Inter-system synchronization.....	16
4.2.7 Reference timer adjustment for synchronization .....	17
4.3 Cells (access in space).....	17
4.4 Physical packets .....	17
4.4.0 General.....	17
4.4.1 The short physical packet P00 .....	17
4.4.2 The basic physical packet P32 .....	18
4.4.3 The variable capacity physical packet P00j .....	18
4.4.4 The high capacity physical packet P80 .....	19
4.5 Physical channels .....	19
4.5.0 General.....	19
4.5.1 Ra (K, L, M, N) notation .....	19
4.5.2 The short physical channel R00 (K, L, M, N).....	20
4.5.3 The basic physical channel R32 (K, L, M, N) .....	20
4.5.4 The variable-rate physical channel R00j (K, L, M, N) .....	21
4.5.5 The high capacity physical channel R80 (K, L, M, N) .....	22
4.6 Synchronization field S .....	22
4.7 D-field .....	23
4.7.1 Physical packet P00 .....	23
4.7.2 Physical packet P32 .....	23
4.7.3 Physical packet P00j .....	23
4.7.4 Physical packet P80 .....	23
4.8 Z-field.....	24
4.9 Bit pattern during ramping .....	24
5 Transmission of physical packets.....	24
5.1 Definitions .....	24
5.1.1 End of the physical packet .....	24
5.1.2 Transmitted power .....	24
5.1.3 Normal Transmitted Power (NTP).....	24
5.2 Transmission burst .....	25
5.2.0 General.....	25
5.2.1 Transmitter attack time .....	25
5.2.2 Transmitter release time.....	25

5.2.3	Minimum power .....	25
5.2.4	Maximum power.....	25
5.2.5	Maintenance of transmission after packet end.....	25
5.2.6	Transmitter idle power output.....	25
5.3	Transmitted power.....	26
5.3.1	Peak power per transceiver .....	26
5.3.1.1	PP and RFP with an integral antenna .....	26
5.3.1.2	PP and RFP with external connections for all antennas .....	26
5.3.2	Maximum EIRP and number of transceivers .....	26
5.4	RF carrier modulation .....	26
5.4.1	Modulation method.....	26
5.4.2	Definition of "1" and "0" .....	26
5.4.3	Deviation limits .....	26
5.5	Unwanted RF power radiation.....	27
5.5.1	Emissions due to modulation.....	27
5.5.2	Emissions due to transmitter transients.....	27
5.5.3	Emissions due to intermodulation.....	27
5.5.4	Spurious emissions when allocated a transmit channel .....	28
6	Reception of physical packets .....	28
6.1	Definitions and conditions for clause 6 .....	28
6.1.1	Power levels and field strength.....	28
6.1.2	Test conditions.....	28
6.1.3	Reference DECT radio end point.....	29
6.2	Radio receiver sensitivity .....	29
6.3	Radio receiver reference bit error rate and frame error ratio.....	29
6.4	Radio receiver interference performance.....	29
6.5	Radio receiver blocking.....	30
6.5.1	Owing to signals occurring at the same time but on other frequencies.....	30
6.5.2	Owing to signals occurring at a different time.....	30
6.6	Receiver intermodulation performance .....	30
6.7	Spurious emissions when not allocated a transmit channel.....	30
6.7.1	Out of band .....	30
6.7.2	In the DECT band.....	31
7	Primitives between physical layer and other entities .....	31
7.0	General .....	31
7.1	Medium access control layer (D-SAP).....	31
7.1.0	D-SAP general .....	31
7.1.1	PL_TX {req} .....	31
7.1.2	PL_RX {req, cfm} .....	32
7.1.3	PL_FREQ_ADJ {req} .....	32
7.2	Management entity (PM-SAP).....	32
7.2.0	PM-SAP general .....	32
7.2.1	PL_ME_SYNC {req, cfm} .....	32
7.2.2	PL_ME_SIG_STR {req, cfm} .....	32
7.2.3	PL_ME_TIME_ADJ {req, cfm} .....	32
8	PHL procedures.....	33
8.1	Addition of synchronization field and transmission.....	33
8.2	Packet reception and removal of synchronization field.....	33
8.3	Measurement of signal strength.....	33
8.4	Synchronization pulse detection.....	34
8.5	Timing adjustment.....	34
8.6	Frequency adjustment.....	34
9	Management entity procedures related to PHL.....	34
9.1	List of quietest physical channels.....	34
9.2	Physical channels with greatest field strength (PP only).....	34
9.3	Extract timing.....	34
<b>Annex A (informative): RF exposure requirements.....</b>		<b>35</b>
A.0	General .....	35

A.1	Recommendation.....	35
A.2	Compliance distances.....	35
<b>Annex B (normative): Synchronization port.....</b>		<b>37</b>
B.1	General requirements .....	37
B.2	Wired synchronization ports .....	37
B.2.0	Wired synchronization general.....	37
B.2.1	Synchronization signal .....	38
B.3	GPS synchronization .....	39
B.3.0	GPS synchronization general .....	39
B.3.1	Synchronization signal .....	40
B.3.2	DECT timings derivation from the GPS time.....	40
B.3.2.0	Timings derivation general .....	40
B.3.2.1	DECT multiframe number synchronization using GPS.....	41
B.3.2.2	DECT PSCN synchronization using GPS.....	41
B.4	Guidance for installation .....	42
B.4.1	Interconnection cable .....	42
B.4.2	Propagation delay of synchronization signals .....	42
B.4.2.1	Calculation of Propagation delay (informative).....	42
B.4.2.2	Delay compensation.....	43
B.4.3	GPS receiver stability.....	43
<b>Annex C (informative): Prolonged preamble.....</b>		<b>44</b>
C.0	General .....	44
C.1	Bit pattern.....	44
C.2	The power-time template.....	44
<b>Annex D (normative): 4-level/8-level/16-level/64-level modulation option .....</b>		<b>45</b>
D.0	General .....	45
D.1	The $\pi/2$ -DBPSK modulation scheme .....	46
D.1.1	RF carrier modulation .....	46
D.1.1.0	Filter and phase change.....	46
D.1.1.1	Modulation accuracy.....	46
D.1.2	Transmission of physical packets.....	47
D.2	The $\pi/4$ -DQPSK modulation scheme.....	47
D.2.1	RF carrier modulation .....	47
D.2.1.0	Filter and phase change.....	47
D.2.1.1	Modulation accuracy.....	47
D.2.2	Transmission of physical packets .....	47
D.3	The $\pi/8$ -D8PSK modulation scheme.....	47
D.3.1	RF carrier modulation .....	47
D.3.1.0	Filter and phase change.....	47
D.3.1.1	Modulation accuracy.....	48
D.3.2	Transmission of physical packets.....	48
D.4	The 16 QAM modulation scheme .....	48
D.4.1	RF carrier modulation .....	48
D.4.1.0	Filter and constellation symbols .....	48
D.4.1.1	Modulation accuracy.....	49
D.4.2	Transmission of physical packets.....	49
D.5	The 64 QAM modulation scheme .....	49
D.5.1	RF carrier modulation .....	49
D.5.1.0	Filter and constellation symbols .....	49
D.5.1.1	Modulation accuracy.....	50

D.5.2	Transmission of physical packets .....	51
D.6	Transmission of physical packets .....	51
D.6.1	Error vector magnitude definition .....	51
D.6.2	EVM requirement .....	51
<b>Annex E (normative):</b>	<b>Power control procedures .....</b>	<b>52</b>
E.0	General .....	52
E.1	Definitions of parameters and relations between parameters .....	52
E.2	Procedure for PP power adjustment due to movement .....	53
E.3	Setting the power control threshold, RSSpT .....	54
<b>Annex F (normative):</b>	<b>DECT carrier numbers and carrier positions in the range 1 880 MHz to 2 025 MHz and for the US market 902 MHz to 928 MHz and 2 400 MHz to 2 483,5 MHz.....</b>	<b>55</b>
F.1	Introduction .....	55
F.2	1 880 MHz to 1 978 MHz and 2 010 MHz to 2 025 MHz RF band 00001 .....	55
F.3	1 880 MHz to 1 925 MHz and 2 010 MHz to 2 025 MHz RF band 00010.....	56
F.4	1 880 MHz to 1 900 MHz, 1 915 MHz to 1 940 MHz and 2 010 MHz to 2 025 MHz RF band 00011 .....	57
F.5	1 880 MHz to 1 900 MHz, 1 935 MHz to 1 960 MHz and 2 010 MHz to 2 025 MHz RF band 00100.....	58
F.6	1 880 MHz to 1 900 MHz, 1 955 MHz to 1 980 MHz and 2 010 MHz to 2 025 MHz RF band 00101 .....	59
F.7	US ISM band carriers .....	60
F.7.0	General .....	60
F.7.1	902 MHz to 928 MHz RF band 01000 .....	60
F.7.2	2 400 MHz to 2 483,5 MHz RF band 01001 .....	61
<b>Annex G (informative):</b>	<b>Bibliography.....</b>	<b>62</b>
<b>Annex H (informative):</b>	<b>Change history .....</b>	<b>63</b>
History .....		64

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 2 of a multi-part deliverable ([1] to [8]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2].

<b>National transposition dates</b>	
Date of adoption of this EN:	24 July 2015
Date of latest announcement of this EN (doa):	31 October 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2016
Date of withdrawal of any conflicting National Standard (dow):	30 April 2016

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.



---

# 1 Scope

The present document is one of the parts of the specification of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI).

The present document specifies the physical channel arrangements. DECT physical channels are radio communication paths between two radio end points. A radio end point is either part of the fixed infrastructure, a privately owned Fixed Part (FP), typically a base station, or a Portable Part (PP), typically a handset. The assignment of one or more particular physical channels to a call is the task of higher layers.

The Physical Layer (PHL) interfaces with the Medium Access Control (MAC) layer, and with the Lower Layer Management Entity (LLME). On the other side of the PHL is the radio transmission medium which has to be shared extensively with other DECT users and a wide variety of other radio services. The tasks of the PHL can be grouped into five categories:

- a) to modulate and demodulate radio carriers with a bit stream of a defined rate to create a radio frequency channel;
- b) to acquire and maintain bit and slot synchronization between transmitters and receivers;
- c) to transmit or receive a defined number of bits at a requested time and on a particular frequency;
- d) to add and remove the synchronization field and the Z-field used for rear end collision detection;
- e) to observe the radio environment to report signal strengths.

The present document includes New Generation DECT, a further development of the DECT standard introducing wideband speech, improved data services, new slot types and other technical enhancements.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] Void.
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".

- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [9] ETSI EN 300 176-1: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio".
- [10] Recommendation ITU-R M.1457-11: "Detailed specifications of the terrestrial radio interfaces of International Mobile Telecommunications-2000 (IMT-2000)".
- [11] Recommendation ITU-T V.11: "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [12] Federal Communications Commission FCC 02-151: "Second Report and Order, Amendment of Part 15 of the Commission's Rules Regarding Spread Spectrum Devices".
- [13] CEPT/ECC/DEC/(06)01: "ECC Decision of 24 March 2006 amended 02 November 2012 on the harmonised utilisation of the bands 1920-1980 MHz and 2110-2170 MHz for mobile/fixed communications networks (MFCN) including terrestrial IMT systems".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 178: "Digital Enhanced Cordless Telecommunications (DECT); A High Level Guide to the DECT Standardization".
- [i.2] ETSI ETR 043: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Services and facilities requirements specification".
- [i.3] International Commission on Non-Ionizing Radiation Protection (ICNIRP): "Guidelines for limiting exposure to time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz), Health Physics", vol. 74, pp 494-522, April 1998.
- [i.4] Council Recommendation 1999/519/EC of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) (Official Journal of the European Communities, July 1999).
- [i.5] CENELEC EN 50360: "Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz - 3 GHz)", European Committee for Electrotechnical Standardization (CENELEC), July 2001. (Harmonized standard listed under the R&TTE directive).
- [i.6] CENELEC EN 50385: "Product standard to demonstrate the compliance of radio base stations and fixed terminal stations for wireless telecommunication systems with the basic restrictions or the reference levels related to human exposure to radio frequency electromagnetic fields (110 MHz - 40 GHz) - General public", European Committee for Electrotechnical Standardization (CENELEC), November 2001 (draft).
- [i.7] CENELEC EN 50383: "Basic standard for the calculation and measurement of electromagnetic field strength and SAR related to human exposure from radio base stations and fixed terminal stations for wireless telecommunication systems (110 MHz - 40 GHz)", European Committee for Electrotechnical Standardization (CENELEC), November 2001 (draft).

- [i.8] IEEE 802.11b: "Standard for Information Technology - Telecommunications and Information Exchange Between Systems - Local and Metropolitan Area Networks - Specific Requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".

**koniec náhľadu – text ďalej pokračuje v platenej verzii STN**