

STN

**Bunkové siete IMT. Harmonizovaná EN
vzťahujúca sa na základné požiadavky podľa
článku 3.2 smernice R&TTE. Časť 3: Základňové
stanice (BS) CDMA s priamym rozprestrením
(UTRA FDD).**

**STN
EN 301 908-3
V7.1.1**

87 1908

IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 3: CDMA Direct Spread (UTRA FDD) Base Stations (BS)

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 12/15

Obsahuje: EN 301 908-3 V7.1.1:2015

122026

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, 2016
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy
rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

ETSI EN 301 908-3 V7.1.1 (2015-07)



**IMT cellular networks;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 3: CDMA Direct Spread (UTRA FDD) Base Stations (BS)**

Reference

REN/MSG-TFES-011-03

Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT, IMT-Advanced, LTE, mobile, radio, regulation, UMTS, WCDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	11
3.3 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	13
4.2.1 Introduction.....	13
4.2.2 Spectrum emissions mask	16
4.2.2.1 Definition	16
4.2.2.2 Limit.....	16
4.2.2.3 Conformance	22
4.2.3 Adjacent channel leakage power ratio (ACLR).....	23
4.2.3.1 Definition	23
4.2.3.2 Limits	23
4.2.3.3 Cumulative ACLR test requirement in non-contiguous spectrum or multiple-bands	24
4.2.3.4 Conformance	25
4.2.4 Transmitter spurious emissions.....	25
4.2.4.1 Definition	25
4.2.4.2 Limits	25
4.2.4.2.1 Spurious emissions	25
4.2.4.2.2 Co-existence with other systems	26
4.2.4.2.3 Co-existence with services in adjacent frequency bands.....	27
4.2.4.2.4 Protection of the BS receiver of own or different BS	27
4.2.4.2.5 Co-existence with Home BS operating in other bands	29
4.2.4.3 Conformance	29
4.2.5 Base Station maximum output power	29
4.2.5.1 Definition	29
4.2.5.2 Limit.....	29
4.2.5.3 Conformance	30
4.2.6 Transmitter intermodulation	30
4.2.6.1 Definition	30
4.2.6.2 Limit.....	31
4.2.6.3 Conformance	31
4.2.7 Receiver spurious emissions	31
4.2.7.1 Definition	31
4.2.7.2 Limit.....	31
4.2.7.3 Conformance	31
4.2.8 Blocking characteristics	31
4.2.8.1 Definition	31
4.2.8.2 Limit.....	32
4.2.8.3 Conformance	36
4.2.9 Receiver intermodulation characteristics	36
4.2.9.1 Definition	36
4.2.9.2 Limit.....	36
4.2.9.3 Conformance	38

4.2.10	Receiver adjacent channel selectivity	38
4.2.10.1	Definition	38
4.2.10.2	Limit.....	38
4.2.10.3	Conformance	39
4.2.11	Home BS output power for adjacent channel protection	39
4.2.11.1	Definition	39
4.2.11.2	Limit.....	39
4.2.11.3	Conformance	40
5	Testing for compliance with technical requirements.....	40
5.1	Environmental conditions for testing	40
5.2	Interpretation of the measurement results	40
5.3	Essential radio test suites.....	42
5.3.0	Introduction.....	42
5.3.1	Spectrum emission mask	42
5.3.1.0	General	42
5.3.1.1	Initial conditions	42
5.3.1.2	Procedures.....	42
5.3.2	Adjacent Channel Leakage power Ratio (ACLR)	43
5.3.2.1	Initial conditions	43
5.3.2.2	Procedure	43
5.3.3	Transmitter spurious emissions.....	44
5.3.3.0	General	44
5.3.3.1	Initial conditions	44
5.3.3.2	Procedure	44
5.3.4	Base Station maximum output power	45
5.3.4.0	General	45
5.3.4.1	Initial conditions	45
5.3.4.2	Procedure	45
5.3.5	Transmit intermodulation	45
5.3.5.0	General	45
5.3.5.1	Initial conditions	45
5.3.5.2	Procedures.....	46
5.3.6	Receiver spurious emissions	46
5.3.6.0	General	46
5.3.6.1	Initial conditions	47
5.3.6.2	Procedure	47
5.3.7	Blocking characteristics.....	47
5.3.7.0	General	47
5.3.7.1	Initial conditions	47
5.3.7.2	Procedure	48
5.3.8	Receiver intermodulation characteristics	49
5.3.8.0	General	49
5.3.8.1	Initial conditions	49
5.3.8.2	Procedures.....	49
5.3.9	Adjacent Channel Selectivity (ACS)	50
5.3.9.0	General	50
5.3.9.1	Initial conditions	50
5.3.9.2	Procedure	50
5.3.10	Home BS output power for adjacent channel protection	50
5.3.10.1	Initial conditions	50
5.3.10.2	Procedure	51
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	52
Annex B (normative):	Base Station configurations.....	54
B.1	Receiver diversity.....	54
B.2	Duplexers	54
B.3	Power supply options	54

B.4	Ancillary RF amplifiers.....	55
B.5	BS using antenna arrays	55
B.5.0	Introduction	55
B.5.1	Receiver tests.....	56
B.5.2	Transmitter tests	56
B.6	Transmit diversity and MIMO transmission	56
B.7	BS with integrated Iuant BS modem.....	57
Annex C (informative):	Environmental profile specification	58
Annex D:	Void	59
Annex E (informative):	Bibliography.....	60
History		61

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to mandates M/284 and M/406 issued from the European Commission under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.7].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.5].

National transposition dates	
Date of adoption of this EN:	1 July 2015
Date of latest announcement of this EN (doa):	31 October 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2016
Date of withdrawal of any conflicting National Standard (dow):	30 April 2017

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in ETSI EG 201 399 [i.3].

1 Scope

The present document applies to the following {radio}{telecommunications terminal} equipment types:

- 1) Stations for IMT 2000 CDMA Direct Spread (UTRA FDD).

This radio equipment type is capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: UTRA FDD Base Station operating bands

UTRA FDD band	Direction of transmission	UTRA FDD Base Station operating bands
I	Transmit	2 110 MHz to 2 170 MHz
	Receive	1 920 MHz to 1 980 MHz
III	Transmit	1 805 MHz to 1 880 MHz
	Receive	1 710 MHz to 1 785 MHz
VII	Transmit	2 620 MHz to 2 690 MHz
	Receive	2 500 MHz to 2 570 MHz
VIII	Transmit	925 MHz to 960 MHz
	Receive	880 MHz to 915 MHz
XV	Transmit	2 600 MHz to 2 620 MHz
	Receive	1 900 MHz to 1 920 MHz
XVI	Transmit	2 585 MHz to 2 600 MHz
	Receive	2 010 MHz to 2 025 MHz
XX	Transmit	791 MHz to 821 MHz
	Receive	832 MHz to 862 MHz
XXII	Transmit	3 510 MHz to 3 590 MHz
	Receive	3 410 MHz to 3 490 MHz
XXXII (see note)	Transmit	1 452 MHz to 1 492 MHz
	Receive	-

NOTE: The down link frequenc(ies) of this band are paired with the uplink frequenc(ies) of the other FDD band (external) of the dual band configuration.

The present document covers requirements for UTRA FDD Base Stations for 3GPP Releases 99, 4, 5, 6, 7, 8, 9, 10 and 11. This includes the requirements for BS operating bands from 3GPP Release 12. In addition, the present document covers requirements for UTRA FDD Base Stations in the operating bands specified in ETSI TS 102 735 [i.4].

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive), Article 3.2, which states that "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] ETSI TS 125 141 (V11.10.0) (01-2015): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 11.10.0 Release 11)".
- [3] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [4] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [5] ETSI TS 136 104 (V11.11.0) (01-2015): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104 version 11.11.0 Release 11)".
- [6] ETSI TS 145 004 (V11.0.0) (10-2012): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 11.0.0 Release 11)".
- [7] Void.
- [8] Void.
- [9] ETSI TS 125 104 (V11.10.0) (01-2015): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 11.10.0 Release 11)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio Equipment Directive".
- [i.4] ETSI TS 102 735 (V7.1.0): "Universal Mobile Telecommunications System (UMTS); Band-specific requirements for UMTS Frequency Division Duplex (FDD) operation in the bands 1 900 MHz to 1 920 MHz paired with 2 600 MHz to 2 620 MHz and 2 010 MHz to 2 025 MHz paired with 2 585 MHz to 2 600 MHz".
- [i.5] ETSI EN 301 908-1 (V7.1.1) (09-2014): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 1: Introduction and common requirements".
- [i.6] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

- [i.8] ETSI EN 301 908-18 (V7.1.2) (07-2014): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS)".
- [i.9] CEPT ECC Decision (13)03: "The harmonised use of the frequency band 1452-1492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".

koniec náhľadu – text ďalej pokračuje v platenej verzii STN