

<b>STN</b>	<b>Železnice. Koľaj. Protihlukové bariéry a súvisiace zariadenia proti šíreniu zvuku. Skúšobná metóda určovania akustických vlastností. Časť 7: Vonkajšie charakteristiky. Hodnoty vloženého útlmu zvuku na mieste uloženia (in situ).</b>	<b>STN P CEN/TS 16272-7</b>  <b>73 6381</b>
------------	--	---

Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Test method for determining the acoustic performance - Part 7: Extrinsic characteristics - In situ values of insertion loss

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 04/16

Táto predbežná STN je určená na overenie. Pripomienky zasielajte ÚNMS SR najneskôr do augusta 2017.

Obsahuje: CEN/TS 16272-7:2015

**122743**

---

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, 2016

Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

## TECHNICAL SPECIFICATION

**CEN/TS 16272-7**

## SPÉCIFICATION TECHNIQUE

## TECHNISCHE SPEZIFIKATION

September 2015

ICS 93.100

English Version

**Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Test method for determining the acoustic performance - Part 7: Extrinsic characteristics - In situ values of insertion loss**

Applications ferroviaires - Voie - Dispositifs de réduction du bruit - Méthode d'essai pour la détermination des performances acoustiques - Partie 7 : Caractéristiques extrinsèques - Valeurs in situ de la perte par insertion

Bahnanwendungen - Oberbau - Lärmschutzwände und verwandte Vorrichtungen zur Beeinflussung der Luftschallausbreitung - Prüfverfahren zur Bestimmung der akustischen Eigenschaften - Teil 7: Fremdspezifische Merkmale - In-situ-Werte zur Einfügungsdämpfung

This Technical Specification (CEN/TS) was approved by CEN on 17 August 2015 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

	Page
<b>European foreword.....</b>	<b>4</b>
<b>Introduction .....</b>	<b>5</b>
<b>1 Scope.....</b>	<b>6</b>
<b>2 Normative references.....</b>	<b>6</b>
<b>3 Terms and definitions .....</b>	<b>7</b>
<b>4 Symbols and abbreviations .....</b>	<b>9</b>
<b>5 Methods .....</b>	<b>10</b>
<b>5.1 General.....</b>	<b>10</b>
<b>5.2 Direct measurement method.....</b>	<b>10</b>
<b>5.3 Indirect measurement method .....</b>	<b>10</b>
<b>6 Instrumentation .....</b>	<b>10</b>
<b>6.1 Sound level meter and analyzer .....</b>	<b>10</b>
<b>6.2 Sound calibrator.....</b>	<b>10</b>
<b>6.3 Windscreen .....</b>	<b>11</b>
<b>6.4 Other instrumentation system.....</b>	<b>11</b>
<b>6.5 Meteorological equipment.....</b>	<b>11</b>
<b>7 Acoustic environment .....</b>	<b>11</b>
<b>7.1 General.....</b>	<b>11</b>
<b>7.2 Terrain profile and ground surface equivalence.....</b>	<b>11</b>
<b>7.3 Meteorological conditions .....</b>	<b>12</b>
<b>7.3.1 General.....</b>	<b>12</b>
<b>7.3.2 Wind.....</b>	<b>12</b>
<b>7.3.3 Temperature.....</b>	<b>13</b>
<b>7.3.4 Humidity.....</b>	<b>13</b>
<b>7.3.5 Cloud cover .....</b>	<b>13</b>
<b>7.3.6 Others .....</b>	<b>14</b>
<b>7.3.7 Background noise .....</b>	<b>14</b>
<b>8 Sources and source equivalence.....</b>	<b>14</b>
<b>8.1 Source type .....</b>	<b>14</b>
<b>8.1.1 General.....</b>	<b>14</b>
<b>8.1.2 Source type A .....</b>	<b>14</b>
<b>8.1.3 Source type B .....</b>	<b>14</b>
<b>8.1.4 Source type C.....</b>	<b>14</b>
<b>8.2 Source equivalence.....</b>	<b>15</b>
<b>8.2.1 General.....</b>	<b>15</b>
<b>8.2.2 Operational parameters .....</b>	<b>16</b>
<b>8.2.3 Reference microphone position .....</b>	<b>16</b>
<b>9 Measurement procedure.....</b>	<b>17</b>
<b>9.1 General planning .....</b>	<b>17</b>
<b>9.1.1 Measurement.....</b>	<b>17</b>
<b>9.1.2 Receiver positions.....</b>	<b>17</b>
<b>9.1.3 Quantities to be measured.....</b>	<b>17</b>

<b>9.2</b>	<b>Determination of barrier insertion loss .....</b>	<b>18</b>
<b>9.2.1</b>	<b>Direct measurement method .....</b>	<b>18</b>
<b>9.2.2</b>	<b>Indirect measurement method.....</b>	<b>18</b>
<b>10</b>	<b>Measurement uncertainty.....</b>	<b>19</b>
<b>11</b>	<b>Test report .....</b>	<b>19</b>
<b>11.1</b>	<b>Information to be recorded.....</b>	<b>19</b>
<b>11.1.1</b>	<b>Type of method.....</b>	<b>19</b>
<b>11.1.2</b>	<b>Instrumentation.....</b>	<b>19</b>
<b>11.1.3</b>	<b>Acoustic environment.....</b>	<b>19</b>
<b>11.1.4</b>	<b>Sound source .....</b>	<b>19</b>
<b>11.1.5</b>	<b>Barrier to be tested.....</b>	<b>19</b>
<b>11.1.6</b>	<b>Site layout.....</b>	<b>19</b>
<b>11.1.7</b>	<b>Acoustical data.....</b>	<b>20</b>
<b>11.2</b>	<b>Expression of results .....</b>	<b>20</b>
<b>11.3</b>	<b>Further information .....</b>	<b>20</b>
	<b>Annex A (informative) Measurement uncertainty.....</b>	<b>21</b>
<b>A.1</b>	<b>General .....</b>	<b>21</b>
<b>A.2</b>	<b>Measurement uncertainty based upon reproducibility data .....</b>	<b>21</b>
	<b>Bibliography .....</b>	<b>22</b>

## European foreword

This document (CEN/TS 16272-7:2015) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This Technical Specification is one of the series EN 16272, *Railway applications — Track — Noise barriers and related devices acting on airborne sound propagation — Test method for determining the acoustic performance*, as listed below:

- *Part 1: Intrinsic characteristics — Sound absorption in the laboratory under diffuse sound field conditions;*
- *Part 2: Intrinsic characteristics — Airborne sound insulation in the laboratory under diffuse sound field conditions;*
- *Part 3-1: Normalized railway noise spectrum and single number ratings for diffuse field applications;*
- *Part 3-2: Normalized railway noise spectrum and single number ratings for direct field applications;*
- *Part 4: Intrinsic characteristics — In situ values of sound diffraction under direct sound field conditions [currently at Enquiry stage];*
- *Part 5: Intrinsic characteristics — In situ values of sound reflection under direct sound field conditions;*
- *Part 6: Intrinsic characteristics — In situ values of airborne sound insulation under direct sound field conditions;*
- *Part 7: Extrinsic characteristics — In situ values of insertion loss [the present document].*

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## Introduction

The purpose of insertion loss measurements is to have an indication of the “efficiency” of the complete installation in attenuating noise from a technical point of view, *as is usually done with calculations*. The insertion loss is not intended to compare products; in fact, it is site-dependent, so that the same product may give different results when installed on different sites.

In order to be representative, these measurements need to be done in well-defined conditions regarding:

- the noise source (number and type of trains, speed, etc.);
- the meteorological window;
- the measurement time;
- the reference time, i.e. the time over which the measured insertion loss is evaluated based on the measurement results.

When it is not possible to carry out measurements before the construction of the noise barrier, an “equivalent” site is used for the “before” measurements.

The assessment of insertion loss limiting values is out of the scope of this Technical Specification.

## 1 Scope

This Technical Specification specifies methods for the determination of insertion loss of outdoor noise barriers intended to shield railway noise. It specifies detailed procedures for *in situ* measurement of barrier insertion loss including microphone positions, source conditions and acoustic environments of the measurement sites.

This Technical Specification allows one to measure the insertion loss of a given noise barrier at a given site including given meteorological conditions. It does not make it possible to compare insertion loss values of an equivalent barrier at a different site. It can be used for comparing insertion loss values of different types of barriers at the same site under given meteorological conditions by the "direct method".

This Technical Specification gives a method for determining insertion loss:

- a) from the level difference before and after the installation of noise barriers (the "direct method");
- b) when the direct method is not applicable, because a barrier has already been installed, using an "indirect method" to estimate the sound pressure levels before installation of the barrier by measurement at another site which has been judged to be equivalent.

For equivalent sites, a close match is required in source characteristics, microphone locations, terrain profiles ground surface characteristics, surrounding artificial structures and meteorological conditions. This Technical Specification prescribes principles for ensuring that sufficiently equivalent conditions are maintained between "before" and "after" cases to permit certain, reliable and repeatable determination of barrier insertion loss.

This Technical Specification does not cover the determination of the intrinsic acoustic characteristics of the barrier, for example the sound insulation index and the sound absorption coefficient.

The equivalent continuous A-weighted sound pressure level and one-third-octave band sound pressure level are used as noise descriptors.

This Technical Specification can be used for routine determination of barrier performance or for engineering or diagnostic evaluation. It can be used in situations where the barrier is to be installed or has already been installed.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60942, *Electroacoustics — Sound calibrators (IEC 60942)*

EN 61260, *Electroacoustics — Octave-band and fractional-octave-band filters (IEC 61260)*

EN 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications (IEC 61672-1)*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

**koniec náhľadu – text d'alej pokračuje v platenej verzii STN**