

STN	Prenosné rádiové zariadenia s veľmi vysokou frekvenciou (VHF) používané v námornej pohyblivej službe v pásmach VHF (okrem systému GMDSS). Harmonizovaná norma vzťahujúca sa na základné požiadavky podľa článku 3.2 smernice 2014/53/EÚ.	STN EN 301 178 V2.1.1 87 1178
------------	---	---

Portable Very High Frequency (VHF) radiotelephone equipment for the maritime mobile service operating in the VHF bands (for non-GMDSS applications only); Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 09/16

Obsahuje: EN 301 178 V2.1.1:2015

123532

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, 2016
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

ETSI EN 301 178 V2.1.1 (2015-12)



HARMONISED EUROPEAN STANDARD

**Portable Very High Frequency (VHF) radiotelephone equipment
for the maritime mobile service operating in the VHF bands
(for non-GMDSS applications only);
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

Reference

REN/ERM-TG26-138

Keywords

maritime, radio, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	9
3.3 Abbreviations	9
4 General and operational requirements.....	10
4.1 Construction	10
4.2 Controls and indicators.....	10
4.3 Microphone and loudspeaker	11
4.4 Safety precautions	11
4.5 Labelling.....	11
5 Technical requirements specifications	12
5.1 Environmental profile.....	12
5.2 Conformance requirements	12
5.2.1 Switching time	12
5.2.2 Class of emission and modulation characteristics.....	12
6 General conditions of measurement	12
6.1 Arrangements for RF connections to the equipment	12
6.1.1 RF connections to integral antenna equipment	12
6.1.2 RF connection to equipment with a detachable antenna.....	12
6.2 Arrangements for test signals applied to the receiver input.....	12
6.3 Squelch.....	12
6.4 Normal test modulation	12
6.5 Artificial antenna.....	13
6.6 Arrangements for test signals applied to the transmitter input	13
6.7 Test channels.....	13
6.8 Test conditions, power sources and ambient temperatures.....	13
6.8.1 Normal and extreme test conditions.....	13
6.8.2 Test power source	13
6.9 Normal test conditions.....	13
6.9.1 Normal temperature and humidity	13
6.9.2 Normal power sources	13
6.9.2.1 Battery power source.....	13
6.9.2.2 Other power sources.....	14
6.10 Extreme test conditions	14
6.10.0 General.....	14
6.10.1 Extreme temperatures	14
6.10.2 Extreme values of test power sources	14
6.10.2.1 Battery power source.....	14
6.10.2.2 Other power sources.....	14
6.11 Procedure for tests at extreme temperatures.....	14
7 Environmental tests	14
7.1 Procedure.....	14
7.2 Performance check	15
7.3 Drop test.....	15
7.3.1 Definition.....	15
7.3.2 Method of measurement	15

7.3.3	Requirement.....	15
7.4	Temperature tests	15
7.4.1	Definition.....	15
7.4.2	Dry heat	15
7.4.2.1	Definition	15
7.4.2.2	Method of measurement.....	15
7.4.2.3	Requirement	16
7.4.3	Damp heat.....	16
7.4.3.1	Definition	16
7.4.3.2	Method of measurement.....	16
7.4.3.3	Requirement	16
7.4.4	Low temperature cycle.....	16
7.4.4.1	Definition	16
7.4.4.2	Method of measurement.....	16
7.4.4.3	Requirement	16
8	Transmitter	16
8.1	Frequency error	16
8.1.1	Definition.....	16
8.1.2	Method of measurement	17
8.1.3	Limits.....	17
8.2	Carrier power.....	17
8.2.1	Definitions	17
8.2.2	Method of measurement	17
8.2.3	Limits, Normal and extreme test conditions	17
8.3	Frequency deviation	17
8.3.1	Definition.....	17
8.3.2	Maximum permissible frequency deviation.....	17
8.3.2.1	Method of measurement.....	17
8.3.2.2	Limits	17
8.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz.....	18
8.3.3.1	Method of measurement.....	18
8.3.3.2	Limits	18
8.4	Sensitivity of the modulator, including microphone	19
8.4.1	Definition.....	19
8.4.2	Method of measurement	19
8.4.3	Limits.....	19
8.5	Audio frequency response	19
8.5.1	Definition.....	19
8.5.2	Method of measurement	19
8.5.3	Limit	19
8.6	Audio frequency harmonic distortion of the emission.....	20
8.6.1	Definition.....	20
8.6.2	Method of measurement	20
8.6.2.1	RF Coupling to the test demodulator	20
8.6.2.2	Normal test conditions	20
8.6.2.3	Extreme test conditions	21
8.6.3	Limits.....	21
8.7	Adjacent channel power	21
8.7.1	Definition.....	21
8.7.2	Method of measurement	21
8.7.3	Limits.....	21
8.8	Conducted spurious emissions conveyed to the antenna	22
8.8.1	Definition.....	22
8.8.2	Method of measurement	22
8.8.3	Limit	22
8.9	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	22
8.9.1	Definitions	22
8.9.2	Method of measurement	22
8.9.3	Limits.....	23
8.10	Residual modulation of the transmitter	23
8.10.1	Definition.....	23

8.10.2	Method of measurement	23
8.10.3	Limit	24
8.11	Transient frequency behaviour of the transmitter.....	24
8.11.1	Definitions	24
8.11.2	Method of measurement	24
8.11.3	Limits.....	25
9	Receiver.....	27
9.1	Harmonic distortion and rated audio frequency output power	27
9.1.1	Definition.....	27
9.1.2	Methods of measurement.....	27
9.1.3	Limits.....	27
9.2	Audio frequency response	27
9.2.1	Definition.....	27
9.2.2	Method of measurement	27
9.2.3	Limits.....	28
9.3	Maximum usable sensitivity	28
9.3.1	Definition.....	28
9.3.2	Method of measurement	29
9.3.3	Limits.....	29
9.4	Co-channel rejection.....	29
9.4.1	Definition.....	29
9.4.2	Method of measurement	29
9.4.3	Limit	29
9.5	Adjacent channel selectivity.....	30
9.5.1	Definition.....	30
9.5.2	Method of measurement	30
9.5.3	Limits.....	30
9.6	Spurious response rejection.....	30
9.6.1	Definition.....	30
9.6.2	Method of measurement	30
9.6.3	Limit	31
9.7	Intermodulation response	31
9.7.1	Definition.....	31
9.7.2	Method of measurement	31
9.7.3	Limit	31
9.8	Blocking or desensitization	31
9.8.1	Definition.....	31
9.8.2	Method of measurement	31
9.8.3	Limit	32
9.9	Conducted spurious emissions	32
9.9.1	Definition.....	32
9.9.2	Method of measurement	32
9.9.3	Limit	32
9.10	Radiated spurious emissions.....	32
9.10.1	Definition.....	32
9.10.2	Method of measurements.....	32
9.10.3	Limit	33
9.11	Receiver noise and hum level.....	33
9.11.1	Definition.....	33
9.11.2	Method of measurement	33
9.11.3	Limit	34
9.12	Squelch operation.....	34
9.12.1	Definition.....	34
9.12.2	Method of measurement	34
9.12.3	Limits.....	34
9.13	Squelch hysteresis	34
9.13.1	Definition.....	34
9.13.2	Method of measurement	35
9.13.3	Limit	35
10	Testing for compliance with technical requirements.....	35

10.1	Environmental conditions for testing	35
10.2	Interpretation of the measurement results	35
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	37
Annex B (normative):	Measuring receiver for adjacent channel power measurement.....	39
B.1	Power measuring receiver specification.....	39
B.1.0	General	39
B.1.1	IF filter	39
B.1.2	Attenuation indicator.....	40
B.1.3	rms value indicator	40
B.1.4	Oscillator and amplifier	40
History	41

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared in reply to the Commission's standardisation request Commission Implementing Decision C(2015) 5376 final of 04.08.2015 to provide a means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment.

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	7 December 2015
Date of latest announcement of this EN (doa):	31 March 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2016
Date of withdrawal of any conflicting National Standard (dow):	30 September 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document states the minimum technical characteristics and methods of measurement required for portable Very High Frequency (VHF) radiotelephones not providing maritime distress and safety communications functions (i.e. not forming part of the Global Maritime Distress and Safety System (GMDSS)) operating in certain frequency bands allocated to the maritime mobile service using either 25 kHz or 25 kHz and 12,5 kHz channels.

The present document also specifies technical characteristics, methods of measurement and required test results.

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" [i.2] and that "...*radio equipment supports certain features ensuring access to emergency services*" [i.2].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ITU Radio Regulations (2012), appendix 18: "Table of transmitting frequencies in the VHF maritime mobile band".
- [2] Recommendation ITU-T E.161 (2001): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [3] Recommendation ITU-R M.493-13 (2009): "Digital selective-calling system for use in the maritime mobile service".
- [4] Recommendation ITU-R M.541-9 (2004): "Operational procedures for the use of digital selective-calling equipment in the maritime mobile service".
- [5] ETSI EN 300 225 (V1.4.1) (12-2004): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for survival craft portable VHF radiotelephone apparatus".
- [6] Recommendation ITU-T O.41 (10-1994): "Psophometer for use on telephone-type circuits".
- [7] Recommendation ITU-R M.1084-5 (03-2012): "Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service".
- [8] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R SM.332-4: "Selectivity of receivers".
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.4] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".

koniec náhľadu – text ďalej pokračuje v platenej verzii STN