

STN	Technické charakteristiky a metódy merania na dvojcestných radiotelefonných VHF prístrojoch určených na pevné zabudovanie do záchranných plavidiel.	STN EN 301 466 V1.2.1
		87 1466

Technical characteristics and methods of measurement for two-way VHF radiotelephone apparatus for fixed installation in survival craft

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 09/16

Obsahuje: EN 301 466 V1.2.1:2015

123533

ETSI EN 301 466 V1.2.1 (2015-12)



**Technical characteristics and methods of measurement
for two-way VHF radiotelephone apparatus
for fixed installation in survival craft**

Reference

REN/ERM-TG26-516

Keywords

emergency, GMDSS, maritime, radio, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important noticeThe present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	9
3.3 Abbreviations	9
4 General requirements	10
4.1 Construction	10
4.2 Frequencies and power.....	10
4.3 Controls	10
4.4 Switching time.....	11
4.5 Safety precautions	11
4.6 Class of emission and modulation characteristics	11
4.7 Power supply	11
4.7.1 Power supply capacity	11
4.7.2 Primary batteries.....	11
4.7.3 Secondary batteries.....	12
4.7.4 Connection to a survival craft battery.....	12
4.8 Labelling.....	12
4.9 Audio processing.....	12
5 Test conditions, power sources and ambient temperatures	13
5.1 Normal and extreme test conditions	13
5.2 Test power source.....	13
5.3 Normal test conditions.....	13
5.3.1 Normal temperature and humidity	13
5.3.2 Normal power sources	13
5.3.2.1 External battery power source.....	13
5.3.2.2 Integrated battery power source	13
5.4 Extreme test conditions	13
5.4.1 Extreme temperatures	13
5.4.1.1 Upper extreme temperature.....	13
5.4.1.2 Lower extreme temperature	13
5.4.2 Extreme test power supply values.....	14
5.4.2.1 Upper extreme test voltage.....	14
5.4.2.1.1 External battery power source	14
5.4.2.1.2 Internal battery power source	14
5.4.2.2 Lower extreme test voltage	14
5.4.2.2.1 External battery power source	14
5.4.2.2.2 Internal battery power source	14
5.5 Procedure for tests at extreme temperatures.....	14
6 General conditions of measurement	14
6.1 Test connections	14
6.2 Arrangements for test signals applied to the receiver input.....	15
6.3 Receiver mute or squelch facility	15
6.4 Normal test modulation	15
6.5 Artificial antenna.....	15
6.6 Test channels	15
6.7 Measurement uncertainty and interpretation of the measuring results	15
6.7.1 Measurement uncertainty.....	15

6.7.2	Interpretation of the measurement results	16
7	Environmental tests	16
7.1	Introduction	16
7.2	Procedure.....	16
7.3	Performance check	16
7.4	Vibration test.....	16
7.4.1	Definition.....	16
7.4.2	Method of measurement	17
7.4.3	Requirement.....	17
7.5	Shock tests.....	17
7.5.1	Definition.....	17
7.5.2	Method of measurement	17
7.5.3	Requirement.....	17
7.6	Temperature tests	18
7.6.1	General.....	18
7.6.2	Dry heat cycle	18
7.6.2.1	Method of measurement.....	18
7.6.2.2	Requirement	18
7.6.3	Damp heat cycle	18
7.6.3.1	Method of measurement.....	18
7.6.3.2	Requirement	18
7.6.4	Low temperature cycle.....	19
7.6.4.1	Method of measurement.....	19
7.6.4.2	Requirement	19
7.7	Corrosion test	19
7.7.1	General.....	19
7.7.2	Method of measurement	19
7.7.3	Requirements	20
7.8	Immersion test	20
7.8.1	Method of measurement	20
7.8.2	Requirements	20
7.9	Thermal shock	20
7.9.1	Method of measurement	20
7.9.2	Requirements	20
7.10	Oil resistance test.....	20
7.10.0	Applicability	20
7.10.1	Method of measurement	21
7.10.2	Requirement.....	21
8	Transmitter	21
8.0	General	21
8.1	Frequency error	21
8.1.1	Definition.....	21
8.1.2	Method of measurement	21
8.1.3	Limit	21
8.2	Carrier power.....	21
8.2.1	Definitions	21
8.2.2	Method of measurement	22
8.2.3	Limits.....	22
8.3	Frequency deviation	22
8.3.1	Definition.....	22
8.3.2	Maximum frequency deviation.....	22
8.3.2.1	Method of measurement.....	22
8.3.2.2	Limit.....	22
8.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz.....	22
8.3.3.1	Method of measurement.....	22
8.3.3.2	Limits	22
8.4	Sensitivity of the modulator, including microphone	23
8.4.1	Definition.....	23
8.4.2	Method of measurement	23
8.4.3	Limit	23

8.5	Audio frequency response	23
8.5.1	Definition	23
8.5.2	Method of measurement	23
8.5.3	Limit	23
8.6	Audio frequency harmonic distortion of the emission.....	24
8.6.1	Definition.....	24
8.6.2	Method of measurement	24
8.6.2.1	Normal test conditions	24
8.6.2.2	Extreme test conditions	24
8.6.3	Limit	24
8.7	Adjacent channel power	24
8.7.1	Definition.....	24
8.7.2	Method of measurement	24
8.7.3	Limit	25
8.8	Conducted spurious emissions conveyed to the antenna	25
8.8.1	Definition.....	25
8.8.2	Method of measurement	25
8.8.3	Limit	25
8.9	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	25
8.9.1	Definitions	25
8.9.2	Method of measurement	25
8.9.3	Limits.....	26
8.10	Residual modulation of the transmitter	26
8.10.1	Definition.....	26
8.10.2	Method of measurement	26
8.10.3	Limit	27
8.11	Transient frequency behaviour of the transmitter.....	27
8.11.1	Definitions	27
8.11.2	Method of measurement	27
8.11.3	Limits.....	28
9	Receiver.....	30
9.1	Harmonic distortion and rated audio frequency output power	30
9.1.1	Definition.....	30
9.1.2	Methods of measurement.....	30
9.1.3	Limits.....	30
9.2	Audio frequency response	30
9.2.1	Definition.....	30
9.2.2	Method of measurement	30
9.2.3	Limits.....	31
9.3	Maximum usable sensitivity.....	31
9.3.1	Definition.....	31
9.3.2	Method of measurement	31
9.3.3	Limits.....	32
9.4	Co-channel rejection.....	32
9.4.1	Definition.....	32
9.4.2	Method of measurement	32
9.4.3	Limit	32
9.5	Adjacent channel selectivity.....	32
9.5.1	Definition.....	32
9.5.2	Method of measurement	32
9.5.3	Limits.....	33
9.6	Spurious response rejection.....	33
9.6.1	Definition.....	33
9.6.2	Method of measurement	33
9.6.3	Limit	33
9.7	Intermodulation response	33
9.7.1	Definition.....	33
9.7.2	Method of measurement	33
9.7.3	Limit	34
9.8	Blocking or desensitization	34
9.8.1	Definition.....	34

9.8.2	Method of measurement	34
9.8.3	Limit	34
9.9	Conducted spurious emissions	34
9.9.1	Definition.....	34
9.9.2	Method of measurement	34
9.9.3	Limit	34
9.10	Radiated spurious emissions.....	35
9.10.1	Definition.....	35
9.10.2	Method of measurements.....	35
9.10.3	Limit	35
9.11	Amplitude response of the receiver limiter	36
9.11.1	Definition.....	36
9.11.2	Method of measurement	36
9.11.3	Limit	36
9.12	Receiver noise	36
9.12.1	Definition.....	36
9.12.2	Method of measurement	36
9.12.3	Limit	36
9.13	Squelch operation.....	36
9.13.1	Definition.....	36
9.13.2	Method of measurement	36
9.13.3	Limits.....	37
9.14	Squelch hysteresis	37
9.14.1	Definition.....	37
9.14.2	Method of measurement	37
9.14.3	Limit	37
10	Secondary battery charger	37
10.1	General	37
10.2	Environmental tests	38
10.2.1	Introduction.....	38
10.2.2	Vibration test	38
10.2.2.1	Definition	38
10.2.2.2	Method of measurement.....	38
10.2.2.3	Requirement	38
10.2.3	Shock tests	38
10.2.3.1	Definition	38
10.2.3.2	Method of measurement.....	38
10.2.3.3	Requirement	39
10.2.4	Temperature tests.....	39
10.2.4.1	General	39
10.2.4.2	Dry heat cycle	39
10.2.4.3	Damp heat cycle.....	39
10.2.4.4	Low temperature cycle.....	39
10.2.5	Corrosion test.....	40
10.2.5.1	General	40
10.2.5.2	Method of measurement.....	40
10.2.5.3	Requirements	40
10.3	Charging time	40
Annex A (normative): Measuring receiver for adjacent channel power measurement.....		41
A.1	Power measuring receiver specification.....	41
A.1.0	Description	41
A.1.1	IF filter	41
A.1.2	Attenuation indicator.....	42
A.1.3	rms value indicator	42
A.1.4	Oscillator and amplifier.....	42
History		43

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

National transposition dates	
Date of adoption of this EN:	7 December 2015
Date of latest announcement of this EN (doa):	31 March 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2016
Date of withdrawal of any conflicting National Standard (dow):	30 September 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document states the minimum technical characteristics required for VHF radiotelephone equipment, operating in the bands between 156 MHz and 174 MHz allocated to the Maritime Mobile Services and suitable for fixed installations in survival craft in accordance with the provisions of the Global Maritime Distress and Safety System (GMDSS). The relevant requirements detailed in the Radio Regulations [5], International Convention for the Safety Of Life At Sea SOLAS 1974 [4] and the International Maritime Organization Resolutions A.694 [i.3] and A.809 [i.2] as well as all relevant requirements of CENELEC EN 60945 [i.5] are incorporated in the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T O.41 (1994): "Psophometer for use on telephone-type circuits".
- [2] IEC 60068-2-27: 2008 Edition 4.0: "Environmental testing. Part 2-27: Tests - Test Ea and guidance: Shock".
- [3] ISO 25862 (2009): "Ships and marine technology -- Marine magnetic compasses, binnacles and azimuth reading devices".
- [4] SOLAS 1974: "International Maritime Organization (IMO), International Convention for the Safety Of Life At Sea (SOLAS), (1974 as amended)".
- [5] ITU Radio Regulations (2012), Appendix 18: "Table of transmitting frequencies in the VHF maritime mobile band".
- [6] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] International Maritime Organization Resolution A.809 (19): "Performance standards for survival craft two way VHF radiotelephone apparatus".
- [i.3] International Maritime Organization Resolution A.694 (17): "General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for Electronic Navigational Aids".

- [i.4] Void.
- [i.5] CENELEC EN 60945 (2002) + Corrigendum 1 (2008): "Maritime navigation and radio communication equipment and systems - General requirements - Methods of testing and required test results".
- [i.6] ETSI TR 100 028 (All parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

koniec náhľadu – text ďalej pokračuje v platenej verzii STN