

STN	Digitálne bezšnúrové telekomunikácie (DECT). Harmonizovaná norma vzťahujúca sa na základné požiadavky podľa článku 3.2 smernice 2014/53/EÚ.	STN EN 301 406 V2.2.2
		87 1406

Digital Enhanced Cordless Telecommunications (DECT); Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 01/17

Obsahuje: EN 301 406 V2.2.2:2016

124070

Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, 2017
Podľa zákona č. 264/1999 Z. z. v znení neskorších predpisov sa môžu slovenské technické normy
rozmnožovať a rozširovať iba so súhlasom Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

ETSI EN 301 406 v2.2.2 (2016-09)



**Digital Enhanced Cordless Telecommunications (DECT);
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

Reference

REN/DECT-000300-CR

Keywords

DECT, digital, generic, radio, regulation, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
Modal verbs terminology.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	13
3.1 Definitions.....	13
3.2 Symbols.....	15
3.3 Abbreviations	15
4 Technical requirements specifications	16
4.1 Environmental profile.....	16
4.2 Overview	16
4.2.0 General.....	16
4.2.1 Test suites	16
4.2.2 Test groups.....	17
4.2.3 Test cases.....	17
4.3 Applicant's declaration	18
4.4 Applicability of tests	18
4.4.0 Introduction.....	18
4.4.1 Equipment that includes only a DECT RF receiver.....	18
4.4.2 Equipment that includes a radio transmitter	18
4.4.3 CTAs.....	18
4.4.4 Equipment with combined FT and PT functionality.....	19
4.4.4.0 General	19
4.4.4.1 Wireless Relay Station	19
4.4.4.2 Direct PP to PP communication	19
4.4.4.3 Distributed Communications.....	19
4.4.5 Provision of 4 Mbit/s services. Equipment that is capable of using higher level modulation.....	19
4.4.6 Equipment supporting additional carriers	19
4.5 Conformance requirements	20
4.5.1 Accuracy and stability of RF carriers	20
4.5.1.1 Definition	20
4.5.1.2 Limits	20
4.5.1.3 Conformance	20
4.5.2 Accuracy and stability of timing parameters	20
4.5.2.0 General	20
4.5.2.1 Definitions.....	20
4.5.2.1.1 Slot structure.....	20
4.5.2.1.2 Definition of the position of p0	21
4.5.2.2 Limits	21
4.5.2.3 Conformance	21
4.5.3 Transmission burst.....	21
4.5.3.1 Definitions.....	21
4.5.3.1.1 Physical packets.....	21
4.5.3.1.2 Transmitted power.....	21
4.5.3.1.3 Normal Transmitted Power (NTP)	21
4.5.3.1.4 Transmitter attack time.....	21
4.5.3.1.5 Transmitter release time	21
4.5.3.1.6 Minimum power	21
4.5.3.1.7 Maximum power	22
4.5.3.1.8 Maintenance of transmission after packet end.....	22
4.5.3.1.9 Transmitter idle power output	22

4.5.3.2	Limits	22
4.5.3.3	Conformance	22
4.5.4	Transmitted power	22
4.5.4.1	Definitions	22
4.5.4.1.0	Transceiver and P _{NTP} definitions	22
4.5.4.1.1	PP and RFP with an integral antenna	22
4.5.4.1.2	PP and RFP with external connections for all antennas	23
4.5.4.1.3	PP and RFP with both integral and external antennas	23
4.5.4.2	Limits	23
4.5.4.3	Conformance	23
4.5.4.4	Multi-transceiver systems	23
4.5.5	RF carrier modulation	23
4.5.5.1	Definition	23
4.5.5.2	Limits	23
4.5.5.3	Conformance	23
4.5.6	Unwanted RF power radiation	24
4.5.6.1	General	24
4.5.6.2	Emissions due to modulation	24
4.5.6.2.1	Definition	24
4.5.6.2.2	Limits	24
4.5.6.2.3	Conformance	24
4.5.6.3	Emissions due to transmitter transients	24
4.5.6.3.1	Definition	24
4.5.6.3.2	Limits	24
4.5.6.3.3	Conformance	24
4.5.6.4	Emissions due to intermodulation	24
4.5.6.4.1	Definition	24
4.5.6.4.2	Limits	24
4.5.6.4.3	Conformance	24
4.5.6.5	Spurious emissions when allocated a transmit channel	25
4.5.6.5.1	Definition	25
4.5.6.5.2	Limits	25
4.5.6.5.3	Conformance	25
4.5.7	Radio receiver testing	25
4.5.7.1	Radio receiver sensitivity	25
4.5.7.1.1	Definition	25
4.5.7.1.2	Limits	25
4.5.7.1.3	Conformance	25
4.5.7.2	Radio receiver reference BER and FER	25
4.5.7.2.1	Definition	25
4.5.7.2.2	Limits	25
4.5.7.2.3	Conformance	25
4.5.7.3	Radio receiver interference performance	25
4.5.7.3.1	Definition	25
4.5.7.3.2	Limits	26
4.5.7.3.3	Conformance	26
4.5.7.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	26
4.5.7.4.1	Definition	26
4.5.7.4.2	Limits	26
4.5.7.4.3	Conformance	26
4.5.7.5	Radio receiver blocking case 2: owing to signals occurring at a different time	26
4.5.7.5.1	Definition	26
4.5.7.5.2	Limits	26
4.5.7.5.3	Conformance	26
4.5.7.6	Receiver intermodulation performance	26
4.5.7.6.1	Definition	26
4.5.7.6.2	Limits	26
4.5.7.6.3	Conformance	26
4.5.7.7	Spurious emissions when the PP has no allocated transmit channel	27
4.5.7.7.1	Definition	27

4.5.7.7.2	Limits	27
4.5.7.7.3	Conformance	27
4.5.8	Channel access.....	27
4.5.8.1	Channel selection	27
4.5.8.2	Channel confirmation.....	27
4.5.8.2.1	For the PT.....	27
4.5.8.2.2	For the FT.....	27
4.5.8.3	Channel release	28
4.5.8.4	General.....	28
4.5.8.5	Channel selection and confirmation for DECT ULE	28
4.5.8.5.1	General	28
4.5.8.5.2	For the PT.....	28
4.5.8.5.3	For the FT.....	29
4.5.9	WRS testing.....	29
4.5.9.0	General requirements	29
4.5.9.1	Testing as a PP	29
4.5.9.2	Testing as an RFP	29
4.5.9.3	Additional requirements.....	30
4.5.9.4	Conformance	30
4.5.10	Requirements for PPs with direct PP to PP communication mode	30
4.5.10.0	General requirements	30
4.5.10.1	Setting the EUT in direct communications mode.....	30
4.5.10.2	When the EUT has not initiated a call.....	30
4.5.10.3	When the EUT initiates a call	31
4.5.10.4	Conformance	31
4.5.11	Distributed Communications	31
4.5.11.0	General requirements	31
4.5.11.1	Testing as a PP	31
4.5.11.2	Testing as an RFP	32
4.5.11.3	Conformance	32
4.5.12	Higher level modulation options.....	32
4.5.12.0	Requirements	32
4.5.12.1	Conformance	33
5	Testing for compliance with technical requirements.....	33
5.1	General test requirements	33
5.1.1	Test philosophy.....	33
5.1.2	Test site.....	34
5.1.2.1	Open air test site	34
5.1.2.1.1	Description	34
5.1.2.1.2	Calibration	35
5.1.2.2	Anechoic chamber.....	36
5.1.2.2.1	General	36
5.1.2.2.2	Description	36
5.1.2.2.3	Influence of parasitic reflections	38
5.1.2.2.4	Calibration and mode of use	38
5.1.2.3	Stripline coupler.....	38
5.1.2.3.0	General	38
5.1.2.3.1	Description	38
5.1.2.3.2	Calibration	38
5.1.2.3.3	Mode of use	38
5.1.3	Standard position	39
5.1.4	Test antenna of the LT	39
5.1.5	Substitution antenna.....	39
5.1.6	Test fixture.....	39
5.1.6.1	Description	39
5.1.6.2	Calibration of the test fixture for the measurement of transmitter characteristics	40
5.1.6.3	Calibration of the test fixture for the measurement of receiver characteristics	40
5.1.6.4	Mode of use.....	41
5.1.7	Equipment with a temporary or internal permanent antenna connector.....	41
5.1.7.1	General	41
5.1.7.2	Equipment with a temporary antenna connector	41

5.1.8	Indoor test site.....	42
5.1.8.0	General	42
5.1.8.1	Description	42
5.1.8.2	Test for parasitic reflections	42
5.1.8.3	Calibration and mode of use	43
5.1.9	Lower Tester (LT)	43
5.1.9.1	Description	43
5.1.9.2	Connections between the EUT and the LT	43
5.1.9.3	Functions and abilities	43
5.1.9.4	Signal generation uncertainty	44
5.1.9.5	Modulated DECT-like carrier	44
5.1.9.6	CW interferers	44
5.1.9.7	DECT RF signal	44
5.1.9.8	Test modulation signals	45
5.1.10	Upper Tester (UT)	45
5.1.10.1	Description of the UT	45
5.1.10.2	The test standby mode	45
5.1.10.3	Test messages	45
5.1.10.4	Dummy setting when EUT is a RFP and it is in test stand-by mode	46
5.1.11	Description of the lower tester FT and PT	46
5.1.12	General test methods	46
5.1.12.1	General	46
5.1.12.2	Sampling the RF signal	46
5.1.12.2.1	Introduction	46
5.1.12.2.2	Sampling method	46
5.1.12.3	Determining the reference position	47
5.1.12.3.0	General	47
5.1.12.3.1	Case 1: EUTs that cannot transmit	47
5.1.12.3.2	Case 2: EUTs that can transmit	47
5.1.12.4	Bit error rate (BER) and Frame Error Ratio (FER) measurements	47
5.1.13	Test setup	47
5.1.13.1	General	47
5.1.13.2	Test setup 1	48
5.1.13.3	Test setup 2	48
5.1.13.4	Test setup 3	48
5.1.13.5	Test setup 4	49
5.1.13.6	Test setup 5	49
5.1.14	Test arrangements for intermodulation measurements	50
5.1.14.1	PT to PT arrangement	50
5.1.14.2	FT to FT arrangement	50
5.1.14.3	FT to PT arrangement	51
5.1.15	Test conditions, power supply and ambient temperatures	51
5.1.15.1	General	51
5.1.15.2	Nominal test conditions	52
5.1.15.3	Extreme test conditions	52
5.1.15.4	Test power source - general requirements	53
5.1.15.5	Nominal test power source	54
5.1.15.5.1	Mains voltage	54
5.1.15.5.2	Regulated lead acid battery power sources	54
5.1.15.5.3	Nickel cadmium battery	54
5.1.15.5.4	Other power sources	54
5.1.15.6	Extreme test power source	54
5.1.15.6.1	Mains voltage	54
5.1.15.6.2	Regulated lead acid battery power sources	54
5.1.15.6.3	Nickel cadmium battery	54
5.1.15.6.4	Other power sources	54
5.1.15.7	Testing of host connected equipment and plug-in cards	55
5.1.15.7.1	Approaches	55
5.1.15.7.2	Alternative A: composite equipment	55
5.1.15.7.3	Alternative B: use of a test jig and three hosts	55
5.2	Interpretation of the measurement results	55
5.3	Radio test suites	56

5.3.1	Accuracy and stability of RF carriers	56
5.3.1.1	Test environment.....	56
5.3.1.2	Method of measurement.....	56
5.3.1.3	Verdict criteria when the EUT is a RFP.....	57
5.3.1.4	Verdict criteria when the EUT is a PP	57
5.3.2	Accuracy and stability of timing parameters	57
5.3.2.1	Measurement of packet timing jitter	57
5.3.2.1.1	Test environment.....	57
5.3.2.1.2	Method of measurement	58
5.3.2.1.3	Verdict criteria.....	58
5.3.2.2	Measurement of the reference timing accuracy of a RFP	58
5.3.2.2.1	Test environment.....	58
5.3.2.2.2	Method of measurement	58
5.3.2.2.3	Verdict criteria.....	59
5.3.2.3	Measurement of packet transmission accuracy of a PP	59
5.3.2.3.1	Test environment.....	59
5.3.2.3.2	Method of measurement	59
5.3.2.3.3	Verdict criteria.....	60
5.3.3	Transmission burst.....	60
5.3.3.1	Test environment.....	60
5.3.3.2	Method of measurement	60
5.3.3.3	Verdict criteria	60
5.3.4	Transmitted power	61
5.3.4.1	PP and RFP with an integral antenna	61
5.3.4.1.1	Test environment.....	61
5.3.4.1.2	Method of measurement	61
5.3.4.1.3	Verdict criteria for all EUTs.....	62
5.3.4.2	PP and RFP with external antenna connection(s).....	62
5.3.4.2.1	Test environment.....	62
5.3.4.2.2	Method of measurement	63
5.3.4.2.3	Verdict criteria for all EUTs.....	63
5.3.5	RF carrier modulation.....	63
5.3.5.1	Test environment.....	63
5.3.5.2	Method of measurement, parts 1 and 2	63
5.3.5.2.1	Introduction	63
5.3.5.2.2	Part 1	64
5.3.5.2.3	Part 2	64
5.3.5.3	Method of measurement, parts 3 and 4	64
5.3.5.3.0	General	64
5.3.5.3.1	Part 3	64
5.3.5.3.2	Part 4	65
5.3.5.4	Verdict criteria for part 1.....	65
5.3.5.5	Verdict criteria for part 2.....	65
5.3.5.6	Verdict criteria for part 3.....	65
5.3.5.7	Verdict criteria for part 4.....	65
5.3.6	Unwanted RF power radiation.....	67
5.3.6.1	General test conditions	67
5.3.6.2	Emissions due to modulation	67
5.3.6.2.1	Test environment	67
5.3.6.2.2	Method of measurement	67
5.3.6.2.3	Verdict criteria.....	68
5.3.6.3	Emissions due to transmitter transients	68
5.3.6.3.1	Test environment	68
5.3.6.3.2	Method of measurement	69
5.3.6.3.3	Verdict criteria.....	69
5.3.6.4	Emissions due to intermodulation	70
5.3.6.4.1	Test environment	70
5.3.6.4.2	Method of measurement	70
5.3.6.4.3	Verdict criteria.....	71
5.3.6.5	Spurious emissions when allocated a transmit channel.....	71
5.3.6.5.1	Radiated emissions	71
5.3.6.5.2	Conducted spurious emissions when the EUT has a permanent external antenna connector	72

5.3.7	Radio receiver testing	73
5.3.7.1	Radio receiver sensitivity	73
5.3.7.1.1	Test environment	73
5.3.7.1.2	Method of measurement	73
5.3.7.1.3	Verdict criteria	74
5.3.7.2	Radio receiver reference BER and FER	74
5.3.7.2.1	Test environment	74
5.3.7.2.2	Method of measurement	74
5.3.7.2.3	Verdict criteria	74
5.3.7.3	Radio receiver interference performance	74
5.3.7.3.1	Test environment	74
5.3.7.3.2	Method of measurement	74
5.3.7.3.3	Verdict criteria	75
5.3.7.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	75
5.3.7.4.1	Test environment	75
5.3.7.4.2	Method of measurement	75
5.3.7.4.3	Verdict criteria	76
5.3.7.5	Radio receiver blocking case 2: owing to signals occurring at a different time	77
5.3.7.5.1	Test environment	77
5.3.7.5.2	Method of measurement	77
5.3.7.5.3	Verdict criteria	77
5.3.7.6	Receiver intermodulation performance	78
5.3.7.6.1	Test environment	78
5.3.7.6.2	Method of measurement	78
5.3.7.6.3	Verdict criteria	78
5.3.7.7	Spurious emissions when the PP has no allocated transmit channel	78
5.3.7.7.1	Test environment	78
5.3.7.7.2	Method of measurement	79
5.3.7.7.3	Verdict criteria (outside the DECT band)	79
5.3.7.7.4	Verdict criteria (inside the DECT band)	79
5.3.8	Channel access	79
5.3.9	WRS testing	79
5.3.9.0	General	79
5.3.9.1	Testing as a PP	79
5.3.9.2	Testing as an RFP	80
5.3.9.3	Additional requirements	80
5.3.10	Requirements for PPs with direct PP to PP communication mode	80
5.3.10.0	General	80
5.3.10.1	Setting the EUT in direct communications mode	80
5.3.10.2	When the EUT has not initiated a call	81
5.3.10.3	When the EUT initiates a call	81
5.3.10.4	Applicants declarations	81
5.3.11	Distributed Communications	81
5.3.11.0	General	81
5.3.11.1	Testing as a PP	81
5.3.11.2	Testing as an RFP	82
5.3.11.3	Applicants declaration	82
5.3.12	Higher level modulation options	82
5.3.12.0	General	82
5.3.12.1	Activation of higher level modulations when EUT is in test stand-by mode	83
5.3.12.2	Applicants declaration	83
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	84
Annex B (normative):	Procedures for test fixture calibration and for measurement of radiated spurious emissions	86
B.1	Calibration of test fixture for receiver measurements	86
B.1.0	Procedure	86
B.1.1	Method of measurement	86

B.2 Radiated measurements.....	87
B.2.1 General	87
B.2.2 Radiated spurious emissions.....	88
B.2.2.1 Definition.....	88
B.2.2.2 Method of measurement	88
B.2.3 Cabinet radiation	90
B.2.3.1 Definition.....	90
B.2.3.2 Method of measurement	90
Annex C (normative): Procedure for measurement of conducted spurious emissions.....	91
C.1 Conducted spurious emissions	91
C.1.1 Definition	91
C.1.2 Method of measurement	91
Annex D (normative): Measurement of BER and FER.....	92
Annex E (informative): Procedures for the measurement of synchronization loss at the EUT by the LT	93
E.1 Description	93
E.2 Method	93
Annex F (informative): Bibliography.....	94
History	95

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.16] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [8].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates	
Date of latest announcement of this EN (doa):	23 December 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2017
Date of withdrawal of any conflicting National Standard (dow):	30 June 2018

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to the following equipment types for the Digital Enhanced Cordless Telecommunications (DECT) common interface:

- a) Fixed Part (FP);
- b) Portable Part (PP);
- c) Cordless Terminal Adapter (CTA);
- d) Wireless Relay Station (WRS) (FP and PP combined);
- e) Hybrid Part (HyP) (a PP with capability to act as a FP to provide PP to PP communication).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1.

Table 1: Radiocommunications service frequency bands

	Radiocommunications service frequency bands
Transmit	1 880 MHz to 1 900 MHz
Receive	1 880 MHz to 1 900 MHz

The DECT service frequency band for transmitting and receiving for all elements is 1 880 MHz to 1 900 MHz.

Details of the DECT Common Interface may be found in ETSI EN 300 175-1 [i.10], ETSI EN 300 175 parts 2 to 3 [1] to [2], ETSI EN 300 175-4 [i.11], ETSI EN 300 175 parts 5 to 6 [3] to [4], and ETSI EN 300 175 parts 7 to 8 [i.12] to [i.13]. Further details of the DECT system may be found in the ETSI Technical Reports, ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2]. Information about ULE may be found in the ETSI Technical Specifications ETSI TS 102 939-1 [i.14] and ETSI TS 102 939-2 [i.15].

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-2 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [2] ETSI EN 300 175-3 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) Layer".
- [3] ETSI EN 300 175-5 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".

- [4] ETSI EN 300 175-6 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [5] Void.
- [6] ETSI EN 300 700 (V1.2.1) (09-2000): "Digital Enhanced Cordless Telecommunications (DECT); Wireless Relay Station (WRS)".
- [7] Recommendation ITU-T O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [8] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 178: "Digital Enhanced Cordless Telecommunications (DECT); A High Level Guide to the DECT Standardization".
- [i.2] ETSI ETR 043: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Services and facilities requirements specification".
- [i.3] Void.
- [i.4] Void.
- [i.5] Void.
- [i.6] Void.
- [i.7] Void.
- [i.8] ETSI TR 100 028: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.9] ISO/IEC 9646-1 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [i.10] ETSI EN 300 175-1 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [i.11] ETSI EN 300 175-4 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) Layer".
- [i.12] ETSI EN 300 175-7 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [i.13] ETSI EN 300 175-8 (V2.6.1) (07-2015): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [i.14] ETSI TS 102 939-1: "Digital Enhanced Cordless Telecommunications (DECT); Ultra Low Energy (ULE); Machine to Machine Communications; Part 1: Home Automation Network (phase 1)".

- [i.15] ETSI TS 102 939-2: "Digital Enhanced Cordless Telecommunications (DECT); Ultra Low Energy (ULE); Machine to Machine Communications; Part 2: Home Automation Network (phase 2)".
- [i.16] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
-

koniec náhľadu – text ďalej pokračuje v platenej verzii STN