

<b>STN</b>	<b>Pomocné meteorologické prostriedky (Met Aids). Rádiosondy používané vo frekvenčnom rozsahu od 400,15 MHz do 406 MHz s výkonovou úrovňou dosahujúcou 200 mW. Časť 1: Technické charakteristiky a metódy merania.</b>	<b>STN EN 302 054-1 V1.2.1</b>  87 2054
------------	--	---

Meteorological Aids (Met Aids); Radiosondes to be used in the 400,15 MHz to 406 MHz frequency range with power levels ranging up to 200 mW; Part 1: Technical characteristics and test methods

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 03/17

Obsahuje: EN 302 054-1 V1.2.1:2015

**124399**

---

Úrad pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky, 2017  
Podľa zákona č. 264/1999 Z. z. o technických požiadavkách na výrobky a o posudzovaní zhody a o zmene a doplnení niektorých zákonov v znení neskorších predpisov sa slovenská technická norma a časti slovenskej technickej normy môžu rozmnožovať alebo rozširovať len so súhlasom slovenského národného normalizačného orgánu.

# ETSI EN 302 054-1 V1.2.1 (2015-10)



EUROPEAN STANDARD

**Meteorological Aids (Met Aids);  
Radiosondes to be used in the 400,15 MHz to 406 MHz  
frequency range with power levels ranging up to 200 mW;  
Part 1: Technical characteristics and  
test methods**

---

**Reference**

REN/ERM-JTFEA-25

---

**Keywords**

radio, short range, testing, UHF

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction .....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations .....	7
3.1 Definitions .....	7
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 Technical requirement specifications.....	8
4.1 Presentation of equipment for testing purposes.....	8
4.1.1 General Considerations.....	8
4.1.2 Choice of model for testing .....	8
4.1.3 Testing of equipment with alternative power levels .....	9
4.1.4 Testing of equipment that does not have an external 50 $\Omega$ RF connector (integral antenna equipment).....	9
4.1.4.1 Equipment with an internal permanent or temporary antenna connector.....	9
4.1.4.2 Equipment with an internal permanent antenna .....	9
4.2 Mechanical and electrical design.....	9
4.2.1 Marking (equipment identification).....	9
4.2.1.1 Equipment identification .....	9
4.2.1.2 Marking.....	9
4.2.2 Auxiliary test equipment.....	9
5 Test conditions, power sources and ambient temperatures .....	9
5.1 Normal and extreme test conditions .....	9
5.2 Test power source.....	10
5.2.1 External test power source .....	10
5.2.2 Internal test power source .....	10
5.3 Normal test conditions.....	10
5.3.1 Normal temperature and humidity .....	10
5.3.2 Normal test power source .....	10
5.4 Extreme test conditions .....	10
5.4.1 General.....	10
5.4.2 Procedure for tests at extreme conditions .....	11
5.4.3 Special Radiosondes .....	11
5.4.4 Extreme test source voltages.....	11
5.4.4.1 Power sources using batteries .....	11
5.4.4.2 Other power sources.....	11
6 General conditions.....	12
6.1 Normal test signals and test modulation.....	12
6.2 Artificial antenna.....	12
6.3 Test fixture .....	12
6.4 Test sites and general arrangements for radiated measurements .....	12
6.5 Modes of operation of the transmitter .....	12
6.6 Measuring receiver .....	13
7 Methods of measurement and limits for transmitter parameters .....	13
7.1 General .....	13
7.2 Frequency error .....	13
7.2.1 Definitions .....	13

7.2.2	Method of measurement .....	13
7.2.3	Limit .....	13
7.3	Carrier power (conducted).....	13
7.3.1	Definition.....	13
7.3.2	Method of measurement .....	14
7.3.3	Limits.....	14
7.4	Effective radiated power .....	14
7.4.1	Definition.....	14
7.4.2	Methods of measurement.....	14
7.4.3	Limit .....	15
7.5	Modulation bandwidth .....	15
7.5.1	Definition.....	15
7.5.2	Method of measurement .....	15
7.5.3	Limits.....	16
7.6	Spurious emissions .....	16
7.6.1	Definition.....	16
7.6.2	Methods of measurement.....	16
7.6.2.0	General requirement.....	16
7.6.2.1	Method of measuring the power level in a specified load, clause 7.6.2.0 a) i).....	16
7.6.2.2	Method of measuring the effective radiated power, clause 7.6.2.0 a) ii).....	17
7.6.2.3	Method of measuring the effective radiated power, clause 7.6.2.0 b).....	17
7.6.3	Limits.....	18
7.7	Frequency stability under low voltage conditions .....	18
7.7.1	Definition.....	18
7.7.2	Method of measurement .....	18
7.7.3	Limits.....	18
	History .....	19

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document is part 1 of a multi-part deliverable covering digitally modulated Radiosonde transmitters in the Meteorological Aids frequency band from 400,15 MHz to 406 MHz, as identified below:

**Part 1:** "Technical characteristics and test methods";

Part 2: "Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

National transposition dates	
Date of adoption of this EN:	22 October 2015
Date of latest announcement of this EN (doa):	31 January 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2016
Date of withdrawal of any conflicting National Standard (dow):	31 July 2017

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

Meteorological aids, Radiosondes, are light weight, disposable precision measurement instruments mainly used for *in situ* upper air measurements of meteorological variables (pressure, temperature, relative humidity, wind speed and direction) in the atmosphere up to an altitude of 36 km. The measurements are vital to international weather forecasting capability (and hence severe weather warning services for the public involving protection of life and property). The Radiosonde systems provide simultaneous measurements of the vertical profile of temperature, relative humidity as well as wind speed and direction. The variation of these meteorological variables in the vertical contains the majority of the critical information for weather forecasting. These systems are the only meteorological observing systems able to regularly provide the vertical resolution that meteorologists need for all five variables.

Typically the Radiosonde observations are produced by Radiosondes measuring atmosphere for approximately 2 hours and carried by ascending balloons launched from land stations or ships. Radiosonde observations are carried out routinely by almost all countries, two to four times a day. The observation data is then circulated immediately to all other countries within a few hours via the WMO (World Meteorological Organization) Global Telecommunications System (GTS). The observing systems and data dissemination are all organized under the framework of the World Weather Watch Programme of WMO.

The observation stations are required, worldwide, at a horizontal spacing of less than or equal to 250 km, during the first decade of the twenty-first century, with a frequency of observation of from one to four times per day.

Remotely sensed measurements from satellites do not have the vertical resolution available from Radiosondes. Successful derivation of vertical temperature structure from these satellite measurements usually requires a computation initialized either directly from Radiosonde statistics or from the numerical weather forecast itself. In the latter case, the Radiosonde measurements ensure that the vertical structure in these forecasts remains accurate and stable with time. In addition, the Radiosonde measurements are used to calibrate satellite observations by a variety of techniques.

Radiosonde observations are thus seen to remain absolutely necessary for meteorological operations for the foreseeable future.

Other applications, independent of the main civilian meteorological organizations include environmental pollution, hydrology, radioactivity in the free atmosphere, significant weather phenomena (e.g. winter storms, thunderstorms, etc.) and investigation of a range of physical and chemical properties of the atmosphere.

About 150 000 Radiosondes are annually used in Europe, about 90 % of them are in 403 MHz band. This use is not decreasing with time, since with modern automation it is now much easier to successfully operate systems without highly skilled operators and a large amount of supporting equipment.

The Radiosondes use unidirectional transmission on two frequency bands: 403 MHz band covers primary and co-primary allocations from 400,15 MHz to 406 MHz and 1 680 MHz band from 1 668,4 MHz to 1 690 MHz. The 403 MHz Radiosonde technology applies GNSS (Global Navigation Satellite Systems) for wind measurement, whereas the 1 680 MHz systems may base the wind measurement on balloon tracking with a Radio Direction Finding antenna. Because the 403 MHz wind measurement depends on the availability of the GNSS signals, many operators do not consider this technology secure enough for critical applications (e.g. defence and national security), and consequently prefer 1 680 MHz systems.

National regulatory conditions may apply regarding the, channel/frequency separations, and the inclusion of an automatic transmitter shut-off feature as a condition of an individual or general license, or, as a condition of use under license exemption. The automatic transmitter shut-off facility of the Radiosonde may be based on elapsed time from the beginning of the sounding, or atmospheric pressure or height measured by the Radiosonde.

---

# 1 Scope

The present document defines the technical requirements for transmitters used in Radiosondes operating in the range from 400,15 MHz to 406 MHz and with power levels ranging up to 200 mW.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-1: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [2] ETSI TS 103 052 (V1.1.1) (2011-03): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [3] ETSI EN 300 220-1 (V2.4.1) (2012-05): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical characteristics and test methods".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

---

**koniec náhľadu – text ďalej pokračuje v platenej verzii STN**