ICS 33.060.20 SLOVENSKÁ TECHNICKÁ NORMA Apríl 2017

STN	**Postupy merania na posúdenie špecifickej miery absorpcie pri vystavení človeka účinkom vysokofrekvenčných polí z bezdrôtových komunikačných ručných zariadení a zariadení upevnených na tele. Časť 1: Zariadenia používané v blízkosti ucha (frekvenčný rozsah od 300 MHz do 6 GHz).**	**STN EN 62209-1** 36 7080

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 03/17

Obsahuje: EN 62209-1:2016, IEC 62209-1:2016

Oznámením tejto normy sa od 10.08.2019 ruší
STN EN 62209-1 (36 7080) z marca 2007

124511

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62209-1

November 2016

ICS 33.060.20

Supersedes EN 62209-1:2006

English Version

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz) (IEC 62209-1:2016)

Procédure de mesure pour l'évaluation du débit d'absorption spécifique de l'exposition humaine aux champs radiofréquences produits par les dispositifs de communications sans fil tenus à la main ou portés près du corps - Partie 1: Dispositifs utilisés à proximité de l'oreille (Plage de fréquences de 300 MHz à 6 GHz) (IEC 62209-1:2016)

Sicherheit von Personen in hochfrequenten Feldern von handgehaltenen und am Körper getragenen schnurlosen Kommunikationsgeräten - Körpermodelle, Messgeräte und -verfahren - Teil 1: Verfahren zur Bestimmung der spezifischen Absorptionsrate (SAR) von Geräten, die in enger Nachbarschaft zum Ohr benutzt werden (Frequenzbereich von 300 MHz bis 6 GHz) (IEC 62209-1:2016)

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Ref. No. EN 62209-1:2016 E

EN 62209-1:2016

European foreword

The text of document 106/361/FDIS, future edition 2 of IEC 62209-1 prepared by IEC/TC 106X "Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62209-1:2016.

The following dates are fixed:

• latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2017-05-10
• latest date by which the national standards conflicting with the document have to be withdrawn	(dow)	2019-08-10

This document supersedes EN 62209-1:2006.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62209-1:2016 was approved by CENELEC as a European Standard without any modification.

Annex ZA
(normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

Publication	Year	Title	EN/HD	Year
ISO/IEC 17025	2005	General requirements for the competence of testing and calibration laboratories	EN ISO/IEC 17025	2005
ISO/IEC 17043	2010	Conformity assessment - General requirements for proficiency testing	EN ISO/IEC 17043	2010

IEC 62209-1

Edition 2.0 2016-07

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)

Procédure de mesure pour l'évaluation du débit d'absorption spécifique de l'exposition humaine aux champs radiofréquences produits par les dispositifs de communications sans fil tenus à la main ou portés près du corps – Partie 1: Dispositifs utilisés à proximité de l'oreille (Plage de fréquences de 300 MHz à 6 GHz)

IEC 62209-1:2016-07(en-fr)

IEC 62209-1

Edition 2.0 2016-07

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)

Procédure de mesure pour l'évaluation du débit d'absorption spécifique de l'exposition humaine aux champs radiofréquences produits par les dispositifs de communications sans fil tenus à la main ou portés près du corps – Partie 1: Dispositifs utilisés à proximité de l'oreille (Plage de fréquences de 300 MHz à 6 GHz)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 33.060.20

ISBN 978-2-8322-3500-3

CONTENTS

FOREWORD....11
INTRODUCTION....13
1 Scope....14
2 Normative references....14
3 Terms and definitions....14
4 Symbols and abbreviations....19
4.1 Physical quantities....19
4.2 Constants....20
4.3 Abbreviations....20
5 Measurement system specifications....20
5.1 General requirements....20
5.2 Phantom specifications (shell and liquid)....22
5.3 Hand and device holder considerations....23
5.4 Scanning system requirements....23
5.5 Device holder specifications....23
5.6 Characteristics of the readout electronics....24
6 Protocol for SAR assessment....24
6.1 General....24
6.2 Measurement preparation....24
6.2.1 Preparation of tissue-equivalent liquid and *system check*....24
6.2.2 Preparation of the wireless device under test (DUT)....25
6.2.3 Operating modes....26
6.2.4 Positioning of the DUT in relation to the phantom....27
6.2.5 Test frequencies for DUT....34
6.3 Tests to be performed....34
6.4 Measurement procedure....36
6.4.1 General....36
6.4.2 General procedure....37
6.4.3 SAR measurements of handsets with multiple antennas or multiple transmitters....39
6.5 Post-processing of SAR measurement data....45
6.5.1 Interpolation....45
6.5.2 Extrapolation....46
6.5.3 Definition of the averaging volume....46
6.5.4 Searching for the maxima....46
6.6 Fast SAR testing....46
6.6.1 General....46
6.6.2 Fast SAR measurement procedure A....47
6.6.3 Fast SAR testing of required frequency bands....49
6.6.4 Fast SAR measurement procedure B....50
6.7 SAR test reduction....52
6.7.1 General requirements....52
6.7.2 Test reduction for different operating modes in the same frequency band using the same wireless technology....53
6.7.3 Test reduction based on characteristics of DUT design....54
6.7.4 Test reduction based on SAR level analysis....55

6.7.5 Test reduction based on simultaneous multi-band transmission considerations 57
7 Uncertainty estimation 58
7.1 General considerations 58
7.1.1 Concept of uncertainty estimation 58
7.1.2 Type A and Type B evaluation 59
7.1.3 Degrees of freedom and coverage factor 59
7.2 Components contributing to uncertainty 60
7.2.1 General 60
7.2.2 Calibration of the SAR probes 60
7.2.3 Contribution of mechanical constraints 65
7.2.4 Phantom shell 66
7.2.5 Device positioning and holder uncertainties 67
7.2.6 Tissue-equivalent liquid parameter uncertainty 69
7.2.7 Uncertainty in SAR correction for deviations in permittivity and conductivity 72
7.2.8 Measured SAR drift 74
7.2.9 RF ambient conditions 75
7.2.10 Contribution of post-processing 76
7.2.11 SAR scaling uncertainty 81
7.2.12 Deviation of experimental sources 82
7.2.13 Other uncertainty contributions when using *system validation* sources 82
7.3 Calculation of the uncertainty budget 83
7.3.1 Combined and expanded uncertainties 83
7.3.2 Maximum expanded uncertainty 83
7.4 Uncertainty of fast SAR methods based on specific measurement procedures and post-processing techniques 92
7.4.1 General 92
7.4.2 Measurement uncertainty evaluation 92
8 Measurement report 101
8.1 General 101
8.2 Items to be recorded in the measurement report 101
Annex A (normative) Phantom specifications 104
A.1 Rationale for the SAM phantom shape 104
A.2 SAM phantom specifications 104
A.2.1 General 104
A.2.2 Phantom shell 108
A.3 Flat phantom specifications 110
A.4 Tissue-equivalent liquids 111
Annex B (normative) Calibration and characterization of dosimetric probes 113
B.1 Introductory remarks 113
B.2 Linearity 114
B.3 Assessment of the sensitivity of the dipole sensors 114
B.3.1 General 114
B.3.2 Two-step calibration procedures 114
B.3.3 One step calibration procedures 120
B.3.4 Coaxial calorimeter method 124
B.4 Isotropy 126
B.4.1 Axial isotropy 126

B.4.2 Hemispherical isotropy 126
B.5 Lower detection limit 131
B.6 Boundary effects 131
B.7 Response time 131
Annex C (normative) Post-processing techniques 132
C.1 Extrapolation and interpolation schemes 132
C.1.1 Introductory remarks 132
C.1.2 Interpolation schemes 132
C.1.3 Extrapolation schemes 132
C.2 Averaging scheme and maximum finding 132
C.2.1 Volume average schemes 132
C.2.2 Extrude method of averaging 132
C.2.3 Maximum peak SAR finding and uncertainty estimation 133
C.3 Example implementation of parameters for scanning and data evaluation 133
C.3.1 General 133
C.3.2 Area scan measurement requirements 133
C.3.3 Zoom scan 133
C.3.4 Extrapolation 134
C.3.5 Interpolation 134
C.3.6 Integration 134
Annex D (normative) SAR measurement system verification 135
D.1 Overview 135
D.2 *System check* 135
D.2.1 Purpose 135
D.2.2 Phantom set-up 136
D.2.3 *System check* source 136
D.2.4 *System check* source input power measurement 137
D.2.5 *System check* procedure 138
D.3 *System validation* 139
D.3.1 Purpose 139
D.3.2 Phantom set-up 139
D.3.3 *System validation* sources 139
D.3.4 Reference dipole input power measurement 140
D.3.5 *System validation* procedure 140
D.3.6 Numerical target SAR values 141
D.4 Fast SAR method *system validation* and *system check* 144
D.4.1 General 144
D.4.2 Fast SAR method *system validation* 144
D.4.3 Fast SAR method *system check* 145
Annex E (normative) Interlaboratory comparisons 146
E.1 Purpose 146
E.2 Phantom set-up 146
E.3 Reference wireless handsets 146
E.4 Power set-up 146
E.5 Interlaboratory comparison – Procedure 147
Annex F (informative) Definition of a phantom coordinate system and a device under test coordinate system 148
Annex G (informative) SAR *system validation* sources 150

G.1 Standard dipole source 150
G.2 Standard waveguide source 151
Annex H (informative) Flat phantom 153
Annex I (informative) Example recipes for phantom head tissue-equivalent liquids 156
I.1 Overview 156
I.2 Ingredients 156
I.3 Tissue-equivalent liquid formulas (permittivity/conductivity) 157
Annex J (informative) Measurement of the dielectric properties of liquids and uncertainty estimation 160
J.1 Introductory remarks 160
J.2 Measurement techniques 160
J.2.1 General 160
J.2.2 Instrumentation 160
J.2.3 General principles 160
J.3 Slotted coaxial transmission line 161
J.3.1 General 161
J.3.2 Equipment set-up 161
J.3.3 Measurement procedure 161
J.4 Contact coaxial probe 162
J.4.1 General 162
J.4.2 Equipment set-up 162
J.4.3 Measurement procedure 164
J.5 TEM transmission line 164
J.5.1 General 164
J.5.2 Equipment set-up 164
J.5.3 Measurement procedure 165
J.6 Dielectric properties of reference liquids 166
Annex K (informative) Measurement uncertainty of specific fast SAR methods and fast SAR examples 169
K.1 General 169
K.2 Measurement uncertainty evaluation 169
K.2.1 General 169
K.2.2 Probe calibration and system calibration drift 170
K.2.3 Isotropy 170
K.2.4 Sensor positioning uncertainty 171
K.2.5 Sensor location sensitivity 171
K.2.6 Mutual sensor coupling 172
K.2.7 Sensor coupling with the DUT 172
K.2.8 Measurement system immunity / secondary reception 172
K.2.9 Deviations in phantom shape 172
K.2.10 Spatial variation in dielectric parameters 173
K.3 Fast SAR examples 178
K.3.1 General 178
K.3.2 Example 1: Tests for one frequency band and mode 179
K.3.3 Example 2: Tests over multiple frequency bands and modes 183
K.3.4 Example 3: Tests for one frequency band and mode (Procedure B) 186
K.3.5 Example 4: Tests over multiple frequency bands and modes (Procedure B) 190
Annex L (informative) SAR test reduction supporting information 194

L.1 General 194
L.2 Test reduction based on characteristics of DUT design 194
L.2.1 General 194
L.2.2 Statistical analysis overview 194
L.2.3 Analysis results 195
L.2.4 Conclusions 198
L.2.5 Expansion to multi transmission antennas 198
L.2.6 Test reduction based on analysis of SAR results on other signal modulations 198
L.3 Test reduction based on SAR level analysis 200
L.3.1 General 200
L.3.2 Statistical analysis 201
L.3.3 Test reduction applicability example 204
L.4 Other statistical approaches to search for the high SAR test conditions 205
L.4.1 General 205
L.4.2 Test reductions based on a design of experiments (DOE) 205
L.4.3 Analysis of unstructured data 206
Annex M (informative) Applying the head SAR test procedures 207
Annex N (informative) Studies for potential hand effects on head SAR 210
N.1 Overview 210
N.2 Background 210
N.2.1 General 210
N.2.2 Hand phantoms 211
N.3 Summary of experimental studies 211
N.3.1 General 211
N.3.2 Experimental studies using fully compliant SAR measurement systems 211
N.3.3 Experimental studies using other SAR measurement systems 211
N.4 Summary of computational studies 212
N.5 Conclusions 212
Annex O (informative) Quick start guide 213
O.1 General 213
O.2 Quick start guide high level flow-chart 213
Bibliography 217

Figure 1 – Vertical and horizontal reference lines and reference Points A, B on two example device types: a full touch screen smart phone (top) and a keyboard handset (bottom) 29
Figure 2 – Cheek position of the wireless device on the left side of SAM where the device shall be maintained for the phantom test set-up. 32
Figure 3 – Tilt position of the wireless device on the left side of SAM 32
Figure 4 – An alternative form factor DUT and standard coordinate and reference points applied 33
Figure 5 – Block diagram of the tests to be performed 36
Figure 6 – Orientation of the probe with respect to the line normal to the phantom surface, shown at two different locations 39
Figure 7 – Measurement procedure for different types of correlated signals 45
Figure 8 – The Fast SAR measurement procedure B. 52
Figure 9 – Modified chart of 6.4.2 57

Figure 10 – Orientation and surface of the averaging volume relative to the phantom surface 81
Figure A.1 – Illustration of dimensions in Table A.1 and Table A.2 105
Figure A.2 – Close-up side view of phantom showing the ear region 107
Figure A.3 – Side view of the phantom showing relevant markings 107
Figure A.4 – Sagittally bisected phantom with extended perimeter (shown placed on its side as used for device SAR tests) 109
Figure A.5 – Picture of the phantom showing the central strip 109
Figure A.6 – Cross-sectional view of SAM at the reference plane 110
Figure A.7 – Dimensions of the elliptical phantom 111
Figure B.1 – Experimental set-up for assessment of the sensitivity (conversion factor) using a vertically-oriented rectangular waveguide 118
Figure B.2 – Illustration of the antenna gain evaluation set-up 121
Figure B.3 – Schematic of the coaxial calorimeter system 125
Figure B.4 – Set-up to assess spherical isotropy deviation in tissue-equivalent liquid 127
Figure B.5 – Alternative set-up to assess spherical isotropy deviation in tissue-equivalent liquid 128
Figure B.6 – Experimental set-up for the hemispherical isotropy assessment 129
Figure B.7 – Conventions for dipole position (ξ) and polarization (θ) 129
Figure B.8 – Measurement of hemispherical isotropy with reference antenna 130
Figure C.1 – Extrude method of averaging 133
Figure C.2 – Extrapolation of SAR data to the inner surface of the phantom based on a fourth-order least-square polynomial fit of the measured data (squares) 134
Figure D.1 – Test set-up for the *system check* 137
Figure F.1 – Example reference coordinate system for the left ERP of the SAM phantom 148
Figure F.2 – Example coordinate system on the device under test 149
Figure G.1 – Mechanical details of the standard dipole 151
Figure G.2 – Standard waveguide source (dimensions are according to Table G.2) 152
Figure H.1 – Dimensions of the flat phantom set-up used for deriving the minimal phantom dimensions for W and L for a given phantom depth D 154
Figure H.2 – FDTD predicted uncertainty in the 10 g peak spatial-average SAR as a function of the dimensions of the flat phantom compared with an infinite flat phantom, at 800 MHz 154
Figure J.1 – Slotted line set-up 161
Figure J.2 – An open-ended coaxial probe with inner and outer radii a and b, respectively 163
Figure J.3 – TEM line dielectric test set-up [143] 165
Figure K.1 – SAR values for twelve hypothetical test configurations measured in the same frequency band and modulation (e.g. GSM 900 MHz) using a hypothetical full SAR (full SAR) and two fast SAR (fast SAR 1 and fast SAR 2) evaluations 178
Figure L.1 – Distribution of "Tilt/Cheek" 195
Figure L.2 – SAR relative to SAR in position with maximum SAR in GSM mode 200
Figure L.3 – Two points identifying the minimum distance between the position of the interpolated maximum SAR and the points at 0,6 × SAR_{max} 201
Figure L.4 – Histogram for D_{min} in the case of GSM 900 and iso-level at 0,6 × SAR_{max} 202
Figure L.5 – Histogram for random variable $Factor1g1800$ 203

Figure O.1 – Quick guide flow-chart 214

Table 1 – Area scan parameters 38
Table 2 – Zoom scan parameters 38
Table 3 – Example method to determine the combined SAR value using Alternative 1 43
Table 4 – Threshold values $\mathrm{TH}(f)$ used in this proposed test reduction protocol 56
Table 5 – Example uncertainty template and example numerical values for dielectric constant ($\varepsilon'_{\mathrm{r}}$) and conductivity ($\sigma$) measurement 71
Table 6 –Uncertainty of Formula (41) as a function of the maximum change in permittivity or conductivity 73
Table 7 – Parameters for the reference function f_1 in Formula (48) 77
Table 8 – Uncertainties relating to the deviations of the parameters of the standard waveguide source from theory 82
Table 9 – Other uncertainty contributions relating to the dipole sources described in Annex G. 83
Table 10 – Other uncertainty contributions relating to the standard waveguide sources described in Annex G 83
Table 11 – Example of measurement uncertainty evaluation template for handset SAR test 85
Table 12 – Example of measurement uncertainty evaluation template for *system validation* 88
Table 13 – Example of measurement repeatability evaluation template for *system check* (applicable for one system). 90
Table 14 – Measurement uncertainty budget for relative fast SAR tests 97
Table 15 – Measurement uncertainty budget for *system check* using fast SAR methods 99
Table A.1 – Dimensions used in deriving SAM phantom from the ARMY 90th percentile male head data (Gordon et al. [56]) 106
Table A.2 – Additional SAM dimensions compared with selected dimensions from the ARMY 90th-percentile male head data (Gordon et al. [56]) – specialist head measurement section 106
Table A.3 – Dielectric properties of the head tissue-equivalent liquid 112
Table B.1 – Uncertainty analysis for transfer calibration using temperature probes 116
Table B.2 – Guidelines for designing calibration waveguides 119
Table B.3 – Uncertainty analysis of the probe calibration in waveguide 120
Table B.4 – Uncertainty template for evaluation of reference antenna gain 122
Table B.5 – Uncertainty template for calibration using reference antenna 123
Table B.6 – Uncertainty components for probe calibration using thermal methods 126
Table D.1 – Numerical target SAR values (W/kg) for standard dipole and flat phantom 142
Table D.2 – Numerical target SAR values for waveguides specified in Clause G.2 placed in contact with flat phantom [94] 143
Table G.1 – Mechanical dimensions of the reference dipoles 150
Table G.2 – Mechanical dimensions of the standard waveguide 152
Table H.1 – Parameters used for calculation of reference SAR values in Table D.1 155
Table I.1 – Suggested recipes for achieving target dielectric parameters: 300 MHz to 900 MHz 157
Table I.2 – Suggested recipes for achieving target dielectric parameters: 1 450 MHz to 2 000 MHz 158

Table I.3 – Suggested recipes for achieving target dielectric parameters: 2 100 MHz to 5 800 MHz 159
Table J.1 – Parameters for calculating the dielectric properties of various reference liquids 167
Table J.2 – Dielectric properties of reference liquids at 20 °C 167
Table K.1 – Measurement uncertainty budget for relative fast SAR tests complying with Annex K requirements, for tests performed within one frequency band and modulation 174
Table K.2 – Measurement uncertainty budget for *system check* using fast SAR methods complying with Annex K requirements 176
Table K.3 – Measurements conducted according to Step a) 179
Table K.4 – Measurements conducted according to Step b) 180
Table K.5 – Measurements conducted according to Step c) 180
Table K.6 – Measurements conducted according to 6.4.2, Step 2) 181
Table K.7 – Measurements conducted according to 6.4.2, Step 3) 182
Table K.8 – Measurements conducted according to 6.4.2, Step 4) 182
Table K.9 – Fast SAR measurements conducted according to Step a) 183
Table K.10 – Fast SAR measurements showing highest SAR value according to Step b) 184
Table K.11 – Full SAR measurements conducted according to Step b) 184
Table K.12 – Fast SAR measurements showing values according-to requirements in Step c) 185
Table K.13 – Full SAR measurements conducted according to Step c) 185
Table K.14 – Fast SAR measurements showing values according to requirements in Step e) 186
Table K.15 – Full SAR measurements conducted according to Step e) 186
Table K.16 – Measurements conducted according to Step a) 187
Table K.17 – Measurements conducted according to Step b) 188
Table K.18 – Measurements conducted according to Step c) 188
Table K.19 – Measurements conducted according to Step e) 189
Table K.20 – Measurements conducted according to Step f) 190
Table K.21 – Fast SAR measurements conducted according to Step a) 191
Table K.22 – Full SAR measurements conducted according to Step b) 191
Table K.23 – Full SAR measurements conducted according to Step e) 192
Table K.24 – Full SAR measurements conducted according to Step e) 193
Table L.1 – The number of handsets used for the statistical study 195
Table L.2 – Statistical analysis results of P(Tilt/Cheek > x) for various x values 196
Table L.3 – Statistical analysis results of P(Tilt/Cheek > x) for 1 g and 10 g peak spatial-average SAR 196
Table L.4 – Statistical analysis results of P(Tilt/Cheek > x) for various antenna locations 197
Table L.5 – Statistical analysis results of P(Tilt/Cheek > x) for various frequency bands 197
Table L.6 – Statistical analysis results of P(Tilt/Cheek > x) for various device types 198
Table L.7 – Distance D_{min}^{*} for various iso-level values 202
Table L.8 – Experimental thresholds to have a 95 % probability that the maximum measured SAR value from the area scan will also have a peak spatial-average SAR 203
Table L.9 – SAR values from the area scan (GSM 900 band) 204
Table L.10 – SAR values from the area scan (GSM 900 band) 205

Table M.1 – SAR results tables for example test results – GSM 850 207
Table M.2 – SAR results table for example test results – GSM 900 208
Table M.3 – SAR results table for example test results – GSM 1800 208
Table M.4 – SAR results table for example test results – GSM 1900 209
Table O.1 – Quick start guide: SAR evaluation steps 215

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_____

MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62209-1 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure.

This second edition cancels and replaces the first edition published in 2005. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) Extension of the frequency range to 300 MHz to 6 GHz.
b) Fast SAR methods.

c) Test reduction techniques.

d) SAR measurements of terminals with multiple antennas and multiple transmitters.

e) Deviation of dielectric characteristics of the tissue-equivalent liquids is relaxed up to 10 %.

f) Uncertainty evaluation guidelines for temperature and dielectric parameter deviations of tissue-equivalent liquids.

g) Addition of the following annexes:

- Annex K (informative) Measurement uncertainty of specific fast SAR methods and fast SAR examples
- Annex L (informative) SAR test reduction supporting information
- Annex M (informative) Applying the head SAR test procedures
- Annex N (informative) Studies for potential hand effects on head SAR
- Annex O (informative) Quick start guide.

The text of this standard is based on the following documents:

FDIS	Report on voting
106/361/FDIS	106/365/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types are used:

– specific test protocols: in *italic* type.

A list of all parts in the IEC 62209 series, published under the general title *Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC TC 106 has the scope to prepare International Standards on measurement and calculation methods used to assess human exposure to electric, magnetic and electromagnetic fields. IEC TC 106 has developed this part of IEC 62209 to provide procedures to evaluate the specific absorption rate (SAR) of human exposures due to electromagnetic field (EMF) transmitting devices when held close to the ear. The types of devices include but are not limited to mobile telephones, cordless telephones, headphones, etc., which are used close to the ear. The IEC TC 106 standards do not deal with the exposure limits. Conformity assessment depends on the policy of national regulatory bodies. While basic restrictions on SAR in the ICNIRP Guidelines [64] [1] go up to 10 GHz, the frequency range for this part of IEC 62209 is limited to an upper end frequency of 6 GHz since current wireless handsets operate below this frequency.

IEC TC 106 and IEEE/ICES TC34[2] worked together formally through common membership to achieve the goal of harmonization, between IEC TC 106 Maintenance Team 1 for this part of IEC 62209 and IEEE/ICES TC34 for IEEE Std 1528 [66]. During the process a primary effort involved was to harmonize these two standards.

To aid the user of this part of IEC 62209, a quick start guide has been prepared and included as an informative annex (see Annex O). The quick start guide is not a substitute for following the detailed procedure of the standard.

---

1 Numbers in square brackets refer to the Bibliography.

2 The International Committee on Electromagnetic Safety of the IEEE.

MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)

1 Scope

This part of IEC 62209 specifies protocols and test procedures for measurement of the peak spatial-average SAR induced inside a simplified model of the head with defined reproducibility. It applies to certain electromagnetic field (EMF) transmitting devices that are positioned next to the ear, where the radiating structures of the device are in close proximity to the human head, such as mobile phones, cordless phones, certain headsets, etc. These protocols and test procedures provide a conservative estimate with limited uncertainty for the peak-spatial SAR that would occur in the head for a significant majority of people during normal use of these devices. The applicable frequency range is from 300 MHz to 6 GHz.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 17043:2010, *Conformity assessment – General requirements for proficiency testing*

ISO/IEC 17025:2005, *General requirements for the competence of testing and calibration laboratories*