

| | | |
|------------|--|--|
| STN | Železnice Koľaj Parametre návrhu usporiadania koľaje Rozchod 1 435 mm a širší | STN EN 13803 73 6360 |
|------------|--|--|

Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 09/17

Obsahuje: EN 13803:2017

Oznámením tejto normy sa ruší
STN EN 13803-1 (73 6360) z decembra 2010

STN EN 13803-2+A1 (73 6360) z mája 2010

125364

Úrad pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky, 2017
Podľa zákona č. 264/1999 Z. z. o technických požiadavkách na výrobky a o posudzovaní zhody a o zmene a doplnení niektorých zákonov v znení neskorších predpisov sa slovenská technická norma a časti slovenskej technickej normy môžu rozmnožovať alebo rozširovať len so súhlasom slovenského národného normalizačného orgánu.

EUROPEAN STANDARD

EN 13803

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2017

ICS 93.100

Supersedes EN 13803-1:2010, EN 13803-2:2006+A1:2009

English Version

Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

Applications ferroviaires - Voie - Paramètres de conception du tracé de la voie - Écartement 1 435 mm et plus large

Bahnanwendungen - Oberbau - Trassierungsparameter - Spurweiten 1 435 mm und größer

This European Standard was approved by CEN on 21 December 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

| | Page |
|--|-----------|
| European foreword..... | 6 |
| 1 Scope | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 7 |
| 4 Symbols and abbreviations | 10 |
| 5 General..... | 11 |
| 5.1 Background | 11 |
| 5.2 Alignment characteristics | 11 |
| 6 Limits for 1 435 mm gauge | 13 |
| 6.1 Radius of horizontal curve R | 13 |
| 6.2 Cant D | 13 |
| 6.3 Cant deficiency I | 14 |
| 6.4 Cant excess E | 16 |
| 6.5 Length of cant transitions L_D and transition curves in the horizontal plane L_K | 17 |
| 6.5.1 General..... | 17 |
| 6.5.2 Lengths of linear cant transitions and clothoids | 17 |
| 6.5.3 Lengths of transition curves with non-constant gradient of curvature and cant | 18 |
| 6.6 Cant gradient dD/ds | 19 |
| 6.7 Rate of change of cant dD/dt | 19 |
| 6.8 Rate of change of cant deficiency dI/dt | 20 |
| 6.9 Length of constant cant between two linear cant transitions L_i | 21 |
| 6.10 Abrupt change of horizontal curvature..... | 22 |
| 6.11 Abrupt change of cant deficiency ΔI | 22 |
| 6.12 Length between two abrupt changes of horizontal curvature L_c | 22 |
| 6.13 Length between two abrupt changes of cant deficiency L_s | 23 |
| 6.14 Track gradients p | 24 |
| 6.15 Vertical radius R_v | 25 |
| 6.16 Length of vertical curves L_v | 25 |
| 6.17 Abrupt change of track gradient Δp | 26 |
| Annex A (normative) Rules for converting parameter values for track gauges wider than 1 435 mm..... | 27 |
| A.1 Scope | 27 |
| A.2 Symbols and abbreviations | 27 |
| A.3 Basic assumptions and equivalence rules..... | 29 |
| A.3.1 General..... | 29 |
| A.3.2 Basic formulae..... | 29 |
| A.3.3 Basic data | 30 |
| A.4 Detailed conversion rules | 30 |
| A.4.1 General..... | 30 |
| A.4.2 Cant D_1 (Subclause 6.2 of the main body of the standard) | 30 |
| A.4.3 Cant deficiency I_1 (Subclause 6.3 of the main body of the standard) | 32 |
| A.4.4 Cant excess E_1 (Subclause 6.4 of the main body of the standard)..... | 33 |
| A.4.5 Lengths of cant transitions L_D and transition curves in the horizontal plane L_K (Subclause 6.5 of the main body of the standard)..... | 33 |

| | | |
|---|---|-----------|
| A.4.6 | Cant gradient dD_1/ds (Subclause 6.6 of the main body of the standard) | 34 |
| A.4.7 | Rate of change of cant dD_1/dt (Subclause 6.7 of the main body of the standard) | 34 |
| A.4.8 | Rate of change of cant deficiency dI_1/dt (Subclause 6.8 of the main body of the standard) | 35 |
| A.4.9 | Abrupt change of curvature and abrupt change of cant deficiency ΔI_1 (Subclauses 6.10 and 6.11 of the main body of the standard)..... | 36 |
| A.4.10 | Other parameters (Subclauses 6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16 and 6.17 of the main body of the standard)..... | 36 |
| Annex B (normative) Track alignment design parameter limits for track gauges wider than 1 435 mm | | |
| | | 37 |
| B.1 | Scope | 37 |
| B.2 | Requirements for a gauge of 1 520 mm and 1 524 mm | 37 |
| B.2.1 | General | 37 |
| B.2.2 | Radius of horizontal curve R_1 | 37 |
| B.2.3 | Cant D_1 | 37 |
| B.2.4 | Cant deficiency I_1 | 38 |
| B.2.5 | Cant excess E_1 | 39 |
| B.2.6 | Length of cant transitions L_{D1} and transition curves in the horizontal plane L_{K1} | 39 |
| B.2.7 | Cant gradient dD_1/ds | 40 |
| B.2.8 | Rate of change of cant dD_1/dt | 41 |
| B.2.9 | Rate of change of cant deficiency dI_1/dt | 41 |
| B.2.10 | Length of constant cant between two linear cant transitions L_{i1} | 42 |
| B.2.11 | Abrupt change of horizontal curvature | 43 |
| B.2.12 | Abrupt change of cant deficiency ΔI_1 | 43 |
| B.2.13 | Length between two abrupt changes of horizontal curvature L_{C1} | 43 |
| B.2.14 | Length between two abrupt changes of cant deficiency L_{s1} | 43 |
| B.2.15 | Track gradients p_1 | 44 |
| B.2.16 | Vertical radius R_{v1} | 44 |
| B.2.17 | Length vertical curves L_{v1} | 44 |
| B.2.18 | Abrupt change of track gradient Δp_1 | 44 |
| B.3 | Requirements for a gauge of 1 668 mm..... | 44 |
| B.3.1 | General | 44 |
| B.3.2 | Radius of horizontal curve R_1 | 44 |
| B.3.3 | Cant D_1 | 44 |
| B.3.4 | Cant deficiency I_1 | 45 |
| B.3.5 | Cant excess E_1 | 46 |
| B.3.6 | Length of cant transitions L_{D1} and transition curves in the horizontal plane L_{K1} | 46 |
| B.3.7 | Cant gradient dD_1/ds | 47 |
| B.3.8 | Rate of change of cant dD_1/dt | 48 |
| B.3.9 | Rate of change of cant deficiency dI_1/dt | 49 |
| B.3.10 | Length of constant cant between two linear cant transitions L_{i1} | 50 |
| B.3.11 | Abrupt change of horizontal curvature | 50 |
| B.3.12 | Abrupt change of cant deficiency ΔI_1 | 50 |
| B.3.13 | Length between two abrupt changes of horizontal curvature L_{C1} | 51 |
| B.3.14 | Length between two abrupt changes of cant deficiency L_{s1} | 51 |
| B.3.15 | Track gradients p_1 | 51 |
| B.3.16 | Vertical radius R_{v1} | 51 |
| B.3.17 | Length vertical curves L_{v1} | 52 |
| B.3.18 | Abrupt change of track gradient Δp_1 | 52 |
| Annex C (informative) Supplementary information about shape and length of transition curves..... | | |
| | | 53 |
| C.1 | General | 53 |

| | | |
|---|---|----|
| C.2 | Definitions and properties of different transition curves and cant transitions..... | 53 |
| C.2.1 | Definitions | 53 |
| C.2.2 | Properties | 54 |
| C.3 | Further aspects that may be considered for a progressive track alignment design | 59 |
| C.3.1 | Background | 59 |
| C.3.2 | Progressive track alignment design..... | 59 |
| Annex D (informative) Constraints and risks associated with the use of exceptional limits | | 62 |
| Annex E (informative) Evaluation of conditions at the toe of a switch..... | | 63 |
| E.1 | General..... | 63 |
| E.2 | Method based on effective radius | 63 |
| Annex F (informative) Design considerations for switch and crossing units..... | | 65 |
| F.1 | Examples of common switch and crossing units | 65 |
| F.2 | Use of diamond crossings, diamond crossings with slips and tandem turnouts | 67 |
| F.3 | Switch and crossing units on, or near, under-bridges | 67 |
| F.4 | Abutting switch and crossing units..... | 67 |
| F.5 | Switch and crossing units on horizontal curves..... | 67 |
| F.6 | Switch and crossing units on canted track..... | 68 |
| F.7 | Vertical alignments and switch and crossing units | 68 |
| Annex G (informative) Examples of applications | | 71 |
| G.1 | General..... | 71 |
| G.2 | Example of crossover on horizontal curve..... | 71 |
| G.3 | Example of bi-linear cant transition | 72 |
| G.4 | Example where a cant transition is designed without a coinciding transition curve | 73 |
| G.5 | Example of substandard transition curve..... | 74 |
| G.6 | Example where several alignment elements forms an intermediate length..... | 75 |
| Annex H (informative) Examples of local limits for cant deficiency..... | | 76 |
| Annex I (informative) Considerations regarding cant deficiency and cant excess | | 77 |
| I.1 | Introduction | 77 |
| I.2 | Cant deficiency | 77 |
| I.3 | Cant excess..... | 77 |
| I.4 | Wheel climb criterion..... | 77 |
| I.5 | Vehicle overturning..... | 78 |
| I.6 | The lateral strength of a track under loading (<i>Prud'homme limit</i>)..... | 78 |
| I.7 | Cant deficiency at switch and crossing layouts on curves..... | 78 |
| Annex J (informative) Passenger comfort on curves..... | | 79 |
| J.1 | General..... | 79 |
| J.2 | Lateral acceleration | 79 |
| J.3 | Lateral jerk | 79 |
| J.3.1 | Lateral jerk as a function of rate of change of cant deficiency..... | 79 |
| J.3.2 | Lateral jerk as a function of an abrupt change of cant deficiency | 80 |
| J.4 | Roll motions | 80 |
| Annex K (normative) Sign rules for calculation of ΔD , ΔI and Δp | | 81 |
| K.1 | General regarding the sign rules..... | 81 |
| K.2 | Sign rules for calculation of ΔD | 81 |
| K.3 | Sign rules for calculation of ΔI | 81 |
| K.4 | Sign rules for calculation of Δp | 82 |
| Annex L (informative) Length of constant cant between two linear cant transitions L_i | | 84 |
| Annex M (informative) The principle of virtual transition..... | | 85 |

| | | |
|-------------------------------|---|-----------|
| M.1 | Virtual transition at an abrupt change of cant deficiency..... | 85 |
| M.2 | Virtual transition at a short intermediate length between two abrupt changes of cant deficiency..... | 86 |
| M.3 | Limits based on the principle of the virtual transition..... | 87 |
| M.3.1 | General | 87 |
| M.3.2 | Characteristic vehicle with a distance of 20 m between bogie centres..... | 87 |
| M.3.3 | Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres | 87 |
| Annex N (normative) | Lengths of intermediate elements L_c to prevent buffer locking..... | 89 |
| N.1 | General | 89 |
| N.2 | Basic vehicles and running conditions | 89 |
| N.3 | Lengths L_c of an intermediate straight track between two long circular curves in the opposite directions | 89 |
| N.4 | General cases for end throw differences..... | 90 |
| Annex O (informative) | Considerations for track gradients..... | 93 |
| O.1 | Uphill gradients..... | 93 |
| O.2 | Downhill gradients..... | 93 |
| O.3 | Gradients for stabling tracks and at platforms..... | 93 |
| Annex ZA (informative) | Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC..... | 94 |
| Bibliography | | 97 |

European foreword

This document (EN 13803:2017) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2017, and conflicting national standards shall be withdrawn at the latest by October 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13803-1:2010 and EN 13803-2:2006+A1:2009.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2008/57/EC.

For relationship with EU Directive 2008/57/EC, see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

The purpose of this European Standard is to specify rules and limits for track alignment design parameters, including alignments within switches and crossings. Several of these limits are functions of speed. Alternatively, for a given track alignment, it specifies rules and limits that determine permissible speed.

This European Standard applies to nominal track gauges 1 435 mm and wider with speeds up to 360 km/h. Normative Annex A describes the conversion rules which shall be applied for tracks with nominal gauges wider than 1 435 mm. Normative Annex B is applied for nominal track gauges 1 520 mm, 1 524 mm and 1 668 mm.

This European Standard is also applicable where track alignment takes into account vehicles that have been approved for high cant deficiencies (including tilting trains).

More restrictive requirements of Technical specifications for interoperability relating to the 'infrastructure' subsystem of the rail system in the European Union (TSI INF) and other (national, company, etc.) rules will apply.

This European Standard need not be applicable to lines, or dedicated parts of railway infrastructure that are not interoperable with railway vehicles tested and approved according to EN 14363.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13848-5, *Railway applications — Track — Track geometry quality — Part 5: Geometric quality levels — Plain line*

EN 14363, *Railway applications - Testing and Simulation for the acceptance of running characteristics of railway vehicles - Running Behaviour and stationary tests*

EN 15273-1, *Railway applications — Gauges — Part 1: General — Common rules for infrastructure and rolling stock*

EN 15273-2, *Railway applications — Gauges — Part 2: Rolling stock gauge*

EN ISO 80000-3, *Quantities and units - Part 3: Space and time (ISO 80000-3)*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN