

STN	Priechodky nad 1 kV do 52 kV a od 250 A do 3,15 kA pre transformátory plnené kvapalinou Časť 3: Požiadavky na upevnenie priechodky Zmena A1	STN EN 50180-3/A1 34 8153
------------	--	---

Bushings above 1 kV up to 52 kV and from 250 A to 3,15 kA for liquid filled transformers - Part 3: Requirements for bushing fixations

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 11/17

STN EN 50180-3 z februára 2016 sa bez zmeny A1 môže používať do 10. 5. 2020.

Obsahuje: EN 50180-3:2015/A1:2017

125752

Úrad pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky, 2017
Podľa zákona č. 264/1999 Z. z. o technických požiadavkách na výrobky a o posudzovaní zhody a o zmene a doplnení niektorých zákonov v znení neskorších predpisov sa slovenská technická norma a časti slovenskej technickej normy môžu rozmnožovať alebo rozširovať len so súhlasom slovenského národného normalizačného orgánu.

EUROPEAN STANDARD

EN 50180-3:2015/A1

NORME EUROPÉENNE

EUROPÄISCHE NORM

June 2017

ICS 29.080.20

English Version

Bushings above 1 kV up to 52 kV and from 250 A to 3,15 kA for liquid filled transformers - Part 3: Requirements for bushing fixations

Traversées de tensions supérieures à 1 kV jusqu'à 52 kV et de 250 A à 3,15 kA pour transformateurs immergés dans un liquide - Partie 3 : Exigences relatives aux fixations de traversée

Durchführungen über 1 kV bis 52 kV und von 250 A bis 3,15 kA für flüssigkeitsgefüllte Transformatoren - Teil 3: Anforderungen an Einzelteile der Befestigung

This amendment A1 modifies the European Standard EN 50180-3:2015; it was approved by CENELEC on 2017-05-10. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this amendment the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This amendment exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

European foreword	3
1 Modification to Clause 1, Scope	4
2 Modifications to 4.1, Fixation for bushings	4
3 Modifications to 4.2, Details for fixations	4

European foreword

This document [EN 50180-3:2015/A1:2017] has been prepared by CLC/TC 36A "Insulated bushings".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2018-05-10
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2020-05-10

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

1 Modification to Clause 1, Scope

Delete the last two paragraphs:

"For a better understanding of additional information some dimension from EN 50180-1 are repeated in this European Standard.

This European Standard was extended for fastenings of bushings for a highest voltage of 52 kV."

koniec náhľadu – text ďalej pokračuje v platenej verzii STN