

STN	Fľaše na plyn Ventily na zvyškový tlak Všeobecné požiadavky a typová skúška ventilov obsahujúcich zariadenia na zvyškový tlak (ISO 15996: 2017)	STN EN ISO 15996 07 8607
------------	--	--

Gas cylinders - Residual pressure valves - Specification and type testing of cylinder valves incorporating residual pressure devices (ISO 15996:2017)

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 02/18

Obsahuje: EN ISO 15996:2017, ISO 15996:2017

Oznámením tejto normy sa ruší
STN EN ISO 15996 (07 8607) z októbra 2005

126196

Úrad pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky, 2018
Podľa zákona č. 264/1999 Z. z. o technických požiadavkách na výrobky a o posudzovaní zhody a o zmene a doplnení niektorých zákonov v znení neskorších predpisov sa slovenská technická norma a časti slovenskej technickej normy môžu rozmnožovať alebo rozširovať len so súhlasom slovenského národného normalizačného orgánu.

EUROPEAN STANDARD

EN ISO 15996

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2017

ICS 23.020.35

Supersedes EN ISO 15996:2005

English Version

Gas cylinders - Residual pressure valves - Specification and type testing of cylinder valves incorporating residual pressure devices (ISO 15996:2017)

Bouteilles à gaz - Robinets à pression résiduelle -
Spécifications et essais de type de robinets de bouteille
intégrant des dispositifs de pression résiduelle (ISO
15996:2017)

Gasflaschen - Restdruckventile - Spezifikation und
Baumusterprüfungen von Flaschenventilen mit
integrierten Restdruckeinrichtungen (ISO
15996:2017)

This European Standard was approved by CEN on 11 July 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword.....	3

European foreword

This document (EN ISO 15996:2017) has been prepared by Technical Committee ISO/TC 58 “Gas cylinders” in collaboration with Technical Committee CEN/TC 23 “Transportable gas cylinders” the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2018, and conflicting national standards shall be withdrawn at the latest by March 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 15996:2005.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Serbia, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 15996:2017 has been approved by CEN as EN ISO 15996:2017 without any modification.

**Gas cylinders — Residual pressure
valves — Specification and type testing
of cylinder valves incorporating
residual pressure devices**

*Bouteilles à gaz — Robinets à pression résiduelle — Spécifications
et essais de type de robinets de bouteille intégrant des dispositifs de
pression résiduelle*





COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 RPV design considerations and requirements	3
4.1 Design considerations.....	3
4.1.1 Resistance against vibration.....	3
4.1.2 Integrity under high flow.....	4
4.2 Design requirements.....	4
4.2.1 General.....	4
4.2.2 Valve outlet connection.....	4
4.3 Performance requirements for RPDs.....	4
4.3.1 Requirements for type 1 and type 2 RPDs.....	4
4.3.2 Additional requirements for type 1 RPDs.....	5
5 RPV type testing	5
5.1 General.....	5
5.2 Documentation.....	6
5.3 Test samples.....	6
5.4 Test report.....	7
5.5 Test temperatures.....	7
5.6 Test pressures.....	7
5.6.1 RPV test pressure.....	7
5.6.2 Other test pressures.....	7
5.7 Test gases.....	7
5.7.1 Gas quality.....	7
5.7.2 Verification of opening pressure and closing-off pressure.....	8
5.7.3 Leak tightness test in the reverse direction for type 1 RPDs.....	8
5.7.4 Endurance test.....	8
5.7.5 Oxygen pressure surge test.....	8
5.7.6 Vibration test.....	8
5.7.7 Integrity under high flow test.....	9
5.8 Test schedule.....	9
5.9 RPD performance tests.....	10
5.9.1 Strength test of the non-return function in the reverse direction for type 1 RPDs.....	10
5.9.2 Verification of opening pressure and closing-off pressure.....	10
5.9.3 Endurance test.....	11
5.9.4 Leak tightness test in the reverse direction for type 1 RPDs.....	11
5.9.5 Visual examination.....	12
6 Marking	12
Annex A (informative) Design considerations	13
Annex B (normative) Oxygen pressure surge test	14
Annex C (informative) Vibration test	15
Annex D (informative) Integrity under high flow test	16
Annex E (informative) Examples of test equipment	18
Bibliography	21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

This second edition cancels and replaces the first edition (ISO 15996:2005), which has been technically revised. It also incorporates the Amendment ISO 15996:2005/Amd 1:2007.

The main changes compared to the previous edition are as follows:

- a) Title and scope: extension to cover the complete RPV (valve including the residual pressure device) and not the RPD (residual pressure device) only; informative reference to ISO 10297 was modified;
- b) Scope: inclusion of main valves, valves with integrated pressure regulator (VIPRs) and RPVs for pressure drums and tubes; exclusion of dissolved gases, possible application for RPD stand-alone devices;
- c) Terms, definitions and symbols: introduction of new definitions and adaptation of existing definitions; introduction of different types of RPDs to replace the old descriptions and change of order (type A became type 2 and type B became type 1);
- d) Valve design considerations: inclusion of design considerations with addition of informative [Annex A](#);
- e) Performance requirements and considerations:
 - 1) Closing-off pressure and opening pressure: introduction of requirements for opening pressure and closing-off pressure, especially of a minimum value for the closing-off pressure;
 - 2) Endurance: reduction of number of endurance cycles for type 2 RPDs;
 - 3) Visual examination: introduction of visual examination at the end of the complete test procedure;

- 4) Resistance of the non-return function against pressure in the reverse direction for type 1 RPDs: exclusion of RPDs in VIPRs and adaptation of pass-fail requirements;
 - 5) Leak tightness in the reverse direction for type 1 RPDs: exclusion of RPDs in VIPRs;
 - 6) Integrity under high flow: exclusion of RPDs when installed outside the filling path in a VIPR;
- f) RPV type testing:
- 1) General: introduction of information on how to deal with changes within the RPV design;
 - 2) Test samples: addition of requirement to submit the test samples for oxygen pressure surge testing with the relevant filling connector(s);
 - 3) Test gases: introduction of requirements on the use and quality of the test gases;
 - 4) Test schedule: adaptation to meet the new requirements, addition of test pressure and test temperature; deletion of information on variants;
 - 5) Strength test of the non-return function in the reverse direction for type 1 RPD tests: decrease of number of test samples to one;
 - 6) Verification of opening pressure and closing-off pressure: addition of verification at low and high temperature; addition of detailed test procedure;
 - 7) Leak tightness test in the reverse direction for type 1 RPDs: modification and clarification of tightness test in the flow direction; addition of test at 0,5 bar in the reverse direction;
 - 8) Visual examination: addition of visual examination to the test sequence;
 - 9) Oxygen pressure surge test: information transferred to normative [Annex B](#); addition of test for main valves; addition of detailed information on test procedure;
- g) Marking: introduction of marking requirements;
- h) [Annex A](#) (informative): deletion of examples of RPV designs; introduction of design considerations;
- i) [Annex B](#) (normative): information on test equipment transferred to informative [Annex D](#); new [Annex B](#) giving mandatory requirements on oxygen pressure surge test;
- j) [Annex C](#) (informative): update of MIL standard reference for vibration test;
- k) [Annex D](#) (informative): complete modification of integrity under high flow test (reduction of number of test samples, adaptation of gases for which an additional test with carbon dioxide should be carried out, change from liquid carbon dioxide to gaseous carbon dioxide as test gas, modification of test procedure);
- l) [Annex E](#): new informative [Annex E](#) giving information on test equipment (former [Annex B](#)).

Introduction

Increased requirements to avoid contamination of gases and cylinders have led to the development of valves incorporating residual pressure devices (RPDs) hereinafter referred to as residual pressure valves (RPVs).

These devices are designed to maintain a positive pressure relative to atmosphere within the cylinder by closing off its internal gas passages in the discharging direction. This prevents the cylinder from being completely emptied in customer use and stops ingress of atmospheric contamination if the valve operating mechanism (main shut-off) is left open. Many of these devices include a non-return function that protects the cylinder from backflow from downstream processes.

This document has been written so that it is suitable for the application of the UN Model Regulations.

Considering the changes described in the Foreword, when an RPV has been approved according to the previous version of this document, the body responsible for approving the same RPV to this new edition should consider which tests need to be performed.

In this document the unit bar is used, due to its universal use in the field of technical gases. It should, however, be noted that bar is not an SI unit, and that the corresponding SI unit for pressure is Pa ($1 \text{ bar} = 10^5 \text{ Pa} = 10^5 \text{ N/m}^2$).

Pressure values given in this document are given as gauge pressure (pressure exceeding atmospheric pressure) unless noted otherwise.

Gas cylinders — Residual pressure valves — Specification and type testing of cylinder valves incorporating residual pressure devices

1 Scope

This document specifies design, type testing and marking requirements for cylinder valves incorporating residual pressure devices, hereinafter referred to as residual pressure valves (RPVs). This document applies to the following types of RPVs:

- a) cylinder valves intended to be fitted to refillable transportable gas cylinders;
- b) main valves (excluding ball valves) for cylinder bundles;
- c) cylinder valves or main valves with integrated pressure regulator (VIPR);
- d) valves for pressure drums and tubes;

which convey compressed or liquefied gases.

NOTE Where there is no risk of ambiguity, cylinders, pressure drums, tubes and cylinder bundles are addressed with the collective term “cylinder” within this document.

These requirements are in addition to those in ISO 10297.

For RPD stand-alone devices this document can also be applied.

This document does not apply to RPVs for portable fire extinguishers, cryogenic equipment, low pressure refrigerant gases (cylinder test pressure less than 50 bar), dissolved gases or liquefied petroleum gas (LPG).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies

ISO 10286, *Gas cylinders — Terminology*

ISO 10297:2014, *Gas cylinders — Cylinder valves — Specification and type testing*

ISO 10524-3, *Pressure regulators for use with medical gases — Part 3: Pressure regulators integrated with cylinder valves*

ISO 22435, *Gas cylinders — Cylinder valves with integrated pressure regulators — Specification and type testing*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN