

|            |   |  |
|------------|---|--|
| <b>STN</b> | <b>Stanovenie intenzity vysokofrekvenčných polí, hustoty výkonu a špecifickej miery absorpcie (SAR) v okolí rádiokomunikačných základňových staníc na účely hodnotenia expozície osôb</b> | <b>STN<br/>EN 62232</b><br><br>36 7087 |
|------------|---|--|

Determination of RF field strength, power density and SAR in the vicinity of radiocommunication base stations for the purpose of evaluating human exposure

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 03/18

Obsahuje: EN 62232:2017, IEC 62232:2017

Oznámením tejto normy sa od 27.09.2020 ruší  
STN EN 50383 (36 7087) z januára 2011

STN EN 50400 (36 7080) z januára 2007

STN EN 50492 (36 7945) z augusta 2009

**126467**



EUROPEAN STANDARD

**EN 62232**

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2017

ICS 13.280; 17.240

Supersedes EN 50383:2010, EN 50400:2006,  
EN 50492:2008

English Version

Determination of RF field strength, power density and SAR in the vicinity of radiocommunication base stations for the purpose of evaluating human exposure  
(IEC 62232:2017)

Détermination des champs de radiofréquences, densité de puissance et du DAS aux environs des stations de base utilisées pour les communications radio dans le but d'évaluer l'exposition humaine  
(IEC 62232:2017)

Bestimmung der HF-Feldstärke, der Leistungsdichte und der spezifischen Absorptionsrate (SAR) in der Nachbarschaft von Funkkommunikations-Basisstationen zur Ermittlung der menschlichen Exposition  
(IEC 62232:2017)

This European Standard was approved by CENELEC on 2017-09-27. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

**EN 62232:2017****European foreword**

The text of document 106/397/FDIS, future edition 2 of IEC 62232, prepared by IEC/TC 106 "Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62232:2017.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2018-06-27
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2020-09-27

This document supersedes EN 50400:2006 + AC:2011 + A1:2012, EN 50383:2010 + AC:2013 and EN 50492:2008 + A1:2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

**Endorsement notice**

The text of the International Standard IEC 62232:2017 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

|               |      |                                 |
|---------------|------|---------------------------------|
| ISO/IEC 17025 | NOTE | Harmonized as EN ISO/IEC 17025. |
| CISPR 16-4-2  | NOTE | Harmonized as EN 55016-4-2.     |

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: [www.cenelec.eu](http://www.cenelec.eu).

| <u>Publication</u> | <u>Year</u> | <u>Title</u>  | <u>EN/HD</u> | <u>Year</u> |
|--------------------|-------------|---|--------------|-------------|
| IEC 62209-1        | -           | Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)                    | EN 62209-1   | -           |
| IEC 62209-2        | -           | Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz) | EN 62209-2   | -           |
| IEC 62479          | -           | Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)   | EN 62479     | -           |
| IEC 62311          | -           | Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)  | EN 62311     | -           |





IEC 62232

Edition 2.0 2017-08

# INTERNATIONAL STANDARD



**Determination of RF field strength, power density and *SAR* in the vicinity of radiocommunication base stations for the purpose of evaluating human exposure**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2017 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

#### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### **IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)**

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### **IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### **IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### **Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### **IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### **IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).





IEC 62232

Edition 2.0 2017-08

# INTERNATIONAL STANDARD



---

**Determination of RF field strength, power density and *SAR* in the vicinity of radiocommunication base stations for the purpose of evaluating human exposure**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 13.280; 17.240

ISBN 978-2-8322-4635-1

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

|  |    |
|--|----|
| FOREWORD.....  | 12 |
| INTRODUCTION.....  | 14 |
| 1 Scope.....   | 15 |
| 2 Normative references .....   | 15 |
| 3 Terms and definitions .....  | 16 |
| 4 Symbols and abbreviated terms.....   | 22 |
| 4.1 Physical quantities .....  | 22 |
| 4.2 Constants .....  | 23 |
| 4.3 Abbreviated terms.....   | 23 |
| 5 Quick start guide and how to use this document .....   | 24 |
| 5.1 Overview.....  | 24 |
| 5.2 Quick start guide.....   | 24 |
| 5.3 How to use this document.....  | 26 |
| 5.4 Worked case studies.....   | 27 |
| 6 Evaluation processes for product compliance, product installation compliance and in-situ RF exposure assessments ..... | 27 |
| 6.1 Evaluation process for product compliance .....  | 27 |
| 6.1.1 General .....  | 27 |
| 6.1.2 Establishing compliance boundaries .....   | 27 |
| 6.1.3 Iso-surface compliance boundary definition .....   | 28 |
| 6.1.4 Simple compliance boundaries .....   | 28 |
| 6.1.5 Methods for establishing the compliance boundary .....   | 30 |
| 6.1.6 Uncertainty .....  | 32 |
| 6.1.7 Reporting.....   | 32 |
| 6.2 Evaluation process used for product installation compliance .....  | 33 |
| 6.2.1 General .....  | 33 |
| 6.2.2 General evaluation procedure for product installations.....  | 33 |
| 6.2.3 Product installation data collection.....  | 34 |
| 6.2.4 Simplified product installation evaluation process .....   | 35 |
| 6.2.5 Assessment area selection .....  | 37 |
| 6.2.6 Measurements.....  | 39 |
| 6.2.7 Computations .....   | 40 |
| 6.2.8 Uncertainty .....  | 41 |
| 6.2.9 Reporting.....   | 41 |
| 6.3 Evaluation processes for in-situ RF exposure assessment .....  | 42 |
| 6.3.1 General requirements, source determination and site analysis.....  | 42 |
| 6.3.2 Measurement procedures .....   | 44 |
| 6.3.3 Uncertainty .....  | 45 |
| 6.3.4 Reporting.....   | 45 |
| 6.4 Averaging procedures .....   | 46 |
| 6.4.1 Spatial averaging.....   | 46 |
| 6.4.2 Time averaging.....  | 46 |
| 7 Determining the evaluation method.....   | 46 |
| 7.1 Overview.....  | 46 |
| 7.2 Process to determine the evaluation method .....   | 46 |
| 7.2.1 General .....  | 46 |

|   |   |     |
|---|---|-----|
| 7.2.2   | Establishing the evaluation points in relation to the source-environment plane .....                      | 47  |
| 7.2.3   | Exposure metric selection.....  | 49  |
| 8   | Evaluation methods .....  | 49  |
| 8.1   | Overview.....   | 49  |
| 8.2   | Measurement methods.....  | 50  |
| 8.2.1   | General .....   | 50  |
| 8.2.2   | RF field strength measurements .....  | 50  |
| 8.2.3   | <i>SAR</i> measurements .....   | 51  |
| 8.3   | Computation methods .....   | 52  |
| 9   | Uncertainty.....  | 53  |
| 10  | Reporting.....  | 54  |
| 10.1  | General requirements .....  | 54  |
| 10.2  | Report format.....  | 54  |
| 10.3  | Opinions and interpretations .....  | 55  |
| Annex A (informative) Source environment plane and guidance on the evaluation method selection..... |   | 56  |
| A.1   | Guidance on the source-environment plane .....  | 56  |
| A.1.1   | General .....   | 56  |
| A.1.2   | Source-environment plane example .....  | 56  |
| A.1.3   | Source regions .....  | 57  |
| A.2   | Select between computation or measurement approaches .....  | 63  |
| A.3   | Select measurement method.....  | 64  |
| A.3.1   | Selection stages .....  | 64  |
| A.3.2   | Selecting between field strength and <i>SAR</i> measurement approaches .....                              | 64  |
| A.3.3   | Selecting between broadband and frequency-selective measurement .....                                     | 65  |
| A.3.4   | Selecting RF field strength measurement procedures .....  | 66  |
| A.4   | Select computation method.....  | 66  |
| A.5   | Additional considerations .....   | 68  |
| A.5.1   | Simplicity.....   | 68  |
| A.5.2   | Evaluation method ranking .....   | 68  |
| A.5.3   | Applying multiple methods for RF exposure evaluation .....  | 68  |
| Annex B (normative) Evaluation methods.....   |   | 69  |
| B.1   | Overview.....   | 69  |
| B.2   | Evaluation parameters .....   | 69  |
| B.2.1   | Overview .....  | 69  |
| B.2.2   | Coordinate systems .....  | 69  |
| B.2.3   | Reference points .....  | 70  |
| B.2.4   | Variables .....   | 70  |
| B.3   | Measurement methods.....  | 73  |
| B.3.1   | RF field strength measurements .....  | 73  |
| B.3.2   | <i>SAR</i> measurements .....   | 104 |
| B.4   | Computation methods .....   | 114 |
| B.4.1   | Overview and general requirements.....  | 114 |
| B.4.2   | Formulas .....  | 115 |
| B.4.3   | Basic algorithms .....  | 123 |
| B.4.4   | Advanced computation methods .....  | 129 |
| B.5   | Extrapolation from the evaluated <i>SAR</i> / RF field strength to the required assessment condition..... | 150 |

|                       |  |     |
|-----------------------|--|-----|
| B.5.1                 | Extrapolation method .....   | 150 |
| B.5.2                 | Extrapolation to maximum RF field strength using broadband measurements .....                  | 151 |
| B.5.3                 | Extrapolation to maximum RF field strength for frequency and code selective measurements ..... | 151 |
| B.5.4                 | Influence of traffic in real operating network .....   | 152 |
| B.6                   | Summation of multiple RF fields .....  | 152 |
| B.6.1                 | Applicability .....  | 152 |
| B.6.2                 | Uncorrelated fields .....  | 153 |
| B.6.3                 | Correlated fields .....  | 153 |
| B.6.4                 | Ambient fields .....   | 153 |
| Annex C (informative) | Rationale supporting simplified product installation criteria .....                            | 154 |
| C.1                   | General .....  | 154 |
| C.2                   | Class E2 .....   | 154 |
| C.3                   | Class E10 .....  | 155 |
| C.4                   | Class E100 .....   | 155 |
| C.5                   | Class E+ .....   | 157 |
| Annex D (informative) | Guidance on comparing evaluated parameters with a limit value .....                            | 159 |
| D.1                   | Overview .....   | 159 |
| D.2                   | Information required to compare evaluated value against limit value .....                      | 159 |
| D.3                   | Performing a limit comparison at a given confidence level .....                                | 159 |
| D.4                   | Performing a limit comparison using a process based assessment scheme .....                    | 160 |
| Annex E (informative) | Uncertainty .....  | 161 |
| E.1                   | Background .....   | 161 |
| E.2                   | Requirement to estimate uncertainty .....  | 161 |
| E.3                   | How to estimate uncertainty .....  | 162 |
| E.4                   | Guidance on uncertainty and assessment schemes .....   | 162 |
| E.4.1                 | General .....  | 162 |
| E.4.2                 | Overview of assessment schemes .....   | 162 |
| E.4.3                 | Examples of assessment schemes .....   | 163 |
| E.4.4                 | Assessment schemes and compliance probabilities .....  | 166 |
| E.5                   | Guidance on uncertainty .....  | 168 |
| E.5.1                 | Overview .....   | 168 |
| E.5.2                 | Measurement uncertainty and confidence levels .....  | 169 |
| E.6                   | Applying uncertainty for compliance assessments .....  | 170 |
| E.7                   | Example influence quantities for field measurements .....                                      | 170 |
| E.7.1                 | General .....  | 170 |
| E.7.2                 | Calibration uncertainty of measurement antenna or field probe .....                            | 171 |
| E.7.3                 | Frequency response of the measurement antenna or field probe .....                             | 171 |
| E.7.4                 | Isotropy of the measurement antenna or field probe .....                                       | 173 |
| E.7.5                 | Frequency response of the spectrum analyser .....  | 173 |
| E.7.6                 | Temperature response of a broadband field probe .....  | 173 |
| E.7.7                 | Linearity deviation of a broadband field probe .....   | 173 |
| E.7.8                 | Mismatch uncertainty .....   | 173 |
| E.7.9                 | Deviation of the experimental source from numerical source .....                               | 174 |
| E.7.10                | Meter fluctuation uncertainty for time varying signals .....                                   | 174 |
| E.7.11                | Uncertainty due to power variation in the RF source .....                                      | 174 |
| E.7.12                | Uncertainty due to field gradients .....   | 174 |

|                       |   |     |
|-----------------------|---|-----|
| E.7.13                | Mutual coupling between measurement antenna or isotropic probe and object .....   | 176 |
| E.7.14                | Uncertainty due to field scattering from the surveyor's body .....  | 177 |
| E.7.15                | Measurement device.....   | 178 |
| E.7.16                | Fields out of measurement range.....  | 178 |
| E.7.17                | Noise.....  | 179 |
| E.7.18                | Integration time .....  | 179 |
| E.7.19                | Power chain.....  | 179 |
| E.7.20                | Positioning system.....   | 179 |
| E.7.21                | Matching between probe and the EUT .....  | 179 |
| E.7.22                | Drifts in output power of the EUT, probe, temperature, and humidity.....  | 179 |
| E.7.23                | Perturbation by the environment .....   | 179 |
| E.8                   | Example influence quantities for RF field strength computations by ray tracing or full wave methods .....                             | 180 |
| E.8.1                 | General .....   | 180 |
| E.8.2                 | System .....  | 180 |
| E.8.3                 | Technique uncertainties.....  | 181 |
| E.8.4                 | Environmental uncertainties.....  | 181 |
| E.9                   | Influence quantities for <i>SAR</i> measurements .....  | 182 |
| E.9.1                 | General .....   | 182 |
| E.9.2                 | Post-processing.....  | 182 |
| E.9.3                 | Device holder .....   | 182 |
| E.9.4                 | Test sample positioning .....   | 183 |
| E.9.5                 | Phantom shell uncertainty.....  | 184 |
| E.9.6                 | <i>SAR</i> correction / target liquid permittivity and conductivity .....   | 184 |
| E.9.7                 | Liquid permittivity and conductivity measurements.....  | 184 |
| E.9.8                 | Liquid temperature.....   | 185 |
| E.10                  | Influence quantities for <i>SAR</i> calculations .....  | 185 |
| E.11                  | Spatial averaging .....   | 185 |
| E.11.1                | General .....   | 185 |
| E.11.2                | Small-scale fading variations .....   | 186 |
| E.11.3                | Error on the estimation of local average power density .....  | 186 |
| E.11.4                | Error on the estimation of local average power density .....  | 187 |
| E.11.5                | Characterization of environment statistical properties .....  | 187 |
| E.11.6                | Characterization of different averaging schemes.....  | 188 |
| E.12                  | Influence of human body on probe measurements of the electrical field strength .....  | 192 |
| E.12.1                | Simulations of the influence of human body on probe measurements based on the Method of Moments (Surface Equivalence Principle) ..... | 192 |
| E.12.2                | Comparison with measurements .....  | 194 |
| E.12.3                | Conclusions.....  | 194 |
| Annex F (informative) | Technology-specific guidance.....   | 195 |
| F.1                   | Overview to guidance on specific technologies .....   | 195 |
| F.2                   | Summary of technology-specific information .....  | 195 |
| F.3                   | Guidance on spectrum analyser settings .....  | 199 |
| F.3.1                 | Overview of spectrum analyser settings.....   | 199 |
| F.3.2                 | Detection algorithms.....   | 199 |
| F.3.3                 | Resolution bandwidth and channel power processing .....   | 200 |
| F.3.4                 | Integration per service .....   | 202 |
| F.4                   | Constant power components .....   | 203 |

|        |   |     |
|--------|---|-----|
| F.4.1  | TDMA/FDMA technology.....   | 203 |
| F.4.2  | WCDMA/UMTS technology .....   | 203 |
| F.4.3  | OFDM technology .....   | 204 |
| F.5    | WCDMA measurement and calibration using a code domain analyser .....  | 204 |
| F.5.1  | WCDMA measurements – General.....   | 204 |
| F.5.2  | Requirements for the code domain analyser .....   | 204 |
| F.5.3  | Calibration .....   | 205 |
| F.6    | Wi-Fi measurements .....  | 207 |
| F.6.1  | General .....   | 207 |
| F.6.2  | Integration time for reproducible measurements .....  | 207 |
| F.6.3  | Channel occupation .....  | 208 |
| F.6.4  | Some considerations .....   | 208 |
| F.6.5  | Scalability by channel occupation .....   | 209 |
| F.6.6  | Influence of the application layers.....  | 209 |
| F.7    | LTE measurements for Frequency Division Duplexing (FDD) .....   | 209 |
| F.7.1  | Overview .....  | 209 |
| F.7.2  | Maximum LTE exposure evaluation .....   | 210 |
| F.7.3  | Instantaneous LTE exposure evaluation .....   | 213 |
| F.7.4  | MIMO multiplexing of LTE base station.....  | 213 |
| F.8    | LTE measurements for Time Division Duplexing (TDD) .....  | 214 |
| F.8.1  | General .....   | 214 |
| F.8.2  | Definitions and transmission modes.....   | 214 |
| F.8.3  | TDD frame structure .....   | 215 |
| F.8.4  | Maximum LTE exposure evaluation .....   | 217 |
| F.9    | Establishing compliance boundaries using numerical simulations of MIMO array antennas emitting correlated wave-forms .....    | 220 |
| F.9.1  | General .....   | 220 |
| F.9.2  | Field combining near radio base stations for correlated exposure with the purpose of establishing compliance boundaries ..... | 221 |
| F.9.3  | Numerical simulations of MIMO array antennas with densely packed columns .....  | 222 |
| F.9.4  | Numerical simulations of large MIMO array antennas .....  | 222 |
| F.10   | Smart antennas .....  | 223 |
| F.10.1 | Overview .....  | 223 |
| F.10.2 | Deterministic conservative approach .....   | 223 |
| F.10.3 | Statistical conservative approach.....  | 223 |
| F.10.4 | Example approaches .....  | 224 |
| F.10.5 | Smart antenna (TD-LTE).....   | 233 |
| F.11   | Establishing compliance boundary for systems using dish antennas .....  | 233 |
| F.11.1 | General .....   | 233 |
| F.11.2 | Overview .....  | 234 |
| F.11.3 | Compliance boundary of a dish antenna .....   | 234 |
|        | Bibliography.....   | 236 |
|        | Figure 1 – Quick start guide to the evaluation process .....  | 25  |
|        | Figure 2 – Example of complex compliance boundary .....   | 28  |
|        | Figure 3 – Example of circular cylindrical compliance boundaries .....  | 28  |
|        | Figure 4 – Example of box shaped compliance boundary .....  | 29  |
|        | Figure 5 – Example of truncated box shaped compliance boundary .....  | 29  |

|   |     |
|---|-----|
| Figure 6 – Example of dish antenna compliance boundary (from [11]).....   | 30  |
| Figure 7 – Example illustrating the linear scaling procedure.....   | 31  |
| Figure 8 – Flowchart describing the product installation evaluation process.....  | 34  |
| Figure 9 – Square-shaped assessment domain boundary (ADB) with size $D_{ad}$ .....  | 39  |
| Figure 10 – Alternative routes to evaluate in-situ RF exposure.....   | 43  |
| Figure 11 – Source-environment plane concept.....   | 48  |
| Figure 12 – Flow chart of the measurement methods.....  | 50  |
| Figure 13 – Flow chart of the relevant computation methods.....   | 52  |
| Figure A.1 – Example source-environment plane regions near a radio base station antenna on a tower which has a narrow vertical (elevation plane) beamwidth (not to scale).....      | 56  |
| Figure A.2 – Example source-environment plane regions near a roof-top antenna which has a narrow vertical (elevation plane) beamwidth (not to scale).....                           | 57  |
| Figure A.3 – Geometry of an antenna with largest linear dimension $L_{eff}$ and largest end dimension $L_{end}$ .....   | 58  |
| Figure A.4 – Maximum path difference for an antenna with largest linear dimension $L$ .....   | 62  |
| Figure B.1 – Cylindrical, cartesian and spherical coordinates relative to the RBS antenna.....  | 70  |
| Figure B.2 – Evaluation locations.....  | 81  |
| Figure B.3 – Relationship of separation of remote radio source and evaluation area to separation of evaluation points.....  | 82  |
| Figure B.4 – Outline of the surface scanning methodology.....   | 84  |
| Figure B.5 – Block diagram of the near-field antenna measurement system.....  | 85  |
| Figure B.6 – Minimum radius constraint where $a$ denotes the minimum radius of a sphere, centred at the reference point, that will encompass the EUT.....                           | 86  |
| Figure B.7 – Maximum angular sampling spacing constraint.....   | 86  |
| Figure B.8 – Outline of the volume/surface scanning methodology.....  | 90  |
| Figure B.9 – Block diagram of typical near-field EUT measurement system.....  | 91  |
| Figure B.10 – Spatial averaging schemes relative to foot support level and in the vertical plane oriented to offer maximum area in the direction of the source being evaluated..... | 97  |
| Figure B.11 – Spatial averaging relative to spatial-peak field strength point height.....   | 97  |
| Figure B.12 – Positioning of the EUT relative to the relevant phantom.....  | 105 |
| Figure B.13 – Phantom liquid volume and measurement volume used for whole-body $SAR$ measurements with the box-shaped phantoms.....   | 111 |
| Figure B.14 – Reflection due to the presence of a ground plane.....   | 116 |
| Figure B.15 – Enclosed cylinder around collinear arrays, with and without electrical downtilt.....  | 116 |
| Figure B.16 – Leaky feeder geometry.....  | 118 |
| Figure B.17 – Directions for which $SAR$ estimation expressions are given.....  | 119 |
| Figure B.18 – Reference frame employed for cylindrical formulas for field strength computation at a point P (left), and on a line perpendicular to boresight (right).....           | 124 |
| Figure B.19 – Views illustrating the three valid zones for field strength computation around an antenna.....  | 125 |
| Figure B.20 – Cylindrical formulas reference results.....   | 128 |
| Figure B.21 – Spherical formulas reference results.....   | 129 |
| Figure B.22 – Synthetic model and ray tracing algorithms geometry and parameters.....   | 131 |

|   |     |
|---|-----|
| Figure B.23 – Line 4 far-field positions for synthetic model and ray tracing validation example .....   | 134 |
| Figure B.24 – Antenna parameters for synthetic model and ray tracing algorithms validation example .....  | 135 |
| Figure B.25 – Generic 900 MHz RBS antenna with nine dipole radiators .....  | 142 |
| Figure B.26 – Line 1, 2 and 3 near-field positions for full wave and ray tracing validation .....   | 142 |
| Figure B.27 – Generic 1 800 MHz RBS antenna with five slot radiators .....  | 143 |
| Figure B.28 – RBS antenna placed in front of a multi-layered lossy cylinder .....   | 149 |
| Figure B.29 – Time variation over 24 h of the exposure induced by GSM 1800 MHz (left) and FM (right) both normalized to mean .....  | 152 |
| Figure C.1 – Measured $ER$ as a function of distance for a low power BS ( $G = 5$ dBi, $f = 2\,100$ MHz) transmitting with an $EIRP$ of 2 W (class E2) and 10 W (class E10) ..... | 154 |
| Figure C.2 – Minimum installation height as a function of transmitting power corresponding to class E10 .....   | 155 |
| Figure C.3 – Compliance distance in the main lobe as a function of $EIRP$ established according to the far-field formula corresponding to class E100 .....                        | 156 |
| Figure C.4 – Minimum installation height as a function of transmitting power corresponding to class E100 .....  | 156 |
| Figure C.5 – Averaged power density at ground level for various installation configurations of equipment with 100 W $EIRP$ (class E100) .....                                     | 157 |
| Figure C.6 – Compliance distance in the main lobe as a function of $EIRP$ established according to the far-field formula corresponding to class E+ .....                          | 158 |
| Figure C.7 – Minimum installation height as a function of transmitting power corresponding to class E+ .....  | 158 |
| Figure E.1 – Examples of general assessment schemes .....   | 164 |
| Figure E.2 – Target uncertainty scheme overview .....   | 165 |
| Figure E.3 – Probability of the true value being above (respectively below) the evaluated value depending on the confidence level assuming a normal distribution .....            | 169 |
| Figure E.4 – Plot of the calibration factors for $E$ (not $E^2$ ) provided from an example calibration report for an electric field probe .....                                   | 172 |
| Figure E.5 – Computational model used for the variational analysis of reflected RF fields from the front of a surveyor .....  | 177 |
| Figure E.6 – Positioning device and different positioning errors .....  | 183 |
| Figure E.7 – Physical model of Rayleigh (a) and Rice (b) small-scale fading variations .....  | 185 |
| Figure E.8 – Example of $E$ field strength variations in line of sight of an antenna operating at 2,2 GHz .....   | 186 |
| Figure E.9 – Error at 95% on average power estimation .....   | 187 |
| Figure E.10 – 343 measurement positions building a cube (centre) and different templates consisting of a different number of positions .....                                      | 188 |
| Figure E.11 – Moving a template (Line 3) through the CUBE .....   | 189 |
| Figure E.12 – Standard deviations for GSM 900, DCS 1800 and UMTS .....  | 191 |
| Figure E.13 – Simulation arrangement .....  | 193 |
| Figure E.14 – Body influence .....  | 193 |
| Figure E.15 – Simulation arrangement .....  | 194 |
| Figure F.1 – Spectral occupancy for GMSK .....  | 200 |
| Figure F.2 – Spectral occupancy for CDMA .....  | 201 |
| Figure F.3 – Channel allocation for a WCDMA signal .....  | 204 |



|  |     |
|--|-----|
| Figure F.4 – Example of Wi-Fi frames .....   | 207 |
| Figure F.5 – Channel occupation versus the integration time for IEEE 802.11b standard .....  | 208 |
| Figure F.6 – Channel occupation versus nominal throughput rate for IEEE 802.11b/g standards.....   | 208 |
| Figure F.7 – Wi-Fi spectrum trace snapshot.....  | 209 |
| Figure F.8 – Frame structure of transmission signal for LTE downlink .....   | 210 |
| Figure F.9 – Examples of received waves from LTE downlink signals using a spectrum analyser using zero span mode.....  | 213 |
| Figure F.10 – Frame structure type 2 (for 5 ms switch-point periodicity).....  | 216 |
| Figure F.11 – Frame structure of transmission signal for TDD LTE .....   | 216 |
| Figure F.12 – PBCH measurement example.....  | 218 |
| Figure F.13 – PBCH measurement example spectrum analyser using zero span mode .....  | 220 |
| Figure F.14 – MIMO array antenna with densely packed columns .....   | 221 |
| Figure F.15 – Plan view representation of statistical conservative model .....   | 224 |
| Figure F.16 – Binomial cumulative probability function for $N = 24$ , $PR = 0,125$ .....   | 232 |
| Figure F.17 – Binomial cumulative probability function for $N = 18$ , $PR = 2/7$ .....   | 233 |
| Figure F.18 – Flowchart for the assessment of EMF compliance boundary in the line of sight of dish antennas (from [11]).....                                     | 235 |
| <br>   |     |
| Table 1 – Quick start guide evaluation steps .....   | 26  |
| Table 2 – Example of product installation classes where a simplified evaluation process is applicable (based on ICNIRP general public limits [13]) .....         | 36  |
| Table 3 – Exposure metrics validity for evaluation points in each source region .....  | 49  |
| Table 4 – Requirements for RF field strength measurements .....  | 51  |
| Table 5 – Whole-body <i>SAR</i> exclusions based on RF power levels.....   | 51  |
| Table 6 – Requirements for <i>SAR</i> measurements.....  | 51  |
| Table 7 – Applicability of computation methods for source-environment regions of Figure 10 .....   | 53  |
| Table 8 – Requirements for computation methods.....  | 53  |
| Table A.1 – Definition of source regions.....  | 59  |
| Table A.2 – Default source region boundaries.....  | 59  |
| Table A.3 – Source region boundaries for antennas with maximum dimension less than $2,5 \lambda$ .....   | 60  |
| Table A.4 – Source region boundaries for linear/planar antenna arrays with a maximum dimension greater than or equal to $2,5 \lambda$ .....                      | 60  |
| Table A.5 – Source region boundaries for equiphase radiation aperture (e.g. dish) antennas with maximum reflector dimension much greater than a wavelength ..... | 61  |
| Table A.6 – Source region boundaries for leaky feeders .....   | 61  |
| Table A.7 – Far-field distance $r$ measured in metres as a function of angle $\beta$ .....   | 63  |
| Table A.8 – Guidance on selecting between computation and measurement approaches.....  | 64  |
| Table A.9 – Guidance on selecting between broadband and frequency-selective measurement.....   | 65  |
| Table A.10 – Guidance on selecting RF field strength measurement procedures.....   | 66  |
| Table A.11 – Guidance on selecting computation methods.....  | 67  |

|  |     |
|--|-----|
| Table A.12 – Guidance on specific evaluation method ranking .....  | 68  |
| Table B.1 – Dimension variables.....   | 70  |
| Table B.2 – RF power variables .....   | 71  |
| Table B.3 – Antenna variables .....  | 72  |
| Table B.4 – Exposure metric variables.....   | 73  |
| Table B.5 – Broadband measurement system requirements.....   | 75  |
| Table B.6 – Frequency-selective measurement system requirements.....   | 76  |
| Table B.7 – Sample template for estimating the expanded uncertainty of an in-situ<br>RF field strength measurement that used a frequency-selective instrument .....  | 100 |
| Table B.8 – Sample template for estimating the expanded uncertainty of an in-situ<br>RF field strength measurement that used a broadband instrument .....  | 101 |
| Table B.9 – Sample template for estimating the expanded uncertainty of a laboratory-<br>based RF field strength measurement using the surface scanning method.....   | 102 |
| Table B.10 – Sample template for estimating the expanded uncertainty of a laboratory-<br>based RF field strength measurement using the volume scanning method .....  | 103 |
| Table B.11 – Numerical reference <i>SAR</i> values for reference dipoles and flat phantom –<br>All values are normalized to a forward power of 1 W .....   | 108 |
| Table B.12 – Phantom liquid volume and measurement volume used for whole-body<br><i>SAR</i> measurements [35], [29] .....  | 111 |
| Table B.13 – Correction factor to compensate for a possible bias in the obtained<br>general public whole-body <i>SAR</i> when assessed using the large box-shaped phantom<br>for child exposure configurations [36]..... | 111 |
| Table B.14 – Measurement uncertainty evaluation template for EUT whole-body <i>SAR</i> test .  | 112 |
| Table B.15 – Measurement uncertainty evaluation template for whole-body <i>SAR</i><br>system validation .....  | 113 |
| Table B.16 – Applicability of <i>SAR</i> estimation formulas .....   | 120 |
| Table B.17 – Definition of $C(f)$ .....  | 121 |
| Table B.18 – Input parameters for <i>SAR</i> estimation formulas validation.....   | 123 |
| Table B.19 – $SAR_{10g}$ and $SAR_{wb}$ estimation formula reference results for Table B.18<br>parameters and a body mass of 46 kg.....  | 123 |
| Table B.20 – Definition of boundaries for selecting the zone of computation .....  | 126 |
| Table B.21 – Input parameters for cylinder and spherical formulas validation.....  | 128 |
| Table B.22 – Sample template for estimating the expanded uncertainty of a synthetic<br>model and ray tracing RF field strength computation.....  | 133 |
| Table B.23 – Synthetic model and ray tracing power density reference results.....  | 136 |
| Table B.24 – Sample template for estimating the expanded uncertainty of a full wave<br>RF field strength computation .....   | 140 |
| Table B.25 – Validation 1 full wave field reference results.....   | 143 |
| Table B.26 – Validation 2 full wave field reference results.....   | 144 |
| Table B.27 – Sample template for estimating the expanded uncertainty of a full wave<br><i>SAR</i> computation .....  | 147 |
| Table B.28 – Validation reference <i>SAR</i> results for computation method .....  | 149 |
| Table E.1 – Determining target uncertainty .....   | 165 |
| Table E.2 – Monte Carlo simulation of 10 000 trials, both surveyor and auditor using<br>best estimate .....  | 167 |
| Table E.3 – Monte Carlo simulation of 10 000 trials, both surveyor and auditor using<br>target uncertainty of 4 dB.....  | 167 |

|  |     |
|--|-----|
| Table E.4 – Monte Carlo simulation of 10 000 trials surveyor uses upper 95 % CI vs. auditor uses lower 95 % CI .....   | 168 |
| Table E.5 – Guidance on minimum separation distances for some dipole lengths to ensure that the uncertainty does not exceed 5 % or 10 % in a measurement of $E$ .....                    | 175 |
| Table E.6 – Guidance on minimum separation distances for some loop diameters to ensure that the uncertainty does not exceed 5 % or 10 % in a measurement of $H$ .....                    | 176 |
| Table E.7 – Example minimum separation conditions for selected dipole lengths for 10 % uncertainty in $E$ .....  | 176 |
| Table E.8 – Standard estimates of dB variation for the perturbations in front of a surveyor due to body reflected fields as described in Figure E.5 .....                                | 178 |
| Table E.9 – Standard uncertainty ( $u$ ) estimates for $E$ and $H$ due to body reflections from the surveyor for common radio services derived from estimates provided in Table E.8..... | 178 |
| Table E.10 – Maximum sensitivity coefficients for liquid permittivity and conductivity over the frequency range 300 MHz to 6 GHz.....  | 185 |
| Table E.11 – Uncertainty at 95 % for different fading models .....   | 188 |
| Table E.12 – Correlation coefficients for GSM 900 and DCS 1800 .....   | 190 |
| Table E.13 – Variations of the standard deviations for the GSM 900, DCS 1800 and UMTS frequency band .....   | 191 |
| Table E.14 – Examples of total uncertainty calculation.....  | 192 |
| Table E.15 – Maximum simulated error due to the influence of a human body on the measurement values of an omni-directional probe .....   | 194 |
| Table E.16 – Measured influence of a human body on omni-directional probe measurements .....   | 194 |
| Table F.1 – Technology specific information .....  | 196 |
| Table F.2 – Example of spectrum analyser settings for an integration per service .....   | 202 |
| Table F.3 – Example constant power components for specific TDMA/FDMA technologies .....  | 203 |
| Table F.4 – WCDMA decoder requirements .....   | 205 |
| Table F.5 – Signal configurations.....   | 205 |
| Table F.6 – WCDMA generator setting for power linearity .....  | 206 |
| Table F.7 – WCDMA generator setting for decoder calibration .....  | 206 |
| Table F.8 – WCDMA generator setting for reflection coefficient measurement .....   | 207 |
| Table F.9 – Theoretical extrapolation factor, $N_{RS}$ , based on frame structure given in 3GPP TS 36.104 [10].....  | 212 |
| Table F.10 – Configuration of special subframe (lengths of DwPTS/GP/UpPTS) .....   | 217 |
| Table F.11 – Uplink-downlink configurations .....  | 217 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**DETERMINATION OF RF FIELD STRENGTH, POWER DENSITY AND *SAR*  
IN THE VICINITY OF RADIOCOMMUNICATION BASE STATIONS FOR  
THE PURPOSE OF EVALUATING HUMAN EXPOSURE**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62232 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure.

This second edition cancels and replaces the first edition published in 2011 and constitutes a technical revision.

The significant changes with respect to the previous edition are the following:

- a) Increased frequency range from 110 MHz to 100 GHz (including consideration of ambient sources 100 kHz to 300 GHz);
- b) product compliance – determination of compliance boundary information for an RBS product before it is placed on the market;
- c) product installation compliance – determination of the total RF exposure levels before the product is put into service;

- d) simplified document structure and methods of assessment for new technologies such as LTE–TDD, FDD and WiFi.

This publication contains attached files in the form of a CD-ROM for the paper version and embedded files for the electronic version. These files are intended to be used as a complement and do not form an integral part of the standard.

The text of this International Standard is based on the following documents:

|              |                  |
|--------------|------------------|
| FDIS         | Report on voting |
| 106/397/FDIS | 106/406/RVD      |

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

This document addresses the evaluation of radiofrequency (RF) field strength, power density or specific absorption rate (*SAR*) levels in the vicinity of radiocommunication base stations (RBS), also called product or Equipment Under Test (EUT), intentionally radiating in the frequency range 110 MHz to 100 GHz according to the scope (see Clause 1). It does not address the evaluation of current density which exposure guidelines often do not consider to be relevant when evaluating RF fields in the intended RBS operating frequency range.

This document specifies the RF exposure evaluation methods to be used for product compliance, product installation compliance and in-situ RF exposure assessments. It does not define human exposure limits, also called “exposure limits”. When implementing RF exposure assessments, the surveyor refers to the set of exposure limits applicable where exposure takes place.

Clause 2, Clause 3 and Clause 4 address normative references, terms and definitions, and symbols and abbreviated terms, respectively.

Clause 5 provides a quick start guide and details how to use this document.

Clause 6 describes the three main application areas of this document: RF exposure evaluation methods for product compliance, product installation compliance, and in-situ RF exposure assessments. Further details are provided in Annex C.

Clause 7 provides guidelines on how to select the evaluation method. Further details are provided in Annex A.

Clause 8 defines the RF exposure evaluation methods to be used and refers to further details in Annexes B and F.

Clause 9 addresses the estimation of uncertainty and refers to Annex E for further details.

Clause 10 describes reporting requirements for the evaluation or assessment.

Annexes and the bibliography are referenced extensively to provide useful clarifications or guidance.

Additional guidance can be found in IEC TR 62669 which includes a set of worked case studies giving practical examples of the application of this document.

# DETERMINATION OF RF FIELD STRENGTH, POWER DENSITY AND *SAR* IN THE VICINITY OF RADIOCOMMUNICATION BASE STATIONS FOR THE PURPOSE OF EVALUATING HUMAN EXPOSURE

## 1 Scope

This document provides methods for the determination of radio-frequency (RF) field strength and specific absorption rate (*SAR*) in the vicinity of radiocommunication base stations (RBS) for the purpose of evaluating human exposure.

This document:

- a) considers intentionally radiating RBS which transmit on one or more antennas using one or more frequencies in the range 110 MHz to 100 GHz;
- b) considers the impact of ambient sources on RF exposure at least in the 100 kHz to 300 GHz frequency range;
- c) specifies the methods to be used for RF exposure evaluation for compliance assessment applications, namely:
  - 1) product compliance – determination of compliance boundary information for an RBS product before it is placed on the market;
  - 2) product installation compliance – determination of the total RF exposure levels in accessible areas from an RBS product and other relevant sources before the product is put into service;
  - 3) in-situ RF exposure assessment – measurement of in-situ RF exposure levels in the vicinity of an RBS installation after the product has been taken into operation;
- d) describes several RF field strength and *SAR* measurement and computation methodologies with guidance on their applicability to address both the in-situ evaluation of installed RBS and laboratory-based evaluations;
- e) describes how surveyors, with a sufficient level of expertise, establish their specific evaluation procedures appropriate for their evaluation purpose;
- f) provides guidance on how to report, interpret and compare results from different evaluation methodologies and, where the evaluation purpose requires it, determine a justified decision against a limit value;
- g) provides short descriptions of the informative example case studies given in the companion Technical Report IEC TR 62669 [1].

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62209-1, *Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)*

IEC 62209-2, *Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)*

IEC 62479, *Assessment of the compliance of low power electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (10 MHz – 300 GHz)*

IEC 62311, *Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz)*

**koniec náhľadu – text ďalej pokračuje v platenej verzii STN**