

<b>STN</b>	<p><b>Pevné rádiové systémy Charakteristiky a požiadavky na zariadenia a antény bod-bod Časť 1: Prehľad a spoločné charakteristiky nezávislé od systému</b></p>	<p><b>STN EN 302 217-1 V3.1.1</b></p>
		87 2217

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola označená vo Vestníku ÚNMS SR č. 09/18

Obsahuje: EN 302 217-1 V3.1.1:2017

**127270**

# ETSI EN 302 217-1 V3.1.1 (2017-05)



**Fixed Radio Systems;  
Characteristics and requirements for  
point-to-point equipment and antennas;  
Part 1: Overview, common characteristics and  
system-independent requirements**

---

Reference

REN/ATTM-04028

---

Keywordsantenna, DFRS, DRRS, FWA, point-to-point,  
radio, transmission***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations .....	12
3.1 Definitions.....	12
3.2 Symbols.....	17
3.3 Abbreviations .....	18
4 Structure and applicability of the ETSI EN 302 217 series.....	20
4.1 Generality .....	20
4.2 Cross references to previously relevant ENs and TSs .....	21
4.3 Summary of system options provided .....	22
4.4 User's guide .....	25
5 General characteristics .....	27
5.1 Frequency bands and channel arrangements .....	27
5.2 Special compatibility requirements between systems .....	27
5.3 Transmission capacity and spectral efficiency .....	27
5.4 Performance and availability requirements .....	28
5.5 Environmental profiles .....	28
5.5.0 Introduction.....	28
5.5.1 Environmental profile declared under Directive 2014/53/EU .....	28
5.5.2 ETSI environmental profiles.....	28
5.5.2.0 Generality.....	28
5.5.2.1 Equipment intended for telecommunications applications installed in weather-protected locations (indoor locations) .....	29
5.5.2.2 Equipment intended for telecommunications applications installed in not-weather-protected locations (outdoor locations).....	29
5.5.3 Test environment profiles .....	29
5.6 Power supply .....	29
5.6.0 Introduction.....	29
5.6.1 Power supply profile declared under Directive 2014/53/EU .....	30
5.6.2 ETSI power supply profile.....	30
5.7 System block diagram .....	30
6 Baseband interfaces and parameters.....	31
6.0 Introduction .....	31
6.1 Ethernet interfaces.....	31
6.2 Plesiochronous interfaces .....	31
6.3 Synchronous digital hierarchy interfaces .....	31
6.4 Other baseband data interfaces .....	31
7 Main requirements.....	32
7.0 Introduction .....	32
7.1 General requirements .....	32
7.1.1 System identification .....	32
7.1.2 System nominal loading.....	32
7.1.3 Environmental profile .....	32
7.2 Transmitter characteristics.....	33
7.2.1 Transmitter power and power tolerance.....	33
7.2.1.1 Maximum power and EIRP.....	33
7.2.1.2 Combined TX power and EIRP limits .....	33

7.2.1.3	Output power tolerance .....	33
7.2.2	Transmitter power and frequency control.....	34
7.2.2.1	Transmitter power control (ATPC and RTPC) .....	34
7.2.2.1.1	Automatic Transmitter Power Control (ATPC).....	34
7.2.2.1.2	Remote Transmitter Power Control (RTPC) .....	34
7.2.2.2	Remote Frequency Control (RFC) .....	35
7.2.3	Radio Frequency (RF) spectrum mask.....	35
7.2.4	Discrete CW components exceeding the spectrum mask limit .....	35
7.2.4.1	Discrete CW components at the symbol rate .....	35
7.2.4.2	Other discrete CW components exceeding the spectrum mask limit .....	35
7.2.5	Unwanted emissions in the spurious domain - external.....	35
7.2.6	Dynamic change of modulation order.....	35
7.2.7	Radio frequency tolerance .....	35
7.2.8	Emission limitations outside the allocated band .....	35
7.3	Receiver characteristics .....	36
7.3.1	Unwanted emissions in the spurious domain - external.....	36
7.3.2	BER as a function of receiver signal level .....	36
7.3.3	Receiver selectivity .....	36
7.3.3.1	Introduction .....	36
7.3.3.2	Co-channel "external", first and second adjacent channel interference sensitivity .....	36
7.3.3.3	CW spurious interference (blocking and spurious response) .....	36
7.4	Antenna characteristics.....	36
8	Complementary requirements .....	37
8.0	Introduction .....	37
8.1	Branching/feeder requirements .....	37
8.1.1	Waveguide flanges (or other connectors) .....	37
8.1.2	Return loss of feeder/antenna systems at equipment antenna port (C/C' reference point) .....	38
8.2	Intermodulation products .....	38
8.3	Transmitter characteristics.....	39
8.3.1	Unwanted emissions - internal .....	39
8.3.2	Radio Frequency (RF) spectrum mask when mixed manufacturer compatibility is required .....	39
8.4	Receiver characteristics.....	40
8.4.1	Maximum input level and input level range .....	40
8.4.2	Unwanted emissions - internal .....	41
8.4.3	Image rejection .....	41
8.4.4	Innermost channel selectivity .....	42
8.5	System performance without diversity .....	42
8.5.1	Equipment Residual BER (RBER) .....	42
8.5.2	Distortion sensitivity.....	44
8.5.2.1	Introduction .....	44
8.5.2.2	Requirement .....	44
8.5.2.3	Assessment .....	45
8.5.3	Interference sensitivity for CCDP with XPIC operation .....	46
8.5.3.1	General .....	46
8.5.3.2	Co-channel "internal" interference sensitivity in flat fading conditions .....	46
8.6	System characteristics with diversity .....	46
8.6.0	Introduction.....	46
8.6.1	Differential delay compensation .....	46
8.6.2	BER performance .....	46
<b>Annex A (normative):</b>	<b>Spectrum masks and receiver selectivity when mixed manufacturer compatibility is required .....</b>	<b>47</b>
A.0	Introduction .....	47
A.1	TX masks assessment .....	48
A.2	Normal channels - Emission mask floor .....	48
A.2.1	RBER impact.....	48
A.2.2	Local TX to RX compatibility .....	48
A.2.2.1	Spectrum mask.....	48
A.2.2.2	Receiver selectivity .....	49

<b>A.3</b>	Innermost channels for channel arrangements from about 4 GHz to about 8,5 GHz with channel separation of 28 MHz to 30 MHz.....	49
A.3.0	Introduction .....	49
A.3.1	Innermost channels spectrum masks .....	49
A.3.2	Receiver innermost channel selectivity .....	51
<b>A.4</b>	Innermost channels for channel arrangements from about 4 GHz to 11 GHz with channel separation of 40 MHz .....	52
A.4.0	Introduction .....	52
A.4.1	Innermost channels spectrum masks .....	52
A.4.2	Receiver innermost channels selectivity.....	53
<b>A.5</b>	Innermost channels for 18 GHz channel arrangements with channel separation of 55 MHz .....	54
A.5.0	Introduction .....	54
A.5.1	Innermost channels spectrum masks .....	54
A.5.2	Receiver innermost channels selectivity.....	55
<b>Annex B (normative):</b>	<b>Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface.....</b>	<b>57</b>
<b>Annex C (informative):</b>	<b>Information on <i>Multi-channel</i> and <i>Channel-aggregation</i> differences and operation .....</b>	<b>58</b>
<b>Annex D (informative):</b>	<b>Additional information on relevant characteristics and operation .....</b>	<b>60</b>
D.1	Residual Bit Error Ratio (RBER) and Residual Frame Error Ratio (RFER) .....	60
D.2	Measurement test set for XPI characteristics .....	61
D.3	Differential delay compensation range.....	62
D.4	FER/BER equivalence and FER performance measurement equipment settings (example) .....	63
D.4.1	FER/BER equivalence.....	63
D.4.2	FER equipment settings and measurement techniques (example).....	64
D.5	Impact of power control (ATPC and/or RTPC), mixed-mode and bandwidth adaptive operation on spectrum mask and link design requirements.....	64
D.5.0	Introduction .....	64
D.5.1	ATPC and RTPC .....	64
D.5.1.1	ATPC .....	64
D.5.1.2	ATPC and RTPC implementation background.....	65
D.5.2	Mixed–mode and bandwidth adaptive operation impact.....	67
D.5.2.1	Mixed–mode basic concepts.....	67
D.5.2.2	Bandwidth adaptive .....	68
D.5.2.2.1	Basic concepts.....	68
D.5.2.2.2	Bandwidth (channel) occupancy .....	68
D.5.3	Impact on frequency co ordination.....	68
D.5.4	Impact of operating conditions on "essential" parameters in article 3.2 of Directive 2014/53/EU .....	68
D.6	Typical interference sensitivity behaviour for frequency planning purpose .....	69
<b>Annex E (informative):</b>	<b>Mechanical characteristics.....</b>	<b>70</b>
<b>Annex F (informative):</b>	<b>Mitigation techniques referred in ERC/DEC(00)07 (18 GHz band).....</b>	<b>71</b>
<b>Annex G (informative):</b>	<b>Change history .....</b>	<b>72</b>
History .....	73	

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).

The present document is part 1 of a multi-part deliverable covering the Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas, as identified below (see note):

**Part 1: "Overview, common characteristics and system-independent requirements";**

Part 2: "Digital systems operating in frequency bands from 1 GHz to 86 GHz; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU";

Part 4: "Antennas".

NOTE: In previous regulatory regime of harmonised standards under Directive 1999/5/EC more parts were published, which have been superseded since Directive 2014/53/EU [i.1] repealed Directive 1999/5/EC; they are:

Part 2-1: which technical content merged in the present document (Part 1);

Part 2-2: which technical content is merged in Part 2;

Part 3: which technical content is merged in Part 2 (with addition of a complete set of receiver parameters);

Part 4-1: which technical content is merged in Part 4;

Part 4-2: which technical content is merged in Part 4.

<b>National transposition dates</b>	
Date of adoption of this EN:	27 March 2017
Date of latest announcement of this EN (doa):	30 June 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2017
Date of withdrawal of any conflicting National Standard (dow):	31 December 2018

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document applies to Digital Fixed Radio Systems (DFRS) in point-to-point operation with integral and external antennas in the frequency range of 1 GHz to 86 GHz corresponding to the appropriate frequency bands 1,4 GHz to 86 GHz as described in ETSI EN 302 217-2 [18], annex B to annex J.

The present document summarizes:

- all characteristics, principles and, of utmost importance, terms and definitions that are common to all P-P equipment and antennas and its consultation is necessary when using all other parts of ETSI EN 302 217 series;
- all system-dependent requirements for Point-to-Point (P-P) equipment in applications deployed in bands where frequency co-ordination is generally applied. These requirements are introduced in two different clauses sub-sets:
  - **Main requirements** are requirements that are also related to the "essential requirements" under article 3.2 of Directive 2014/53/EU [i.1] and further detailed in the Harmonised Standard ETSI EN 302 217-2 [18].
  - **Complementary requirements** are requirements that are not related to essential requirements under article 3.2 of Directive 2014/53/EU [i.1]. Nevertheless they have been commonly agreed for proper system operation and deployment when specific deployment conditions or compatibility requirements are present. Compliance to all or some of these requirements is left to manufacturer decision.

Technical background for most of the parameters and requirements referred to in this multi-part deliverable may be found in ETSI TR 101 036-1 [i.16].

Health and safety requirements, relevant to article 3.1a of Directive 2014/53/EU [i.1] are not considered in any part of this ETSI EN 302 217 series. CENELEC is responsible for the relevant standards.

EMC conditions and requirements, relevant to article 3.1b of Directive 2014/53/EU [i.1] and any other essential requirement relevant to article 3.3 of Directive 2014/53/EU [i.1] are not in the scope of any part of this ETSI EN 302 217 series. EMC requirements may be found in ETSI EN 301 489-1 [i.11] and ETSI EN 301 489-4 [i.12].

NOTE: A list of such harmonised standards is available on the web site <http://www.newapproach.org>.

---

# 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CENELEC EN 122150: "Sectional Specification: Radio frequency coaxial connectors - Series EIA flange".
- [2] ERC/DEC(00)07: "ERC Decision of 19 October 2000 on the shared use of the band 17.7 - 19.7 GHz by the fixed service and Earth stations of the fixed-satellite service (space-to-Earth)".

- [3] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [4] ETSI EN 300 019-2-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction".
- [5] ETSI EN 300 019-1-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-1: Classification of environmental conditions; Storage".
- [6] ETSI EN 300 019-2-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-1: Specification of environmental tests; Storage".
- [7] ETSI EN 300 019-1-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-2: Classification of environmental conditions; Transportation".
- [8] ETSI EN 300 019-2-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-2: Specification of environmental tests; Transportation".
- [9] ETSI EN 300 019-1-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations".
- [10] ETSI EN 300 019-2-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-3: Specification of environmental tests; Stationary use at weather protected locations".
- [11] ETSI EN 300 019-1-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weather protected locations".
- [12] ETSI EN 300 019-2-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-4: Specification of environmental tests; Stationary use at non-weather protected locations".
- [13] ETSI EN 300 132-2: "Environmental Engineering (EE); Power supply interface at the input to telecommunications and datacom (ICT) equipment; Part 2: Operated by -48 V direct current (dc)".
- [14] ETSI EN 300 132-3: "Environmental Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 3: Operated by rectified current source, alternating current source or direct current source up to 400 V".
- [15] ETSI EN 301 126-1: "Fixed Radio Systems; Conformance testing; Part 1: Point-to-Point equipment - Definitions, general requirements and test procedures".
- [16] ETSI EN 302 099: "Environmental Engineering (EE); Powering of equipment in access network".
- [17] ETSI EN 301 126-3-1: "Fixed Radio Systems; Conformance testing; Part 3-1: Point-to-Point antennas; Definitions, general requirements and test procedures".
- [18] ETSI EN 302 217-2 (V3.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 2: Digital systems operating in frequency bands from 1 GHz to 86 GHz; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".
- [19] ETSI EN 302 217-4 (V2.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 4: Antennas".

- [20] IEC 60835-2-4: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 4: Transmitter/receiver including modulator/demodulator".
- [21] IEC 60835-2-8: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 8: Adaptive equalizer".
- [22] IEEE 802.3-2012<sup>TM</sup>: "IEEE Standard for Ethernet".
- [23] Recommendation ITU-R F.746: "Radio-frequency arrangements for fixed service systems".
- [24] Recommendation ITU-R F.1668: "Error performance objectives for real digital fixed wireless links used in 27 500 km hypothetical reference paths and connections".
- [25] Recommendation ITU-R F.1703: "Availability objectives for real digital fixed wireless links used in 27 500 km hypothetical reference paths and connections".
- [26] Recommendation ITU-R P.530: "Propagation data and prediction methods required for the design of terrestrial line-of-sight systems".
- [27] Recommendation ITU-T G.703: "Physical/electrical characteristics of hierarchical digital interfaces".
- [28] Recommendation ITU-T G.704: "Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44 736 kbit/s hierarchical levels".
- [29] Recommendation ITU-T G.707: "Network node interface for the synchronous digital hierarchy (SDH)".
- [30] Recommendation ITU-T G.708: "Sub STM-0 network node interface for the synchronous digital hierarchy (SDH)".
- [31] Recommendation ITU-T G.826: "End-to-end error performance parameters and objectives for international, constant bit-rate digital paths and connections".
- [32] Recommendation ITU-T G.828: "Error performance parameters and objectives for international, constant bit-rate synchronous digital paths".
- [33] Recommendation ITU-T G.829: "Error performance events for SDH multiplex and regenerator sections".
- [34] Recommendation ITU-T G.957: "Optical interfaces for equipment and systems relating to the synchronous digital hierarchy".
- [35] Recommendation ITU-T I.356: "B-ISDN ATM layer cell transfer performance".
- [36] Recommendation ITU-T I.357: "B-ISDN semi-permanent connection availability".
- [37] Recommendation ITU-T O.151: "Error performance measuring equipment operating at the primary rate and above".
- [38] Recommendation ITU-T O.181: "Equipment to assess error performance on STM-N interfaces".
- [39] Recommendation ITU-T O.191: "Equipment to measure the cell transfer performance of ATM connections".
- [40] Recommendation ITU-T V.11: "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [41] Recommendation ITU-T V.24: "List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)".
- [42] Recommendation ITU-T V.28: "Electrical characteristics for unbalanced double-current interchange circuits".

- [43] Recommendation ITU-T Y.1540: "Internet protocol data communication service - IP packet transfer and availability performance parameters".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
  - [i.2] ETSI TR 101 035: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH) aspects regarding Digital Radio Relay Systems (DRRS)".
  - [i.3] ETSI TR 102 243-1: "Fixed Radio Systems; Representative values for transmitter power and antenna gain to support inter- and intra-compatibility and sharing analysis; Part 1: Digital point-to-point systems".
  - [i.4] CEPT/ERC/REC 12-03: "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 17,7 GHz to 19,7 GHz".
  - [i.5] Void.
  - [i.6] CEPT/ECC/REC(02)06: "Channel arrangements for digital Fixed Service Systems operating in the frequency range 7 125-8 500 MHz".
  - [i.7] CEPT/ECC/REP 80: "Enhancing harmonisation and introducing flexibility in the spectrum regulatory framework".
  - [i.8] CEPT/ECC/REP 198: "Adaptive modulation and ATPC operations in fixed point-to-point systems - Guideline on coordination procedures".
  - [i.9] CEPT/ERC/REC 14-01: "Radio-frequency channel arrangements for high capacity analogue and digital radio-relay systems operating in the band 5 925 MHz - 6 425 MHz".
  - [i.10] CEPT/ERC/REC 14-02: "Radio-frequency channel arrangements for high, medium and low capacity digital fixed service systems operating in the band 6 425-7 125 MHz".
  - [i.11] ETSI EN 301 489-1: "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU and the essential requirements of article 6 of Directive 2014/30/EU".
  - [i.12] ETSI EN 301 489-4: "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 4: Specific conditions for fixed radio links and ancillary equipment; Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU".
  - [i.13] ETSI EN 302 217-1 (V2.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 1: Overview and system-independent common characteristics".
- NOTE: Previous superseded version of the present document not applicable in Directive 2014/53/EU [i.1] regime.
- [i.14] Void.
  - [i.15] ETSI EN 300 119 (all parts): "Environmental Engineering (EE); European telecommunication standard for equipment practice".

- [i.16] ETSI TR 101 036-1: "Fixed Radio Systems; Generic wordings for standards on DFRS (Digital Fixed Radio Systems) characteristics; Part 1: General aspects and point-to-point equipment parameters".
- [i.17] ETSI TR 101 506 (V2.1.1): "Fixed Radio Systems; Generic definitions, terminology and applicability of essential requirements covering article 3.2 of Directive 2014/53/EU to Fixed Radio Systems".
- [i.18] ETSI TR 101 854: "Fixed Radio Systems; Point-to-point equipment; Derivation of receiver interference parameters useful for planning fixed service point-to-point systems operating different equipment classes and/or capacities".
- [i.19] ETSI TR 103 103: "Fixed Radio Systems; Point-to-point systems; ATPC, RTPC, Adaptive Modulation (mixed-mode) and Bandwidth Adaptive functionalities; Technical background and impact on deployment, link design and coordination".
- [i.20] IEC 60153-2: "Hollow metallic waveguides. Part 2: Relevant specifications for ordinary rectangular waveguides".
- [i.21] IEC 60154-2: "Flanges for waveguides. Part 2: Relevant specifications for flanges for ordinary rectangular waveguides".
- [i.22] IEC 60169-1: "Radio-frequency connectors. Part 1: General requirements and measuring methods".
- [i.23] IEC 60339 (all parts): "General purpose rigid coaxial transmission lines and their associated flange connectors".
- [i.24] Recommendation ITU-R F.383-9: "Radio-frequency channel arrangements for high capacity fixed wireless systems operating in the lower 6 GHz (5 925 to 6 425 MHz) band".
- [i.25] Recommendation ITU-R F.384-11: "Radio -frequency channel arrangements for medium- and high-capacity digital fixed wireless systems operating in the 6 425-7 125 MHz band".
- [i.26] Recommendation ITU-R F.385-10: "Radio-frequency channel arrangements for fixed wireless systems operating in the 7 110-7 900 MHz band".
- [i.27] Recommendation ITU-R F.595-10: "Radio-frequency channel arrangements for fixed wireless systems operating in the 17.7-19.7 GHz frequency band".
- [i.28] Recommendation ITU-R F.750: "Architectures and functional aspects of radio-relay systems for synchronous digital hierarchy (SDH)-based network".
- [i.29] Void.
- [i.30] Recommendation ITU-R F.752: "Diversity techniques for point-to-point fixed wireless systems".
- [i.31] Recommendation ITU-R F.1093: "Effects of multipath propagation on the design and operation of line-of-sight digital fixed wireless systems".
- [i.32] Recommendation ITU-R F.1101: "Characteristics of digital fixed wireless systems below about 17 GHz".
- [i.33] Recommendation ITU-R F.1102: "Characteristics of fixed wireless systems operating in frequency bands above about 17 GHz".
- [i.34] Recommendation ITU-R F.1191: "Bandwidths and unwanted emissions of digital fixed service systems".
- [i.35] Void.
- [i.36] Recommendation ITU-T G.783: "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks".
- [i.37] Recommendation ITU-T G.784: "Management aspects of the synchronous digital hierarchy (SDH) transport network element".

- [i.38] Recommendation ITU-T I.414: "Overview of Recommendations on layer 1 for ISDN and B-ISDN customer accesses".
- [i.39] The Radio Regulations, Edition of 2016.
- [i.40] J. Redd: "Calculating Statistical Confidence Levels for Error-Probability Estimates" Lightwave Magazine, pp. 110-114, April 2000 (see note).

NOTE: Available on the web at <http://www.lightwaveonline.com/>.

---

koniec náhľadu – text ďalej pokračuje v platenej verzii STN