

<b>STN</b>	<b>Režim 2 digitálneho spoja VHF (VDL) vzduch-zem Technické charakteristiky a meracie metódy na pozemné zariadenia Časť 2: Horné vrstvy</b>	<b>STN EN 301 841-2 V1.2.1</b>
		87 1841

VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment; Part 2:  
Upper layers

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 12/19

Obsahuje: EN 301 841-2 V1.2.1:2019

**129668**

# ETSI EN 301 841-2 V1.2.1 (2019-05)



**VHF air-ground Digital Link (VDL) Mode 2;  
Technical characteristics and  
methods of measurement  
for ground-based equipment;  
Part 2: Upper layers**

---

Reference

REN/ERM-TGAERO-56

---

Keywords

aeronautical, radio, testing

***ETSI***


---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and  
of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	11
Foreword.....	11
Modal verbs terminology.....	11
Introduction .....	12
1    Scope .....	13
2    References .....	13
2.1    Normative references .....	13
2.2    Informative references.....	14
3    Definition of terms, symbols and abbreviations.....	14
3.1    Terms.....	14
3.1.1    Basic reference model terms .....	14
3.1.2    Service conventions terms .....	15
3.1.3    General terms.....	15
3.2    Symbols.....	15
3.3    Abbreviations .....	15
4    General architecture of VDL Mode 2.....	17
5    Link layer protocols and services functional specifications.....	18
5.0    Overview .....	18
5.1    MAC sublayer specifications .....	19
5.1.0    MAC General Requirements.....	19
5.1.1    MAC services .....	19
5.1.1.1    Multiple access.....	19
5.1.1.2    Channel congestion .....	19
5.1.2    MAC service system parameters .....	20
5.1.2.0    General Requirements .....	20
5.1.2.1    Timer TM1 (inter-access delay timer).....	20
5.1.2.2    Timer TM2 (channel busy timer) .....	20
5.1.2.3    Parameter p (persistence) .....	20
5.1.2.4    Counter M1 (maximum number of access attempts) .....	20
5.1.3    Description of procedures .....	20
5.1.3.1    Channel sensing .....	20
5.1.3.2    P-persistent CSMA access times.....	20
5.1.3.3    Inter-access interval .....	21
5.1.3.4    Channel access procedure .....	21
5.1.3.4.1    Purpose .....	21
5.1.3.4.2    Use.....	21
5.1.3.4.3    Procedure.....	21
5.1.3.5    AVLC frame reception.....	21
5.1.3.5.1    Purpose .....	21
5.1.3.5.2    Use.....	21
5.1.3.5.3    Procedure.....	21
5.2    Data link layer service protocol specifications.....	22
5.2.1    Interface with MAC sub layer.....	22
5.2.1.0    General considerations .....	22
5.2.1.1    Sequence of primitives .....	22
5.2.2    Data Link State Machines.....	23
5.2.2.0    Introduction.....	23
5.2.2.1    LME state machine .....	24
5.2.2.2    DLE top state machine .....	25
5.2.2.3    DLE data transfer state diagram.....	25
5.2.2.4    DLE selective reject state machines .....	26
5.2.2.4.1    SRM mode Sending SREJ.....	26
5.2.2.4.2    SRM mode Receiving SREJ.....	27

5.2.2.4.3	FRM mode.....	28
5.2.2.5	DLE termination state machine.....	28
5.2.3	Services.....	29
5.2.3.1	Received frame sequencing procedure.....	29
5.2.3.1.0	General requirements.....	29
5.2.3.1.1	Purpose .....	29
5.2.3.1.2	Use.....	29
5.2.3.1.3	Procedure.....	29
5.2.3.2	Error detection procedure.....	29
5.2.3.2.1	Purpose .....	29
5.2.3.2.2	Use.....	29
5.2.3.2.3	Procedure.....	30
5.2.3.3	Station identification.....	30
5.2.3.4	Broadcast addressing.....	30
5.2.3.5	Data transfer.....	30
5.2.4	Frame format .....	30
5.2.4.0	General.....	30
5.2.4.1	Address structure.....	30
5.2.4.2	Address fields.....	31
5.2.4.2.0	General requirements.....	31
5.2.4.2.1	Air-ground status bit.....	31
5.2.4.2.2	Command/response status bit .....	31
5.2.4.2.3	Data link service addresses.....	31
5.2.4.2.4	Address type .....	31
5.2.4.2.5	Aircraft specific addresses.....	31
5.2.4.2.6	ICAO-administered ground station specific addresses .....	31
5.2.4.2.7	ICAO-delegated ground station specific addresses .....	32
5.2.4.3	Broadcast address.....	32
5.2.4.3.0	General Requirements .....	32
5.2.4.3.1	Encoding.....	32
5.2.4.4	Link control field .....	32
5.2.4.5	Information field .....	32
5.2.5	Transmit queues management.....	33
5.2.6	Data link service system parameters.....	33
5.2.6.0	General requirements .....	33
5.2.6.1	Parameter T1 (delay before non acknowledged retransmission).....	34
5.2.6.2	Parameter T2 (delay before acknowledgment).....	34
5.2.6.3	Parameter T3 (link initialization time) .....	34
5.2.6.4	Parameter T4 (maximum delay between transmissions).....	34
5.2.6.4.0	General requirements.....	34
5.2.6.4.1	Recommendation.....	34
5.2.6.5	Parameter N1 (maximum number of bits of any frame) .....	35
5.2.6.6	Counter N2 (maximum number of transmissions) .....	35
5.2.6.7	Parameter k (window size).....	35
5.2.6.8	Parameter G (Maximum number of frames in a burst) .....	35
5.2.7	DLE retransmission timers .....	35
5.2.8	Description of procedures.....	35
5.2.8.0	General Requirements .....	35
5.2.8.1	Procedure retransmission schedule .....	35
5.2.8.1.1	Purpose .....	35
5.2.8.1.2	Use.....	35
5.2.8.1.3	Procedure .....	36
5.2.8.2	Procedure frame retransmission .....	36
5.2.8.2.1	Purpose .....	36
5.2.8.2.2	Use.....	36
5.2.8.2.3	Procedure .....	36
5.2.8.3	Procedure XID frame retransmission .....	36
5.2.8.3.1	Purpose .....	36
5.2.8.3.2	Use.....	36
5.2.8.3.3	Procedure .....	36
5.2.8.4	Procedure link monitoring.....	36
5.2.8.4.1	Purpose .....	36

5.2.8.4.2	Use.....	36
5.2.8.4.3	Procedure.....	37
5.2.8.5	Procedure link recovery .....	37
5.2.8.5.1	Purpose .....	37
5.2.8.5.2	Use.....	37
5.2.8.5.3	Procedure.....	37
5.2.9	Modes of operation to be supported.....	37
5.2.9.1	Operational mode.....	37
5.2.9.2	Non-operational mode.....	37
5.2.9.2.0	General .....	37
5.2.9.2.1	DISC frame.....	37
5.2.9.2.2	DM frame .....	37
5.2.9.3	Frame reject mode.....	38
5.2.9.4	Sent selective reject mode.....	38
5.2.10	Use of the P/F bit .....	38
5.2.10.1	General.....	38
5.2.10.2	INFO frames .....	38
5.2.10.3	Recommendation .....	38
5.2.10.4	Unnumbered frames.....	38
5.2.11	Unnumbered command frame collisions .....	38
5.2.11.0	General Requirements.....	38
5.2.11.1	DLE procedures .....	38
5.2.11.2	LME procedures.....	39
5.2.12	XID frame.....	39
5.2.13	Broadcast .....	39
5.2.14	Information transfer .....	39
5.2.14.1	General Requirements and Recommendation .....	39
5.2.14.1.0	Procedures for information transfer.....	39
5.2.14.1.1	Eliminate redundant frames.....	39
5.2.14.1.2	Recommendation.....	39
5.2.14.1.3	Recommendation.....	39
5.2.14.1.4	Recommendation.....	39
5.2.14.1.5	Procedures for transmission.....	39
5.2.14.1.6	Recommendation.....	39
5.2.14.1.7	Recommendation.....	40
5.2.14.1.8	Recommendation.....	40
5.2.14.2	SREJ frame .....	40
5.2.14.3	FRMR frame .....	40
5.2.14.4	UA frame .....	40
5.2.14.5	UI frame .....	40
5.2.14.6	TEST frame.....	40
5.3	VDL management entity .....	41
5.3.1	Services.....	41
5.3.1.1	Link provision .....	41
5.3.1.2	Link change notifications .....	41
5.3.2	Exchange identity (XID) parameter.....	41
5.3.2.0	Overview.....	41
5.3.2.1	Encoding .....	41
5.3.2.2	Public parameters .....	41
5.3.2.2.0	General requirements.....	41
5.3.2.2.1	HDLC public parameter set identifier .....	42
5.3.2.2.2	Timer T1 parameter .....	42
5.3.2.3	VDL private parameters .....	42
5.3.2.4	General purpose information private parameters .....	43
5.3.2.4.0	General requirements.....	43
5.3.2.4.1	VDL private parameter set identifier .....	43
5.3.2.4.2	Connection management parameter .....	43
5.3.2.4.3	Signal Quality Parameter (SQP).....	44
5.3.2.4.4	XID sequencing parameter .....	44
5.3.2.4.5	AVLC specific options parameter .....	45
5.3.2.4.6	Expedited subnetwork connection parameter .....	45
5.3.2.4.7	LCR cause parameter .....	45

5.3.2.5	Aircraft-initiated information private parameters .....	47
5.3.2.5.0	General requirements.....	47
5.3.2.5.1	Modulation support parameter.....	47
5.3.2.5.2	Acceptable alternate ground station parameter.....	47
5.3.2.5.3	Destination airport parameter .....	48
5.3.2.5.4	Aircraft location parameter.....	48
5.3.2.6	Ground-based initiated modification private parameters .....	48
5.3.2.6.0	General requirements.....	48
5.3.2.6.1	Autotune frequency parameter .....	48
5.3.2.6.2	Replacement ground station list .....	49
5.3.2.6.3	Timer T4 parameter .....	49
5.3.2.6.4	MAC persistence parameter .....	49
5.3.2.6.5	Counter M1 parameter.....	50
5.3.2.6.6	Timer TM2 parameter .....	50
5.3.2.6.7	Timer TG5 parameter .....	50
5.3.2.6.8	T3min parameter .....	50
5.3.2.6.9	Ground station address filter parameter.....	50
5.3.2.6.10	Broadcast connection parameter.....	51
5.3.2.7	Ground-based initiated information private parameters .....	52
5.3.2.7.0	General requirements.....	52
5.3.2.7.1	Frequency support list .....	52
5.3.2.7.2	Airport coverage indication parameter .....	52
5.3.2.7.3	Nearest airport parameter .....	52
5.3.2.7.4	ATN router NETs parameter .....	53
5.3.2.7.5	Ground-based system mask parameter .....	53
5.3.2.7.6	Timer TG3 parameter .....	53
5.3.2.7.7	Timer TG4 parameter .....	54
5.3.2.7.8	Ground station location parameter.....	54
5.3.3	VME service system parameters.....	54
5.3.4	VME procedures .....	54
5.3.4.1	Minimum frequency dwell time procedure .....	54
5.3.4.1.1	Purpose .....	54
5.3.4.1.2	Use.....	55
5.3.4.1.3	Procedure .....	55
5.3.4.1.4	Recommendation.....	55
5.3.4.2	Maximum idle activity time procedure .....	55
5.3.4.2.1	Purpose .....	55
5.3.4.2.2	Use.....	55
5.3.4.2.3	Procedure .....	55
5.3.4.3	Maximum time between transmissions procedure .....	55
5.3.4.3.1	Purpose .....	55
5.3.4.3.2	Use.....	55
5.3.4.3.3	Procedure .....	55
5.3.4.4	Maximum time between GSIFs.....	56
5.3.4.4.1	Purpose .....	56
5.3.4.4.2	Use.....	56
5.3.4.4.3	Procedure .....	56
5.3.4.5	Maximum link overlap time procedure .....	56
5.3.4.5.1	Purpose .....	56
5.3.4.5.2	Use.....	56
5.3.4.5.3	Procedure .....	56
5.3.5	Description of LME procedures.....	56
5.3.5.0	General requirements .....	56
5.3.5.1	Frequency management procedures .....	60
5.3.5.1.0	General .....	60
5.3.5.1.1	Frequency search .....	60
5.3.5.1.2	Frequency recovery .....	60
5.3.5.2	Link connectivity procedures .....	61
5.3.5.3	Ground station identification.....	61
5.3.5.3.0	General .....	61
5.3.5.3.1	Single-DSP ID ground station .....	61
5.3.5.3.2	Multi-DSP ID ground station .....	61

5.3.5.3.3	GSIF details .....	61
5.3.5.4	Link establishment .....	61
5.3.5.4.0	General requirements.....	61
5.3.5.4.1	Aircraft initiation .....	62
5.3.5.4.2	General ground response .....	62
5.3.5.4.3	Exceptional cases.....	62
5.3.5.5	Link parameter modification.....	62
5.3.5.5.1	Ground-based initiation .....	62
5.3.5.5.2	General aircraft response .....	62
5.3.5.5.3	Recommendation.....	62
5.3.5.6	Aircraft-initiated handoff .....	62
5.3.5.6.0	General requirements.....	62
5.3.5.6.1	Aircraft handoff.....	63
5.3.5.6.2	Site selection preference.....	63
5.3.5.6.3	Recommendation.....	63
5.3.5.6.4	Interaction of LMEs .....	63
5.3.5.6.5	General ground response .....	63
5.3.5.6.6	Disconnecting old link.....	63
5.3.5.6.7	Exceptional cases.....	63
5.3.5.7	Aircraft-requested ground-initiated handoff .....	64
5.3.5.7.0	Applicability .....	64
5.3.5.7.1	Aircraft action.....	64
5.3.5.7.2	General ground response .....	64
5.3.5.7.3	Exceptional cases.....	64
5.3.5.8	Ground-based initiated handoff.....	64
5.3.5.8.0	General Requirements .....	64
5.3.5.8.1	Ground action.....	64
5.3.5.8.2	General aircraft response .....	65
5.3.5.8.3	Disconnecting old link.....	65
5.3.5.8.4	Exceptional cases.....	65
5.3.5.8.5	Recommendation.....	65
5.3.5.9	Ground-based requested aircraft-initiated handoff.....	65
5.3.5.9.0	Applicability .....	65
5.3.5.9.1	Ground action .....	65
5.3.5.9.2	General aircraft response .....	65
5.3.5.9.3	Exceptional cases.....	65
5.3.5.9.4	Recommendation.....	65
5.3.5.10	Ground-based requested broadcast handoff .....	66
5.3.5.10.0	General .....	66
5.3.5.10.1	Ground action .....	66
5.3.5.10.2	Aircraft response .....	66
5.3.5.10.3	Exceptional cases.....	66
5.3.5.11	Ground-based commanded autotune .....	67
5.3.5.11.1	Ground action .....	67
5.3.5.11.2	General aircraft response .....	67
5.3.5.11.3	Exceptional cases.....	67
5.3.5.12	Expedited subnetwork connection management .....	67
5.3.5.12.0	Applicability and general requirements .....	67
5.3.5.12.1	Initiating station of subnetwork connection management .....	67
5.3.5.12.2	General responder action .....	67
5.3.5.12.3	Exceptional cases.....	67
6	Subnetwork layer protocols and services functional specifications .....	68
6.1	Architecture .....	68
6.1.0	General.....	68
6.1.1	Access points .....	68
6.2	Services .....	68
6.2.0	General.....	68
6.2.1	Subnetwork connection management .....	68
6.2.2	Packet fragmentation and reassembly .....	68
6.2.3	Error recovery .....	68
6.2.3.0	General requirements .....	68

6.2.3.1	Recommendation .....	68
6.2.4	Connection flow control .....	69
6.2.4.0	General requirements .....	69
6.2.4.1	Recommendation .....	69
6.3	Packet format.....	69
6.3.0	General requirements.....	69
6.3.1	General format identifier .....	69
6.3.2	Calling and called DTE addresses .....	69
6.3.2.0	General requirements .....	69
6.3.2.1	Encoding .....	69
6.3.2.1.0	General .....	69
6.3.2.1.1	Address field.....	69
6.3.2.2	Aircraft DTE address .....	69
6.3.2.3	Ground DTE address.....	70
6.3.2.4	Ground network DTE addresses .....	70
6.3.3	Call user data field .....	70
6.3.4	Packet types .....	70
6.4	Subnetwork layer service system parameters .....	70
6.4.0	General requirements.....	70
6.4.1	Packet size .....	71
6.4.2	Parameter W (transmit window size).....	71
6.4.3	Parameter A (acknowledgment window size) .....	71
6.5	Effects of layers 1 and 2 on the subnetwork layer.....	71
6.6	Description of procedures .....	71
6.6.0	General requirements.....	71
6.6.1	Supported facilities .....	71
6.6.2	Unsupported facilities .....	71
6.6.3	Subnetwork establishment and connection management.....	72
6.6.3.0	General requirements .....	72
6.6.3.1	Subnetwork entity initialization .....	72
6.6.3.2	Subnetwork connection establishment .....	72
6.6.3.2.0	General .....	72
6.6.3.2.1	Explicit subnetwork connection establishment.....	73
6.6.3.2.2	Expedited subnetwork connection establishment .....	73
6.6.3.3	Subnetwork connection maintenance .....	73
6.6.3.3.0	General requirements.....	73
6.6.3.3.1	Explicit subnetwork connection maintenance .....	73
6.6.3.3.2	Expedited subnetwork connection maintenance .....	73
6.6.3.3.3	Broadcast subnetwork connection maintenance .....	74
6.6.4	Error handling.....	74
6.6.5	Acknowledgements.....	74
7	The VDL mobile SubNetwork Dependent Convergence Function (SNDCF) .....	74
7.1	Introduction .....	74
7.2	New function .....	74
7.3	Call user data encoding .....	74
7.3.0	General requirements .....	74
7.3.1	ISH PDU .....	74
7.3.2	Maintained/initialized status bit.....	75
7.3.3	Call request .....	75
7.3.4	Call confirmation .....	75
8	Link layer test cases .....	75
8.1	MAC sublayer test cases .....	75
8.1.1	Test of listen before talk MAC .....	75
8.1.1.1	Purpose.....	75
8.1.1.2	Test architecture .....	75
8.1.1.3	Test scenario .....	75
8.1.2	Test of minimal MAC performance.....	75
8.1.2.1	Purpose.....	75
8.1.2.2	Test architecture .....	75
8.1.2.3	Test scenarios .....	76

8.1.3	Test of p-persistent MAC performance on idle channel .....	76
8.1.3.1	Purpose.....	76
8.1.3.2	Test architecture.....	76
8.1.3.3	Test scenarios.....	76
8.1.4	Test of p-persistent MAC performance on busy channel.....	78
8.1.4.1	Purpose.....	78
8.1.4.2	Test architecture.....	78
8.1.4.3	Test scenarios.....	78
8.2	Data link sublayer test cases.....	80
8.2.1	Test of maximum time between GSIF transmissions .....	80
8.2.1.1	Test of maximum time between GSIF transmissions - single-DSP ID ground station .....	80
8.2.1.1.1	Purpose .....	80
8.2.1.1.2	Test architecture .....	80
8.2.1.1.3	Test scenario.....	80
8.2.1.2	Test of maximum time between GSIF transmissions - Multi-DSP ID ground station .....	80
8.2.1.2.1	Purpose .....	80
8.2.1.2.2	Test architecture .....	80
8.2.1.2.3	Test scenario.....	80
8.2.2	Test of link establishment.....	81
8.2.2.1	Purpose.....	81
8.2.2.2	Test architecture.....	81
8.2.2.3	Test scenario .....	81
8.2.3	Test of IUT link parameters recovery.....	81
8.2.3.1	Purpose.....	81
8.2.3.2	Test architecture.....	81
8.2.4	Test of received AVLC frame format.....	82
8.2.4.1	Purpose.....	82
8.2.4.2	Test architecture .....	82
8.2.4.3	Test scenario .....	82
8.2.5	Test of transmitted AVLC frames format.....	82
8.2.5.1	Purpose.....	82
8.2.5.2	Test architecture .....	82
8.2.5.3	Test scenario .....	82
8.2.6	Test of retransmission procedure of unacknowledged frames other than XID .....	82
8.2.6.1	Purpose.....	82
8.2.6.2	Test architecture .....	82
8.2.6.3	Test scenario .....	83
8.2.7	Test of maximum window size .....	94
8.2.7.1	Purpose.....	94
8.2.7.2	Test architecture .....	94
8.2.7.3	Test scenario .....	94
8.2.8	Test of window size .....	94
8.2.8.1	Purpose.....	94
8.2.8.2	Test architecture .....	95
8.2.8.3	Test scenario .....	95
8.2.9	Test of maximum acknowledgement delay .....	95
8.2.9.1	Purpose.....	95
8.2.9.2	Test architecture .....	95
8.2.9.3	Test scenario .....	95
8.2.10	Test of acknowledgement delay.....	95
8.2.10.1	Purpose.....	95
8.2.10.2	Test architecture .....	95
8.2.10.3	Test scenario .....	95
8.2.11	Test of retransmission procedure of unacknowledged XID .....	95
8.2.11.1	Purpose.....	95
8.2.11.2	Test architecture .....	95
8.2.11.3	Test scenario .....	96
8.2.12	Test of minimal link monitoring .....	101
8.2.12.1	Purpose.....	101
8.2.12.2	Test architecture .....	101
8.2.12.3	Test scenario .....	101
8.2.13	Test of link monitoring .....	101

8.2.13.1	Purpose.....	101
8.2.13.2	Test architecture .....	102
8.2.13.3	Test scenario .....	102
8.2.14	Test of illegal reception .....	102
8.2.14.1	Purpose.....	102
8.2.14.2	Test architecture .....	102
8.2.14.3	Test scenario .....	102
8.2.15	Test of time between GSIF transmissions.....	102
8.2.15.1	Test of time between GSIF transmissions - single DSP ID ground station.....	102
8.2.15.1.1	Purpose .....	102
8.2.15.1.2	Test architecture .....	102
8.2.15.1.3	Test scenario .....	102
8.2.15.2	Test of time between GSIF transmissions - multi-DSP ID ground station.....	103
8.2.15.2.1	Purpose .....	103
8.2.15.2.2	Test architecture .....	103
8.2.15.2.3	Test scenario.....	103
8.2.16	Test of maximal link overlap .....	104
8.2.16.1	Purpose.....	104
8.2.16.2	Test architecture .....	104
8.2.16.3	Test scenario .....	104
8.2.17	Test of link hand-off .....	104
8.2.17.1	Purpose.....	104
8.2.17.2	Test architecture .....	104
8.2.17.3	Test scenario .....	105
8.2.18	Frame collision with tester precedence test .....	105
8.2.18.1	Purpose.....	105
8.2.18.2	Test architecture .....	105
8.2.18.3	Test scenario .....	105
8.2.19	Frame collision with IUT precedence test .....	105
8.2.19.1	Purpose.....	105
8.2.19.2	Test architecture .....	105
8.2.19.3	Test scenario .....	105
8.2.20	Selective acknowledgement test .....	105
8.2.20.1	Purpose.....	105
8.2.20.2	Test architecture .....	105
8.2.20.3	Test scenario .....	106
8.3	Test summary .....	106
8.4	PCO summary .....	106
<b>Annex A (informative):</b>	<b>Bibliography .....</b>	<b>108</b>
History .....		109

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

# Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 2 of a multi-part deliverable covering VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

Part 1: "Physical layer and MAC sub-layer";

**Part 2: "Upper layers";**

Part 3: "Harmonised Standard for access to radio spectrum".

<b>National transposition dates</b>	
Date of adoption of this EN:	9 May 2019
Date of latest announcement of this EN (doa):	31 August 2019
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	29 February 2020
Date of withdrawal of any conflicting National Standard (dow):	29 February 2020

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The VDL Mode 2 system provides data communication exchanges between aircraft and ground-based systems.

The VDL Mode 2 system is designed to be a Ground/Air sub-system of the Aeronautical Telecommunication Network (ATN) using the AM(R)S band and it is organized according to the Open Systems Interconnection (OSI) model (defined by ISO). It will provide reliable subnetwork services to the ATN system.

The present document together with ETSI EN 301 841-1 [i.3] state the technical specifications for ground-based equipment implementing Very High Frequency (VHF) Digital Link (VDL) Mode 2 air interface, operating in the VHF band (117,975 MHz to 137,000 MHz) with 25 kHz channel spacing.

The present document may be used to produce tests for the assessment of the performance of the equipment.

---

# 1 Scope

The present document covers the link and sub-network access layers of Very High Frequency (VHF) Digital Link. The present document applies to VDL Mode 2 ground-based stations operating in the VHF band (117,975 MHz to 137,000 MHz) with 25 kHz channel spacing and using Differential Eight Phase Shift Keying (D8PSK).

The present document provides functional specifications for ground-based radio transmitters, receivers, and transceivers intended to be used for ground-air data communications. The present document is derived from the following documents:

- VDL Mode 2 SARPs. ICAO, annex 10 Volume III part I [1] second edition, July 2007;
  - ICAO Doc 9776: "Manual on VHF Digital Link (VDL) Mode 2" [10].
- 

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ICAO Annex 10 to the Convention on International Civil Aviation, International Civil Aviation Organization.
- [2] Void.
- [3] Void.
- [4] Void.
- [5] ISO/IEC 8208:2000: "Information technology - Data communications - X.25 Packet Layer Protocol for Data Terminal Equipment".
- [6] Void.
- [7] ISO/IEC 13239:2002: "Information technology - Telecommunications and information exchange between systems - High-level data link control (HDLC) procedures".
- [8] Void.
- [9] Recommendation ITU-T X.25: "Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit".
- [10] ICAO Doc 9776: "Manual on VHF Digital Link (VDL) Mode 2" 2<sup>nd</sup> Edition (2015).
- [11] ICAO Doc 9880: "Manual on Detailed Technical Specifications for the Aeronautical Telecommunication Network (ATN) using ISO/OSI Standards and Protocols".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ELSA (Enhanced Large Scale ATN deployment) Deliverable D11: "VDL Mode 2 Measurement, Analysis and Simulation Campaign - Final Report".
- [i.2] Void.
- [i.3] ETSI EN 301 841-1: "VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment; Part 1: Physical layer and MAC sub-layer".
- [i.4] ISO/IEC 7498-1:1994: "Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model".
- [i.5] ISO/IEC 10731:1994: "Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services".
- [i.6] ISO/IEC 15802-1:1995: "Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Common specifications - Part 1: Medium Access Control (MAC) service definition".
- [i.7] ISO/IEC 646:1991: "Information technology -- ISO 7-bit coded character set for information interchange".

koniec náhľadu – text d'alej pokračuje v platenej verzii STN