

STN	Bunkové siete IMT Harmonizovaná norma pre prístup k rádiovému spektru Časť 13: Používateľské zariadenia (UE) zdokonaleného univerzálneho pozemského rádiového prístupu (E-UTRA)	STN EN 301 908-13 V13.1.1 87 1908
------------	--	---

IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 06/20

Obsahuje: EN 301 908-13 V13.1.1:2019

130723

ETSI EN 301 908-13 V13.1.1 (2019-11)



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA)
User Equipment (UE)**

Reference

REN/MSG-TFES-13-13

Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT, LTE,
LTE-Advanced, mobile, radio, regulation, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	11
Introduction	12
1 Scope	13
2 References	16
2.1 Normative references	16
2.2 Informative references.....	17
3 Definition of terms, symbols and abbreviations.....	17
3.1 Terms.....	17
3.2 Symbols.....	21
3.3 Abbreviations	23
4 Technical requirements specifications	24
4.1 Environmental profile.....	24
4.2 Conformance requirements	24
4.2.0 General.....	24
4.2.1 Introduction.....	24
4.2.2 Transmitter Maximum Output Power	25
4.2.2.1 Transmitter maximum output power for Single Carrier.....	25
4.2.2.1.1 Definition.....	25
4.2.2.1.2 Limits	26
4.2.2.1.3 Conformance	26
4.2.2.2 Transmitter output power for Carrier Aggregation (DL CA and UL CA)	26
4.2.2.2.1 Definition.....	26
4.2.2.2.2 Limits	27
4.2.2.2.3 Conformance	28
4.2.2.3 Transmitter output power for UL-MIMO	28
4.2.2.3.1 Definition.....	28
4.2.2.3.2 Limits	28
4.2.2.3.3 Conformance	28
4.2.2.4 Transmitter output power for category NB1	29
4.2.2.4.1 Definition.....	29
4.2.2.4.2 Limits	29
4.2.2.4.3 Conformance	29
4.2.2.5 Transmitter output power for UE category M1.....	29
4.2.2.5.1 Definition.....	29
4.2.2.5.2 Limits	29
4.2.2.5.3 Conformance	30
4.2.3 Transmitter Spectrum Emission Mask.....	30
4.2.3.1 Transmitter spectrum emission mask for Single Carrier.....	30
4.2.3.1.1 Definition.....	30
4.2.3.1.2 Limits	30
4.2.3.1.3 Conformance	31
4.2.3.2 Transmitter spectrum emission mask for Carrier Aggregation (DL CA and UL CA)	31
4.2.3.2.1 Definition.....	31
4.2.3.2.2 Limits	31
4.2.3.2.3 Conformance	33
4.2.3.3 Transmitter spectrum emission mask for UL-MIMO	33
4.2.3.3.1 Definition.....	33
4.2.3.3.2 Limits	33
4.2.3.3.3 Conformance	33
4.2.3.4 Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier	33
4.2.3.4.1 Definition.....	33
4.2.3.4.2 Limits	33

4.2.3.4.3	Conformance	33
4.2.3.5	Transmitter spectrum emission mask for category NB1	33
4.2.3.5.1	Definition.....	33
4.2.3.5.2	Limits	33
4.2.3.5.3	Conformance	34
4.2.4	Transmitter Spurious Emissions	34
4.2.4.1	Transmitter spurious emissions for Single Carrier	34
4.2.4.1.1	Definition.....	34
4.2.4.1.2	Limits	34
4.2.4.1.3	Conformance	38
4.2.4.2	Transmitter spurious emissions for Carrier Aggregation (DL CA and UL CA)	38
4.2.4.2.1	Definition.....	38
4.2.4.2.2	Limits	38
4.2.4.2.3	Conformance	44
4.2.4.3	Transmitter spurious emissions for UL-MIMO	44
4.2.4.3.1	Definition.....	44
4.2.4.3.2	Limits	44
4.2.4.3.3	Conformance	44
4.2.4.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier	44
4.2.4.4.1	Definition.....	44
4.2.4.4.2	Limits	44
4.2.4.4.3	Conformance	45
4.2.4.5	Transmitter spurious emissions for category NB1	45
4.2.4.5.1	Definition.....	45
4.2.4.5.2	Limits	45
4.2.4.5.3	Conformance	45
4.2.5	Transmitter Minimum Output Power.....	45
4.2.5.1	Transmitter minimum output power for Single Carrier.....	45
4.2.5.1.1	Definition.....	45
4.2.5.1.2	Limits	45
4.2.5.1.3	Conformance	45
4.2.5.2	Transmitter minimum output power for Carrier Aggregation (DL CA and UL CA)	46
4.2.5.2.1	Definition.....	46
4.2.5.2.2	Limits	46
4.2.5.2.3	Conformance	46
4.2.5.3	Transmitter minimum output power for UL-MIMO	46
4.2.5.3.1	Definition.....	46
4.2.5.3.2	Limits	46
4.2.5.3.3	Conformance	47
4.2.5.4	Transmitter minimum output power for category NB1.....	47
4.2.5.4.1	Definition.....	47
4.2.5.4.2	Limits	47
4.2.5.4.3	Conformance	47
4.2.6	Receiver Adjacent Channel Selectivity (ACS)	47
4.2.6.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier	47
4.2.6.1.1	Definition.....	47
4.2.6.1.2	Limits	47
4.2.6.1.3	Conformance	48
4.2.6.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands	48
4.2.6.2.1	Definition.....	48
4.2.6.2.2	Limits	49
4.2.6.2.3	Conformance	49
4.2.6.3	Receiver Adjacent Channel Selectivity (ACS) for category NB1.....	50
4.2.6.3.1	Definition.....	50
4.2.6.3.2	Limits	50
4.2.6.3.3	Conformance	50
4.2.7	Receiver Blocking Characteristics	50
4.2.7.1	Receiver Blocking Characteristics for Single Carrier	50
4.2.7.1.1	Definition.....	50
4.2.7.1.2	Limits	50
4.2.7.1.3	Conformance	52
4.2.7.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands.....	52

4.2.7.2.1	Definition.....	52
4.2.7.2.2	Limits	53
4.2.7.2.3	Conformance	55
4.2.7.3	Receiver Blocking Characteristics for category NB1	56
4.2.7.3.1	Definition.....	56
4.2.7.3.2	Limits	56
4.2.7.3.3	Conformance	57
4.2.8	Receiver Spurious Response.....	57
4.2.8.1	Receiver Spurious Response for Single Carrier	57
4.2.8.1.1	Definition.....	57
4.2.8.1.2	Limits	57
4.2.8.1.3	Conformance	58
4.2.8.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands	58
4.2.8.2.1	Definition.....	58
4.2.8.2.2	Limits	58
4.2.8.2.3	Conformance	58
4.2.8.3	Receiver Spurious Response for category NB1	58
4.2.8.3.1	Definition.....	58
4.2.8.3.2	Limits	58
4.2.8.3.3	Conformance	59
4.2.9	Receiver Intermodulation Characteristic	59
4.2.9.1	Receiver Intermodulation Characteristics for Single Carrier	59
4.2.9.1.1	Definition.....	59
4.2.9.1.2	Limits	59
4.2.9.1.3	Conformance	59
4.2.9.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	60
4.2.9.2.1	Definition.....	60
4.2.9.2.2	Limits	60
4.2.9.2.3	Conformance	60
4.2.9.3	Receiver Intermodulation Characteristics for category NB1	60
4.2.9.3.1	Definition.....	60
4.2.9.3.2	Limits	61
4.2.9.3.3	Conformance	61
4.2.10	Receiver Spurious Emissions.....	61
4.2.10.1	Receiver Spurious Emissions for Single Carrier	61
4.2.10.1.1	Definition.....	61
4.2.10.1.2	Limits	61
4.2.10.1.3	Conformance	61
4.2.10.2	Receiver Spurious Emissions in DL-only bands	61
4.2.10.2.1	Definition.....	61
4.2.10.2.2	Limits	62
4.2.10.2.3	Conformance	62
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio.....	62
4.2.11.1	Transmitter adjacent channel leakage power ratio for Single Carrier	62
4.2.11.1.1	Definition.....	62
4.2.11.1.2	Limits	62
4.2.11.1.3	Conformance	63
4.2.11.2	Transmitter adjacent channel leakage power ratio for Carrier Aggregation (DL CA and UL CA).....	63
4.2.11.2.1	Definition.....	63
4.2.11.2.2	Limits for CA UTRA.....	64
4.2.11.2.3	Limits for CA EUTRA	65
4.2.11.2.4	Conformance	65
4.2.11.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	65
4.2.11.3.1	Definition.....	65
4.2.11.3.2	Limits	66
4.2.11.3.3	Conformance	67
4.2.11.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier	67
4.2.11.4.1	Definition.....	67
4.2.11.4.2	Limits	67
4.2.11.4.3	Conformance	67
4.2.11.5	Transmitter adjacent channel leakage power ratio for category NB1	67

4.2.11.5.1	Definition.....	67
4.2.11.5.2	Limits	67
4.2.11.5.3	Conformance	68
4.2.12	Receiver Reference Sensitivity Level	68
4.2.12.0	General	68
4.2.12.1	Receiver Reference Sensitivity Level for Single Carrier	68
4.2.12.1.1	Definition.....	68
4.2.12.1.2	Limits	68
4.2.12.1.3	Conformance	68
4.2.12.2	Receiver Reference Sensitivity Level for Carrier Aggregation in DL-only bands.....	69
4.2.12.2.1	Definition.....	69
4.2.12.2.2	Limits	69
4.2.12.2.3	Conformance	70
4.2.12.3	Receiver Reference Sensitivity Level for category NB1.....	70
4.2.12.3.1	Definition.....	70
4.2.12.3.2	Limits	70
4.2.12.3.3	Conformance	70
4.2.12.4	Receiver Reference Sensitivity Level for UE category 0.....	70
4.2.12.4.1	Definition.....	70
4.2.12.4.2	Limits	70
4.2.12.4.3	Conformance	71
4.2.12.5	Receiver Reference Sensitivity Level for UE category M1	71
4.2.12.5.1	Definition.....	71
4.2.12.5.2	Limits	71
4.2.12.5.3	Conformance	72
5	Testing for compliance with technical requirements.....	73
5.1	Environmental conditions for testing	73
5.2	Interpretation of the measurement results	73
5.3	Essential radio test suites.....	73
5.3.0	General.....	73
5.3.1	Transmitter Maximum Output Power	73
5.3.1.1	Transmitter maximum output power for Single Carrier.....	73
5.3.1.1.1	Method of test.....	73
5.3.1.1.2	Test requirements	74
5.3.1.2	Transmitter maximum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	74
5.3.1.2.1	Method of test.....	74
5.3.1.2.2	Test requirements	75
5.3.1.2A	Transmitter maximum output power for inter-band Carrier Aggregation (DL CA and UL CA).....	75
5.3.1.2A.1	Method of test.....	75
5.3.1.2A.2	Test requirements	76
5.3.1.3	Transmitter maximum output power for UL-MIMO	76
5.3.1.3.1	Method of test.....	76
5.3.1.3.2	Test requirements	77
5.3.1.4	Transmitter maximum output power for category NB1	77
5.3.1.4.1	Method of Test	77
5.3.1.4.2	Test requirements	78
5.3.1.5	Transmitter maximum output power for UE category 0	78
5.3.1.5.1	Method of test.....	78
5.3.1.5.2	Test requirements	78
5.3.1.6	Transmitter maximum output power for UE category M1.....	78
5.3.1.6.1	Method of test.....	78
5.3.1.6.2	Test requirements	79
5.3.2	Transmitter Spectrum Emission Mask.....	79
5.3.2.1	Transmitter spectrum emission mask for Single Carrier.....	79
5.3.2.1.1	Method of test.....	79
5.3.2.1.2	Test requirements	80
5.3.2.2	Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	80
5.3.2.2.1	Method of test.....	80
5.3.2.2.2	Test requirements	81

5.3.2.2A	Transmitter spectrum emission mask for inter-band Carrier Aggregation (DL CA and UL CA)	81
5.3.2.2A.1	Method of test.....	81
5.3.2.2A.2	Test requirements	82
5.3.2.3	Transmitter spectrum emission mask for UL-MIMO	82
5.3.2.3.1	Method of test.....	82
5.3.2.3.2	Test requirements	83
5.3.2.4	Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier	83
5.3.2.4.1	Method of test.....	83
5.3.2.4.2	Test requirements	84
5.3.2.5	Transmitter spectrum emission mask for category NB1	84
5.3.2.5.1	Method of test.....	84
5.3.2.5.2	Test requirements	84
5.3.2.6	Transmitter spectrum emission mask for UE category 0	85
5.3.2.6.1	Method of test.....	85
5.3.2.6.2	Test requirements	85
5.3.2.7	Transmitter spectrum emission mask for UE category M1	85
5.3.2.7.1	Method of test.....	85
5.3.2.7.2	Test requirements	86
5.3.3	Transmitter Spurious Emissions	86
5.3.3.1	Transmitter spurious emissions for Single Carrier	86
5.3.3.1.1	Method of test.....	86
5.3.3.1.2	Test requirements	87
5.3.3.2	Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	87
5.3.3.2.1	Method of test.....	87
5.3.3.2.2	Test requirements	88
5.3.3.2A	Transmitter spurious emissions for inter-band Carrier Aggregation (DL CA and UL CA)	88
5.3.3.2A.1	Method of test.....	88
5.3.3.2A.2	Test requirements	89
5.3.3.3	Transmitter spurious emissions for UL-MIMO	89
5.3.3.3.1	Method of test.....	89
5.3.3.3.2	Test requirements	90
5.3.3.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier	90
5.3.3.4.1	Method of test.....	90
5.3.3.4.2	Test requirements	90
5.3.3.5	Transmitter spurious emissions for category NB1	91
5.3.3.5.1	Method of test.....	91
5.3.3.5.2	Test requirements	91
5.3.3.6	Transmitter spurious emissions for UE category 0	92
5.3.3.6.1	Method of test.....	92
5.3.3.6.2	Test requirements	92
5.3.3.7	Transmitter spurious emissions for UE category M1	92
5.3.3.7.1	Method of test.....	92
5.3.3.7.2	Test requirements	93
5.3.4	Transmitter Minimum Output Power	93
5.3.4.1	Transmitter minimum output power for Single Carrier.....	93
5.3.4.1.1	Method of test.....	93
5.3.4.1.2	Test requirements	94
5.3.4.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA)	94
5.3.4.2.1	Method of test.....	94
5.3.4.2.2	Test requirements	95
5.3.4.2A	Transmitter minimum output power for inter-band Carrier Aggregation (DL CA and UL CA).....	95
5.3.4.2A.1	Method of test.....	95
5.3.4.2A.2	Test requirements	96
5.3.4.3	Transmitter minimum output power for UL-MIMO	96
5.3.4.3.1	Method of test.....	96
5.3.4.3.2	Test requirements	97
5.3.4.4	Transmitter minimum output power for category NB1.....	97
5.3.4.4.1	Method of test.....	97
5.3.4.4.2	Test requirements	97
5.3.4.5	Transmitter minimum output power for UE category 0	98

5.3.4.5.1	Method of test.....	98
5.3.4.5.2	Test requirements	98
5.3.4.6	Transmitter minimum output power for UE category M1	98
5.3.4.6.1	Method of test.....	98
5.3.4.6.2	Test requirements	99
5.3.5	Receiver Adjacent Channel Selectivity (ACS)	99
5.3.5.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier	99
5.3.5.1.1	Method of test.....	99
5.3.5.1.2	Test requirements	100
5.3.5.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands.....	100
5.3.5.2.1	Method of test.....	100
5.3.5.2.2	Test requirements	101
5.3.5.3	Receiver Adjacent Channel Selectivity (ACS) for category NB1.....	101
5.3.5.3.1	Method of test.....	101
5.3.5.3.2	Test requirements	103
5.3.5.4	Receiver Adjacent Channel Selectivity (ACS) for UE category 0	103
5.3.5.4.1	Method of test.....	103
5.3.5.4.2	Test requirements	103
5.3.5.5	Receiver Adjacent Channel Selectivity (ACS) for UE category M1	103
5.3.5.5.1	Method of test.....	103
5.3.5.5.2	Test requirements	104
5.3.6	Receiver Blocking Characteristics	105
5.3.6.1	Receiver Blocking Characteristics for Single Carrier	105
5.3.6.1.1	Method of test.....	105
5.3.6.1.2	Test requirements	106
5.3.6.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands.....	107
5.3.6.2.1	Method of test.....	107
5.3.6.2.2	Test requirements	109
5.3.6.3	Receiver Blocking Characteristics for category NB1	109
5.3.6.3.1	Method of test.....	109
5.3.6.3.2	Test requirements	110
5.3.6.4	Receiver Blocking Characteristics for UE category 0.....	110
5.3.6.4.1	Method of test.....	110
5.3.6.4.2	Test requirements	111
5.3.6.5	Receiver Blocking Characteristics for UE category M1	111
5.3.6.5.1	Method of test.....	111
5.3.6.5.2	Test requirements	113
5.3.7	Receiver Spurious Response.....	113
5.3.7.1	Receiver Spurious Response for Single Carrier	113
5.3.7.1.1	Method of test.....	113
5.3.7.1.2	Test requirements	113
5.3.7.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands	113
5.3.7.2.1	Method of test.....	113
5.3.7.2.2	Test requirements	114
5.3.7.3	Receiver Spurious Response for category NB1	114
5.3.7.3.1	Method of test.....	114
5.3.7.3.2	Test requirements	114
5.3.7.4	Receiver Spurious Response for UE category 0.....	115
5.3.7.4.1	Method of test.....	115
5.3.7.4.2	Test requirements	115
5.3.7.5	Receiver Spurious Response for UE category M1	115
5.3.7.5.1	Method of test.....	115
5.3.7.5.2	Test requirements	115
5.3.8	Receiver Intermodulation Characteristics	116
5.3.8.1	Receiver Intermodulation Characteristics for Single Carrier	116
5.3.8.1.1	Method of test.....	116
5.3.8.1.2	Test requirements	116
5.3.8.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	117
5.3.8.2.1	Method of test.....	117
5.3.8.2.2	Test requirements	118
5.3.8.3	Receiver Intermodulation Characteristics for category NB1	118
5.3.8.3.1	Test requirements	118

5.3.8.3.2	Test requirements	118
5.3.8.4	Receiver Intermodulation Characteristics for UE category 0.....	119
5.3.8.4.1	Method of test.....	119
5.3.8.4.2	Test requirements	119
5.3.8.5	Receiver Intermodulation Characteristics for UE category M1	119
5.3.8.5.1	Method of test.....	119
5.3.8.5.2	Test requirements	120
5.3.9	Receiver Spurious Emissions.....	120
5.3.9.1	Receiver Spurious Emissions for Single Carrier.....	120
5.3.9.1.1	Method of test.....	120
5.3.9.1.2	Test requirements	121
5.3.9.2	Receiver Spurious Emissions in DL-only bands.....	121
5.3.9.2.1	Method of test.....	121
5.3.9.2.2	Test requirements	121
5.3.9.3	Receiver Spurious Emissions for UE category 0	122
5.3.9.3.1	Method of test.....	122
5.3.9.3.2	Test requirements	122
5.3.9.4	Receiver Spurious Emissions for UE category M1	122
5.3.9.4.1	Method of test.....	122
5.3.9.4.2	Test requirements	123
5.3.9.5	Receiver Spurious Emissions for UE category NB1	123
5.3.9.5.1	Method of test.....	123
5.3.9.5.2	Test requirements	123
5.3.10	Transmitter Adjacent Channel Leakage Power Ratio.....	123
5.3.10.1	Transmitter adjacent channel leakage power ratio for Single Carrier	123
5.3.10.1.1	Method of test.....	123
5.3.10.1.2	Test requirements	124
5.3.10.2	Transmitter adjacent channel leakage power ratio for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	124
5.3.10.2.1	Method of test.....	124
5.3.10.2.2	Test requirements	125
5.3.10.2A	Transmitter adjacent channel leakage power ratio for inter-band Carrier Aggregation (DL CA and UL CA).....	126
5.3.10.2A.1	Method of test.....	126
5.3.10.2A.2	Test requirements	127
5.3.10.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	127
5.3.10.3.1	Method of test.....	127
5.3.10.3.2	Test requirements	128
5.3.10.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier	128
5.3.10.4.1	Method of test.....	128
5.3.10.4.2	Test requirements	129
5.3.10.5	Transmitter adjacent channel leakage power ratio for category NB1	129
5.3.10.5.1	Method of test.....	129
5.3.10.5.2	Test requirements	130
5.3.10.6	Transmitter adjacent channel leakage power ratio for UE category 0.....	130
5.3.10.6.1	Method of test.....	130
5.3.10.6.2	Test requirements	130
5.3.10.7	Transmitter adjacent channel leakage power ratio for UE category M1	130
5.3.10.7.1	Method of test.....	130
5.3.10.7.2	Test requirements	131
5.3.11	Receiver Reference Sensitivity Level	131
5.3.11.1	Receiver Reference Sensitivity Level for Single Carrier	131
5.3.11.1.1	Method of test.....	131
5.3.11.1.2	Test requirements	132
5.3.11.2	Receiver Reference Sensitivity Level for Carrier Aggregation in DL-only bands.....	132
5.3.11.2.1	Method of test.....	132
5.3.11.2.2	Test requirements	133
5.3.11.3	Receiver Reference Sensitivity Level for category NB1.....	133
5.3.11.3.1	Method of test.....	133
5.3.11.3.2	Test requirements	134
5.3.11.4	Receiver Reference Sensitivity Level for UE category 0.....	134

5.3.11.4.1	Method of test.....	134
5.3.11.4.2	Test requirements	134
5.3.11.5	Receiver Reference Sensitivity Level for UE category M1	135
5.3.11.5.1	Method of test.....	135
5.3.11.5.2	Test requirements	135
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	136
Annex B (normative):	Environmental profile	138
B.1	General	138
B.1.1	Introduction	138
B.1.2	Temperature	138
B.1.3	Voltage	138
B.1.4	Test environment.....	139
Annex C (informative):	Recommended maximum measurement uncertainty	140
Annex D (informative):	Bibliography.....	141
Annex E (informative):	Change history	142
History		143

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

For non-EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 13 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.12].

National transposition dates	
Date of adoption of this EN:	25 November 2019
Date of latest announcement of this EN (doa):	29 February 2020
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2020
Date of withdrawal of any conflicting National Standard (dow):	31 August 2021

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

1 Scope

The present document applies to the following radio equipment type:

- User Equipment for Evolved Universal Terrestrial Radio Access (E-UTRA).

This radio equipment type is capable of operating in all or any part of the frequency bands given in tables from 1-1 through 1-5.

Table 1-1: E-UTRA UE operating bands

E-UTRA Band	Direction of UE transmission	E-UTRA operating bands
1	Transmit	1 920 MHz to 1 980 MHz
	Receive	2 110 MHz to 2 170 MHz
3	Transmit	1 710 MHz to 1 785 MHz
	Receive	1 805 MHz to 1 880 MHz
7	Transmit	2 500 MHz to 2 570 MHz
	Receive	2 620 MHz to 2 690 MHz
8	Transmit	880 MHz to 915 MHz
	Receive	925 MHz to 960 MHz
20	Transmit	832 MHz to 862 MHz
	Receive	791 MHz to 821 MHz
22	Transmit	3 410 MHz to 3 490 MHz
	Receive	3 510 MHz to 3 590 MHz
28 (see note 6)	Transmit	703 MHz to 748 MHz
	Receive	758 MHz to 803 MHz
31	Transmit	452,5 MHz to 457,5 MHz
	Receive	462,5 MHz to 467,5 MHz
32 (see note 1) (see note 2)	Transmit	N/A
	Receive	1 452 MHz to 1 496 MHz
33	Transmit and Receive	1 900 MHz to 1 920 MHz
34	Transmit and Receive	2 010 MHz to 2 025 MHz
38	Transmit and Receive	2 570 MHz to 2 620 MHz
40	Transmit and Receive	2 300 MHz to 2 400 MHz
42	Transmit and Receive	3 400 MHz to 3 600 MHz
43	Transmit and Receive	3 600 MHz to 3 800 MHz
46 (see note 3) (see note 4)	Transmit and Receive	5 150 MHz to 5 925 MHz
65 (see note 5)	Transmit	1 920 MHz to 2 010 MHz
	Receive	2 110 MHz to 2 200 MHz
67	Transmit	N/A
	Receive	738 MHz to 758 MHz
68	Transmit	698 MHz to 728 MHz
	Receive	753 MHz to 783 MHz
69 (see note 1)	Transmit	N/A
	Receive	2 570 MHz to 2 620 MHz

NOTE 1: Restricted to E-UTRA operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.

NOTE 2: Radio equipment in band 32 is only allowed to operate between 1 452 MHz and 1 492 MHz.

NOTE 3: This band is an unlicensed band restricted to licensed-assisted operation using Frame Structure Type 3.

NOTE 4: In this version of the present document, restricted to E-UTRA DL operation when carrier aggregation is configured.

NOTE 5: A UE that complies with the E-UTRA Band 65 minimum requirements in the present document also complies with the E-UTRA Band 1 minimum requirements.

NOTE 6: Radio equipment in band 28 is only allowed to operate between 758 MHz to 791 MHz for the transmitter and between 703 MHz to 736 MHz for the receiver.

NOTE 1: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

Table 1-1A: Sub-bands for band 46

E-UTRA Band	Downlink (DL) operating band BS transmit UE receive
	$F_{DL_low} - F_{DL_high}$
46a	5 150 MHz - 5 250 MHz
46b	5 250 MHz - 5 350 MHz
46c	5 470 MHz - 5 725 MHz
NOTE: The sub-bands 46a and 46b are restricted to indoor use only.	

Table 1-2: E-UTRA UE Intra-band contiguous CA operating bands

E-UTRA CA Band	E-UTRA Band	Direction of UE transmission	E-UTRA operating bands
CA_1	1	Transmit	1 920 MHz to 1 980 MHz
		Receive	2 110 MHz to 2 170 MHz
CA_3	3	Transmit	1 710 MHz to 1 785 MHz
		Receive	1 805 MHz to 1 880 MHz
CA_7	7	Transmit	2 500 MHz to 2 570 MHz
		Receive	2 620 MHz to 2 690 MHz
CA_38	38	Transmit and Receive	2 570 MHz to 2 620 MHz
CA_40	40	Transmit and Receive	2 300 MHz to 2 400 MHz
CA_42	42	Transmit and Receive	3 400 MHz to 3 600 MHz

Table 1-3: E-UTRA UE Inter-band CA operating bands (two bands)

E-UTRA CA Band	E-UTRA Band	UL operating band	DL operating band
		BS receive/UE transmit	BS transmit/UE receive
		$F_{UL_low} - F_{UL_high}$	$F_{DL_low} - F_{DL_high}$
CA_1-3	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
CA_1-7	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
CA_1-8	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	8	880 MHz to 915 MHz	925 MHz to 960 MHz
CA_1-20	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz
CA_1-42	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	42	3 400 MHz to 3 600 MHz	3 400 MHz to 3 600 MHz
CA_1-46	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	46	5 150 MHz to 5 925 MHz	5 150 MHz to 5 925 MHz
CA_3-7	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
CA_3-8	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	8	880 MHz to 915 MHz	925 MHz to 960 MHz
CA_3-20	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz
CA_3-28	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	28	703 MHz to 748 MHz	758 MHz to 803 MHz
CA_3-42	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	42	3 400 MHz to 3 600 MHz	3 400 MHz to 3 600 MHz
CA_3-46	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	46	5 150 MHz to 5 925 MHz	5 150 MHz to 5 925 MHz
CA_7-20	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz
CA_7-28	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
	28	703 MHz to 748 MHz	758 MHz to 803 MHz
CA_7-46	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
	46	5 150 MHz to 5 925 MHz	5 150 MHz to 5 925 MHz
CA_8-20	8	880 MHz to 915 MHz	925 MHz to 960 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz
CA_8-40	8	880 MHz to 915 MHz	925 MHz to 960 MHz
	40	2 300 MHz to 2 400 MHz	2 300 MHz to 2 400 MHz
CA_20-32 (see note)	20	832 MHz to 862 MHz	791 MHz to 821 MHz
	32	N/A	1 452 MHz to 1 496 MHz
CA_42-46	42	3 400 MHz to 3 600 MHz	3 400 MHz to 3 600 MHz
	46	5 150 MHz to 5 925 MHz	5 150 MHz to 5 925 MHz
CA_20-67	20	832 MHz to 862 MHz	791 MHz to 821 MHz
	67	N/A	738 MHz to 758 MHz

NOTE: Radio equipment in band 32 is only allowed to operate between 1 452 MHz and 1 492 MHz.

Table 1-4: E-UTRA UE Inter-band CA operating bands (three bands)

E-UTRA CA Band	E-UTRA Band	UL operating band	DL operating band
		BS receive/UE transmit	BS transmit/UE receive
		$F_{UL_low} - F_{UL_high}$	$F_{DL_low} - F_{DL_high}$
CA_1-3-8	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	8	880 MHz to 915 MHz	925 MHz to 960 MHz
CA_1-3-20	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz
CA_1-7-20	1	1 920 MHz to 1 980 MHz	2 110 MHz to 2 170 MHz
	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz
CA_3-7-20	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
	20	832 MHz to 862 MHz	791 MHz to 821 MHz

Table 1-5: Intra-band non-contiguous CA operating bands (with two sub-blocks)

E-UTRA CA Band	E-UTRA Band	Uplink (UL) operating band	Downlink (DL) operating band
		BS receive/UE transmit	BS transmit/UE receive
		$F_{UL_low} - F_{UL_high}$	$F_{DL_low} - F_{DL_high}$
CA_3-3	3	1 710 MHz to 1 785 MHz	1 805 MHz to 1 880 MHz
CA_7-7	7	2 500 MHz to 2 570 MHz	2 620 MHz to 2 690 MHz
CA_42-42	42	3 400 MHz to 3 600 MHz	3 400 MHz to 3 600 MHz

E-UTRA NB-IoT is designed to operate in the E-UTRA operating bands 1, 3, 8, 20, 28 and 65 defined in table 1-1. The present document covers requirements for E-UTRA FDD and E-UTRA TDD User Equipment from 3GPP™ Releases 8, 9, 10, 11, 12, and 13 defined in ETSI TS 136 101 [3]. This includes the requirements for E-UTRA UE operating bands and E-UTRA CA operating bands from 3GPP™ Release 13 defined in ETSI TS 136 101 [3].

NOTE 2: For Band 20:

- For user equipment designed to be mobile or nomadic, the requirements in the present document measured at the antenna port also show conformity to the corresponding requirement defined as TRP (total radiated power), as described in Commission Decision 2010/267/EU [i.6], ECC Decision (09)03 [i.7].
- For user equipment designed to be fixed or installed, the present document does not address the requirements described in Commission Decision 2010/267/EU [i.6], ECC Decision (09)03 [i.7]. The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 136 521-1 (V15.2.0) (10-2018): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing (3GPP TS 36.521-1 version 15.2.0 Release 15)".
- [2] ETSI TS 136 508 (V14.5.0) (04-2018): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); Common test environments for User Equipment (UE) conformance testing (3GPP TS 36.508 version 14.5.0 Release 14)".
- [3] ETSI TS 136 101 (V13.11.0) (04-2018): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception (3GPP TS 36.101 version 13.11.0 Release 13)".
- [4] IEC 60068-2-1 (2007): "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [5] IEC 60068-2-2 (2007): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] Commission Decision 2010/267/EU of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.7] ECC Decision (09)03 of 30 October 2009 on harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz.
- [i.8] Void.
- [i.9] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.10] ETSI TS 136 509 (V10.3.0) (09-2014): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); Special conformance testing functions for User Equipment (UE) (3GPP TS 36.509 version 10.3.0 Release 10)".
- [i.11] Void.
- [i.12] ETSI EN 301 908-1 (V11.1.1): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements".

koniec náhľadu – text ďalej pokračuje v platenej verzii STN