

STN	Kozmická technika SpaceWire Linky, uzly, smerovače a siete	STN EN 16603-50-12 31 0543
------------	---	--

Space engineering - SpaceWire - Links, nodes, routers and networks

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 08/20

Obsahuje: EN 16603-50-12:2020

131138

EUROPEAN STANDARD

EN 16603-50-12

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2020

ICS 49.140

English version

Space engineering - SpaceWire - Links, nodes, routers and networks

Ingénierie spatiale - SpaceWire - Liaisons, noeuds,
routeurs et réseaux

Raumfahrttechnik - SpaceWire - Verbindungen,
Knoten, Router und Netzwerke

This European Standard was approved by CEN on 29 December 2019.

CEN and CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN and CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN and CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



**CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels**

Table of contents

European Foreword	7
1 Scope	8
2 Normative references	9
3 Terms, definitions and abbreviated terms	10
3.1 Terms from other standards.....	10
3.2 Terms specific to the present standard	10
3.3 Abbreviated terms.....	20
3.4 Conventions.....	21
3.4.1 Numbers	21
3.4.2 Differential signals.....	21
3.4.3 Order of sending bits in symbols	21
3.4.4 Graphical representation of packets.....	22
3.4.5 State diagram notation	22
3.4.6 UML diagram notation.....	23
3.5 Nomenclature	24
4 Overview of SpaceWire	25
4.1 Introduction.....	25
4.2 SpaceWire Spacecraft Data-Handling Network.....	25
4.2.1 The Rationale for SpaceWire	25
4.2.2 Example SpaceWire Application	26
4.2.3 How SpaceWire Works	28
5 Requirements	33
5.1 Overview	33
5.2 Protocol stack and interface architecture	33
5.2.1 Protocol stack	33
5.2.2 Network layer	34
5.2.3 Data Link layer	34
5.2.4 Encoding layer	35
5.2.5 Physical layer.....	35

5.2.6	Management Information Base	36
5.2.7	Service interfaces	36
5.2.8	SpaceWire Port architecture	36
5.3	Physical layer	37
5.3.1	Introduction	37
5.3.2	Cables.....	38
5.3.3	Connectors	41
5.3.4	Cable assemblies.....	45
5.3.5	PCB tracks.....	50
5.3.6	Line drivers and receivers	51
5.3.7	Data-Strobe skew	59
5.3.8	Physical layer management parameters	62
5.4	Encoding layer.....	63
5.4.1	Introduction	63
5.4.2	Serialisation and de-serialisation.....	63
5.4.3	Character and control code encoding.....	63
5.4.4	Data strobe encoding and decoding.....	66
5.4.5	First Null.....	68
5.4.6	Null detection	68
5.4.7	Parity error	69
5.4.8	Disconnect	69
5.4.9	ESC error.....	69
5.4.10	Data signalling rate	70
5.4.11	Encoding layer management parameters.....	71
5.5	Data link layer.....	71
5.5.1	Introduction.....	71
5.5.2	Data link layer interfaces.....	71
5.5.3	Data link layer management interface	72
5.5.4	Flow control.....	73
5.5.5	Flow control errors	74
5.5.6	Sending priority	75
5.5.7	Link initialisation behaviour	75
5.5.8	Link error recovery	80
5.5.9	Accepting broadcast codes for sending.....	82
5.6	SpaceWire network layer	82
5.6.1	Introduction	82
5.6.2	SpaceWire packets	83

EN 16603-50-12:2020 (E)

5.6.3	Broadcast codes	83
5.6.4	SpaceWire time-codes	84
5.6.5	SpaceWire distributed interrupts	87
5.6.6	SpaceWire nodes	94
5.6.7	SpaceWire node management parameters	96
5.6.8	SpaceWire routing	96
5.6.9	SpaceWire routing switch management parameters	104
5.6.10	SpaceWire network	104
5.7	SpaceWire management information base	106
5.7.1	Introduction	106
5.7.2	General	106
5.7.3	Physical layer management parameters	106
5.7.4	Encoding layer management parameters	106
5.7.5	Data link layer management parameters	106
5.7.6	Network layer management parameters	106
6	Service interfaces	107
6.1	Network layer service interface	107
6.1.1	Packet service interface	107
6.1.2	Time-code service interface	108
6.1.3	Distributed interrupt service interface	109
6.2	Data link layer service interface	111
6.2.1	N-Char service interface	111
6.2.2	Broadcast code service interface	113
6.3	Encoding layer service interface	114
6.3.1	Encoding service interface	114
6.3.2	Decoding service interface	115
6.4	Physical layer service interface	117
6.4.1	Line transmit service interface	117
6.4.2	Line receive service interface	118
6.5	Management information base service interface	119
6.5.1	Set parameter service interface	119
6.5.2	Get parameter service interface	119
Annex A	(informative) Technical Changes	121
Bibliography	123

Figures

Figure 3-1: Convention for first bit to be sent	21
Figure 3-2: Graphical packet notation	22
Figure 3-3: State diagram style	22
Figure 3-4: UML notation	23
Figure 4-1: Example SpaceWire Architecture without redundancy	27
Figure 4-2: SpaceWire Packet Format	29
Figure 4-3: Path Addressing	31
Figure 4-4 Logical Addressing	32
Figure 5-1: SpaceWire protocol stack	34
Figure 5-2: SpaceWire port architecture	37
Figure 5-3: SpaceWire connector contact identification	44
Figure 5-4: SpaceWire cable assembly Type A	47
Figure 5-5: SpaceWire cable assembly Type AL	49
Figure 5-6: SpaceWire LVDS	53
Figure 5-7: LVDS line driver output signals	54
Figure 5-8: LVDS line driver differential output signal	56
Figure 5-9: Physical layer components	59
Figure 5-10: Skew and jitter	62
Figure 5-11: Data character encoding	64
Figure 5-12: Control character encoding	65
Figure 5-13: Null control code encoding	65
Figure 5-14: Broadcast code encoding	66
Figure 5-15: Parity coverage	66
Figure 5-16: Data-Strobe (DS) encoding	67
Figure 5-17: Data and strobe signals for first Null	68
Figure 5-18: Null detection sequence	69
Figure 5-19: Link initialisation behaviour	76
Figure 5-20: Link error recovery behaviour	81
Figure 5-21: SpaceWire packet format	83
Figure 5-22: Specialisations and relationships of a SpaceWire broadcast code	84
Figure 5-23 Network layer time-code	85
Figure 5-24: Network layer interrupt	88
Figure 5-25: Network layer interrupt acknowledgement code	89
Figure 5-26: Components and specialisations of a SpaceWire node	95
Figure 5-27: Components of a SpaceWire routing switch	97
Figure 5-28: Components of a SpaceWire network	105

EN 16603-50-12:2020 (E)**Tables**

Table 5-1: Constants for a SpW cable using 28 AWG differential pairs	39
Table 5-2: Insertion loss values 28AWG SpW cable.....	40
Table 5-3: Constants for a SpaceWire cable using 26 AWG differential pairs	40
Table 5-4: Insertion loss values for 26 AWG SpaceWire cable	40
Table 5-5: Cable PSNEXT specification	41
Table 5-6: Cable PSELFEXT specification	41
Table 5-7: Connector contact identification.....	43
Table 5-8: Cable assembly Type A signal wire connections	47
Table 5-9: Cable assembly Type AL signal wire connections	49
Table 5-10 Example calculation of maximum bit rate.....	61
Table 5-11: Address function.....	99

European Foreword

This document (EN 16603-50-12:2020) has been prepared by Technical Committee CEN-CENELEC/TC 5 "Space", the secretariat of which is held by DIN.

This standard (EN 16603-50-12:2020) originates from ECSS-E-ST-50-12C Rev.1.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2020, and conflicting national standards shall be withdrawn at the latest by September 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a standardization request given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any EN covering the same scope but with a wider domain of applicability (e.g. : aerospace).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

SpaceWire technology has grown from the needs of spacecraft on-board data handling applications. This Standard provides a formal basis for the exploitation of SpaceWire in a wide range of future on-board processing systems.

One of the principal aims of SpaceWire is the support of equipment compatibility and reuse at both the component and subsystem levels. In principle a data-handling system developed for an optical instrument, for example, can be used for a radar instrument by unplugging the optical sensor and plugging in the radar one. Processing units, mass-memory units and down-link telemetry systems developed for one mission can be readily used on another mission, reducing the cost of development, improving reliability and most importantly increasing the amount of scientific work that can be achieved within a limited budget.

Integration and test of complex on-board systems is also supported by SpaceWire with ground support equipment plugging directly into the on-board data-handling system. Monitoring and testing can be carried out with a seamless interface into the on-board system.

SpaceWire is the result of the efforts of many individuals within the European Space Agency, European Space Industry and academia.

This standard may be tailored for the specific characteristics and constraints of a space project in conformance with ECSS-S-ST-00.

2

Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this ECSS Standard. For dated references, subsequent amendments to, or revision of any of these publications do not apply. However, parties to agreements based on this ECSS Standard are encouraged to investigate the possibility of applying the more recent editions of the normative documents indicated below. For undated references, the latest edition of the publication referred to applies.

EN reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS system - Glossary of terms
EN 16602-70-08	ECSS-Q-ST-70-08	Space product assurance - Manual soldering of high-reliability electrical connections
EN 16602-70-26	ECSS-Q-ST-70-26	Space product assurance - Crimping of high-reliability electrical connections
	ESCC 3401	Connectors, electrical, non-filtered circular and rectangular, ESCC Generic Specification no. 3401, Issue 5, March 2018
	ESCC 3401/029:2017	Connectors, Electrical, Rectangular, Microminiature, based on type MDMA, ECSS Detail Specification no. 3401/029, Issue 15, November 2017.
	ESCC 3401/077:2016	Connectors, Electrical, Rectangular, Microminiature, Removable Crimp Contacts, based on type MDMA, ECSS Detail Specification no. 3401/077, Issue 7, April 2016.
	ESCC 3902/003:2014	Cable, "SpaceWire", Round, Quad using Symmetric Cables, Flexible, -200 to +180 °C, Detail Specification no. 3902/003, Issue 4, November 2014.
	ESCC 3902/004:2014	Cable, Low Mass, "SpaceWire", Round, Quad using Symmetric Cables, Flexible, -100 to +150 °C, Detail Specification no. 3902/004, Issue 1, October 2014.
	MIL-DTL-17J:2014	Military Specification: Cables, Radio, Frequency, Flexible and Semirigid, General Specification for, 10 th February 2014.
	TIA-644-A:2012	TIA-644-A, Electrical Characteristics of Low Voltage Differential Signalling (LVDS) Interface Circuits, Revision A, Reaffirmed 12/07/12, Telecommunications Industry Association, 2012.