

## Ochranné zariadenia proti prepätiu nízkeho napätia Časť 32: Prepäťové ochranné zariadenia pripojené na stranu DC fotovoltických zariadení Zásady výberu a použitia

STN P CLC/TS 51643-32

34 1392

Low-voltage surge protective devices - Part 32: Surge protective devices connected to the DC side of photovoltaic installations - Selection and application principles

Táto norma obsahuje anglickú verziu európskej normy. This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 09/20

Obsahuje: CLC/TS 51643-32:2020

Oznámením tejto normy sa ruší STN P CLC/TS 50539-12 (34 1392) z júla 2014



# TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

CLC/TS 51643-32

July 2020

ICS 27.160; 29.120.50

Supersedes CLC/TS 50539-12:2013

#### **English Version**

# Low-voltage surge protective devices - Part 32: Surge protective devices connected to the DC side of photovoltaic installations - Selection and application principles

Parafoudres basse tension - Partie 32 : Parafoudres connectés au côté courant continu des installations photovoltaïques - Principes de choix et d'application

Überspannungsschutzgeräte für Niederspannung - Teil 32: Überspannungsschutzgeräte für den Einsatz auf der Gleichstromseite von Photovoltaik-Installationen - Auswahl und Anwendungsgrundsätze

This Technical Specification was approved by CENELEC on 2020-05-25.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2020 CENELEC

All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. CLC/TS 51643-32:2020 E

Co	ntent	S Comments	Page
Eur	opean f	oreword	5
Intro	ductio	າ	6
1	Scope	9	7
2	Norma	ative references	7
3	Terms	s and definitions	8
4	Syste	ms and equipment to be protected	11
5	Overv	oltages in a PV installation	12
6		tion and erection of SPDs	
6	6.1	General	12
Tab	le 1 —	Selection of SPD type and cross section of bonding conductor	
		Requirements for different PV installations	
	6.2.1	General	
	6.2.2	PV installation without an external LPS	14
Figu	ıre 1 —	Installation of SPDs in the case of a building without an external LPS	14
	6.2.3	PV installation with an external LPS when the separation distance (s) is maintained (excluding multi-earthed solar systems, such as PV power plants)	14
Figu		Installation of SPDs in the case of a PV installation with an external LPS where the ation distance (s) is maintained	15
	6.2.4	PV installation with an external LPS where the separation distance (s) cannot be maintained (including multi-earthed systems, such as PV power plants)	16
Figu		Installation of SPDs in the case of a PV-installation with an external LPS where the ation distance (s) cannot be maintained	16
	6.2.5	PV installation including communication and signalling circuits	16
6	3.3	Selection and erection of SPDs installed on the AC side	17
	6.3.1	General	17
	6.3.2	Selection of SPDs with regard to nominal discharge current <i>I</i> <sub>n</sub> and impulse current <i>I</i> <sub>imp</sub>	17
	6.3.3	Selection of SPDs with regard to voltage protection level $U_p$	17
	6.3.4	Installation of SPDs on the AC side	17
Figu		Installation of SPDs on the AC side with a short distance between the origin of the ation and the PV inverter (E < 10 m)	18
Figu		Installation of SPDs on the AC side with a long distance between the origin of the ation and the PV inverter (E ≥ 10 m)	18
6	6.4	Selection and erection of SPDs installed on the DC side	19
	6.4.1	General	19
	6.4.2	Selection of SPDs with regard to nominal discharge current <i>I</i> <sub>n</sub> and impulse current <i>I</i> <sub>imp</sub>	19
	6.4.3	Selection of U <sub>CPV</sub> of SPDs on the DC side	
	6.4.4	Selection of SPDs with regard to its leakage current /pF	
	6.4.5	Selection of SPDs with regard to voltage protection level $U_{D}$	
Tah		Rated impulse voltage $U_{W}$ for equipment between PV array and inverter (where no	10
· ab		information is available)	20
	6.4.6	Installation of SPDs on the DC side	

Figu	re 6 — Example of overvoltage protection on the DC side of a PV installation	21
	6.4.7 Cross-sections of connecting conductors for SPDs on the DC side	21
	6.4.8 Connection schemes of assemblies of SPDs on the DC side	22
Figu	re 7 — Example of connections (Y, D and U) on the DC side of a PV source	23
Figu	ure 8 — Example of connections (L and I) on the DC side of a reliable earthed PV source when distance between SPDs and the reliable earthing is less than 1 m	23
	6.4.9 Selection of I <sub>SCPV</sub> of SPDs on the DC side	23
6	S.5 Coordination of SPDs	24
7	Earthing Arrangement	24
8	Requirements for the installation of surge protective devices (SPDs) in a PV system	25
9	Maintenance	25
Ann	ex A (normative) Determination of the value of $I_{\text{imp}}$ or $I_{\text{n}}$ for SPDs according to the simplified approach for different structures protected by an LPS	26
A.1	Introduction	26
A.2	Building with a PV installation on the roof according to 6.2.4	27
Figu	ure A.1 — Example of a structure with two external down conductors to determine the value of the discharge current for the selection of SPDs	29
Tab	le A.1 — Values of $l_{\text{imp}}$ ( $l_{10/350}$ ) and $l_{\text{n}}$ ( $l_{8/20}$ ) for voltage limiting SPDs on the DC side of a PV installation mounted on the roof of a building with an external LPS if the separation distance is not maintained.	29
Tab	le A.2 — Values of $l_{\text{imp}}$ ( $l_{10/350}$ ) for voltage switching SPDs on the DC side of a PV installation mounted on the roof of a building with an external LPS, if the separation distance is not maintained.	
A.3	Free- field PV power plant	30
Figu	re A.2 — Example of the structure of an extended PV installation — A PV power plant with multiple earthing and a meshed earthing system	32
Tab	le A.3 — Values of $l_{\text{imp}}$ ( $l_{10/350}$ ) and $l_{\text{n}}$ ( $l_{8/20}$ ) for SPDs used on the DC side in PV power plants with a central inverter, multiple earthing and a meshed earthing system	33
A.4	Selection of Type 1 SPDs impulse current $I_{imp}$ when A.2 or A.3 cannot be applied	
	ex B (informative) Characteristics of a PV source	
	PV source characteristics	
	re B.1 — Equivalent circuit diagram of a PV current source	
	ure B.2 — I/U characteristics of a PV source at different conditions	
	ure B.3 — Comparison of I/U characteristics of a PV source at different radiation conditions and linear DC sources for SPD testing.	
B.2	Calculation of U <sub>OC MAX</sub>	
	Calculation of I <sub>SC MAX</sub>	
		00
Ann	ex C (informative) Additional information to Clause 6: Selection and erection of SPDs and to Clause 7: Earthing Arrangement	39
C.1	PV installation including communication and signalling circuits	39
Figu	re C.1 — Example of SPDs installed on a PV system protected by an external LPS where the separation distance (s) is maintained – Installation includes data acquisition and control system	40
C.2	PV installation and dimensions of equipotential bonding conductors	

Figure C.2 — Example of a building with an external LPS – Dimensions of equipotential bonding conductors when the separation distance (s) is maintained, or an isolated LPS is	
used	41
Figure C.3 — Example of a building with an external LPS – Dimensions of equipotential	
bonding conductors when the separation distance (s) is not maintained.	42
Bibliography	43

# **European foreword**

This document (CLC/TS 51643-32:2020) has been prepared by CLC/TC 37A "Low-voltage surge protective devices".

This document supersedes CLC/TS 50539-12:2013 and all of its amendments and corrigenda (if any).

CLC/TS 51643-32:2020 includes the following significant technical changes with respect to CLC/TS 50539-12:2013:

- slight restructuring without impact on the content (such as changing the title of a clause by changing the text of one clause to another),
- deletion of the current branch concept of an SPD,
- referring to EN 61634-11:2019 instead of EN 50539-11:2013,
- referring to OCFM, SCFM instead of acronyms and concepts SCM and OCM,
- deletion of Annex C relating to the simplified risk assessment A,
- addition of a new annex dealing with telecommunication circuits.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

#### Introduction

This document provides useful information for the selection of SPDs connected to photovoltaic installations.

This document does not address the fundamentals of SPDs that are addressed in CLC/TS 61643-12 which are necessary for its correct understanding and application.

This document provides information to evaluate, with reference to the documents listed in Clause 2, the additional needs for surge protective devices (SPDs) to be installed on the DC side and on the AC side of a photovoltaic (PV) system, to protect against induced and direct lightning effects. It gives guidance for selection, operation and installation of SPDs, including the selection of SPD type, surge current values and cross sections of bonding conductors.

The specific electrical parameters of a PV array or a PV source require specific SPDs on the DC side.

This document considers SPDs used in different locations and in different kinds of PV systems. It gives examples and provides a simplified and common approach to determine impulse discharge current values for the DC side of different PV installations.

#### 1 Scope

This document describes the principles for selection, installation and coordination of SPDs intended for use in Photovoltaic (PV) systems up to 1500 V DC and for the AC side of the PV system rated up to 1000 V RMS 50/60 Hz.

The photovoltaic installation extends from a PV array or a set of interconnected PV-modules to include the associated cabling and protective devices and the converter up to the connection point in the distribution board or the utility supply point.

This document considers SPDs used in different locations and in different kinds of PV systems:

- PV systems located on the top of a building;
- PV systems located on the ground like free field power plants characterized by multiple earthing and a meshed earthing system.

The term PV installation is used to refer to both kinds of PV systems. The term PV power plant is only used for extended free-field multi-earthed power systems located on the ground.

For PV installations including batteries additional requirements could be necessary.

NOTE 1 The HD 60364 series, EN 62305 series and CLC/TS 61643-12 also apply.

NOTE 2 This document deals only with SPDs and not with surge protective components integrated inside equipment (e.g. inverters, (PCE) power conversion equipment).

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

HD 60364-5-534:2016, Low-voltage electrical installations - Part 5-53: Selection and erection of electrical equipment - Isolation, switching and control - Clause 534: Devices for protection against transient overvoltages (IEC 60364-5-53:2001/A2:2015, modified)

EN 60664-1:2007, Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests (IEC 60664-1:2007)

EN 61000-4-5, Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test (IEC 61000-4-5)

CLC/TS 61643-12, Low-voltage surge protective devices - Part 12: Surge protective devices connected to low-voltage power distribution systems - Selection and application principles (IEC 61643-12)

EN 61643-31:2019, Low-voltage surge protective devices - Part 31: Requirements and test methods for SPDs for photovoltaic installations (IEC 61643-31:2018)

ITU-T K.20, Resistibility of telecommunication equipment installed in a telecommunications centre to overvoltages and overcurrents

ITU-T K.21, Resistibility of telecommunication equipment installed in customer premises to overvoltages and overcurrents

# koniec náhľadu – text ďalej pokračuje v platenej verzii STN