

<b>STN</b>	<b>Skúšobné postupy na optické vláknové komunikačné podsystemy</b> <b>Časť 4-5: Inštalované zostavy z optických káblov</b> <b>Meranie tlmenia zostavy z optických káblov s</b> <b>ukončením s konektorom MPO použitím</b> <b>skúšobných zariadení s rozhraniami MPO</b>	<b>STN</b> <b>EN IEC 61280-4-5</b>  35 9270
------------	---	--

Fibre-optic communication subsystem test procedures - Part 4-5: Installed cabling plant - Attenuation measurement of MPO terminated fibre optic cabling plant using test equipment with MPO interfaces

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 12/20

Obsahuje: EN IEC 61280-4-5:2020, IEC 61280-4-5:2020

**132090**



EUROPEAN STANDARD

**EN IEC 61280-4-5**

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2020

ICS 33.180.01

English Version

**Fibre-optic communication subsystem test procedures - Part 4-5:  
Installed cabling plant - Attenuation measurement of MPO  
terminated fibre optic cabling plant using test equipment with  
MPO interfaces  
(IEC 61280-4-5:2020)**

Procédures d'essai des sous-systèmes de  
télécommunication fibroniques - Partie 4-5: Installation  
câblée - Mesure de l'affaiblissement de l'installation câblée  
fibronique à terminaisons MPO utilisant un équipement  
d'essai avec interfaces MPO  
(IEC 61280-4-5:2020)

Prüfverfahren für Lichtwellenleiter-  
Kommunikationsunterssysteme - Teil 4-5: Installierte  
Kabelanlagen - Dämpfungsmessung an Lichtwellenleiter-  
Kabelanlagen mit MPO-Abschlüssen mittels  
Prüfeinrichtungen mit MPO-Steckgesichtern  
(IEC 61280-4-5:2020)

This European Standard was approved by CENELEC on 2020-08-26. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

**EN IEC 61280-4-5:2020 (E)****European foreword**

The text of document 86C/1669/FDIS, future edition 1 of IEC 61280-4-5, prepared by SC 86C "Fibre optic systems and active devices" of IEC/TC 86 "Fibre optics" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61280-4-5:2020.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2021-05-26
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2023-08-26

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

**Endorsement notice**

The text of the International Standard IEC 61280-4-5:2020 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60793-1-40	NOTE	Harmonized as EN IEC 60793-1-40
IEC 60793-2	NOTE	Harmonized as EN 60793-2
IEC 60793-2-10	NOTE	Harmonized as EN IEC 60793-2-10
IEC 60793-2-50	NOTE	Harmonized as EN IEC 60793-2-50
IEC 60876-1:2014	NOTE	Harmonized as EN 60876-1:2014 (not modified)
IEC 61280-4-2	NOTE	Harmonized as EN 61280-4-2
IEC 61300-3-6	NOTE	Harmonized as EN 61300-3-6
IEC 61300-3-45	NOTE	Harmonized as EN 61300-3-45
IEC 61745	NOTE	Harmonized as EN 61745
IEC 61754-7 (series)	NOTE	Harmonized as EN IEC 61754-7 (series)
IEC 61755-3-31	NOTE	Harmonized as EN 61755-3-31

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: [www.cenelec.eu](http://www.cenelec.eu).

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60825	series	Safety of laser products	EN 60825	series
IEC 61280-1-3	-	Fibre optic communication subsystem test procedures - Part 1-3: General communication subsystems - Central wavelength and spectral width measurement	EN 61280-1-3	-
IEC 61280-4-1	2019	Fibre-optic communication subsystem test procedures - Part 4-1: Installed cabling plant - Multimode attenuation measurement	EN IEC 61280-4-1	2019
IEC 61300-3-35	-	Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 3-35: Examinations and measurements - Visual inspection of fibre optic connectors and fibre-stub transceivers	EN 61300-3-35	-
IEC 61315	-	Calibration of fibre-optic power meters	EN IEC 61315	-
IEC 61746-1	-	Calibration of optical time-domain reflectometers (OTDR) - Part 1: OTDR for single mode fibres	EN 61746-1	-
IEC 61746-2	-	Calibration of optical time-domain reflectometers (OTDR) - Part 2: OTDR for multimode fibres	EN 61746-2	-



IEC 61280-4-5

Edition 1.0 2020-07

# INTERNATIONAL STANDARD



**Fibre-optic communication subsystem test procedures –  
Part 4-5: Installed cabling plant – Attenuation measurement of MPO terminated  
fibre optic cabling plant using test equipment with MPO interfaces**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2020 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.



IEC 61280-4-5

Edition 1.0 2020-07

# INTERNATIONAL STANDARD



---

**Fibre-optic communication subsystem test procedures –  
Part 4-5: Installed cabling plant – Attenuation measurement of MPO terminated  
fibre optic cabling plant using test equipment with MPO interfaces**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.180.01

ISBN 978-2-8322-8670-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**



## CONTENTS

FOREWORD.....	7
1 Scope.....	9
2 Normative references .....	9
3 Terms, definitions, graphical symbols and abbreviated terms.....	10
3.1 Terms and definitions.....	10
3.2 Graphical symbols .....	12
3.3 Abbreviated terms.....	14
4 Test methods.....	14
4.1 General.....	14
4.2 Cabling configurations and applicable test methods .....	15
5 Overview of uncertainties .....	16
5.1 General.....	16
5.2 Sources of significant uncertainties.....	16
5.3 Consideration of the PM.....	17
5.4 Consideration of test cord connector grade .....	17
5.5 Typical uncertainty values for multimode testing .....	17
5.6 Typical uncertainty values for single-mode testing .....	19
6 Apparatus.....	20
6.1 General.....	20
6.2 Light source .....	20
6.2.1 General .....	20
6.2.2 Stability .....	20
6.2.3 Spectral characteristics (LSPM measurement).....	21
6.3 Launch cord .....	21
6.4 Receive or tail cord.....	22
6.5 Substitution cord.....	22
6.6 Adapter cord .....	23
6.7 Power meter – LSPM methods only.....	23
6.8 OTDR apparatus.....	24
6.9 Connector end face cleaning and inspection equipment .....	24
6.10 Adapters .....	24
7 Procedures.....	24
7.1 General.....	24
7.2 Common procedures.....	25
7.2.1 Care of the test cords .....	25
7.2.2 Take reference measurements.....	25
7.2.3 Inspect and clean the ends of the optical fibres in the cabling.....	25
7.2.4 Take the measurements .....	25
7.2.5 Make the calculations .....	25
7.2.6 Multi-fibre and bi-directional testing .....	25
7.3 Calibration .....	26
7.4 Safety .....	26
8 Calculations.....	26
9 Documentation .....	26
9.1 Information for each test .....	26
9.2 Information to be available .....	26

Annex A (normative) One-cord method .....	27
A.1 Applicability of the test method .....	27
A.2 Apparatus .....	27
A.3 Procedure for unpinned to unpinned cabling with unpinned power meter.....	27
A.4 Procedure for unpinned to pinned cabling with unpinned power meter .....	28
A.5 Procedure for pinned to pinned cabling with pinned power meter .....	29
A.6 Procedure for unpinned to unpinned cabling with pinned power meter and gender-neutral test cord .....	30
A.7 Calculation.....	31
A.8 Components of reported attenuation .....	31
Annex B (normative) Three-cord method.....	32
B.1 Applicability of the test method .....	32
B.2 Apparatus .....	32
B.3 Procedure for unpinned to unpinned cabling .....	32
B.4 Procedure for unpinned to pinned cabling .....	33
B.5 Procedure for pinned to pinned cabling .....	34
B.6 Procedure, channel test (general) .....	35
B.7 Calculations .....	36
B.8 Components of reported attenuation .....	36
Annex C (normative) Adapter-cord method .....	37
C.1 Applicability of the test method .....	37
C.2 Apparatus .....	37
C.3 Procedure for unpinned to unpinned cabling with pinned power meter .....	37
C.4 Procedure for unpinned to pinned cabling with pinned power meter .....	38
C.5 Procedure for pinned to unpinned cabling with unpinned power meter .....	39
C.6 Procedure for pinned to pinned cabling with unpinned power meter .....	40
C.7 Calculations .....	41
C.8 Components of reported attenuation .....	42
Annex D (normative) Equipment cord method .....	43
D.1 Applicability of the test method .....	43
D.2 Apparatus .....	43
D.3 Procedure .....	43
D.4 Calculation.....	44
D.5 Components of reported attenuation .....	44
D.6 Typical uncertainty values.....	45
Annex E (normative) Optical time domain reflectometer .....	46
E.1 Applicability of the test method .....	46
E.2 Apparatus .....	46
E.2.1 General .....	46
E.2.2 OTDR .....	46
E.2.3 Test cords .....	47
E.3 Procedure (test method) .....	47
E.4 Calculation.....	48
E.4.1 General .....	48
E.4.2 Connection location .....	48
E.4.3 Definition of the power levels $F_1$ and $F_2$ .....	49
E.4.4 Alternative calculation.....	50
E.5 OTDR uncertainties .....	52

Annex F (normative) Requirements for the multimode source characteristics .....	53
Annex G (informative) OTDR configuration information .....	54
G.1 General.....	54
G.2 Other measurement configurations .....	54
G.2.1 General .....	54
G.2.2 Measurement with low return loss connectors or short length cabling .....	54
G.2.3 Measurement with APC connectors .....	56
Annex H (informative) Test cord, breakout cord, and cassette attenuation verification .....	58
H.1 General.....	58
H.2 Apparatus .....	58
H.3 General procedure .....	58
H.3.1 Overview .....	58
H.3.2 Test cord verification .....	59
H.3.3 Cassette and breakout cord verification .....	60
H.4 Test cord verification prior to cabling measurement .....	61
H.4.1 General .....	61
H.4.2 Procedure for unpinned to unpinned cabling measurement .....	61
H.4.3 Procedure for unpinned to pinned cabling measurement.....	62
H.4.4 Procedure for pinned to pinned cabling measurement.....	63
Annex I (normative) On the use of low attenuation grade test cords .....	66
I.1 General.....	66
I.2 Practical configurations and assumptions.....	66
I.2.1 Component specifications .....	66
I.2.2 Conventions .....	67
I.2.3 Reference planes .....	67
I.3 Impact of using low attenuation grade test cords for recommended LSPM methods.....	68
I.4 Examples for LSPM measurements.....	68
I.4.1 Example 1: Configuration Au-u, 1-C method (Annex A).....	68
I.4.2 Example 2: Configuration Du-u, EC method (Annex D) .....	69
I.5 Impact of using reference grade test cords for different configurations using the OTDR test method .....	69
I.5.1 Cabling configurations Au-u, Ap-u and Ap-p .....	69
I.5.2 Cabling configuration Du-u .....	70
Bibliography.....	72
Figure 1 – Connector and apparatus symbols .....	13
Figure 2 – Symbol for cabling under test.....	14
Figure 3 – OTDR schematic with external optical switch .....	24
Figure A.1 – Reference measurement for unpinned to unpinned cabling using unpinned power meter.....	28
Figure A.2 – Test measurement for unpinned to unpinned cabling using unpinned power meter.....	28
Figure A.3 – Reference measurement for unpinned to pinned cabling using unpinned power meter.....	29
Figure A.4 – Test measurement for unpinned to pinned cabling using unpinned power meter.....	29
Figure A.5 – Reference measurement for pinned to pinned cabling using pinned power meter.....	30

Figure A.6 – Test measurement for pinned to pinned cabling using pinned power meter .....	30
Figure A.7 – Reference measurement for unpinned to unpinned cabling using pinned power meter.....	31
Figure A.8 – Test measurement for unpinned to unpinned cabling (gender-neutral TC1) using pinned power meter.....	31
Figure B.1 – Reference measurement for unpinned to unpinned cabling using pinned power meter.....	33
Figure B.2 – Test measurement for unpinned to unpinned cabling using pinned power meter.....	33
Figure B.3 – Reference measurement for unpinned to pinned cabling using pinned power meter.....	34
Figure B.4 – Test measurement for unpinned to pinned cabling using pinned power meter.....	34
Figure B.5 – Reference measurement for pinned to pinned cabling using unpinned power meter.....	35
Figure B.6 – Test measurement for pinned to pinned cabling using unpinned power meter.....	35
Figure B.7 – Reference measurement for channel test using unpinned power meter .....	36
Figure B.8 – Test measurement for channel test using unpinned power meter .....	36
Figure C.1 – Reference measurement for unpinned to unpinned cabling using pinned power meter.....	38
Figure C.2 – Test measurement for unpinned to unpinned cabling using pinned power meter.....	38
Figure C.3 – Reference measurement for unpinned to pinned cabling using pinned power meter.....	39
Figure C.4 – Test measurement for unpinned to pinned cabling using pinned power meter.....	39
Figure C.5 – Reference measurement for unpinned to pinned cabling using unpinned power meter.....	40
Figure C.6 – Test measurement for unpinned to pinned cabling using unpinned power meter.....	40
Figure C.7 – Reference measurement for unpinned to pinned cabling using unpinned power meter.....	41
Figure C.8 – Test measurement for unpinned to pinned cabling using unpinned power meter.....	41
Figure D.1 – Reference measurement using pinned power meter.....	44
Figure D.2 – Test measurement using pinned power meter .....	44
Figure E.1 – OTDR method.....	48
Figure E.2 – Location of the ports of the cabling under test.....	49
Figure E.3 – Graphic construction of $F_1$ and $F_2$ .....	50
Figure E.4 – Graphic construction of $F_1$ , $F_{11}$ , $F_{12}$ and $F_2$ .....	51
Figure G.1 – Attenuation measurement with low return loss connectors .....	55
Figure G.2 – Attenuation measurement of a short length cabling.....	56
Figure G.3 – Attenuation measurement with APC MPO connections .....	57
Figure H.1 – Obtaining reference power level $P_1$ .....	59
Figure H.2 – Obtaining power level $P_2$ .....	59
Figure H.3 – Obtaining reference power level $P_1$ .....	60

Figure H.4 – Obtaining power level $P_2$ .....	60
Figure H.5 – Test measurement for unpinned to unpinned cabling .....	61
Figure H.6 – Step 1: obtaining reference power level $P_1$ .....	61
Figure H.7 – Step 2: verification cords, obtaining power level $P_2$ .....	62
Figure H.8 – Test measurement for unpinned to pinned cabling .....	62
Figure H.9 – Step 1: obtaining reference power level $P_1$ .....	63
Figure H.10 – Step 2: obtaining power level $P_2$ .....	63
Figure H.11 – Test measurement for pinned to pinned cabling .....	63
Figure H.12 – Step 1: obtaining reference power level $P_1$ .....	64
Figure H.13 – Step 2: verification of cords, obtaining power level $P_2$ .....	64
Figure H.14 – Step 3: verification of receive cord, obtaining power level $P_3$ .....	65
Figure I.1 – Cabling configurations Au-u, Ap-u and Ap-p tested with OTDR method .....	70
Figure I.2 – Cabling configuration Du-u tested with OTDR method .....	71
Table 1 – Cabling configurations .....	16
Table 2 – Test methods and configurations .....	16
Table 3 – Measurements bias related to test cord connector grade .....	17
Table 4 – Uncertainty for a given attenuation at 850 nm using same photodetector .....	18
Table 5 – Uncertainty for a given attenuation at 850 nm using different photodetectors .....	19
Table 6 – Uncertainty for a given attenuation at 1 310 nm using same photodetector .....	19
Table 7 – Uncertainty for a given attenuation at 1 310 nm using different photodetectors .....	20
Table 8 – Spectral requirements .....	21
Table D.1 – Uncertainty for a given attenuation when equipment cord method is used .....	45
Table I.1 – Measurement bias adjustment when using low attenuation grade test cords .....	68
Table I.2 – Acceptance figure adjustment using low attenuation grade test cords – OTDR method .....	70

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE-OPTIC COMMUNICATION SUBSYSTEM TEST PROCEDURES –****Part 4-5: Installed cabling plant –  
Attenuation measurement of MPO terminated fibre  
optic cabling plant using test equipment with MPO interfaces**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61280-4-5 has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
86C/1669/FDIS	86C/1679/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

A list of all the parts in the IEC 61280 series, under the general title *Fibre-optic communication subsystem test procedures*, can be found on the IEC website.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## FIBRE-OPTIC COMMUNICATION SUBSYSTEM TEST PROCEDURES –

### Part 4-5: Installed cabling plant – Attenuation measurement of MPO terminated fibre optic cabling plant using test equipment with MPO interfaces

#### 1 Scope

This part of IEC 61280 is applicable to the measurement of attenuation and determination of polarity and length of installed multimode and single-mode optical fibre cabling plant, terminated with MPO connectors, using test equipment having an MPO interface. This cabling plant can include multimode or single-mode optical fibres, connectors, adapters, splices, and other passive devices. The cabling can be installed in a variety of environments including residential, commercial, industrial, and data centre premises, as well as outside plant environments.

In this document, the optical fibres that are addressed include sub-categories A1-OM<sub>x</sub>, where  $x = 2, 3, 4$  and  $5$  (50/125  $\mu\text{m}$ ) multimode optical fibres, as specified in IEC 60793-2-10, and category B-652 and B-657 (9/125  $\mu\text{m}$ ) single-mode optical fibres, as specified in IEC 60793-2-50. The attenuation measurements of the other multimode and single-mode categories can also be made using a light source and power meter (LSPM) or optical time domain reflectometer (OTDR) utilising an internal or external optical switch having one MPO interface. Multimode measurements are made with an 850 nm source because transceivers used for parallel optics applications having an MPO interface only operate at 850 nm; 1 300 nm measurements are optional. Single-mode measurements are made with a 1 310 nm and/or 1 550 nm source because transceivers used for parallel optics applications having an MPO interface operate at these wavelengths. This document does not include descriptions of cabling that is not exclusively MPO to MPO.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60825 (all parts), *Safety of laser products*

IEC 61280-1-3, *Fibre optic communication subsystem test procedures – Part 1-3: General communication subsystems – Central wavelength and spectral width measurement*

IEC 61280-4-1:2019, *Fibre-optic communication subsystem test procedures – Part 4-1: Installed cabling plant – Multimode attenuation measurement*

IEC 61300-3-35, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-35: Examinations and measurements – Visual inspection of fibre optic connectors and fibre-stub transceivers*

IEC 61315, *Calibration of fibre-optic power meters*

IEC 61746-1, *Calibration of optical time-domain reflectometers (OTDR) – Part 1: OTDR for single mode fibres*



IEC 61746-2, *Calibration of optical time-domain reflectometers (OTDR) – Part 2: OTDR for multimode fibres*

**koniec náhľadu – text ďalej pokračuje v platenej verzii STN**