

STN	Železnice Brzdenie Protišmykové zariadenia Oprava AC	STN EN 15595/AC 28 4020
------------	---	---

Railway applications - Braking - Wheel slide protection

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 07/21

Obsahuje: EN 15595: 2018/AC:2021

133060

EUROPEAN STANDARD

EN 15595:2018/AC

NORME EUROPÉENNE

February 2021

EUROPÄISCHE NORM

ICS 45.040

English version

Railway applications - Braking - Wheel slide protection

Applications ferroviaires - Freinage - Anti-
enrayeur

Bahnanwendungen - Bremse - Gleitschutz

This corrigendum becomes effective on 17 February 2021 for incorporation in the official English version of the EN.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2021 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.
Tous droits d'exploitation sous quelque forme et de quelque manière que ce soit réservés dans le monde entier
aux membres nationaux du CEN.
Alle Rechte der Verwertung, gleich in welcher Form und in welchem Verfahren, sind weltweit den nationalen
Mitgliedern von CEN vorbehalten.

Ref. No.: EN 15595:2018/AC:2021 E

EN 15595:2018/AC:2021 (E)**1 Modification to 8.3.3.3.1, Calculation of criterion of minimum slide**

Replace the 1st sentence:

"The GM(n)-value shall be calculated for the first braked wheelsets up to six, after spraying:"

with:

"The GM(n)-value shall be calculated for all the first six braked wheelsets after spraying (or all braked wheelsets after spraying if there are 6 or less braked wheelset after spraying):".

2 Modification to 8.3.3.3.2, Minimum slide criterion 1

Replace the 2nd sentence:

"The GM(n)-value shall be calculated for the first braked wheelsets up to six, after spraying."

with:

"The GM(n)-value shall be calculated for all the first six braked wheelsets after spraying (or all braked wheelsets after spraying if there are 6 or less braked wheelset after spraying).".

3 Modification to 8.3.3.3.3, Minimum slide criterion 2

Replace the 2nd sentence:

"The GM(n)-value shall be calculated for the first braked wheelsets up to six, after spraying."

with:

"The GM(n)-value shall be calculated for all the first six braked wheelsets after spraying (or all braked wheelsets after spraying if there are 6 or less braked wheelset after spraying).".

