STN	Malé lekárske plynové nádoby Strmeňové ventilové spoje Pin-index (ISO 407: 2021)	STN EN ISO 407
		07 8610

Small medical gas cylinders — Pin-index yoke-type valve connections

Táto norma obsahuje anglickú verziu európskej normy. This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 08/21

Obsahuje: EN ISO 407:2021, ISO 407:2021

Oznámením tejto normy sa ruší STN EN ISO 407 (07 8610) z mája 2005 STN EN ISO 407: 2021

### EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

**EN ISO 407** 

June 2021

ICS 11.040.10

Supersedes EN ISO 407:2004

#### **English Version**

## Small medical gas cylinders - Pin-index yoke-type valve connections (ISO 407:2021)

Petites bouteilles à gaz médicaux - Raccords de robinets du type étrier avec ergots de sécurité (ISO 407:2021)

Kleine Gasflaschen für die medizinische Anwendung -Ventilseitenstutzen mit Anschlussbügel nach dem PIN-Index-System (ISO 407:2021)

This European Standard was approved by CEN on 13 May 2021.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	3

#### **European foreword**

This document (EN ISO 407:2021) has been prepared by Technical Committee ISO/TC 58 "Gas cylinders" in collaboration with Technical Committee CEN/TC 23 "Transportable gas cylinders" the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2021, and conflicting national standards shall be withdrawn at the latest by December 2021.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 407:2004.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

#### **Endorsement notice**

The text of ISO 407:2021 has been approved by CEN as EN ISO 407:2021 without any modification.

# INTERNATIONAL STANDARD

**ISO 407** 

Fourth edition 2021-06

# Small medical gas cylinders — Pinindex yoke-type valve connections

Petites bouteilles à gaz médicaux — Raccords de robinets du type étrier avec ergots de sécurité



ISO 407:2021(E)



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Foreword ivalent Scope 1 1 1 Scope 1 1 2 Normative references 1 1 3 Terms and definitions 1 1 4 Valve 1 1 5 Yoke 2 1 5 Yoke 2 2 6 Basic dimensions 2 6.1 General 2 6.2 Pin-index yoke-type valve body. 3 6.3 Single-pin yoke-type valve connection system 4 6.4 Two-pin yoke-type valve connection system with the pins in a single row 4 6.5 Two-pin yoke-type valve connection system with the pins in a double row 5 6.6 Basic dimensions 5 5 7 Requirements for alternative designs of yoke-type valve connections yoke 6 7.2 Examples of alternative construction for the connecting yoke 6 6 7.2 Examples of alternative construction for the connecting yoke 6 6 7.2 Examples of alternative construction for the connecting yoke 6 8 Dimensions and positions of the holes and pins for yoke-type valve connections 9 8.1 General 9 8.2 Outlet connection with single-pin system 9 8.3 Outlet connection with single-pin system 9 8.3 Outlet connection for oxygen 10 8.3.1 Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7\%$ ) 11 8.3.3 Outlet connection for oxygen/helium mixture ( $He \le 80\%$ ) 11 8.3.4 Outlet connection for oxygen/helium mixture ( $He \le 80\%$ ) 11 8.3.5 Outlet connection for introus oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 12 8.3.6 Outlet connection for cyclopropane 12 8.3.7 Outlet connection for cyclopropane 12 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 12 8.3.9 Outlet connection for carbon dioxide (with or without liquid draw-off) 14 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection with two-pin/double-row system 15	Co	ntents		Page
Normative references	Foreword			iv
Terms and definitions14Valve15Yoke26Basic dimensions26.1General26.2Pin-index yoke-type valve body36.3Single-pin yoke-type valve connection system46.4Two-pin yoke-type valve connection system with the pins in a single row46.5Two-pin yoke-type valve connection system with the pins in a double row56.6Basic dimensions57Requirements for alternative designs of yoke-type valve connections67.1Requirements for the design of the connecting yoke67.2Examples of alternative construction for the connecting yoke68Dimensions and positions of the holes and pins for yoke-type valve connections98.1General98.2Outlet connection with single-pin system98.3Outlet connection for oxygen108.3.1Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 < 7 \%$ )118.3.2Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 < 7 \%$ )118.3.4Outlet connection for ethylene128.3.5Outlet connection for procyclopropane138.3.6Outlet connection for carbon dioxide (with or without liquid draw-off)128.3.7Outlet connection for carbon dioxide (with or without liquid draw-off)148.3.9Outlet connection for medical air148.3.9Outlet connection for medical air14 <t< th=""><th>1</th><th>Scope</th><th></th><th>1</th></t<>	1	Scope		1
4 Valve	2	Norma	ative references	1
5Yoke26Basic dimensions26.1General26.2Pin-index yoke-type valve body36.3Single-pin yoke-type valve connection system46.4Two-pin yoke-type valve connection system with the pins in a single row46.5Two-pin yoke-type valve connection system with the pins in a double row56.6Basic dimensions57Requirements for alternative designs of yoke-type valve connections67.1Requirements for the design of the connecting yoke67.2Examples of alternative construction for the connecting yoke68Dimensions and positions of the holes and pins for yoke-type valve connections98.1General98.2Outlet connection with single-pin system98.3Outlet connections with two-pin/single-row system108.3.1Outlet connection for oxygen108.3.2Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7$ %)118.3.3Outlet connection for oxygen/helium mixture (He ≤ 80%)118.3.4Outlet connection for rethylene128.3.5Outlet connection for ritrous oxide (with or without liquid draw-off)128.3.6Outlet connection for helium and for helium/oxygen mixture ( $CO_2 < 20$ %)138.3.8Outlet connection for carbon dioxide (with or without liquid draw-off)148.3.9Outlet connection for medical air148.3.10Outlet connection for medical air1	3	Terms	and definitions	1
6       Basic dimensions       2         6.1       General       2         6.2       Pin-index yoke-type valve body       3         6.3       Single-pin yoke-type valve connection system       4         6.4       Two-pin yoke-type valve connection system with the pins in a single row       4         6.5       Two-pin yoke-type valve connection system with the pins in a double row       5         6.6       Basic dimensions       5         7       Requirements for alternative designs of yoke-type valve connections       6         7.1       Requirements for the design of the connecting yoke       6         7.2       Examples of alternative construction for the connecting yoke       6         8       Dimensions and positions of the holes and pins for yoke-type valve connections       9         8.1       General       9         8.2       Outlet connection with single-pin system       9         8.3       Outlet connections with two-pin/single-row system       10         8.3.1       Outlet connection for oxygen       10         8.3.2       Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7$ %)       11         8.3.3       Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7$ %)       11         8.3.4       Outlet connecti	4	Valve		1
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	5	Yoke		2
6.2 Pin-index yoke-type valve body 6.3 Single-pin yoke-type valve connection system 6.4 Two-pin yoke-type valve connection system with the pins in a single row. 6.5 Two-pin yoke-type valve connection system with the pins in a double row 6.6 Basic dimensions  7 Requirements for alternative designs of yoke-type valve connections 7.1 Requirements for the design of the connecting yoke 7.2 Examples of alternative construction for the connecting yoke 6 The connection system 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the holes and pins for yoke-type valve connections 9 Summarisms and positions of the connection for oxygen wisture (CO₂ ≤ 7 %) 11 Summarisms and positions of the holes and pins for yoke-type valve connection for ethylene 12 Summarisms and positions of the connection for ethylene 13 Summarisms and positions of the pins in a single row single value for the pins in a double forms and for connection for ethylene 12 Summarisms and positions of the connection for ethylene 13 Summarisms and positions of the connection for ethylene 14 Summarisms and positions and positions and pins for pins for pins for definitions and pins for pins for pins for definitions and pins for pins f	6	Basic o	dimensions	2
6.3 Single-pin yoke-type valve connection system		6.1	General	2
6.4 Two-pin yoke-type valve connection system with the pins in a single row 6.5 Two-pin yoke-type valve connection system with the pins in a double row 5 6.6 Basic dimensions 5  7 Requirements for alternative designs of yoke-type valve connections 6  7.1 Requirements for the design of the connecting yoke 6  7.2 Examples of alternative construction for the connecting yoke 6  8 Dimensions and positions of the holes and pins for yoke-type valve connections 9  8.1 General 9  8.2 Outlet connection with single-pin system 9  8.3 Outlet connections with two-pin/single-row system 10  8.3.1 Outlet connection for oxygen 10  8.3.2 Outlet connection for oxygen/carbon dioxide mixture (CO₂ ≤ 7 %) 11  8.3.3 Outlet connection for oxygen/helium mixture (He ≤ 80 %) 11  8.3.4 Outlet connection for ethylene 12  8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12  8.3.6 Outlet connection for cyclopropane 13  8.3.7 Outlet connection for cyclopropane 13  8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 13  8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 14  8.3.9 Outlet connection for medical air 14  8.3.10 Outlet connection for medical air 14  8.3.10 Outlet connection for nitrogen 15		6.2	Pin-index yoke-type valve body	3
6.5 Two-pin yoke-type valve connection system with the pins in a double row 6.6 Basic dimensions 5  Requirements for alternative designs of yoke-type valve connections 7.1 Requirements for the design of the connecting yoke 6 7.2 Examples of alternative construction for the connecting yoke 6  Bimensions and positions of the holes and pins for yoke-type valve connections 9 8.1 General 9 8.2 Outlet connection with single-pin system 9 8.3 Outlet connections with two-pin/single-row system 10 8.3.1 Outlet connection for oxygen 10 8.3.2 Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7\%$ ) 11 8.3.3 Outlet connection for oxygen/helium mixture ( $EV_2 \le 7\%$ ) 11 8.3.4 Outlet connection for ethylene 12 8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for helium and for helium/oxygen mixture ( $V_2 \le 7\%$ ) 13 8.3.7 Outlet connection for carbon dioxide (with or without liquid draw-off) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 14 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for mitrogen 15		6.3		
6.6Basic dimensions.57Requirements for alternative designs of yoke-type valve connections.67.1Requirements for the design of the connecting yoke.67.2Examples of alternative construction for the connecting yoke.68Dimensions and positions of the holes and pins for yoke-type valve connections.98.1General.98.2Outlet connection with single-pin system.98.3Outlet connections with two-pin/single-row system.108.3.1Outlet connection for oxygen.108.3.2Outlet connection for oxygen/carbon dioxide mixture $(CO_2 \le 7\%)$ .118.3.3Outlet connection for oxygen/helium mixture (He $\le 80\%$ ).118.3.4Outlet connection for ethylene.128.3.5Outlet connection for nitrous oxide (with or without liquid draw-off).128.3.6Outlet connection for cyclopropane.138.3.7Outlet connection for helium and for helium/oxygen mixture $(O_2 < 20\%)$ .138.3.8Outlet connection for carbon dioxide (with or without liquid draw-off).148.3.9Outlet connection for medical air.148.3.10Outlet connection for nitrogen.15		6.4		
7Requirements for alternative designs of yoke-type valve connections67.1Requirements for the design of the connecting yoke67.2Examples of alternative construction for the connecting yoke68Dimensions and positions of the holes and pins for yoke-type valve connections98.1General98.2Outlet connection with single-pin system98.3Outlet connections with two-pin/single-row system108.3.1Outlet connection for oxygen108.3.2Outlet connection for oxygen/carbon dioxide mixture $(CO_2 \le 7 \%)$ 118.3.3Outlet connection for oxygen/helium mixture $(He \le 80 \%)$ 118.3.4Outlet connection for ethylene128.3.5Outlet connection for introus oxide (with or without liquid draw-off)128.3.6Outlet connection for cyclopropane138.3.7Outlet connection for helium and for helium/oxygen mixture $(O_2 < 20 \%)$ 138.3.8Outlet connection for carbon dioxide (with or without liquid draw-off)148.3.9Outlet connection for medical air148.3.10Outlet connection for nitrogen15		6.5		
7.1Requirements for the design of the connecting yoke67.2Examples of alternative construction for the connecting yoke68Dimensions and positions of the holes and pins for yoke-type valve connections98.1General98.2Outlet connection with single-pin system98.3Outlet connections with two-pin/single-row system108.3.1Outlet connection for oxygen108.3.2Outlet connection for oxygen/carbon dioxide mixture $(CO_2 \le 7 \%)$ 118.3.3Outlet connection for oxygen/helium mixture $(He \le 80 \%)$ 118.3.4Outlet connection for ethylene128.3.5Outlet connection for nitrous oxide (with or without liquid draw-off)128.3.6Outlet connection for cyclopropane138.3.7Outlet connection for helium and for helium/oxygen mixture $(O_2 < 20 \%)$ 138.3.8Outlet connection for carbon dioxide (with or without liquid draw-off)148.3.9Outlet connection for medical air148.3.10Outlet connection for nitrogen15		6.6	Basic dimensions	5
7.2 Examples of alternative construction for the connecting yoke 6  8 Dimensions and positions of the holes and pins for yoke-type valve connections 9  8.1 General 9  8.2 Outlet connection with single-pin system 9  8.3 Outlet connections with two-pin/single-row system 10  8.3.1 Outlet connection for oxygen 10  8.3.2 Outlet connection for oxygen/carbon dioxide mixture $(CO_2 \le 7 \%)$ 11  8.3.3 Outlet connection for oxygen/helium mixture $(He \le 80 \%)$ 11  8.3.4 Outlet connection for ethylene 12  8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12  8.3.6 Outlet connection for cyclopropane 13  8.3.7 Outlet connection for helium and for helium/oxygen mixture $(O_2 < 20 \%)$ 13  8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 14  8.3.9 Outlet connection for medical air 14  8.3.10 Outlet connection for nitrogen 15	7	Requir	rements for alternative designs of yoke-type valve connections	6
8Dimensions and positions of the holes and pins for yoke-type valve connections98.1General98.2Outlet connection with single-pin system98.3Outlet connections with two-pin/single-row system108.3.1Outlet connection for oxygen108.3.2Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7\%$ )118.3.3Outlet connection for oxygen/helium mixture ( $EV_2 \le 7\%$ )118.3.4Outlet connection for ethylene128.3.5Outlet connection for nitrous oxide (with or without liquid draw-off)128.3.6Outlet connection for cyclopropane138.3.7Outlet connection for helium and for helium/oxygen mixture ( $CV_2 \le 7\%$ )138.3.8Outlet connection for carbon dioxide (with or without liquid draw-off)148.3.9Outlet connection for medical air148.3.10Outlet connection for nitrogen15			Requirements for the design of the connecting yoke	6
8.1 General 9 8.2 Outlet connection with single-pin system 9 8.3 Outlet connections with two-pin/single-row system 10 8.3.1 Outlet connection for oxygen 10 8.3.2 Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7\%$ ) 11 8.3.3 Outlet connection for oxygen/helium mixture ( $CO_2 \le 7\%$ ) 11 8.3.4 Outlet connection for ethylene 12 8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 13 8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $CO_2 \le 20\%$ ) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 11 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for nitrogen 15				
8.2 Outlet connection with single-pin system 9 8.3 Outlet connections with two-pin/single-row system 10 8.3.1 Outlet connection for oxygen 10 8.3.2 Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7\%$ ) 11 8.3.3 Outlet connection for oxygen/helium mixture ( $EV_2 \le 7\%$ ) 11 8.3.4 Outlet connection for ethylene 12 8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 13 8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $EV_2 \le 20\%$ ) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 11 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for nitrogen 15	8		isions and positions of the holes and pins for yoke-type valve connections	9
8.3 Outlet connections with two-pin/single-row system				
8.3.1 Outlet connection for oxygen 10 8.3.2 Outlet connection for oxygen/carbon dioxide mixture ( $CO_2 \le 7\%$ ) 11 8.3.3 Outlet connection for oxygen/helium mixture ( $EV_2 \le 7\%$ ) 11 8.3.4 Outlet connection for ethylene 12 8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 13 8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $EV_2 \le 20\%$ ) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) 13 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for nitrogen 15			Outlet connection with single-pin system	9
8.3.2 Outlet connection for oxygen/carbon dioxide mixture ( $\mathrm{CO_2} \le 7\%$ ) 11 8.3.3 Outlet connection for oxygen/helium mixture ( $\mathrm{He} \le 80\%$ ) 11 8.3.4 Outlet connection for ethylene 12 8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 13 8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $\mathrm{O_2} < 20\%$ ) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture ( $\mathrm{CO_2} > 7\%$ ) 14 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for nitrogen 15		8.3		
8.3.3 Outlet connection for oxygen/helium mixture (He $\leq$ 80 %) 11 8.3.4 Outlet connection for ethylene 12 8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 13 8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $O_2 < 20$ %) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture ( $O_2 > 7$ %) 14 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for nitrogen 15				
8.3.4 Outlet connection for ethylene			0.5.2 Outlet connection for oxygen/carbon dioxide illixture ( $CO_2 \le 7 \%$ )	11
8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off) 12 8.3.6 Outlet connection for cyclopropane 13 8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $O_2 < 20$ %) 13 8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture ( $O_2 > 7$ %) 14 8.3.9 Outlet connection for medical air 14 8.3.10 Outlet connection for nitrogen 15				
8.3.6 Outlet connection for cyclopropane				
8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $O_2 < 20 \%$ )				
8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture (CO <sub>2</sub> > 7 %)			8 3 7 Outlet connection for helium and for helium/oxygen mixture (0 < 20 %)	13
and for carbon dioxide/oxygen mixture ( $\mathrm{CO_2} > 7$ %)				13
8.3.9 Outlet connection for medical air				14
8.3.10 Outlet connection for nitrogen15			8.3.9 Outlet connection for medical air	14
		8.4		

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinders fittings*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 23, *Transportable gas cylinders*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fourth edition cancels and replaces the third edition (ISO 407:2004), which has been technically revised.

The main changes compared to the previous edition are as follows:

- addition of a note in <u>Figure 1</u> on the introduction of a radius to avoid stress concentration;
- addition of dimension *m* in Figure 1;
- revision of the basic dimensions for pin index yoke type value connections (see <u>Table 2</u>);
- addition of a requirement for the design of the connecting yoke.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

#### INTERNATIONAL STANDARD

## Small medical gas cylinders — Pin-index yoke-type valve connections

#### 1 Scope

This document is applicable to pin-index yoke-type valve connections for medical gas cylinders, with a working pressure up to a maximum of 200 bar or test pressure up to a maximum of 300 bar, or both.

NOTE 1 This type of connection is primarily used for small cylinders (5 l or below).

NOTE 2 In this document the unit bar is used, due to its universal use in the field of technical gases. It should, however, be noted that bar is not an SI unit, and that the corresponding SI unit for pressure is Pa (1 bar =  $10^5$  Pa =  $10^5$  N/m<sup>2</sup>).

This document specifies:

- basic dimensions;
- requirements for alternative designs of the yoke-type valve connections;
- dimensions and positions for the holes and pins for the outlet connections.

It also specifies the dimensions and positions for the holes and pins for the outlet connections for gases and gas mixtures.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 32, Gas cylinders for medical use — Marking for identification of content

koniec náhľadu – text ďalej pokračuje v platenej verzii STN