

STN	<p>Družicové zemské stanice a systémy (SES) Družicové pohyblivé lietadlové zemské stanice (AES) pracujúce vo frekvenčných pásmach 11/12/14 GHz Harmonizovaná norma pre prístup k rádiovému spektru</p>	<p>STN EN 302 186 V2.2.1</p>
		87 2186

Satellite Earth Stations and Systems (SES); Satellite mobile Aircraft Earth Stations (AESs) operating in the 11/12/14 GHz frequency bands;
Harmonised Standard for access to radio spectrum

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 09/21

Obsahuje: EN 302 186 V2.2.1:2021

133655

ETSI EN 302 186 v2.2.1 (2021-05)



**Satellite Earth Stations and Systems (SES);
Satellite mobile Aircraft Earth Stations (AESS)
operating in the 11/12/14 GHz frequency bands;
Harmonised Standard for access to radio spectrum**

ReferenceREN/SES-00435

Keywords

aeronautical, air interface, AMSS, earth station,
FSS, GSO, mobile, MSS, regulation, satellite

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction	8
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	15
3.3 Abbreviations	15
4 Technical requirement specifications.....	16
4.1 General	16
4.1.0 Introduction.....	16
4.1.1 Environmental profile	16
4.2 Conformance requirements	17
4.2.1 General.....	17
4.2.2 Off-axis spurious radiation	17
4.2.2.1 Justification	17
4.2.2.2 Specification.....	17
4.2.2.3 Conformance tests.....	19
4.2.3 On-axis spurious radiation.....	19
4.2.3.1 Justification	19
4.2.3.2 Specification.....	19
4.2.3.2.1 "Carrier-on" state	19
4.2.3.2.2 "Carrier-off" state and "transmission disabled" state.....	20
4.2.3.3 Conformance tests.....	20
4.2.4 Off-axis EIRP emissions density in the nominated bandwidth for 14 GHz AES and the power flux-density resulting from the 13 GHz AES towards any location in the geostationary-satellite orbit.....	20
4.2.4.1 Justification	20
4.2.4.2 Specification.....	20
4.2.4.2.1 14 GHz AES	20
4.2.4.2.2 13 GHz AES	21
4.2.4.3 Conformance tests.....	21
4.2.5 Control and Monitoring Functions (CMFs).....	21
4.2.5.0 General	21
4.2.5.1 Processor monitoring	22
4.2.5.1.1 Justification	22
4.2.5.1.2 Specification.....	22
4.2.5.1.3 Conformance tests	22
4.2.5.2 Transmit subsystem monitoring.....	23
4.2.5.2.1 Justification	23
4.2.5.2.2 Specification.....	23
4.2.5.2.3 Conformance tests	23
4.2.5.3 Power-on/Reset	23
4.2.5.3.1 Justification	23
4.2.5.3.2 Specification.....	23
4.2.5.3.3 Conformance tests	23
4.2.5.4 Control Channel (CC) reception	23
4.2.5.4.1 Justification	23
4.2.5.4.2 Specification.....	23
4.2.5.4.3 Conformance tests	23
4.2.5.5 Network control commands	24

4.2.5.5.1	Justification	24
4.2.5.5.2	Specification.....	24
4.2.5.5.3	Conformance tests	24
4.2.5.6	Initial burst transmission	24
4.2.5.6.1	General	24
4.2.5.6.2	Specification.....	24
4.2.5.6.3	Conformance tests	25
4.2.6	Power Flux Density at the surface of the earth	25
4.2.6.0	General.....	25
4.2.6.1	14 GHz AES.....	25
4.2.6.1.1	Power flux density limits in the 14,00 GHz to 14,50 GHz frequency band	25
4.2.6.2	13 GHz AES.....	27
4.2.6.2.0	General	27
4.2.6.2.1	Justification	27
4.2.6.2.2	Specification.....	28
4.2.6.2.3	Conformance tests	28
4.2.7	Receive antenna off-axis gain pattern.....	28
4.2.7.1	Justification	28
4.2.7.2	Specification.....	28
4.2.7.3	Conformance tests	28
4.2.8	Blocking performance.....	29
4.2.8.1	Justification	29
4.2.8.2	Specification.....	29
4.2.8.3	Conformance tests	29
4.2.9	Adjacent signal selectivity	29
4.2.9.1	Justification	29
4.2.9.2	Specification.....	29
4.2.9.3	Conformance tests	29
4.2.10	Image frequency rejection	30
4.2.10.1	Justification	30
4.2.10.2	Specification.....	30
4.2.10.3	Conformance tests	30
5	Testing for compliance with technical requirements.....	30
5.1	Environmental conditions for testing	30
5.2	Nominated Bandwidth.....	30
6	Test methods	30
6.0	General	30
6.1	Off-axis spurious radiation	31
6.1.1	Test method	31
6.1.1.0	Introduction	31
6.1.1.1	Up to 1 000 MHz (see clause 4.2.2.2, table 2)	32
6.1.1.1.1	Test site.....	32
6.1.1.1.2	Measuring receivers.....	32
6.1.1.1.3	Procedure	32
6.1.1.2	Above 1 000 MHz (see clause 4.2.2.2, tables 3 and 4)	32
6.1.1.2.0	General	32
6.1.1.2.1	Identification of the significant frequencies of spurious radiation	33
6.1.1.2.2	Measurement of radiated power levels of identified spurious radiation	33
6.2	On-axis spurious radiation.....	34
6.2.1	Test method	34
6.2.1.1	Void.....	34
6.2.1.2	Method of measurement.....	34
6.2.1.2.1	General	34
6.2.1.2.2	Method of measurement at the antenna flange	35
6.2.1.2.3	Method of measurement with a test antenna	36
6.3	Off-axis EIRP emissions density in the nominated bandwidth for 14 GHz AES and the power flux-density resulting from the 13 GHz AES towards any location in the geostationary-satellite orbit	37
6.3.1	14 GHz AES	37
6.3.1.1	General.....	37
6.3.1.2	rms antenna pointing accuracy	37

6.3.1.2.1	Method of measurement	37
6.3.1.3	Measurement of the off-axis EIRP without the antenna.....	38
6.3.1.3.1	Transmitter output power density	38
6.3.1.3.2	Antenna transmit gain.....	39
6.3.1.3.3	Antenna transmit radiation patterns.....	40
6.3.1.3.4	Computation of results	42
6.3.1.4	Measurement of the off-axis EIRP with the antenna.....	42
6.3.1.4.1	General	42
6.3.1.4.2	Maximum EIRP density per 40 kHz ratio relative to the EIRP.....	42
6.3.1.4.3	Maximum on-axis EIRP	42
6.3.1.4.4	Antenna transmit radiation patterns.....	44
6.3.1.4.5	Computation of results	46
6.3.2	13 GHz AES	46
6.3.2.1	General.....	46
6.4	Power Flux Density Test	46
6.4.1	14 GHz AES	46
6.4.1.1	General.....	46
6.4.1.2	Verification of specification 1: Mode of PFD limitation	47
6.4.1.3	Verification of specification 2: Location where to limit the PFD	47
6.4.1.4	Verification of specification 3: PFD limitation	47
6.4.1.4.1	Measurement of the antenna radiation pattern below the aircraft fuselage	47
6.4.1.4.2	Measurement of on-axis EIRP as a function of altitude	49
6.4.1.4.3	Computation of the power flux density at the surface of the Earth	50
6.4.1.5	Verification of specification 4: Fault conditions	50
6.4.1.5.1	Test Arrangement	50
6.4.1.5.2	Test method	51
6.4.2	13 GHz AES	51
6.4.2.1	Test Method	51
6.5	Control and monitoring	52
6.5.0	General.....	52
6.5.1	Test arrangement	52
6.5.2	Processor monitoring	53
6.5.2.1	Test method.....	53
6.5.3	Transmit subsystem monitoring.....	53
6.5.3.1	Test method.....	53
6.5.4	Power-on/Reset.....	53
6.5.4.1	Test method.....	53
6.5.5	Control Channel (CC) reception	54
6.5.5.1	Test method.....	54
6.5.6	Network control commands.....	55
6.5.6.1	Test method.....	55
6.5.7	Initial burst transmission.....	56
6.5.7.1	Test method.....	56
6.6	Receive antenna off-axis gain pattern	56
6.6.1	Test method	56
6.6.1.1	Test site	56
6.6.1.2	Method of measurement.....	56
6.6.1.3	Computation.....	57
6.7	Blocking performance	57
6.7.1	General.....	57
6.7.2	Test method	57
6.8	Adjacent signal selectivity.....	58
6.8.0	General.....	58
6.8.1	Test method	58
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	60
Annex B (normative):	Environmental conditions	62
B.1	General	62
B.2	Environmental conformance requirements.....	62

B.3	Environmental test conditions	62
Annex C (informative):	Maximum Measurement Uncertainty.....	64
Annex D (informative):	Applicability of parameters given in ETSI EG 203 336	65
Annex E (informative):	Bibliography.....	67
History		68

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.7].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	26 April 2021
Date of latest announcement of this EN (doa):	31 July 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2022
Date of withdrawal of any conflicting National Standard (dow):	31 January 2023

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio equipment within the scope of the Directive 2014/53/EU [i.7]. Each standard is a module in the structure. The modular structure is shown in ETSI EG 201 399 [i.1].

The requirements have been selected to ensure an adequate level of compatibility with other radio services.

The present document may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena or a continuous phenomenon is present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference, or the interfered part or both.

The present document does not contain any requirement, recommendation or information about the installation of the AES on aircraft.

The determination of the parameters of the AES using a given Geostationary Satellite Orbit (GSO) satellite for the protection of the spectrum allocated to that satellite, is considered to be under the responsibility of the satellite operator or the satellite network operators.

1 Scope

The present document specifies certain minimum technical performance requirements of Aircraft Earth Station (AES) equipment with both transmit and receive capabilities for provision of aeronautical mobile satellite service, in the frequency bands given in table 1.

Table 1: Frequency bands for the AES equipment specified in the present document

Mode of Operation	Frequency Band
AES transmit	14,00 GHz to 14,50 GHz
AES transmit	12,75 GHz to 13,25 GHz
AES receive	10,70 GHz to 12,75 GHz

The AES has the following characteristics:

- These AESs are equipment for installation on aircraft.
- The AESs transmit in the 14,00 GHz to 14,50 GHz band receive within the range from 10,70 GHz to 12,75 GHz ("14 GHz"), referred to as "14 GHz AES" in the present document, are operating in one or more frequency ranges of the Fixed-Satellite Service and Mobile-Satellite Service.
- The AESs transmit in the 12,75 GHz to 13,25 GHz band receive within the range from 10,70 GHz to 12,75 GHz ("13 GHz"), referred to as "13 GHz AES" in the present document, are operating in one or more frequency ranges of the Fixed-Satellite Service.

NOTE 1: When the term "AES" used in the present document without stating 13 GHz AES or 14 GHz AES, it is a reference to both 14 GHz AES and 13 GHz AES.

- The AES could consist of a number of modules from the antenna subsystem to the user interfaces.
- The AES uses linear polarization.
- The AES system uses digital modulation.
- The 14 GHz AES operates through a GSO satellite at least 3° away from any other geostationary satellite operating in the same frequency band and covering the same area.
- The 13 GHz AES operates with a GSO satellite network whose frequency assignments are from the List of Appendix 30B of the Radio Regulations.
- The antenna of the AES is directional, with means of tracking the satellites, which can be achieved by using either an active phase array or reflective type configuration.
- These AESs are operating as part of a satellite network used for the distribution and/or exchange of information between users.
- These AESs are controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document.
- When on the ground, the 14 GHz AES does not transmit at elevation angles below 7° with respect to the local horizontal plane, except at locations where transmissions below 7° are permitted by the local Administration; (the minimum elevation angle is also limited as per clause 4.2).

The technical requirements in the present document are in two major categories:

- **emission limits:** to protect other radio services and systems from harmful interference generated by the AES in normal use;
- **AES Control and Monitoring Functions (CMFs):** to protect other radio services and systems from unwanted transmissions from the AES. The CMF in each AES is capable of answering to commands from the Network Control Facility (NCF) for its supporting satellite network.

The present document applies to the AESs with their ancillary equipment and its various ports, and when operated within the boundary limits of the operational environmental profile specified by the manufacturer.

The technical requirements for the 14 GHz AES in regard to the Power Flux Density (PFD) limits to protect Fixed Service (FS) and Radio Astronomy Service (RAS) are based on annexes B and C of Recommendation ITU-R M.1643 [5] and ECC Report 26 [i.4]. Furthermore, in relation to the protection of the Fixed Satellite Service (FSS) the technical requirements of the AES take into account annex A of Recommendation ITU-R M.1643 [5].

The technical requirements for the 13 GHz AES in regards to the PFD limits on earth for the protection of FS are based on the ECC Decision (19)04 [6].

The present document is intended to cover the provisions of Directive 2014/53/EU [i.7] (RE Directive) article 3.2, which states that "... *radio equipment shall be so constructed that it both effectively and supports the use of radio spectrum allocated in order to avoid harmful interference*".

NOTE 2: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.7] is given in annex A.

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements of other parts of article 3 of the RE Directive [i.7] may apply to equipment within the scope of the present document.

NOTE 3: A list of such ENs is included on the web site at: https://ec.europa.eu/growth/single-market/european-standards/harmonised-standards/red_en.

The present document does not cover equipment compliance with relevant civil aviation regulations. In this respect, an AES, for its installation and operation on board an aircraft is subject to additional national or international civil aviation airworthiness certification requirements, for example to EUROCAE ED-14 [4].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] CISPR 16-1-1:2019: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [3] IEEE STD 149TM-1979: "IEEE Standard Test Procedures for Antennas".
- [4] EUROCAE ED-14 (2015) (Equivalent to RTCA DO-160D): "Environmental Conditions and Test Procedures for Airborne Equipment".
- [5] Recommendation ITU-R M.1643 (06-2003): "Technical and operational requirements for aircraft earth stations of aeronautical mobile-satellite service including those using fixed-satellite service network transponders in the band 14-14.5 GHz (Earth-to-space)".
- [6] CEPT ECC Decision (19)04 (03-2020): "The harmonised use of spectrum, free circulation and use of earth stations on-board aircraft operating with GSO FSS networks and NGSO FSS systems in the frequency bands 12.75-13.25 GHz (Earth-to-space) and 10.7-12.75 GHz (space-to-Earth)".

- [7] ETSI ETS 300 457 (Edition 1) (11-1995): "Satellite Earth Stations and Systems (SES); Test methods for Television Receive Only (TVRO) operating in the 11/12 GHz frequency bands".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] Recommendation ITU-R S.524-9: "Maximum permissible levels of off-axis e.i.r.p. density from earth stations in geostationary-satellite orbit networks operating in the fixed-satellite service transmitting in the 6 GHz, 13 GHz, 14 GHz and 30 GHz frequency bands".
- [i.4] ECC Report 26 (02-2003): "The compatibility & sharing of the aeronautical mobile satellite service with existing services in the band 14,00 to 14,50 GHz Molde".
- [i.5] ITU Radio Regulations 2020.
- [i.6] ISO 7137 (1995): "Aircraft - Environmental conditions and test procedures for airborne equipment".
- [i.7] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE Directive).
- [i.8] Recommendation ITU-R S.728-1: "Maximum permissible level of off-axis e.i.r.p. density from very small aperture terminals (VSATs)".
- [i.9] ETSI EG 203 336 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

koniec náhl'adu – text d'alej pokračuje v platenej verzii STN