

<b>STN</b>	<b>Družicové zemské stanice a systémy (SES) Pevne inštalované zemské stanice a za pohybu pracujúce zemské stanice komunikujúce s negeostacionárnymi družicovými systémami (NEST) vo frekvenčnom pásme od 11 GHz do 14 GHz Harmonizovaná norma pre prístup k rádiovému spektru</b>	<b>STN EN 303 980 V1.2.1</b>  87 3980
------------	---	---

Satellite Earth Stations and Systems (SES); Fixed and in-motion Earth Stations communicating with non-geostationary satellite systems (NEST) in the 11 GHz to 14 GHz frequency bands; Harmonised Standard for access to radio spectrum

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 09/21

Obsahuje: EN 303 980 V1.2.1:2021

**133670**

# ETSI EN 303 980 V1.2.1 (2021-05)



**Satellite Earth Stations and Systems (SES);  
Fixed and in-motion Earth Stations communicating with  
non-geostationary satellite systems (NEST)  
in the 11 GHz to 14 GHz frequency bands;  
Harmonised Standard for access to radio spectrum**

---

**Reference**

REN/SES-00456

---

**Keywords**broadband, earth station, mobile, regulation,  
satellite**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction .....	8
1 Scope .....	9
2 References .....	10
2.1 Normative references .....	10
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	12
3.3 Abbreviations .....	12
4 Technical requirements specifications .....	13
4.1 General .....	13
4.1.0 Objective.....	13
4.1.1 Environmental profile .....	14
4.1.2 Void .....	14
4.1.3 Operating configurations .....	14
4.1.4 Presentation of equipment for testing purposes .....	14
4.1.5 Choice of model for testing .....	14
4.1.6 Operation of multiple NEST on a single frequency.....	15
4.2 Conformance requirements .....	15
4.2.1 Void .....	15
4.2.2 Antenna beam pointing.....	15
4.2.2.1 Pointing accuracy.....	15
4.2.2.1.1 Purpose .....	15
4.2.2.1.2 Antenna Beam Pointing error .....	15
4.2.2.2 Pointing error detection.....	15
4.2.2.2.1 Purpose .....	15
4.2.2.2.2 Pointing error detection specification.....	15
4.2.2.3 Conformance tests.....	15
4.2.3 Off-axis spurious radiation .....	16
4.2.3.1 Justification .....	16
4.2.3.2 Specification.....	16
4.2.3.3 Conformance tests.....	17
4.2.4 On-axis spurious radiation.....	17
4.2.4.1 Justification .....	17
4.2.4.2 Specification.....	17
4.2.4.2.1 "Carrier-on" radio state.....	17
4.2.4.2.2 "Carrier-off" and "Emissions disabled" radio states .....	18
4.2.4.3 Conformance tests.....	18
4.2.5 Carrier suppression .....	18
4.2.5.1 Justification .....	18
4.2.5.2 Specification.....	18
4.2.5.3 Conformance tests.....	18
4.2.6 Cessation of emissions.....	18
4.2.6.1 Justification .....	18
4.2.6.2 Specification.....	18
4.2.6.2.1 Specification 1: Mode of cessation of emissions.....	18
4.2.6.2.2 Specification 2: Conditions under which the NEST shall cease emissions .....	19
4.2.6.2.3 Specification 3: Cessation of emissions .....	19
4.2.6.2.4 Specification 4: Fault conditions .....	19
4.2.6.3 Conformance tests.....	20
4.2.7 Identification of the NEST and its location .....	20

4.2.7.1	Justification .....	20
4.2.7.2	Specification.....	20
4.2.7.3	Conformance tests .....	20
4.2.8	Control and Monitoring Functions (CMFs).....	20
4.2.8.1	General - Finite State Machine Model .....	20
4.2.8.2	Processor monitoring .....	22
4.2.8.2.1	Justification .....	22
4.2.8.2.2	Specification.....	23
4.2.8.2.3	Conformance tests .....	23
4.2.8.3	Transmit subsystem monitoring.....	23
4.2.8.3.1	Justification .....	23
4.2.8.3.2	Specification.....	23
4.2.8.3.3	Conformance tests .....	23
4.2.8.4	Power-on/Reset .....	23
4.2.8.4.1	Justification .....	23
4.2.8.4.2	Specification.....	23
4.2.8.4.3	Conformance tests .....	23
4.2.8.5	Control Channel (CC) and Response Channel (RC) .....	24
4.2.8.5.1	Justification .....	24
4.2.8.5.2	Specification.....	24
4.2.8.5.3	Conformance tests .....	24
4.2.8.6	Network control commands .....	25
4.2.8.6.1	Justification .....	25
4.2.8.6.2	Specification.....	25
4.2.8.6.3	Conformance tests .....	25
4.2.8.7	Initial burst transmission .....	25
4.2.8.7.1	Justification .....	25
4.2.8.7.2	Specification.....	25
4.2.8.7.3	Conformance tests .....	26
4.2.8.8	Inhibition of transmissions.....	26
4.2.8.8.1	Justification .....	26
4.2.8.8.2	Specification.....	26
4.2.8.8.3	Conformance tests .....	26
4.2.9	Receive antenna off-axis gain pattern.....	26
4.2.9.1	Justification.....	26
4.2.9.2	Specification.....	26
4.2.9.3	Conformance tests.....	27
4.2.10	Blocking performance.....	27
4.2.10.1	Justification .....	27
4.2.10.2	Specification.....	27
4.2.10.3	Conformance tests.....	27
4.2.11	Adjacent Signal Selectivity.....	28
4.2.11.1	Justification .....	28
4.2.11.2	Specification.....	28
4.2.11.3	Conformance tests.....	28
5	Testing for compliance with technical requirements.....	28
5.1	Environmental conditions for testing .....	28
5.2	Ancillary Equipment .....	28
5.3	Nominated Bandwidth.....	29
5.4	Essential radio test suites.....	29
6	Test methods for all aspects of the NEST .....	29
6.1	General .....	29
6.1.1	General requirements.....	29
6.2	Off-axis spurious radiation.....	29
6.2.1	General.....	29
6.2.2	Test method .....	30
6.2.2.1	General .....	30
6.2.2.2	Multi-carrier operation.....	30
6.2.3	Measurements up to 1 000 MHz .....	30
6.2.3.1	Test site .....	30

6.2.3.2	Void.....	31
6.2.3.3	Procedure .....	31
6.2.4	Measurements above 1 000 MHz .....	31
6.2.4.1	General .....	31
6.2.4.2	Identification of the significant frequencies of spurious radiation .....	31
6.2.4.2.1	Test site.....	31
6.2.4.2.2	Procedure.....	32
6.2.4.3	Measurement of radiated power levels of identified spurious radiation.....	32
6.2.4.3.1	Test site.....	32
6.2.4.3.2	Procedure.....	32
6.2.4.4	Measurement of conducted spurious radiation at the antenna flange.....	33
6.2.4.4.1	Test site.....	33
6.2.4.4.2	Procedure.....	34
6.3	On-axis spurious radiation.....	34
6.3.1	Test method .....	34
6.3.1.1	General .....	34
6.3.1.2	Test site .....	34
6.3.1.3	Method of measurement.....	34
6.3.1.3.1	General .....	34
6.3.1.3.2	Method of measurement at the antenna flange .....	35
6.3.1.3.3	Method of measurement for an EUT with antenna.....	37
6.4	Void.....	38
6.5	Carrier suppression.....	38
6.5.1	General.....	38
6.5.2	Test method .....	38
6.6	Antenna beam pointing .....	38
6.6.1	General.....	38
6.6.2	Test methods.....	39
6.7	Cessation of emissions of the NEST .....	40
6.7.1	General.....	40
6.7.2	Test Method.....	40
6.7.2.1	Required documentation .....	40
6.7.2.2	Cessation of emissions from the "Transmission enabled" state .....	40
6.7.2.3	Cessation of emission from the "Transmission disabled" state .....	40
6.7.2.4	Cessation of emission from the "Initial Phase" state.....	41
6.7.2.4.1	EUTs transmitting initial bursts.....	41
6.7.2.4.2	EUTs not transmitting initial bursts.....	41
6.7.2.5	"Single action" means of cessation of emissions.....	41
6.7.2.6	Fault conditions.....	42
6.8	Identification of NEST and location determination.....	42
6.8.1	Test arrangement .....	42
6.8.2	Test method .....	42
6.9	Control and monitoring functions .....	43
6.9.1	General.....	43
6.9.2	Test arrangement .....	43
6.9.3	Processor monitoring-Test method .....	43
6.9.4	Transmit subsystem monitoring-Test method.....	43
6.9.5	Power-on/Reset-Test method.....	43
6.9.6	Control Channel and Response Channel - Test method.....	44
6.9.7	Network Control commands - Test method.....	45
6.9.8	Initial burst transmission - Test method.....	46
6.9.9	Inhibition of transmission - Test method .....	46
6.10	Antenna off-axis gain pattern .....	46
6.10.1	Test Method.....	46
6.10.1.1	Test site .....	46
6.10.1.2	Method of measurement for EUT antenna with linear polarization .....	47
6.10.1.3	Method of measurement for antennas with circular polarization .....	47
6.11	Blocking performance .....	48
6.11.0	General.....	48
6.11.1	Test method .....	48
6.12	Adjacent Signal Selectivity .....	48
6.12.0	General.....	48

6.12.1	Test method .....	49
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>50</b>
<b>Annex B (normative):</b>	<b>Radiated measurement.....</b>	<b>52</b>
B.1	General .....	52
B.2	Free Field Test sites and general arrangements for measurements involving the use of radiated fields.....	52
B.2.1	Anechoic Chamber .....	52
B.2.2	Anechoic Chamber with a conductive ground plane .....	53
B.2.3	Open Area Test Site (OATS) .....	55
B.2.4	Minimum requirements for free field test sites.....	56
B.2.4.1	Measurements above 18 GHz .....	56
B.2.4.2	Test antenna .....	56
B.2.4.3	Substitution antenna.....	57
B.2.4.4	Measuring antenna .....	57
B.2.5	Guidance on the use of free field radiation test sites .....	57
B.2.5.1	General.....	57
B.2.5.2	Verification of the test site.....	57
B.2.5.3	Preparation of the EUT .....	57
B.2.5.4	Power supplies to the EUT .....	57
B.2.5.5	Range length .....	58
B.2.5.6	Site preparation .....	58
B.2.5.7	Coupling of signals .....	59
B.2.5.8	Standard test methods .....	59
B.2.5.8.0	General .....	59
B.2.5.8.1	Calibrated setup.....	59
B.2.5.8.2	Substitution method .....	59
B.3	Guidance on the use of indirect far field test sites.....	60
B.3.1	General .....	60
B.3.2	Far-field criteria.....	61
B.3.3	Calibration Measurement Procedure .....	62
B.4	Guidance on the use of near-field-to-far-field transform test sites.....	63
B.4.1	General .....	63
B.4.2	Calibration Measurement Procedure .....	64
<b>Annex C (normative):</b>	<b>Conducted measurements .....</b>	<b>66</b>
<b>Annex D (informative):</b>	<b>General Requirements for RF Cables.....</b>	<b>67</b>
<b>Annex E (informative):</b>	<b>RF Waveguides .....</b>	<b>68</b>
<b>Annex F (informative):</b>	<b>Measurement Equipment.....</b>	<b>69</b>
F.1	Special considerations for the interpretation of measurement results .....	69
F.2	Maximum measurement uncertainty .....	69
F.3	Measuring receiver .....	70
F.4	Measurement results.....	71
<b>Annex G (informative):</b>	<b>Applicability of parameters given in ETSI EG 203 336 .....</b>	<b>72</b>
<b>Annex H (informative):</b>	<b>Bibliography .....</b>	<b>74</b>
<b>Annex I (informative):</b>	<b>Change history .....</b>	<b>75</b>
History .....		76

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.6].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

<b>National transposition dates</b>	
Date of adoption of this EN:	6 May 2021
Date of latest announcement of this EN (doa):	31 August 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	28 February 2022
Date of withdrawal of any conflicting National Standard (dow):	28 February 2023

---

# Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the RE Directive [i.6]. The modular structure is shown in ETSI EG 201 399 [i.2].

The present document is largely based on ETSI EN 303 979 [i.4], for ESOMPs operating with NGSO satellites.

The present document may also be applicable to the frequency band 14,0 GHz to 14,50 GHz (Earth-to-space) and 10,70 GHz to 12,75 GHz (space-to-Earth) subject to national regulation.

Annex A (informative) provides HS Requirements specifications.

Annex B (normative) describes methods of taking radiated measurements.

Annex C (normative) describes methods of taking conducted measurements.

Annex D (informative) describes requirements for RF measurement cables.

Annex E (informative) describes use of RF waveguides.

Annex F (informative) describes measurement equipment.

Annex G (informative) describes the applicability of parameters in ETSI EG 203 336 [i.7].

Annex H (informative) Bibliography covers other supplementary information.

Recital 10 of Directive 2014/53/EU [i.6] states that "*in order to ensure that radio equipment uses the radio spectrum effectively and supports the efficient use of radio spectrum, radio equipment should be constructed so that: in the case of a transmitter, when the transmitter is properly installed, maintained and used for its intended purpose it generates radio waves emissions that do not create harmful interference, while unwanted radio waves emissions generated by the transmitter (e.g. in adjacent channels) with a potential negative impact on the goals of radio spectrum policy should be limited to such a level that, according to the state of the art, harmful interference is avoided; and, in the case of a receiver, it has a level of performance that allows it to operate as intended and protects it against the risk of harmful interference, in particular from shared or adjacent channels, and, in so doing, supports improvements in the efficient use of shared or adjacent channels*".

Recital 11 of Directive 2014/53/EU [i.6] states that "*although receivers do not themselves cause harmful interference, reception capabilities are an increasingly important factor in ensuring the efficient use of radio spectrum by way of an increased resilience of receivers against harmful interference and unwanted signals on the basis of the relevant essential requirements of Union harmonisation legislation*".

As a consequence, the present document includes both transmitting and receiving parameters aiming to maximize the efficient use of radio spectrum.

# 1 Scope


The present document specifies technical characteristics and methods of measurements for fixed and in-motion Earth Stations communicating with non-geostationary satellite systems (NEST) in the 11 GHz to 14 GHz FSS frequency bands, which have the following characteristics:

- The NEST is designed for both in-motion and stationary operation.
- The NEST operates in-motion on various platforms such as trains, maritime vessels, aircraft and other vehicles and, therefore, may be subject to occasional disturbances and interruptions in the satellite link.
- The NEST is operating as part of a satellite system used for the provision of broadband communications.
- The NEST is comprised of all the equipment, electrical and mechanical, from the antenna itself to the interface with other communications equipment on a mobile platform.
- The NEST comprises one or more emitters and the system overview as given in Figure 1 should be interpreted accordingly.
- The transmit and receive frequencies are shown in Table 1.

**Table 1: Frequency bands**

	Frequency Bands
Transmit (Earth-to-space)	14,0 GHz to 14,50 GHz
Receive (space-to-Earth)	10,70 GHz to 12,75 GHz

- The NEST transmits within the frequency range from 14,0 GHz to 14,50 GHz.
- The NEST receives within the range from 10,70 GHz to 12,75 GHz. The NEST transmits at elevation angles of 35° or greater, relative to the horizontal plane.
- The NEST uses linear or circular polarization.
- The NEST communicates with non-geostationary satellites.
- The NEST is designed for unattended operation.
- The NEST is controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document.



**Figure 1: NEST System Overview**

The present document applies to the NEST with its ancillary equipment and its various telecommunication ports, and when operated within the boundary limits of the operational environmental profile as declared by the manufacturer and when installed as required by the manufacturer's declaration or in the user documentation.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.6] is given in annex A.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-1:2019: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [2] CISPR 16-1-4:2019: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".
- [3] Recommendation ITU-R S.1503-3 (01/2018), Section 3.1: "Generation of Earth Station e.i.r.p density masks".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission Implementing Decision C(2015) 5376 final of 04.08.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.3] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.4] ETSI EN 303 979 (V2.1.2): "Satellite Earth Stations and Systems (SES); Harmonised Standard for Earth Stations on Mobile Platforms (ESOMP) transmitting towards satellites in non-geostationary orbit, operating in the 27,5 GHz to 29,1 GHz and 29,5 GHz to 30,0 GHz frequency bands covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [i.5] Void.

- [i.6] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.7] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.8] IEC 60153 (parts 1 to 7): "Hollow metallic waveguides".
- [i.9] Recommendation ITU-R BO.1213: "Reference receiving Earth station antenna pattern for the broadcasting-satellite service in the 11.7-12.75 GHz band".
- [i.10] ETSI TR 102 273 (all parts) (V1.2.1) (2001-12): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.11] ANSI C63.5 (2006): "American National Standard for Electromagnetic Compatibility Radiated Emission Measurements in Electromagnetic Interference (EMI) Control Calibration of Antennas (9 kHz to 40 GHz)".

**koniec náhľadu – text ďalej pokračuje v platenej verzii STN**