

STN	Informačné technológie Knižnica modulov dôveryhodnej platformy Časť 1: Architektúra	STN ISO/IEC 11889-1 97 4118
------------	--	--

Information technology
Trusted Platform Module Library
Part 1: Architecture

Technologies de l'information
Bibliothèque de module de plate-forme de confiance
Partie 1: Architecture

Informationstechnologie
Trusted Platform Module Library
Teil 1: Architektur

Táto norma obsahuje anglickú verziu ISO/IEC 11889-1: 2015, vrátane opravenej verzie ISO/IEC 11889-1: 2016.

This standard includes the English version of ISO/IEC 11889-1: 2015, including Corrected version ISO/IEC 11889-1: 2016.

Anotácia

Štyri časti ISO/IEC 11889 spoločne určujú architektúru, dátové štruktúry, príkazové rozhranie a správanie modulu dôveryhodnej platformy (Trusted Platform Module – TPM). Správne skonštruovaná platforma, ktorá obsahuje modul TPM splňajúci požiadavky, môže umožniť vytvorenie dôvery v scenáre platformy, zahrnujúce bezpečnosť a súkromie.

TPM vyžadujú hardvérovú ochranu, aby poskytli tri zdroje dôveryhodnosti: ukladanie, meranie a podávanie správ. Základom dôveryhodnosti hardvéru v TPM je zlepšenie oproti softvérovým riešeniam, ktorých ochrany sú citlivé na škodlivý softvér. Architektúra definuje TPM, ktorý je pasívnym komponentom, ktorý prijíma príkazy a vracia odpovede. Definované príkazy vykonávajú primitívne akcie s dôvernými údajmi. Typické implementácie integrujú modul TPM v kontexte platformy, ako je prenosný počítač alebo mobilné zariadenie. Odoslaním príkazov na modul TPM a spracovaním odpovedí narastajú výhody zabezpečenia pre platformu ako celok. Správne skonštruované platformy s TPM môžu poskytnúť hardvérové zdroje dôveryhodnosti pre ukladanie, meranie a/alebo vykazovanie.

Národný predhovor

Normatívne referenčné dokumenty

Nasledujúce dokumenty, celé alebo ich časti, sú v tomto dokumente normatívnymi odkazmi a sú nevyhnutné pri jeho používaní. Pri datovaných odkazoch sa použije len citované vydanie. Pri nedatovaných odkazoch sa použije najnovšie vydanie citovaného dokumentu (vrátane všetkých zmien).

POZNÁMKA 1. – Ak bola medzinárodná publikácia zmenená spoločnými modifikáciami, čo je indikované označením (mod), použije sa príslušná EN/HD.

POZNÁMKA 2. – Aktuálne informácie o platných a zrušených STN možno získať na webovej stránke www.unms.sk.

ISO/IEC 9797-2 dosiaľ nezavedená

ISO/IEC 10116: 2006 dosiaľ nezavedená

ISO/IEC 11889-2 zavedená v STN ISO/IEC 11889-2 Informačné technológie. Knižnica modulov dôveryhodnej platformy. Časť 2: Štruktúry (97 4118)

ISO/IEC 11889-3 zavedená v STN ISO/IEC 11889-3 Informačné technológie. Knižnica modulov dôveryhodnej platformy. Časť 3: Príkazy (97 4118)

ISO/IEC 11889-4 zavedená v STN ISO/IEC 11889-4 Informačné technológie. Knižnica modulov dôveryhodnej platformy. Časť 4: Podporné rutiny (97 4118)

Register algoritmov TCG, dostupný na
http://www.trustedcomputinggroup.org/resources/tcg_algorithm_registry

Vypracovanie normy

Spracovateľ: Úrad pre normalizáciu, metrológiu a skúšobníctvo SR, Bratislava

Technická komisia: TK 37 Informačné technológie

ISO/IEC 11889-1:2015(E)**CONTENTS**

Foreword	xiv
Introduction	xv
1 Scope	1
2 Normative references	2
3 Terms and definitions	3
4 Symbols and Abbreviated Terms	12
4.1 Symbols.....	12
4.2 Abbreviations.....	13
5 Conventions	15
5.1 Bit and Octet Numbering and Order.....	15
5.2 Sized Buffer References	15
5.3 Numbers	16
5.4 KDF Label Parameters.....	16
6 ISO/IEC 11889 Organization.....	17
7 Compliance	19
8 Changes from Previous Versions.....	20
9 Trusted Platforms	21
9.1 Trust	21
9.2 Trust Concepts	21
9.2.1 Trusted Building Block.....	21
9.2.2 Trusted Computing Base.....	21
9.2.3 Trust Boundaries	21
9.2.4 Transitive Trust	22
9.2.5 Trust Authority.....	22
9.3 Trusted Platform Module.....	23
9.4 Roots of Trust.....	23
9.4.1 Introduction	23
9.4.2 Root of Trust for Measurement (RTM)	24
9.4.3 Root of Trust for Storage (RTS).....	24
9.4.4 Root of Trust for Reporting (RTR)	24
9.5 Basic Trusted Platform Features.....	25
9.5.1 Introduction	25
9.5.2 Certification	26
9.5.3 Attestation and Authentication	26
9.5.4 Protected Location.....	29
9.5.5 Integrity Measurement and Reporting	30
10 TPM Protections	31
10.1 Introduction.....	31
10.2 Protection of Protected Capabilities	31
10.3 Protection of Shielded Locations.....	31
10.4 Exceptions and Clarifications	31
11 TPM Architecture.....	33
11.1 Introduction.....	33
11.2 TPM Command Processing Overview	33
11.3 I/O Buffer	37
11.4 Cryptography Subsystem.....	37

11.4.1 Introduction	37
11.4.2 Hash Functions	37
11.4.3 HMAC Algorithm	38
11.4.4 Asymmetric Operations	38
11.4.5 Signature Operations	39
11.4.6 Symmetric Encryption	41
11.4.7 Extend	43
11.4.8 Key Generation	43
11.4.9 Key Derivation Function	43
11.4.10 Random Number Generator (RNG) Module	47
11.4.11 Algorithms	49
11.5 Authorization Subsystem	50
11.6 Random Access Memory	51
11.6.1 Introduction	51
11.6.2 Platform Configuration Registers (PCR)	51
11.6.3 Object Store	52
11.6.4 Session Store	52
11.6.5 Size Requirements	52
11.7 Non-Volatile (NV) Memory	53
11.8 Power Detection Module	53
12 TPM Operational States	54
12.1 Introduction	54
12.2 Basic TPM Operational States	54
12.2.1 Power-off State	54
12.2.2 Initialization State	54
12.2.3 Startup State	55
12.2.4 Shutdown State	58
12.2.5 Startup Alternatives	58
12.3 Self-Test Modes	59
12.4 Failure Mode	60
12.5 Field Upgrade	61
12.5.1 Introduction	61
12.5.2 Field Upgrade Mode	61
12.5.3 Preserved TPM State	64
12.5.4 Field Upgrade Implementation Options	65
13 TPM Control Domains	66
13.1 Introduction	66
13.2 Controls	66
13.3 Platform Controls	67
13.4 Owner Controls	68
13.5 Privacy Administrator Controls	68
13.6 Primary Seed Authorizations	69
13.7 Lockout Control	69
13.8 TPM Ownership	70
13.8.1 Taking Ownership	70
13.8.2 Releasing Ownership	70
14 Primary Seeds	72

ISO/IEC 11889-1:2015(E)

14.1 Introduction.....	72
14.2 Rationale	72
14.3 Primary Seed Properties	73
14.3.1 Introduction	73
14.3.2 Endorsement Primary Seed (EPS).....	73
14.3.3 Platform Primary Seed (PPS).....	74
14.3.4 Storage Primary Seed (SPS).....	74
14.3.5 The Null Seed	74
14.4 Hierarchy Proofs.....	74
15 TPM Handles.....	76
15.1 Introduction.....	76
15.2 PCR Handles (MSO=00 ₁₆)	76
15.3 NV Index Handles (MSO=01 ₁₆).....	76
15.4 Session Handles (MSO=02 ₁₆ and 03 ₁₆).....	76
15.5 Permanent Resource Handles (MSO=40 ₁₆).....	77
15.6 Transient Object Handles (MSO=80 ₁₆)	77
15.7 Persistent Object Handles (MSO=81 ₁₆)	77
16 Names	78
17 PCR Operations.....	80
17.1 Initializing PCR	80
17.2 Extend of a PCR.....	80
17.3 Using Extend with PCR Banks.....	80
17.4 Recording Events	81
17.5 Selecting Multiple PCR.....	81
17.6 Reporting on PCR	82
17.6.1 Reading PCR	82
17.6.2 Attesting to PCR	82
17.7 PCR Authorizations	83
17.7.1 Introduction	83
17.7.2 PCR Not in a Set	83
17.7.3 Authorization Set	83
17.7.4 Policy Set.....	84
17.7.5 Order of Checking.....	84
17.8 PCR Allocation	84
17.9 PCR Change Tracking	84
17.10 Other Uses for PCR	85
18 TPM Command/Response Structure	86
18.1 Introduction.....	86
18.2 Command/Response Header Fields	88
18.2.1 Introduction	88
18.2.2 tag	88
18.2.3 commandSize/responseSize	88
18.2.4 commandCode.....	88
18.2.5 responseCode.....	88
18.3 Handles	89
18.4 Parameters	89
18.5 authorizationSize/parameterSize	90

18.6 Authorization Area.....	90
18.6.1 Introduction.....	90
18.6.2 Authorization Structure	92
18.6.3 Session Handles.....	93
18.6.4 Session Attributes (<i>sessionAttributes</i>).....	93
18.7 Command Parameter Hash (<i>cpHash</i>).....	95
18.8 Response Parameter Hash (<i>rpHash</i>).....	95
18.9 Command Example	96
18.10 Response Example.....	97
19 Authorizations and Acknowledgments	99
19.1 Introduction.....	99
19.2 Authorization Roles	99
19.3 Physical Presence Authorization.....	100
19.4 Password Authorizations.....	101
19.5 Sessions	102
19.6 Session-Based Authorizations	102
19.6.1 Introduction	102
19.6.2 Authorization Session Formats.....	103
19.6.3 Session Nonces	103
19.6.4 Authorization Values.....	105
19.6.5 HMAC Computation.....	106
19.6.6 Note on Use of Nonces in HMAC Computations.....	107
19.6.7 Starting an Authorization Session	107
19.6.8 <i>sessionKey</i> Creation	108
19.6.9 Unbound and Unsalted Session Key Generation	109
19.6.10 Bound Session Key Generation	110
19.6.11 Salted Session Key Generation	112
19.6.12 Salted and Bound Session Key Generation.....	113
19.6.13 Encryption of <i>salt</i>	114
19.6.14 Caution on use of Unsalted Authorization Sessions	115
19.6.15 No HMAC Authorization	115
19.6.16 Authorization Selection Logic for Objects	116
19.6.17 Authorization Session Termination.....	116
19.7 Enhanced Authorization	117
19.7.1 Introduction	117
19.7.2 Policy Assertion	118
19.7.3 Policy AND	118
19.7.4 Policy OR	120
19.7.5 Order of Evaluation	122
19.7.6 Policy Assertions (Policy Commands).....	122
19.7.7 Policy Session Context Values	125
19.7.8 Policy Example	126
19.7.9 Trial Policy	127
19.7.10 Modification of Policies	127
19.7.11 TPM2_PolicySigned(), TPM2_PolicySecret(), and TPM2_PolicyTicket()	128
19.8 Policy Session Creation	130
19.9 Use of TPM for <i>authPolicy</i> Computation	131

ISO/IEC 11889-1:2015(E)

19.10 Trial Policy Session	131
19.11 Dictionary Attack Protection.....	132
19.11.1 Introduction.....	132
19.11.2 Lockout Mode Configuration Parameters.....	132
19.11.3 Lockout Mode.....	133
19.11.4 Recovering from Lockout Mode	133
19.11.5 Authorization Failures Involving lockoutAuth	134
19.11.6 Non-orderly Shutdown.....	134
19.11.7 Justification for Lockout Due to Session Binding	134
19.11.8 Sample Configurations for Lockout Parameters	135
20 Audit Session	136
20.1 Introduction.....	136
20.2 Exclusive Audit Sessions	137
20.3 Command Gating Based on Exclusivity	137
20.4 Audit Session Reporting.....	137
20.5 Audit Establishment Failures.....	138
21 Session-based encryption.....	139
21.1 Introduction.....	139
21.2 XOR Parameter Obfuscation	140
21.3 CFB Mode Parameter Encryption	140
22 Protected Storage	142
22.1 Introduction.....	142
22.2 Object Protections.....	142
22.3 Protection Values	142
22.4 Symmetric Encryption	143
22.5 Integrity.....	144
23 Protected Storage Hierarchy.....	146
23.1 Introduction.....	146
23.2 Hierarchical Relationship between Objects.....	146
23.3 Duplication.....	147
23.3.1 Definition	147
23.3.2 Protections	148
23.4 Duplication Group.....	153
23.5 Protection Group	155
23.6 Summary of Hierarchy Attributes	156
23.7 Primary Seed Hierarchies	156
23.8 Hierarchy Attributes Settings Matrix.....	156
24 Credential Protection.....	158
24.1 Introduction.....	158
24.2 Protocol	158
24.3 Protection of Credential.....	159
24.4 Symmetric Encrypt	159
24.5 HMAC	159
24.6 Summary of Protection Process.....	161
25 Object Attributes	162
25.1 Base Attributes	162
25.1.1 Introduction	162
25.1.2 <i>Restricted</i> Attribute	162
25.1.3 <i>Sign</i> Attribute	162

25.1.4 <i>Decrypt</i> Attribute	163
25.1.5 <i>Uses</i>	163
25.2 Other Attributes	165
25.2.1 <i>fixedTPM</i> and <i>fixedParent</i>	165
25.2.2 <i>stClear</i>	165
25.2.3 <i>sensitiveDataOrigin</i>	165
25.2.4 <i>userWithAuth</i>	165
25.2.5 <i>adminWithPolicy</i>	165
25.2.6 <i>noDA</i>	166
25.2.7 <i>encryptedDuplication</i>	166
26 Object Structure Elements	167
26.1 Introduction	167
26.2 Public Area	167
26.3 Sensitive Area	168
26.4 Private Area	168
26.5 Qualified Name	169
26.6 Sensitive Area Encryption	169
26.7 Sensitive Area Integrity	170
27 Object Creation	171
27.1 Introduction	171
27.2 Public Area Template	171
27.2.1 Introduction	171
27.2.2 <i>type</i>	171
27.2.3 <i>nameAlg</i>	172
27.2.4 <i>objectAttributes</i>	172
27.2.5 <i>authPolicy</i>	172
27.2.6 <i>parameters</i>	172
27.2.7 <i>unique</i>	172
27.3 Sensitive Values	172
27.3.1 Overview	172
27.3.2 <i>userAuth</i>	173
27.3.3 <i>data</i>	173
27.4 Creation PCR	173
27.5 Public Area Creation	173
27.5.1 Introduction	173
27.5.2 <i>type</i> , <i>nameAlg</i> , <i>objectAttributes</i> , <i>authPolicy</i> , and <i>parameters</i>	173
27.5.3 <i>unique</i>	174
27.6 Sensitive Area Creation	175
27.6.1 Introduction	175
27.6.2 <i>type</i>	175
27.6.3 <i>authValue</i>	175
27.6.4 <i>seedValue</i>	175
27.6.5 <i>sensitive</i>	176
27.7 Creation Data and Ticket	177
27.8 Creation Resources	178
28 Object Loading	179

ISO/IEC 11889-1:2015(E)

28.1 Introduction.....	179
28.2 Load of an Ordinary Object.....	179
28.3 Public-only Load.....	179
28.4 External Object Load.....	180
29 Object Creation in Reference Implementation.....	181
30 Context Management.....	182
30.1 Introduction.....	182
30.2 Context Data	183
30.2.1 Introduction	183
30.2.2 Sequence Number.....	183
30.2.3 Handle.....	184
30.2.4 Hierarchy.....	185
30.3 Context Protections	185
30.3.1 Context Confidentiality Protection	185
30.3.2 Context Integrity Protection	186
30.4 Object Context Management	187
30.5 Session Context Management.....	187
30.6 Eviction.....	188
30.7 Incidental Use of Object Slots	189
31 Attestation	190
31.1 Introduction.....	190
31.2 Standard Attestation Structure	190
31.3 Privacy.....	191
31.4 Qualifying Data	191
31.5 Anonymous Signing	191
32 Cryptographic Support Functions.....	192
32.1 Introduction.....	192
32.2 Hash	192
32.3 HMAC	192
32.4 Hash, HMAC, and Event Sequences	193
32.4.1 Introduction	193
32.4.2 Hash Sequence	193
32.4.3 Event Sequence	193
32.4.4 HMAC Sequence	194
32.4.5 Sequence Contexts	194
32.5 Symmetric Encryption	194
32.6 Asymmetric Encryption and Signature Operations	194
33 Locality	195
34 Hardware Core Root of Trust Measurement (H-CRTM) Event Sequence.....	196
34.1 Introduction.....	196
34.2 Dynamic Root of Trust Measurement	196
34.3 H-CRTM before TPM2_Startup()	197
35 Command Audit.....	198
36 Timing Components	200
36.1 Introduction.....	200
36.2 Clock.....	201
36.2.1 Introduction	201
36.2.2 <i>Clock</i> Implementation	201

36.2.3 Orderly Shutdown of <i>Clock</i>	202
36.2.4 <i>Clock</i> Initialization at TPM2_Startup()	202
36.2.5 Setting <i>Clock</i>	203
36.2.6 <i>Clock</i> Periodicity	203
36.3 Time	204
36.4 resetCount	204
36.5 restartCount	204
36.6 Note on the Accuracy and Reliability of <i>Clock</i>	205
36.7 Privacy Aspects of <i>Clock</i>	206
37 NV Memory	207
37.1 Introduction	207
37.2 NV Indices	207
37.2.1 Definition	207
37.2.2 NV Index Allocation	208
37.2.3 NV Index Deletion	209
37.2.4 High-Endurance (Hybrid) Indices	209
37.2.5 Reading an NV Index	210
37.2.6 Updating an Index	211
37.2.7 NV Index in a Policy	214
37.3 Owner and Platform Evict Objects	214
37.4 State Saved by TPM2_Shutdown()	215
37.4.1 Background	215
37.4.2 NV Orderly Data	215
37.4.3 NV Clear Data	216
37.4.4 NV Reset Data	217
37.5 Persistent NV Data	218
37.6 NV Rate Limiting	220
37.7 NV Other Considerations	220
37.7.1 Power Interruption	220
37.7.2 External NV	220
37.7.3 PCR in NV	221
38 Multi-Tasking	222
39 Errors and Response Codes	223
39.1 Error Reporting	223
39.2 TPM State After an Error	223
39.3 Resource Exhaustion Warnings	223
39.3.1 Introduction	223
39.3.2 Transient Resources	223
39.3.3 Temporary Resources	224
39.4 Response Code Details	224
40 General Purpose I/O	226
41 Minimums	227
41.1 Introduction	227
41.2 Authorization Sessions	227
41.3 Transient Objects	227
41.4 NV Counters and Bit Fields	227
Annex A (normative) RSA	228

ISO/IEC 11889-1:2015(E)

A.1	Introduction.....	228
A.2	RSAEP	229
A.3	RSADP	229
A.4	RSAES_OAEP	229
A.5	RSAES_PKCSV1_5.....	229
A.6	RSASSA_PKCS1v1_5	229
A.7	RSASSA_PSS.....	230
A.8	RSA Cryptographic Primitives.....	231
	A.8.1 Introduction	231
	A.8.2 TPM2_RSA_Encrypt()	231
	A.8.3 TPM2_RSA_Decrypt()	231
A.9	Secret Sharing.....	231
	A.9.1 Overview	231
	A.9.2 RSA Encryption of Salt	231
	A.9.3 RSA Secret Sharing for Duplication	232
	A.9.4 RSA Secret Sharing for Credentials	232
Annex B (normative) ECC.....	233	
B.1	Introduction.....	233
B.2	Split Operations.....	233
	B.2.1 Introduction	233
	B.2.2 Commit Random Value.....	233
	B.2.3 TPM2_Commit().....	234
	B.2.4 TPM2_EC_Ephemeral()	235
	B.2.5 Recovering the Private Ephemeral Key.....	236
B.3	ECC-Based Secret Sharing	236
B.4	EC Signing	236
	B.4.1 ECDSA.....	236
	B.4.2 ECDAA.....	236
	B.4.3 EC Schnorr	239
B.5	Secret Sharing.....	240
	B.5.1 ECDH.....	240
	B.5.2 ECDH Encryption of Salt	241
	B.5.3 ECC Secret Sharing for Duplication	241
	B.5.4 ECC Secret Sharing for Credentials	241
B.6	ECC Primitive Operations	241
	B.6.1 Introduction	241
	B.6.2 TPM2_ECDH_KeyGen()	241
	B.6.3 TPM2_ECDH_ZGen()	241
	B.6.4 Two-phase Key Exchange.....	242
Annex C (normative) Support for SMx Family of Algorithms	244	
C.1	Introduction.....	244
C.1	SM2	244
	C.1.1 Introduction	244
	C.1.2 SM2 Digital Signature Algorithm	245
	C.1.3 SM2 Key Exchange	247

C.2 SM3	248
C.3 SM4	248
Annex D (informative) Key Generation	249
D.1 Introduction.....	249
D.2 RSA Key Generation	249
D.2.1 Background.....	249
D.2.2 Prime Generation.....	249
D.2.3 Key Generation Algorithm.....	250
D.3 ECC Ordinary Keys	251
D.4 ECC Primary key.....	251
Annex E (informative) Policy Examples	252
E.1 Introduction.....	252
E.2 ISO/IEC 11889 (first edition) Compatible Authorization.....	252
Annex F (informative) Acknowledgements and contributors	254
F.1 Acknowledgements	254
F.2 Contributors.....	254
Bibliography	256

Tables

Table 1 — KDF Label Parameters	16
Table 2 — Block Cipher Parameters	41
Table 3 — Hierarchy Control Setting Combinations	67
Table 4 — Equations for Computing Entity Names	78
Table 5 — Separators	87
Table 6 — Tag Values	88
Table 7 — Use of Authorization/Session Blocks	91
Table 8 — Description of <i>sessionAttributes</i>	93
Table 9 — Command Layout for Example Command	96
Table 10 — Example Command Showing <i>authorizationSize</i>	97
Table 11 — Response Layout for Example Command	97
Table 12 — Example Response Showing <i>parameterSize</i>	98
Table 13 — Password Authorization of Command	101
Table 14 — Password Acknowledgment in Response	101
Table 15 — Session-Based Authorization of Command	103
Table 16 — Session-Based Acknowledgment in Response	103
Table 17 — Schematic of TPM2_StartAuthSession Command	107
Table 18 — Handle Parameters for TPM2_StartAuthSession.....	108
Table 19 — Format to Start Unbounded, Unsalted Session.....	109
Table 20 — Format to Start Bound Session	111

ISO/IEC 11889-1:2015(E)

Table 21 — Format to Start Salted Session	112
Table 22 — Format to Start Salted and Bound Session.....	113
Table 23 — Mapping of Hierarchy Attributes	156
Table 24 — Allowed Hierarchy Settings	156
Table 25 — Mapping of Functional Attributes.....	163
Table 26 — ISO/IEC 11889 (first edition) Correspondence.....	164
Table 27 — Public Area Parameters	167
Table 28 — Sensitive Area Parameters.....	168
Table 29 — Standard Attestation Structure	190
Table 30 — Contents of the ORDERLY_DATA Structure	216
Table 31 — Contents of the STATE_CLEAR_DATA Structure.....	216
Table 32 — Contents of the STATE_RESET_DATA Structure.....	217
Table 33 — Contents of the PERSISTENT_DATA Structure	218

Figures

Figure 1 — Attestation Hierarchy	30
Figure 2 — Architectural Overview	36
Figure 3 — Command Execution Flow	40
Figure 4 — Random Number Generation	51
Figure 5 — TPM Startup Sequences	60
Figure 6 — On-Demand Self-Test	62
Figure 7 — Failure Mode Behavior	64
Figure 8 — Resuming FUM after _TPM_Init.....	66
Figure 9 — Field Upgrade Mode.....	67
Figure 10 — Command Structure	90
Figure 11 — Response Structure	90
Figure 12 — Command/Response Header Structure.....	91
Figure 13 — Authorization Layout for Command	95
Figure 14 — Authorization Layout for Response.....	95
Figure 15 — A Policy Evaluation	121
Figure 16 — Two Different Policy Expressions.....	122
Figure 17 — A Four-Term Policy	122
Figure 18 — Policy with an OR	123
Figure 19 — Policy where only one OR Branch is Evaluated.....	124
Figure 20 — A 12-input OR Policy.....	124
Figure 21 — Use of TPM2_PolicyAuthorize() to Avoid PCR Brittleness	131
Figure 22 — Creating a Private Structure.....	148
Figure 23 — Symmetric Protection of Hierarchy.....	150
Figure 24 — Duplication Process with Inner and Outer Wrapper.....	154
Figure 25 — Duplication Process with Outer Wrapper and No Inner Wrapper	155
Figure 26 — Duplication Process with Inner Wrapper and TPM_RH_NULL as NP	156
Figure 27 — Duplication Process with no Inner Wrapper and TPM_RH_NULL as NP	156
Figure 28 — Duplication Groups.....	158
Figure 29 — Protection Groups	158
Figure 30 — Creating a Identity Structure	164
Figure 31 — Response Code Evaluation.....	228

ISO/IEC 11889-1:2015(E)

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

ISO/IEC 11889-1 was prepared by the Trusted Computing Group (TCG) and was adopted, under the PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 11889-1:2009), which has been technically revised.

ISO/IEC 11889 consists of the following parts, under the general title *Information technology — Trusted Platform Module Library*:

- *Part 1: Architecture*
- *Part 2: Structures*
- *Part 3: Commands*
- *Part 4: Supporting routines*

This corrected version of ISO/IEC 11889-1:2015 includes the insertion of Figures 7, 9, 15, 18, 21 and 23.

Introduction

Collectively the four parts of ISO/IEC 11889 specify the architecture, data structures, command interface and behavior of a Trusted Platform Module (TPM). A properly constructed platform that incorporates a TPM meeting the requirements may enable establishing trust in platform scenarios involving security and privacy.

TPMs require hardware protections to provide three roots of trust: storage, measurement, and reporting. Basing TPM roots of trust in hardware is an improvement over software based solutions whose protections are vulnerable to malicious software. The architecture defines a TPM that is a passive component that receives commands and returns responses. The commands defined have meticulous descriptions and perform primitive actions on data confidential to the TPM. Typical implementations integrate a TPM in the context of a platform like a laptop or a mobile device. By sending commands to a TPM and processing the responses, security benefits accrue for the platform as a whole. Properly constructed platforms with a TPM can provide hardware based roots of trust for storage, measurement and/or reporting.

The root of trust for storage consists primarily of creating, managing and protecting cryptographic keys and other data values. Artifacts protected by or associated with encryption keys, like passwords, certificates or other credentials, can be used for authentication and many other security scenarios. Cryptographic keys can be created with restrictions on their use or management.

EXAMPLE 1 Cryptographic keys can be created that require a password to be used, have a single purpose (e.g. signing), or cannot be exported elsewhere.

Separate from cryptographic key management, the root of trust for storage also allows data values to be stored in a TPM so they are protected from unauthorized modification or can only be changed in defined ways.

EXAMPLE 2 A data value protected by the TPM might be defined so it can be incremented but not decremented.

Typical use cases can include storing security policy information that can only be updated by an authorized entity or incrementing a value to keep track of failed password entry attempts.

The root of trust for measurement is intended to reflect what software is running on a platform in a trusted way. This root consists of the TPM and other components of a platform that start a chain of measurements. Before software runs, its measurement is calculated and stored in the TPM by sending a command. Later software can add more measurements, but cannot erase its own measurement that was recorded before it started running. If the measurement process unconditionally starts when a platform is powered on, the TPM ends up holding an accurate measurement of all the software running on the system from each power-on. Across power cycles, the same software running on a platform results in the same measurements being present in the TPM. Combining the root of trust for measurement with the root of trust for storage, it is possible to create keys or store data using the TPM that only software with specific measurements can use. The result is specific software on a platform can maintain its own keys, confidential data or security policy information that is not accessible and not able to be tampered with by other software that may run on the platform.

The root of trust for reporting helps entities external to a platform establish trust in platform software measurements or cryptographic keys by proving the values exist in a TPM. TPMs have Endorsement Keys that are essentially unique identities for a TPM. Through commands the TPM provides, it is possible to prove keys exist in a TPM with a specific Endorsement Key. Establishing that a key exists in a TPM permits services external to the TPM to trust a key is protected by a TPM's root of trust for storage. Also, if a key is known to be in a TPM, and the key is used to sign measurements of software, evidence of what software is running on a platform can be shared with an external entity in a trusted way. This enhances privacy protections as the need to share the TPM's Endorsement Key identity directly with a remote verifier can be avoided, resulting in a platform that can anonymously prove to a remote verifier what software is running.

Not all privacy and security use cases enabled by this International Standard are relevant for all platforms. For this reason, this International Standard is defined as a generic library of commands, cryptographic algorithms and capabilities for which a subset can be used to meet the needs of a specific

ISO/IEC 11889-1:2015(E)

platform or implementation, with the flexibility to meet diverse and even contradictory global requirement sets. To address the needs of platform types, market segments, regulations, assurance criteria, certification programs, etc., the structure allows complimentary materials to be developed by interested parties constraining the generic library to address specific requirement sets. To promote product interoperability, implementers are encouraged to consult existing specifications augmenting this International Standard with domain specific considerations for specific applications and platform types. A platform specific context is able to articulate scenarios, functionality, relevant security and privacy goals, implementation considerations and methods of assurance. Because of the generic nature of this International Standard, certification programs are likely to be based on additional specifications that further define platform specific implementations and security characteristics. Having a single TPM library that implementations across different platforms types can use to add security and privacy benefits lowers complexity and permits reuse of software and security analysis across the trusted computing ecosystem.

EXAMPLE 3 Opt-in versus secure by default are examples of contradictory requirements for TPM provisioning that are both supported by this International Standard.

This International Standard is useful for a variety of audiences. Two key audiences are TPM implementers and adopters. Clauses 6 and 7 in this part of ISO/IEC 11889 are useful to orientate audiences to the organization of the four parts and how they are used to build a compliant implementation. Implementers will need to use all four parts to build a compliant implementation. Adopters can benefit from the architectural concepts in this part of ISO/IEC 11889 when developing scenarios and incorporating a TPM into a platform design. ISO/IEC 11889-2 and ISO/IEC 11889-3 are beneficial for adopters to understand the syntax and semantics of using individual TPM commands.

Implementers and adopters of this International Standard need to carefully assess the appropriateness of controllability, security and privacy capabilities and algorithms implemented for satisfying their goals. In assessing algorithms, implementers and adopters should diligently evaluate available information. Solutions involving cryptography are dependent on the solution architecture and on the properties of cryptographic algorithms supported. Over time, cryptographic algorithms can develop deficiencies for reasons like advances in cryptographic techniques or increased computing power. Solutions that support a diversity of algorithms can remain durable when subsets of supported algorithms wane in usefulness. Therefore, implementers intent on providing robust solutions are responsible for evaluating both algorithm appropriateness and diversity.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO and IEC take no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the ISO and IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO and IEC. Information may be obtained from:

Fujitsu Limited
1-1, Kamikodanaka 4-chrome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan
Microsoft Corporation
One Microsoft Way, Redmond, WA 98052
Enterasys Networks, Inc
50 Minuteman Road, US-Andover, MA 01810

Lenovo**1009 Think Place, US-Morrisville, NC 27560-8496****Advanced Micro devices, Inc. - AMD****7171 Southwest Parkway, Mailstop B100.3, US-Austin, Texas 78735****Hewlett-Packard Company****P.O. Box 10490, US-Palo Alto, CA 94303-0969****Infineon Technologies AG - Neubiberg****Am Campeon 1-12, DE-85579 Neubiberg****Sun Microsystems Inc. - Menlo Park, CA****10 Network Circle, UMPK10-146, US-Menlo Park, CA 94025****IBM Corporation****North Castle Drive, US-Armonk, N.Y. 10504****Intel Corporation****5200 Elam Young Parkway, US-Hillsboro, OR 97123**

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (<http://patents.iec.ch>) maintain on-line databases of patents relevant to their standards. Users are encouraged to consult the databases for the most up to date information concerning patents.

Information technology — Trusted Platform Module Library —**Part 1: Architecture****1 Scope**

This part of ISO/IEC 11889 defines the architectural elements of the Trusted Platform Module (TPM), a device which enables trust in computing platforms in general. Some TPM concepts are explained adequately in the context of the TPM itself. Other TPM concepts are explained in the context of how a TPM helps establish trust in a computing platform. When describing how a TPM helps establish trust in a computing platform, this part of ISO/IEC 11889 provides some guidance for platform requirements. However, the scope of ISO/IEC 11889 is limited to TPM requirements.

This part of ISO/IEC 11889 illustrates TPM security and privacy techniques in the context of a platform through the use of cryptography. It includes definitions of how different cryptographic techniques are implemented by a TPM. The scope of ISO/IEC 11889 does not include cryptographic analysis or guidance about the applicability of different algorithms for specific uses cases.

TPM requirements in this part of ISO/IEC 11889 are general, covering concepts like integrity protection, isolation and confidentiality. Defining a specific strength of function or assurance level is out of scope for ISO/IEC 11889. This approach limits the guarantees provided by ISO/IEC 11889 itself, but it does allow the TPM architectural elements defined to be adapted to meet diverse implementation and platform specific needs.

ISO/IEC 11889-1:2015(E)

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- ISO/IEC 9797-2, *Information technology -- Security techniques -- Message Authentication Codes (MACs) -- Part 2: Mechanisms using a dedicated hash-function*
- ISO/IEC 10116:2006, *Information technology — Security techniques — Modes of operation for an n-bit block cipher*
- ISO/IEC 11889-2, *Information technology — Trusted Platform Module Library — Part 2: Structures*
- ISO/IEC 11889-3, *Information technology — Trusted Platform Module Library — Part 3: Commands*
- ISO/IEC 11889-4, *Information technology — Trusted Platform Module Library — Part 4: Supporting routines*
- TCG Algorithm Registry, available at
[<http://www.trustedcomputinggroup.org/resources/tcg_algorithm_registry>](http://www.trustedcomputinggroup.org/resources/tcg_algorithm_registry)

koniec náhľadu – text d'alej pokračuje v platenej verzii STN