

STN	Pevné rádiové systémy Charakteristiky a požiadavky na zariadenia a antény bod-bod Časť 1: Prehľad, spoločné charakteristiky a požiadavky, ktoré sa netýkajú prístupu k rádiovému spektru	STN EN 302 217-1 V3.3.1 87 2217
------------	---	---

Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 1: Overview, common characteristics and requirements not related to access to radio spectrum

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 05/22

Obsahuje: EN 302 217-1 V3.3.1:2021

ETSI EN 302 217-1 V3.3.1 (2021-10)



**Fixed Radio Systems;
Characteristics and requirements for
point-to-point equipment and antennas;
Part 1: Overview, common characteristics and
requirements not related to access to radio spectrum**

Reference

REN/ATTM-0449

Keywordsantenna, DFRS, DRRS, FWA, point-to-point, radio,
transmission**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	14
3.1 Terms.....	14
3.2 Symbols.....	20
3.3 Abbreviations	20
4 Structure and applicability of the ETSI EN 302 217 series.....	23
4.1 Generality	23
4.2 Cross references to previously relevant ENs and TSs	24
4.3 Summary of system options provided	24
4.4 User's guide	28
5 General characteristics	30
5.1 Frequency bands and channel arrangements	30
5.2 Special compatibility requirements between systems	30
5.3 Transmission capacity and spectral efficiency	30
5.4 Performance and availability requirements	30
5.5 Environmental profiles	31
5.5.0 Introduction.....	31
5.5.1 Environmental profile under Directive 2014/53/EU.....	31
5.5.2 ETSI standardized environmental profiles.....	31
5.5.2.0 Generality.....	31
5.5.2.1 Equipment intended for telecommunications applications installed in weather-protected locations (indoor locations)	32
5.5.2.2 Equipment intended for telecommunications applications installed in not-weather-protected locations (outdoor locations).....	32
5.5.3 Test environment profiles	32
5.6 Power supply	32
5.6.0 Introduction.....	32
5.6.1 Power supply profile under Directive 2014/53/EU.....	32
5.6.2 ETSI power supply profile.....	32
5.7 System block diagram	32
6 Baseband interfaces and parameters.....	33
6.0 Introduction	33
6.1 Ethernet interfaces.....	33
6.2 Plesiochronous interfaces	33
6.3 Synchronous digital hierarchy interfaces	34
6.4 Other baseband data interfaces.....	34
7 Main requirements.....	34
7.0 Introduction	34
7.1 General requirements	34
7.1.1 System identification	34
7.1.2 System nominal loading.....	35
7.1.3 Environmental profile	35
7.2 Transmitter characteristics.....	35
7.2.1 Transmitter power and power tolerance.....	35
7.2.1.1 Transmitter maximum power and EIRP.....	35
7.2.1.2 Transmitter combined output power and EIRP limits.....	35

7.2.1.3	Transmitter output power environmental variation	35
7.2.2	Transmitter power and frequency control	36
7.2.2.1	Transmitter Power and Frequency Control (ATPC, RTPC and RFC)	36
7.2.2.1.1	Automatic Transmit Power Control (ATPC)	36
7.2.2.1.2	Remote Transmit Power Control (RTPC)	37
7.2.2.1.3	Transmitter Remote Frequency Control (RFC)	37
7.2.3	Transmitter Radio Frequency spectrum mask	37
7.2.4	Transmitter discrete CW components exceeding the spectrum mask limit	37
7.2.4.1	Transmitter discrete CW components at the symbol rate	37
7.2.4.2	Transmitter other discrete CW components exceeding the spectrum mask limit	37
7.2.5	Transmitter unwanted emissions in the spurious domain	37
7.2.6	Transmitter dynamic change of modulation order	37
7.2.7	Transmitter radio frequency tolerance	37
7.2.8	Transmitter emission limitations outside the allocated band	38
7.3	Receiver characteristics	38
7.3.1	Unwanted emissions in the spurious domain	38
7.3.2	Receiver BER as a function of Receiver Signal Level (RSL)	38
7.3.3	Receiver selectivity	38
7.3.3.1	Introduction	38
7.3.3.2	Receiver co-channel, first and second adjacent channel interference sensitivity	38
7.3.3.3	Blocking (CW spurious interference sensitivity)	38
7.4	Antenna directional characteristics	38
8	Complementary requirements	39
8.0	Introduction	39
8.1	Branching/feeder requirements	39
8.1.1	Waveguide flanges (or other connectors)	39
8.1.2	Return loss of feeder/antenna systems at equipment antenna port (C/C' reference point)	40
8.2	Intermodulation products	41
8.3	Transmitter characteristics	41
8.3.1	Unwanted emissions - internal	41
8.3.2	Transmitter Radio Frequency (RF) spectrum mask when mixed manufacturer compatibility is required	41
8.4	Receiver characteristics	42
8.4.1	Receiver maximum input level and input level range	42
8.4.2	Unwanted emissions - internal	43
8.4.3	Image rejection	43
8.4.4	Innermost channel selectivity	44
8.5	System performance without diversity	44
8.5.1	Equipment Residual BER (RBER)	44
8.5.2	Distortion sensitivity	46
8.5.2.1	Introduction	46
8.5.2.2	Requirement	46
8.5.2.3	Assessment	48
8.5.3	Interference sensitivity for CCDP with XPIC operation	48
8.5.3.1	General	48
8.5.3.2	Co-channel "internal" interference sensitivity in flat fading conditions	48
8.6	System characteristics with diversity	49
8.6.0	Introduction	49
8.6.1	Differential delay compensation	49
8.6.2	BER performance	49
Annex A (normative):	Transmitter Radio Frequency spectrum masks and receiver selectivity when mixed manufacturer compatibility is required	50
A.0	Introduction	50
A.1	Transmitter Radio Frequency masks assessment	51
A.2	Normal channels - Emission mask floor	51
A.2.1	RBER impact	51
A.2.2	Local TX to RX compatibility	51
A.2.2.1	Spectrum mask	51

A.2.2.2	Receiver selectivity.....	52
A.3	Innermost channels for channel arrangements from about 4 GHz to about 8,5 GHz with channel separation of 28 MHz to 30 MHz.....	52
A.3.0	Introduction.....	52
A.3.1	Innermost channels spectrum masks.....	52
A.3.2	Receiver innermost channel selectivity.....	54
A.4	Innermost channels for channel arrangements from about 4 GHz to 11 GHz with channel separation of 40 MHz.....	55
A.4.0	Introduction.....	55
A.4.1	Innermost channels spectrum masks.....	55
A.4.2	Receiver innermost channels selectivity.....	56
A.5	Innermost channels for 18 GHz channel arrangements with channel separation of 55 MHz.....	57
A.5.0	Introduction.....	57
A.5.1	Innermost channels spectrum masks.....	57
A.5.2	Receiver innermost channels selectivity.....	58
Annex B (normative):	Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface.....	60
Annex C (informative):	Information on <i>Multi-channel</i> and <i>Channels-aggregation</i> differences and operation.....	61
C.1	Multi-channel and Channels-aggregation (two channel case).....	61
C.2	Channels-aggregation (more than two channels case).....	62
Annex D (informative):	Additional information on relevant characteristics and operation.....	65
D.1	Residual Bit Error Ratio (RBER) and Residual Frame Error Ratio (RFER).....	65
D.2	Measurement test set for XPI characteristics.....	66
D.3	Differential delay compensation range.....	67
D.4	FER/BER equivalence and FER performance measurement equipment settings (example).....	68
D.4.1	FER/BER equivalence.....	68
D.4.2	FER equipment settings and measurement techniques (example).....	69
D.5	Impact of power control (ATPC and/or RTPC), mixed-mode and bandwidth adaptive operation on spectrum mask and link design requirements.....	69
D.5.0	Introduction.....	69
D.5.1	ATPC and RTPC.....	69
D.5.1.1	ATPC.....	69
D.5.1.2	ATPC and RTPC implementation background.....	70
D.5.2	Mixed-mode and bandwidth adaptive operation impact.....	72
D.5.2.1	Mixed-mode basic concepts.....	72
D.5.2.2	Bandwidth adaptive.....	73
D.5.2.2.1	Basic concepts.....	73
D.5.2.2.2	Bandwidth (channel) occupancy.....	73
D.5.3	Impact on frequency co ordination.....	73
D.5.4	Impact of operating conditions on the access to radio spectrum through European Harmonised Standard.....	73
D.6	Typical interference sensitivity behaviour for frequency planning purpose.....	74
D.7	Band and Carrier Aggregation (BCA) operation.....	74
Annex E (informative):	Mechanical characteristics.....	76
Annex F (informative):	Mitigation techniques referred in CEPT/ERC/DEC(00)07 (18 GHz band).....	77
Annex G (informative):	Bibliography.....	78

Annex H (informative):	Change history	79
History		80

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).

The present document is part 1 of a multi-part deliverable covering the Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas, as identified below (see note):

Part 1: "Overview, common characteristics and requirements not related to access to radio spectrum";

Part 2: "Digital systems operating in frequency bands from 1 GHz to 86 GHz; Harmonised Standard for access to radio spectrum";

Part 4: "Antennas".

NOTE: In previous regulatory regime under Directive 1999/5/EC more parts (harmonised and non-harmonised standards) were published. Since Directive 2014/53/EU [i.1] repealed Directive 1999/5/EC the following parts have been replaced while the content has been moved to other parts of the series.

Those parts are:

Part 2-1: Technical content moved to present document (Part 1);

Part 2-2: Technical content reproduced in Part 2 (*);

(*) Part 2-2- was also published in the OJEU under Directive 2014/53/EU [i.1], presumption of conformity ceased on 31-12-2018;

Part 3: Technical content moved to Part 2 (including a complete new set of receiver parameters);

Part 4-1: Technical content reproduced in Part 4;

Part 4-2: Technical content reproduced in Part 4.

National transposition dates	
Date of adoption of this EN:	30 August 2021
Date of latest announcement of this EN (doa):	30 November 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2022
Date of withdrawal of any conflicting National Standard (dow):	31 May 2022

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to Digital Fixed Radio Systems (DFRS) in point-to-point operation with integral and external antennas in the frequency range of 1 GHz to 86 GHz corresponding to the appropriate frequency bands 1,4 GHz to 86 GHz as described in ETSI EN 302 217-2 [16], annex B to annex J.

The present document summarizes:

- all characteristics, principles and, of utmost importance, terms and definitions that are common to all P-P equipment and antennas and its consultation is necessary when using all other parts of ETSI EN 302 217 series;
- all system-dependent requirements for Point-to-Point (P-P) equipment. These requirements are introduced in two different clauses sub-sets:
 - **Main requirements** are requirements that are also related to the "essential requirements" under article 3.2 of Directive 2014/53/EU [i.1] and further detailed in the Harmonised Standard ETSI EN 302 217-2 [16].
 - **Complementary requirements** are requirements that are not related to essential requirements under article 3.2 of Directive 2014/53/EU [i.1]. Nevertheless they have been commonly agreed for proper system operation and deployment when specific deployment conditions or compatibility requirements are present. Compliance to all or some of these requirements is left to manufacturer decision.

Health and safety requirements and EMC conditions and requirements are not considered in the ETSI EN 302 217 series.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CEPT/ERC/DEC(00)07: "The shared use of the band 17.7 - 19.7 GHz by the fixed service and Earth stations of the fixed-satellite service (space-to-Earth)". ERC Decision, approved 19 October 2000, amended 04 March 2016.
- [2] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [3] ETSI EN 300 019-2-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction".
- [4] ETSI EN 300 019-1-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-1: Classification of environmental conditions; Storage".

- [5] ETSI EN 300 019-2-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-1: Specification of environmental tests; Storage".
- [6] ETSI EN 300 019-1-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-2: Classification of environmental conditions; Transportation".
- [7] ETSI EN 300 019-2-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-2: Specification of environmental tests; Transportation".
- [8] ETSI EN 300 019-1-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations".
- [9] ETSI EN 300 019-2-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-3: Specification of environmental tests; Stationary use at weather protected locations".
- [10] ETSI EN 300 019-1-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weather protected locations".
- [11] ETSI EN 300 019-2-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-4: Specification of environmental tests; Stationary use at non-weather protected locations".
- [12] ETSI EN 300 132-2: "Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 2: -48 V Direct Current (DC)".
- [13] ETSI EN 300 132-3: "Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 3: Up to 400 V Direct Current (DC)".
- [14] ETSI EN 301 126-1: "Fixed Radio Systems; Conformance testing; Part 1: Point-to-Point equipment - Definitions, general requirements and test procedures".
- [15] ETSI EN 302 099: "Environmental Engineering (EE); Powering of equipment in access network".
- [16] ETSI EN 302 217-2 (V3.3.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 2: Digital systems operating in frequency bands from 1 GHz to 86 GHz; Harmonised Standard for access to radio spectrum".
- [17] ETSI EN 302 217-4 (V2.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 4: Antennas".
- [18] EN 60835-2-4: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 4: Transmitter/receiver including modulator/demodulator", produced by CENELEC.
- [19] EN 60835-2-8: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 8: Adaptive equalizer", produced by CENELEC.
- [20] IEEE 802.3-2018™: "IEEE Standard for Ethernet".
- [21] Recommendation ITU-R F.746: "Radio-frequency arrangements for fixed service systems".
- [22] Recommendation ITU-R F.1668: "Error performance objectives for real digital fixed wireless links used in 27 500 km hypothetical reference paths and connections".
- [23] Recommendation ITU-R F.1703: "Availability objectives for real digital fixed wireless links used in 27 500 km hypothetical reference paths and connections".

- [24] Recommendation ITU-R P.530: "Propagation data and prediction methods required for the design of terrestrial line-of-sight systems".
- [25] Recommendation ITU-T G.703: "Physical/electrical characteristics of hierarchical digital interfaces".
- [26] Recommendation ITU-T G.704: "Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44 736 kbit/s hierarchical levels".
- [27] Recommendation ITU-T G.707: "Network node interface for the synchronous digital hierarchy (SDH)".
- [28] Recommendation ITU-T G.708: "Sub STM-0 network node interface for the synchronous digital hierarchy (SDH)".
- [29] Recommendation ITU-T G.826: "End-to-end error performance parameters and objectives for international, constant bit-rate digital paths and connections".
- [30] Recommendation ITU-T G.828: "Error performance parameters and objectives for international, constant bit-rate synchronous digital paths".
- [31] Recommendation ITU-T G.829: "Error performance events for SDH multiplex and regenerator sections".
- [32] Recommendation ITU-T G.957: "Optical interfaces for equipment and systems relating to the synchronous digital hierarchy".
- [33] Recommendation ITU-T I.356: "B-ISDN ATM layer cell transfer performance".
- [34] Recommendation ITU-T I.357: "B-ISDN semi-permanent connection availability".
- [35] Recommendation ITU-T O.151: "Error performance measuring equipment operating at the primary rate and above".
- [36] Recommendation ITU-T O.181: "Equipment to assess error performance on STM-N interfaces".
- [37] Recommendation ITU-T O.191: "Equipment to measure the cell transfer performance of ATM connections".
- [38] Recommendation ITU-T V.11: "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [39] Recommendation ITU-T V.24: "List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)".
- [40] Recommendation ITU-T V.28: "Electrical characteristics for unbalanced double-current interchange circuits".
- [41] Recommendation ITU-T Y.1540: "Internet protocol data communication service - IP packet transfer and availability performance parameters".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI TR 101 035: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH) aspects regarding Digital Radio Relay Systems (DRRS)".
- [i.3] ETSI TR 102 243-1: "Fixed Radio Systems; Representative values for transmitter power and antenna gain to support inter- and intra-compatibility and sharing analysis; Part 1: Digital point-to-point systems".
- [i.4] CEPT/ERC/REC 12-03: "Harmonised radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 17.7 GHz to 19.7 GHz".
- [i.5] CEPT/ECC/REC(02)06: "Preferred channel arrangements for digital Fixed Service Systems operating in the frequency range 7125-8500 MHz".
- [i.6] CEPT/ECC/Report 80: "Enhancing harmonisation and introducing flexibility in the spectrum regulatory framework".
- [i.7] CEPT/ECC/Report 198: "Adaptive modulation and ATPC operations in fixed point-to-point systems - Guideline on coordination procedures".
- [i.8] CEPT/ERC/REC 14-01: "Radio-frequency channel arrangements for high capacity analogue and digital radio-relay systems operating in the band 5925 MHz to 6425 MHz".
- [i.9] CEPT/ERC/REC 14-02: "Radio-frequency channel arrangements for high, medium and low capacity digital fixed service systems operating in the band 6425 to 7125 MHz".
- [i.10] ETSI GR mWT 015: "Frequency Bands and Carrier Aggregation Systems; Band and Carrier Aggregation".
- [i.11] ETSI EN 300 119 (all parts): "Environmental Engineering (EE); European telecommunication standard for equipment practice".
- [i.12] ETSI TR 101 036-1: "Fixed Radio Systems; Generic wordings for standards on DFRS (Digital Fixed Radio Systems) characteristics; Part 1: General aspects and point-to-point equipment parameters".
- [i.13] ETSI TR 101 506 (V2.1.1): "Fixed Radio Systems; Generic definitions, terminology and applicability of essential requirements covering article 3.2 of Directive 2014/53/EU to Fixed Radio Systems".
- [i.14] ETSI TR 101 854: "Fixed Radio Systems; Point-to-point equipment; Derivation of receiver interference parameters useful for planning fixed service point-to-point systems operating different equipment classes and/or capacities".
- [i.15] ETSI TR 103 103: "Fixed Radio Systems; Point-to-point systems; ATPC, RTPC, Adaptive Modulation (mixed-mode) and Bandwidth Adaptive functionalities; Technical background and impact on deployment, link design and coordination".
- [i.16] EN 122150: "Sectional Specification: Radio frequency coaxial connectors - Series EIA flange", produced by CENELEC.
- [i.17] EN 60153-2: "Hollow metallic waveguides. Part 2: Relevant specifications for ordinary rectangular waveguides", produced by CENELEC.
- [i.18] EN 60154-2: "Flanges for waveguides. Part 2: Relevant specifications for flanges for ordinary rectangular waveguides", produced by CENELEC.
- [i.19] IEC 60169-1: "Radio-frequency connectors. Part 1: General requirements and measuring methods".
- [i.20] IEC 60339 (all parts): "General purpose rigid coaxial transmission lines and their associated flange connectors".

- [i.21] Recommendation ITU-R F.383: "Radio-frequency channel arrangements for high capacity fixed wireless systems operating in the lower 6 GHz (5 925 to 6 425 MHz) band".
- [i.22] Recommendation ITU-R F.384: "Radio -frequency channel arrangements for medium- and high-capacity digital fixed wireless systems operating in the 6 425-7 125 MHz band".
- [i.23] Recommendation ITU-R F.385: "Radio-frequency channel arrangements for fixed wireless systems operating in the 7 110-7 900 MHz band".
- [i.24] Recommendation ITU-R F.595: "Radio-frequency channel arrangements for fixed wireless systems operating in the 17.7-19.7 GHz frequency band".
- [i.25] Recommendation ITU-R F.750: "Architectures and functional aspects of radio-relay systems for synchronous digital hierarchy (SDH)-based network".
- [i.26] Recommendation ITU-R F.752: "Diversity techniques for point-to-point fixed wireless systems".
- [i.27] Recommendation ITU-R F.1093: "Effects of multipath propagation on the design and operation of line-of-sight digital fixed wireless systems".
- [i.28] Recommendation ITU-R F.1101: "Characteristics of digital fixed wireless systems below about 17 GHz".
- [i.29] Recommendation ITU-R F.1102: "Characteristics of fixed wireless systems operating in frequency bands above about 17 GHz".
- [i.30] Recommendation ITU-R F.1191: "Bandwidths and unwanted emissions of digital fixed service systems".
- [i.31] Recommendation ITU-T G.783: "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks".
- [i.32] Recommendation ITU-T G.784: "Management aspects of the synchronous digital hierarchy (SDH) transport network element".
- [i.33] Recommendation ITU-T I.414: "Overview of Recommendations on layer 1 for ISDN and B-ISDN customer accesses".
- [i.34] ITU Radio Regulations, Edition of 2020.
- [i.35] J. Redd: "Calculating Statistical Confidence Levels for Error-Probability Estimates". Lightwave Magazine, pp. 110-114, April 2000.

NOTE: Available at <http://www.lightwaveonline.com/>.

- [i.36] Lundgren, C.W.; Rummler, W.D.: "Digital Radio Outage Due to Selective Fading - Observation vs Prediction from Laboratory Simulation". BSTJ 58-5 May-June 1979 pp 1073-1100.

NOTE: Available at <https://archive.org/details/bstj58-5-1073>.

- [i.37] ETSI EN 302 217-1 (V2.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 1: Overview and system-independent common characteristics".

NOTE: Superseded version still containing the information referred in clause 4.2.

koniec náhľadu – text ďalej pokračuje v platenej verzii STN