

| | | |
|------------------|---|--|
| STN P | Potrubné systémy z plastov na zásobovanie vodou a na tlakové nadzemné a podzemné kanalizačné potrubia, stoky a závlahy Orientovaný nemäkčený polyvinylchlorid (PVC-O) Časť 3: Tvarovky | STN P CEN/TS 17176-3 64 3040 |
|------------------|---|--|

Plastics piping systems for water supply and for buried and above ground drainage, sewerage and irrigation under pressure - Oriented unplasticized poly(vinyl chloride) (PVC-O) - Part 3: Fittings

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 07/22

Táto predbežná slovenská technická norma je určená na overenie. Prípadné pripomienky pošlite do apríla 2024 Úradu pre normalizáciu, metrológiu a skúšobníctvo SR.

Obsahuje: CEN/TS 17176-3:2022

Oznámením tejto normy sa ruší
STN P CEN/TS 17176-3 (64 3040) zo septembra 2019

135039

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CEN/TS 17176-3

April 2022

ICS 23.040.20; 23.040.45

Supersedes CEN/TS 17176-3:2019

English Version

Plastics piping systems for water supply and for buried and above ground drainage, sewerage and irrigation under pressure - Oriented unplasticized poly(vinyl chloride) (PVC-O) - Part 3: Fittings

Systèmes de canalisations en plastique pour l'alimentation en eau, les branchements et collecteurs d'assainissement et les systèmes d'irrigation sous pression, enterrés ou aériens - Poly(chlorure de vinyle) non plastifié orienté (PVC-O) - Partie 3 : Raccords

Kunststoff-Rohrleitungssysteme für die Wasserversorgung und für erdverlegte und nicht erdverlegte Entwässerungs-, Abwasser- und Bewässerungsdruckleitungen - Orientiertes weichmacherfreies Polyvinylchlorid (PVC-O) - Teil 3: Formstücke

This Technical Specification (CEN/TS) was approved by CEN on 13 March 2022 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

CEN/TS 17176-3:2022 (E)

| Contents | | Page |
|--|--|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 8 |
| 4 | Symbols | 9 |
| 5 | Material | 9 |
| 5.1 | General | 9 |
| 5.2 | Density | 9 |
| 5.3 | Orientation factor | 10 |
| 6 | General characteristics | 10 |
| 6.1 | Appearance | 10 |
| 6.2 | Colour | 10 |
| 6.3 | Opacity | 10 |
| 6.4 | Classification of fittings | 10 |
| 7 | Geometrical characteristics | 10 |
| 7.1 | Design lengths, bend radii and angles | 10 |
| 7.2 | Measurement of dimensions | 10 |
| 7.3 | Nominal outside diameters and minimum wall thickness | 11 |
| 7.4 | Fittings with integral sockets | 11 |
| 7.5 | Fittings with plain ends | 11 |
| 7.6 | Fittings with integral sockets with solvent cement joints | 11 |
| 8 | Pressure and operating temperature | 11 |
| 8.1 | Selection of nominal pressure for water up to and including 25 °C | 11 |
| 8.2 | Determination of the allowable operating pressure for water up to 45 °C | 11 |
| 9 | Mechanical characteristics - Resistance to hydrostatic pressure | 11 |
| 10 | Physical characteristics | 12 |
| 11 | Sealing rings | 13 |
| 12 | Performance requirements | 13 |
| 13 | Marking | 13 |
| 13.1 | General | 13 |
| 13.2 | Minimum required marking | 13 |
| 13.3 | Additional marking | 14 |
| Annex A (normative) Determination of long term hydrostatic strength | | 15 |
| A.1 | General | 15 |
| A.2 | Test procedure | 15 |
| A.2.1 | General | 15 |
| A.2.2 | Classified feedstock material | 15 |
| A.2.3 | Not classified feedstock material | 15 |
| A.2.4 | Classification according to MRP | 15 |
| A.3 | Confirmation and control points | 16 |

| | | |
|--|------------------------------|-----------|
| A.4 | Test report | 16 |
| Annex B (normative) Determination of circumferential orientation factor | | 17 |
| B.1 | Principle..... | 17 |
| B.2 | Method..... | 17 |
| B.3 | Test parameters | 17 |
| B.4 | Test procedure | 18 |
| B.5 | Test report | 18 |
| Annex C (informative) Recommended dimensions of PVC-O fittings | | 19 |
| C.1 | General | 19 |
| C.2 | Elbows..... | 19 |
| C.3 | Reducers | 20 |
| C.4 | Double sockets..... | 23 |
| Bibliography | | 24 |

CEN/TS 17176-3:2022 (E)

European foreword

This document (CEN/TS 17176-3:2022) has been prepared by Technical Committee CEN/TC 155 “Plastics piping systems and ducting systems”, the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 17176-3:2019.

In comparison with the previous edition, the following modifications have been made:

- in Table 1 60 °C deleted;
- mistakes corrected in Table 2 and Annex B;
- additional information requests as in the B.5 Test report.

The revision of CEN/TS 17176-3:2019 is proposed to revise Annex B, in order to avoid misinterpretation and confusion in the market regarding reporting and use of the test results. In addition, mistakes identified in Table 2 are amended.

EN 17176 consists of the following parts, under the general title *Plastics piping systems for water supply and for buried and above ground drainage, sewerage and irrigation under pressure - Oriented unplasticized poly(vinyl chloride) (PVC-O)*:

- *Part 1: General*;
- *Part 2: Pipes*;
- *Part 3: Fittings* (this document);
- *Part 5: Fitness for purpose of the system*;
- *Part 7: Guidance for assessment of conformity* (in preparation).

For valves, see EN ISO 1452-4.

Guidance for installation is given in ISO/TR 4191 [3].

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

The System Standard, of which this is Part 3, specifies the requirements for a piping system made from oriented unplasticized poly(vinyl chloride) (PVC-O) pipes and its components. The piping system is intended to be used for water supply, pressurized drainage, sewerage, treated waste water and irrigation systems to be used underground or above ground where protected from direct sunlight.

In respect of potential adverse effects on the quality of water intended for human consumption, caused by the products covered by this document, the following is relevant:

- a) This document provides no information as to whether or not the products can be used without restriction.
- b) Existing national regulations concerning the use and/or the characteristics of these products remain in force.

Requirements and test methods for PVC-O material and components, other than fittings, are specified in EN 17176-1 and EN 17176-2. For other components (not manufactured from PVC-O) reference is made to the following standards: EN ISO 1452-3 (PVC-U) and EN 12842 (cast iron). Characteristics for fitness for purpose (mainly for joints) are specified in EN 17176-5.

This document specifies the characteristics of PVC-O fittings.

CEN/TS 17176-3:2022 (E)

1 Scope

This document specifies the characteristics of solid-wall oriented unplasticized poly(vinyl chloride) (PVC-O) fittings for piping systems intended for water supply and for buried drainage, sewerage, treated waste water and irrigation under pressure or above-ground where protected from direct sunlight. The scope of this document is limited to double sockets, repair couplings, reducers and to non-end load bearing elbows.

NOTE 1 The scope of this document is restricted to fittings on the market during the preparation of this document. Therefore, tees, flange adaptors, etc., are excluded from this version of the standard.

NOTE 2 For double sockets, repair couplings and reducers there are no special fittings designs for end-load bearing applications. However, restrained gaskets can be used for end-load bearing applications. In that case, the requirements of EN 17176-5 are applicable.

It also specifies the test parameters for the test methods referred to in this document.

In conjunction with EN 17176-1 and EN 17176-5, this document is applicable to oriented PVC-O fittings intended to be used for the following:

- a) water mains and services lines;
- b) conveyance of water for both outside and inside buildings;
- c) drainage, sewerage and treated waste water under pressure;
- d) irrigation under pressure.

This document is applicable to piping systems intended for the supply of water with a maximum allowable operating pressure (PFA) up to and including 25 bar¹. The piping system according to this document is intended for the conveyance of cold water up to and including 45 °C and especially in those applications where special performance requirements are needed, such as impact loads and pressure fluctuations. For temperatures between 25 °C and 45 °C, EN 17176-2:2019, Figure C.1 applies.

This document specifies a range of fittings sizes and pressure classes and gives a requirement and recommendations concerning colours.

NOTE 3 It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into account their particular requirements and any relevant national regulations and installation practices or codes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 681-1, *Elastomeric seals - Materials requirements for pipe joint seals used in water and drainage applications - Part 1: Vulcanized rubber*

EN 17176-1:2019, *Plastics piping systems for water supply and for buried and above ground drainage, sewerage and irrigation under pressure - Oriented unplasticized poly(vinyl chloride) (PVC-O) - Part 1: General*

¹ 1 bar = 0,1 MPa = 105 Pa; 1 MPa = 1 N/mm².

EN 17176-2:2019, *Plastics piping systems for water supply and for buried and above ground drainage, sewerage and irrigation under pressure - Oriented unplasticized poly(vinyl chloride) (PVC-O) - Part 2: Pipes*

EN 17176-5, *Plastics piping systems for water supply and for buried and above ground drainage, sewerage and irrigation under pressure - Oriented unplasticized poly(vinyl chloride) (PVC-O) - Part 5: Fitness for purpose of the system*

EN ISO 1167-1, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids - Determination of the resistance to internal pressure - Part 1: General method (ISO 1167-1)*

EN ISO 1167-2, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids - Determination of the resistance to internal pressure - Part 2: Preparation of pipe test pieces (ISO 1167-2)*

EN ISO 1167-3, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids - Determination of the resistance to internal pressure - Part 3: Preparation of components (ISO 1167-3)*

EN ISO 1183-1, *Plastics - Methods for determining the density of non-cellular plastics - Part 1: Immersion method, liquid pycnometer method and titration method (ISO 1183-1)*

EN ISO 1452 (all parts), *Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) (ISO 1452)*

EN ISO 3126, *Plastics piping systems - Plastics components - Determination of dimensions (ISO 3126)*

EN ISO 6259-1, *Thermoplastics pipes - Determination of tensile properties - Part 1: General test method (ISO 6259-1)*

EN ISO 6259-2, *Thermoplastics pipes - Determination of tensile properties - Part 2: Pipes made of unplasticized poly(vinyl chloride) (PVC-U), oriented unplasticized poly(vinyl chloride) (PVC-O), chlorinated poly(vinyl chloride) (PVC-C) and high-impact poly(vinyl chloride) (PVC-HI) (ISO 6259-2)*

EN ISO 7686, *Plastics pipes and fittings - Determination of opacity (ISO 7686)*

EN ISO 9080, *Plastics piping and ducting systems - Determination of the long-term hydrostatic strength of thermoplastics materials in pipe form by extrapolation (ISO 9080)*

EN ISO 9852, *Unplasticized poly(vinyl chloride) (PVC-U) pipes - Dichloromethane resistance at specified temperature (DCMT) - Test method (ISO 9852)*

ISO 161-1, *Thermoplastics pipes for the conveyance of fluids - Nominal outside diameters and nominal pressures - Part 1: Metric series*

ISO 2507-1, *Thermoplastics pipes and fittings - Vicat softening temperature - Part 1: General test method*

ISO 18373-1, *Rigid PVC pipes - Differential scanning calorimetry (DSC) method - Part 1: Measurement of the processing temperature*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN