

STN	<p>Vláknové organizátory a kryty používané v optovláknových komunikačných systémoch Špecifikácie výrobku Časť 3-6: Mechanické spoje mnohovidových vláken</p>	<p>STN EN 50411-3-6</p>
		35 9231

Fibre management systems and protective housings to be used in optical fibre communication systems - Product specifications - Part 3-6:
Multi- mode mechanical fibre splice

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 07/22

Obsahuje: EN 50411-3-6:2022

Oznámením tejto normy sa od 14.03.2023 ruší
STN EN 50411-3-6 (35 9231) z augusta 2013

135216

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 50411-3-6

April 2022

ICS 33.180.20

Supersedes EN 50411-3-6:2013 and all of its
amendments and corrigenda (if any)

English Version

**Fibre management systems and protective housings to be used
in optical fibre communication systems - Product specifications -
Part 3-6: Multi- mode mechanical fibre splice**

Systèmes de gestion des fibres et boîtiers de protection
destinés à être utilisés dans les systèmes de
communication par fibres optiques - Spécifications de
produits - Partie 3-6: Epissure mécanique de fibres
multimodales

LWL-Spleißkassetten und -Muffen für die Anwendung in
LWL Kommunikationssystemen - Produktnorm - Teil 3-6:
Mechanische Spleiße von Mehrmoden-Faser für geschützte
Freiluftanwendungen (Kategorie U)

This European Standard was approved by CENELEC on 2022-03-14. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
 Comité Européen de Normalisation Electrotechnique
 Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN 50411-3-6:2022 (E)

Contents	Page
European foreword	3
Introduction	4
1 Scope	5
1.1 Product definition	5
1.2 Interoperability	5
1.3 Expected performance	5
1.4 Operating environment	5
1.5 Reliability	5
1.6 Quality assurance	5
2 Normative references	6
3 Terms and definitions.....	7
4 Description	7
4.1 General.....	7
4.2 Mechanical splice	7
4.3 Materials.....	8
4.4 Dimensions.....	8
4.5 Colour and marking	8
5 Variants	8
6 Dimensional requirements.....	9
7 Tests.....	10
7.1 Introduction	10
7.2 Test sample preparation	10
7.3 Test and measurement methods.....	10
7.4 Pass/fail criteria	10
8 Test report	11
9 Performance requirements	11
9.1 Dimensional and marking requirements	11
9.2 Assembly yield requirement.....	11
9.3 Pass/fail criteria	11
9.4 Optical performance requirements	12
Annex A (normative) Fibre type for test sample.....	18
Annex B (normative) Sample size and product sourcing requirements.....	19
Bibliography	20

European foreword

This document (EN 50411-3-6:2022) has been prepared by CLC/TC 86BXA “Fibre optic interconnect, passive and connectorised components”.

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2023-03-14
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2023-03-14

This document supersedes EN 50411-3-6:2013 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

EN 50411-3-6:2022 includes the following significant technical changes with respect to EN 50411-3-6:2013:

- terms and definitions are added;
- the EN 61753-1:2007 category U tests and test severities are replaced by the EN IEC 61753-1:2018 category OP test and test severities;
- the references are updated.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

EN 50411-3-6:2022 (E)**Introduction**

Fibre management systems and protective housings to be used in optical fibre communication systems - Product specifications																															
Part 3–6: Multimode mechanical fibre splice																															
Description		Performance																													
Type:	Fibre splice	Application:	EN IEC 61753-1, Category OP																												
Style:	Mechanical		with extension of lower temperature to -40 °C																												
Operating wavelengths:	850 nm and/or 1 300 nm	Attenuation grades:	Grade A _m : ≤ 0,25 dB max. for ≥ 97 % of connections ≤ 0,12 dB average																												
Fibre category:	EN IEC 60793-2-10 types A1-OM1, A1-OM2, A1-OM3, A1-OM4 and A1-OM5	Return loss grades:	Grade B _m : ≤ 0,6 dB max. for ≥ 97 % of connections ≤ 0,3 dB average																												
			Grade C _m : ≤ 1,0 dB max. for ≥ 97 % of connections ≤ 0,5 dB average																												
			Grade 2 _m : ≥ 20 dB																												
Related documents:																															
EN IEC 60793-2-10	Optical fibres – Part 2–10: Product specifications - Sectional specification for category A1 multimode fibres (IEC 60793-2-10)																														
EN 60794-2-50:2008	Optical fibre cables – Part 2–50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies (IEC 60794-2-50:2008)																														
EN 61300 series	Fibre optic interconnecting devices and passive components – Basic test and measurement procedures (IEC 61300 series)																														
EN IEC 61753-1	Fibre optic interconnecting devices and passive components – Performance standard – Part 1: General and guidance (IEC 61753-1)																														
Outline and nominal dimensions:																															
		<table border="1"> <thead> <tr> <th>Variant</th> <th>Dimension W mm</th> <th>Dimension H mm</th> <th>Dimension L mm</th> </tr> </thead> <tbody> <tr> <td>Type M1</td> <td>3,8</td> <td>6,4</td> <td>38</td> </tr> <tr> <td>Type M2</td> <td>4,0</td> <td>4,0</td> <td>36</td> </tr> <tr> <td>Type M3</td> <td>3,2</td> <td>3,2</td> <td>46</td> </tr> <tr> <td>Type M4</td> <td>4,2</td> <td>4,2</td> <td>44</td> </tr> <tr> <td>Type M5</td> <td>4,0</td> <td>4,0</td> <td>40</td> </tr> <tr> <td>Type M6</td> <td colspan="2">Ø 5,0</td><td>65</td> </tr> </tbody> </table>		Variant	Dimension W mm	Dimension H mm	Dimension L mm	Type M1	3,8	6,4	38	Type M2	4,0	4,0	36	Type M3	3,2	3,2	46	Type M4	4,2	4,2	44	Type M5	4,0	4,0	40	Type M6	Ø 5,0		65
Variant	Dimension W mm	Dimension H mm	Dimension L mm																												
Type M1	3,8	6,4	38																												
Type M2	4,0	4,0	36																												
Type M3	3,2	3,2	46																												
Type M4	4,2	4,2	44																												
Type M5	4,0	4,0	40																												
Type M6	Ø 5,0		65																												

1 Scope

1.1 Product definition

This document contains the initial, start of life dimensional, optical, mechanical and environmental performance requirements, which multimode mechanical splice needs to meet in order for it to be categorized as a European standard product.

Although, in this document, the product is qualified for EN IEC 60793-2-10 types A1-OM1, A1-OM2, A1-OM3, A1-OM4 and A1-OM5 multimode fibres, it can also be suitable for other fibre types with 125 µm cladding diameter.

1.2 Interoperability

The installed mechanical splice fits into optical fibre management system with optical splice cassettes or splice trays as defined in EN IEC 61756-1. This document specifies the following two physical interface dimensions:

- cross sectional profile with width, height or diameter (in millimetres);
- length (in millimetres).

1.3 Expected performance

In this document, the performance of the mechanical splice is given with identical fibres only as specified in Annex A. Losses associated with tolerances in fibre cladding diameter and core diameter mismatch are not taken into account. The measured attenuation is a function of the core concentricity, cladding non-circularity and alignment capability. The optical return loss performance is a function of the index matching gel and the fibre end face preparation

1.4 Operating environment

The tests selected combined with the severities and durations are representative of an outdoor enclosed environment category OP as defined in EN IEC 61753-1:2018, Table A.5. To ensure that the product can be used in outdoor closures, boxes or street cabinets for categories A, G or S (as defined in EN IEC 61753-1:2018, Tables A.13, A.14 and A.15) the specified lower temperature is extended to -40 °C and a water immersion requirement for temporary flooding conditions has been added.

1.5 Reliability

Whilst the anticipated service life expectancy of the product in this environment is at least 20 years, compliance with this specification does not guarantee the reliability of the product. This is expected to be predicted using a recognized reliability assessment programme.

1.6 Quality assurance

Compliance with this specification does not guarantee the manufacturing consistency of the product. This is expected to be maintained using a recognized quality assurance programme.

EN 50411-3-6:2022 (E)**2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN IEC 60793-2-10, *Optical fibres - Part 2-10: Product specifications - Sectional specification for category A1 multimode fibres*(IEC 60793-2-10)

EN 61300-1, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 1: General and guidance* (IEC 61300 1)

EN 61300-2-1, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-1: Tests - Vibration (sinusoidal)* (IEC 61300 2 1)

EN IEC 61300-2-4, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-4: Tests - Fibre or cable retention* (IEC 61300 2 4)

EN 61300-2-5, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-5: Tests – Torsion* (IEC 61300 2 5)

EN 61300-2-7, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-7: Tests - Bending moment* (IEC 61300 2 7)

EN 61300-2-9, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-9: Tests - Shock* (IEC 61300 2 9)

EN 61300-2-17, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-17: Tests - Cold* (IEC 61300 2 17)

EN 61300-2-18, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-18: Tests - Dry heat - High temperature endurance* (IEC 61300 2 18)

EN 61300-2-22, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-22: Tests - Change of temperature* (IEC 61300 2 22)

EN 61300-2-26, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-26: Tests - Salt mist* (IEC 61300 2 26)

EN 61300-2-27, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-27: Tests - Dust - Laminar flow* (IEC 61300 2 27)

EN 61300-2-33, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-33: Tests - Assembly and disassembly of fibre optic mechanical splices, fibre management systems and closures* (IEC 61300 2 33)

EN 61300-2-45, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-45: Tests - Durability test by water immersion* (IEC 61300 2 45)

EN IEC 61300-2-46, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 2-46: Tests - Damp heat, cyclic* (IEC 61300 2 46)

EN 61300-3-3, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 3-3: Examinations and measurements - Active monitoring of changes in attenuation and return loss* (IEC 61300 3 3)

EN 61300-3-4, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 3-4: Examinations and measurements - Attenuation (IEC 61300 3 4)*

EN 61300-3-6, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 3-6: Examinations and measurements - Return loss (IEC 61300 3 6)*

EN 61300-3-28, *Fibre optic interconnecting devices and passive components - Basic test and measurement procedures - Part 3-28: Examinations and measurements - Transient loss (IEC 61300 3 28)*

koniec náhľadu – text d'alej pokračuje v platenej verzii STN