STN

Železnice Manažérstvo trenia medzi kolesom a koľajnicou Časť 2-1: Vlastnosti a charakteristiky Mazivá okolesníkov

STN EN 15427-2-1

28 2237

Railway applications - Wheel/Rail friction management - Part 2-1: Properties and Characteristics - Flange lubricants

Táto norma obsahuje anglickú verziu európskej normy. This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 08/22

Obsahuje: EN 15427-2-1:2022

Oznámením tejto normy sa ruší STN EN 16028 (73 2280) z januára 2013



STN EN 15427-2-1: 2022

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 15427-2-1

May 2022

ICS 45.040; 75.100

Supersedes EN 16028:2012

English Version

Railway applications - Wheel/Rail friction management - Part 2-1: Properties and Characteristics - Flange lubricants

Applications ferroviaires - Gestion des frottements roue/rail - Partie 2-1: Propriétés et caractéristiques -Lubrification des boudins de roues Bahnanwendungen - Reibungsmanagement zwischen Rad und Schiene - Teil 2 1: Eigenschaften und Merkmale - Spurkranzschmierstoffe

This European Standard was approved by CEN on 17 January 2022.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN 15427-2-1:2022 (E)

Contents European foreword		Page	
			1
2	Normative references	5	
3	Terms and definitions	6	
4	Design requirements	8	
5 5.1 5.2	Technical specification and product approval	8	
5.3 6 6.1 6.2 6.3 6.4	Technical file Control and monitoring of product Manufacturing process Composition of lubricant Routine tests Additional measures	9 9 9	
7 7.1 7.2 7.3 7.4	Technical datasheet	9 9 9	
8	Packaging, labelling and storage	10	
Annex A (normative) Requirements for lubricants and testing		11	
Anno	ex B (informative) Water wash-off test	21	
Annex C (informative) Corrosion test on steel		23	
Anno	ex D (informative) Behaviour at an elevated temperature – adhesion on steel sheet	25	
Anno	ex E (informative) Determination of the volatile constituents in greases	27	
Ann	ex F (informative) Peak forming and droop	29	
Ann	ex G (informative) Functional test on specific equipment	32	
Anno	ex H (informative) Solid flange lubricant stick testing and starvation test on twin-disc machine	38	
Anno	ex I (informative) Mini Traction Machine creep curve test	44	
Bibliography		53	

European foreword

This document (EN 15427-2-1:2022) has been prepared by Technical Committee CEN/TC 256 "Railway Applications", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2022, and conflicting national standards shall be withdrawn at the latest by November 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 16028:2012.

This document is part of the following series:

- EN 15427-1-1, Railway applications Wheel/Rail friction management Part 1-1: Equipment and Application Flange lubrication
- CEN/TS 15427-1-2, Railway applications Wheel/Rail friction management Part 1-2: Equipment and Application Top of Rail materials
- CEN/TS 15427-1-3, Railway applications Wheel/Rail friction management Part 1-3: Equipment and Application Adhesion materials
- EN 15427-2-1, Railway applications Wheel/Rail friction management Part 2-1: Properties and Characteristics Flange lubricants
- CEN/TS 15427-2-2, Railway applications Wheel/Rail friction management Part 2-2: Properties and Characteristics Top of Rail materials
- CEN/TS 15427-2-3, Railway applications Wheel/Rail friction management Part 2-3: Properties and Characteristics Adhesion materials

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

EN 15427-2-1:2022 (E)

Introduction

Friction management using solid or fluid (oil, grease, etc.) substances at the wheel-rail interface is a complex subject and includes the following aspects:

- lubrication of the wheel flange / rail gauge corner interface, commonly referred to as "flange or rail lubrication";
- lubrication of the back of flange/ check rail interface; commonly referred to as "check rail lubrication";
- altering the level of friction at the interface between the top of rail and the wheel tread, commonly referred to as "top of rail friction management";
- altering the level of adhesion at the interface between the top of rail and the wheel tread.

This document sets out requirements for the lubricant for flange or rail lubrication. It specifies requirements for the lubricant, how to test it and how to approve it.

Lubricants should be tested to confirm there is:

- compatibility with lubricating systems;
- no intolerable increased risk of fire:
- accordance with relevant environmental requirements;
- no incompatibility between the different lubricants in use, particularly between solid and fluid systems;
- satisfactory and consistent product quality and performance;
- no degradation to the safety of the railway (braking, signalling).

The main purpose of the lubricant is to reduce friction and wear and reduce the risk of flange climb derailment.

1 Scope

This document specifies the properties and characteristics of lubricants applied to the interface between the wheel flange and the gauge face of the rail, and contact area between the check rail face and the back of the wheel (active interface), either directly or indirectly to the wheel flange or to the rail, and includes both trainborne and trackside solutions.

It outlines the information required for most approval procedures, the method of testing and routine control/monitoring of the lubricant.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 10130, Cold rolled low carbon steel flat products for cold forming - Technical delivery conditions

EN ISO 868, Plastics and ebonite - Determination of indentation hardness by means of a durometer (Shore hardness) (ISO 868)

EN ISO 1183-1, Plastics - Methods for determining the density of non-cellular plastics - Part 1: Immersion method, liquid pycnometer method and titration method (ISO 1183-1)

EN ISO 2592, Petroleum and related products - Determination of flash and fire points - Cleveland open cup method (ISO 2592)

EN ISO 3146, Plastics - Determination of melting behaviour (melting temperature or melting range) of semicrystalline polymers by capillary tube and polarizing-microscope methods (ISO 3146)

EN ISO 3675, Crude petroleum and liquid petroleum products - Laboratory determination of density - Hydrometer method (ISO 3675)

EN ISO 7827, Water quality - Evaluation of the "ready", "ultimate" aerobic biodegradability of organic compounds in an aqueous medium - Method by analysis of dissolved organic carbon (DOC) (ISO 7827)

EN ISO 9408, Water quality - Evaluation of ultimate aerobic biodegradability of organic compounds in aqueous medium by determination of oxygen demand in a closed respirometer (ISO 9408)

EN ISO 9439, Water quality - Evaluation of ultimate aerobic biodegradability of organic compounds in aqueous medium - Carbon dioxide evolution test (ISO 9439)

EN ISO 10707, Water quality - Evaluation in an aqueous medium of the "ultimate" aerobic biodegradability of organic compounds - Method by analysis of biochemical oxygen demand (closed bottle test) (ISO 10707)

EN ISO 12185, Crude petroleum and petroleum products - Determination of density - Oscillating U-tube method (ISO 12185)

EN ISO 20623, Petroleum and related products - Determination of the extreme-pressure and anti-wear properties of lubricants - Four-ball method (European conditions) (ISO 20623)

ISO 760, Determination of water — Karl Fischer method (General method)

ISO 2137, Petroleum products and lubricants — Determination of cone penetration of lubricating greases and petrolatum

EN 15427-2-1:2022 (E)

ISO 2176, Petroleum products — Lubricating grease — Determination of dropping point

ISO 3733, Petroleum products and bituminous materials — Determination of water — Distillation method

ISO 22285, Petroleum products and lubricants — Determination of oil separation from grease — Pressure filtration method

ISO 6072, Rubber — Compatibility between hydraulic fluids and standard elastomeric materials

ISO 6743-99, Lubricants, industrial oils and related products (class L) — Classification — Part 99: General

ISO 13737, Petroleum products and lubricants — Determination of low-temperature cone penetration of lubricating greases

DIN 51631, Mineral spirits — Special boiling point spirits — Requirements

DIN 51807-1, Testing of lubricants — Test of the behaviour of lubricating greases in the presence of water — Part 1: Static test

koniec náhľadu – text ďalej pokračuje v platenej verzii STN