

STN	Spoločné metódy skúšok káblov v podmienkach požiaru Meranie uvoľňovania tepla a tvorby dymu na kábloch počas skúšky šírenia plameňa Skúšobné zariadenia, postupy, výsledky	STN EN 50399 34 7104
------------	---	--

Common test methods for cables under fire conditions - Heat release and smoke production measurement on cables during flame spread test - Test apparatus, procedures, results

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 11/22

Obsahuje: EN 50399:2022

Oznámením tejto normy sa od 08.08.2025 ruší
STN EN 50399 (34 7104) z apríla 2012

EUROPEAN STANDARD

EN 50399

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2022

ICS 13.220.40; 29.060.20

Supersedes EN 50399:2011; EN 50399:2011/A1:2016

English Version

Common test methods for cables under fire conditions - Heat release and smoke production measurement on cables during flame spread test - Test apparatus, procedures, results

Méthodes d'essai communes aux câbles soumis au feu -
Mesure de la chaleur et de la fumée dégagées par les
câbles au cours de l'essai de propagation de la flamme -
Appareillage d'essai, procédure et résultats

Allgemeine Prüfverfahren für das Verhalten von Kabeln und
isolierten Leitungen im Brandfall - Messung der
Wärmefreisetzung und Raucherzeugung während der
Prüfung der Flammenausbreitung - Prüfeinrichtung,
Prüfverfahren und Prüfergebnis

This European Standard was approved by CENELEC on 2022-08-08. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN 50399:2022 (E)

Contents	Page
European foreword	6
Introduction	7
1 Scope	9
2 Normative references	9
3 Terms and definitions	9
4 Test apparatus	11
4.1 General	11
4.2 Test chamber	11
4.3 Ignition source	12
4.4 Ladder	13
4.5 Inlet air supply	13
4.6 Hood	14
4.7 Exhaust duct	14
4.8 Extracting ventilator; effluent cleaning	15
4.9 Smoke production measuring equipment	16
4.10 Combustion gas analysis equipment	16
5 Qualification of test apparatus	17
5.1 General	17
5.2 Flow distribution measurements	17
5.3 Sampling delay time measurement	17
5.4 Commissioning calibrations	18
5.5 Routine calibration	18
5.6 Check of the flame shape	19
5.7 Performance checks of the test equipment	19
6 Test procedure	19
6.1 Initial test conditions	19
6.2 Test sample	19
6.3 Sample conditioning	19
6.4 Determination of the number of test pieces	20
6.5 Mounting of the test sample	21
6.6 Exhaust volume flow	23
6.7 Propane and air flow rates to burner	23
6.8 Flame application time	23
6.9 Testing operations	23
6.10 Observations and measurements during the test	24
7 Determination of parameters derived from the test	25
7.1 Calculation of <i>HRR</i> and <i>SPR</i> parameters	25
7.2 Determination of extent of flame spread (<i>FS</i>)	26
8 Test report	26
8.1 General	26
8.2 Contents	26

Annex A (normative) Calculation of heat release	46
A.1 Volume flow	46
A.2 Generated heat effect.....	46
A.2.1 Heat release from the ignition source.....	46
A.2.2 Heat release from a tested product.....	47
A.3 Calculation of the mole fraction of water vapour in the air	48
Annex B (normative) Smoke production	49
Annex C (informative) Additional information on Reynolds number in Figure 13.....	50
Annex D (normative) Flow distribution inside the duct	51
D.1 General	51
D.2 Velocity profile factor k_c.....	51
D.2.1 General	51
D.2.2 Measurement specifications.....	51
D.2.3 Actions	52
D.2.4 Calculation of k_c.....	52
D.2.5 Measurement report.....	53
Annex E (normative) Commissioning calibrations.....	54
E.1 General procedures for separate pieces of equipment.....	54
E.2 Gas analyser calibrations.....	54
E.2.1 General	54
E.2.2 Oxygen analyser adjustment.....	54
E.2.3 Oxygen analyser output noise and drift	54
E.2.4 Carbon dioxide analyser adjustment.....	55
E.3 HRR calibrations.....	55
E.3.1 General	55
E.3.2 HRR calibration by means of the burner	55
E.3.3 HRR calibration by means of burning a flammable liquid.....	57
E.3.4 Commissioning factor k_t used for HRR calculations	58
E.4 Smoke measurement system calibration	59
E.4.1 General	59
E.4.2 Stability check.....	59
E.4.3 Optical filter check for white light systems.....	59
E.4.4 Smoke calibration by means of burning a flammable liquid.....	59
Annex F (informative) Guidance on calibration procedures for specific measuring equipment	62
F.1 General procedures for separate pieces of equipment.....	62
F.2 Gas analyser calibrations.....	62
F.2.1 Oxygen analyser adjustment.....	62
F.2.2 Carbon dioxide analyser adjustment.....	62
F.3 Check of propane mass flow controller.....	62
F.3.1 General	62
F.3.2 Actions	63
F.3.3 Criterion	63

EN 50399:2022 (E)

F.4 Optical filter check for white light systems	63
F.4.1 General	63
F.4.2 Actions	63
F.4.3 Criterion	63
Annex G (normative) Calculation of HRR_{av}, SPR_{av} and $FIGRA$	64
G.1 Calculation of HRR_{av}	64
G.2 Calculation of SPR_{av}	65
G.3 Calculation of the Fire Growth Rate Index ($FIGRA$)	66
Annex H (informative) Guidance on the choice of test equipment.....	68
H.1 General	68
H.2 Burner and venturi mixer.....	68
H.3 Mass flow controllers.....	68
H.4 Backing board	68
Annex I (normative) Guidance on the file format for data from the test	69
Annex J (normative) Rounding of numbers	73
Annex K (informative) Check of the flame shape for nominal heat output of 20,5 kW.....	74
K.1 Introduction.....	74
K.2 Preparation of the wooden boards.....	74
K.3 Procedure (to be performed in duplicate).....	75
K.4 Evaluation	76
K.5 Flame shape analysis	79
Annex L (informative) Guidance on conducting performance checks of the test equipment. 82	
L.1 Introduction.....	82
L.2 Fire test cable	82
L.3 Performance of the fire test cable	83
L.4 Procedure to check the performance of the test equipment.....	83
L.5 Use of an alternative cable	84
Bibliography	85

Figures

Figure 1 — General arrangement of test apparatus	28
Figure 2 — Test chamber — dimensions	29
Figure 3 — Test chamber — schematic side elevation and air inlet arrangement.....	30
Figure 4 — Thermal insulation of back- and sidewalls of the test chamber	31
Figure 5 — Positioning of burner and typical arrangement of test sample on ladder.....	32
Figure 6 — Burner configuration.....	33
Figure 7 — Arrangement of holes for burners	34
Figure 8 — Schematic diagram of a burner control system using Mass Flow Controllers	35
Figure 9 — Tubular steel ladder for EN 50399 cable test.....	36
Figure 10 — Schematic drawing of a hood.....	37
Figure 11 — Typical guide vanes	38
Figure 12 — Bidirectional probe	39
Figure 13 — Probe response versus Reynolds number.....	40

Figure 14 — Sampling probe	41
Figure 15 — Schematic diagram of sampling line	42
Figure 16 — Schematic drawing of smoke production measuring system	43
Figure 17 — Mounting of bundles	44
Figure 18 — Backboard mounting arrangement for Class B1 _{ca}	45
Figure D.1 — Section of the exhaust duct – Positions for measurement of the gas velocity	52
Figure E.1 — Overview of commissioning calibrations	61
Figure K.1 — Shape and dimensions of the wooden board	75
Figure K.2 — Positioning of the wooden board at the centre of the burner	76
Figure K.3 — Examples of a flame shape on a wooden board (flame profile = dotted line; flame tip = X)	78
Figure K.4 — Envelope of acceptable flame profiles	79
Figure L.1 — Illustration of the recommended fire test cable	83

Tables

Table 1 — Mounting as a function of cable dimension	22
Table E.1 — Burner ignition times and HRR levels	56
Table E.2 — Example of determination of commissioning k_t factor	58
Table I.1 — Example of the required raw data file format	70
Table K.1 — Coordinates for the flame profile envelope (see Figure K.4)	80
Table K.2 — Coordinates for the minimum of the flame tip (see Figure K.4)	81

EN 50399:2022 (E)**European foreword**

This document (EN 50399:2022) has been prepared by CLC/TC 20, "Electric cables".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2023-08-08
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2025-08-08

This document supersedes EN 50399:2011 and all of its amendments and corrigenda (if any).

EN 50399:2022 includes the following significant technical changes with respect to EN 50399:2011:

- inclusion of the detailed description of the test apparatus in this document, rather than by reference to EN 60332-3-10 (see 4.1).
- improvements in the test apparatus (see 4.2 to 4.7), including the mandatory use of mass flow controllers for the supply of gases to the burner.
- several improvements of the qualification of the test equipment, including guidance for a check of the flame shape (5.6) and a performance check of the test equipment (5.7).
- additions for testing of flat cables including mounting (see 6.4 and 6.5).
- new informative Annex K (Check of the flame shape for nominal heat output of 20,5 kW).
- new informative Annex L (Guidance on conducting performance checks of the test equipment).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Introduction

EN 50399 specifies the test apparatus and test procedures for the assessment of the reaction to fire performance of cables to enable classification under the Construction Products Regulation [1, 2] to be achieved.

EN 50399 describes an intermediate scale fire test of multiple cables mounted on a vertical cable ladder and is carried out with a specified ignition source to evaluate the burning behaviour of such cables and enable a direct declaration of performance. The test provides data for the early stages of a cable fire from ignition of cables. It addresses the hazard of propagation of flames along the cable, the potential, by the measurement of the heat release rate, for the fire to affect areas adjacent to the compartment of origin, and the hazard, by the measurement of production of light obstructing smoke, of reduced visibility in the room of origin and surrounding enclosures.

The following parameters may be determined under defined conditions during the test:

- a) flame spread.
- b) heat release rate.
- c) total heat release.
- d) smoke production rate.
- e) total smoke production.
- f) fire growth rate index.
- g) occurrence of flaming droplets/particles.

The apparatus is derived from that of EN 60332-3-10 [3, 4] but with modifications and with additional instrumentation to measure heat release and smoke production during the test. It has been demonstrated [5] that the utilization of these additional measurement techniques, proven for other standard tests e.g. for other building products, are appropriate for assessing the reaction to fire performance of electric cables. These techniques include heat release and smoke production measurements. Compared with the test methods described in the EN 60332-3 series, they enable a more comprehensive assessment system, which is both more precise and sensitive, and enables a wider range of fire performance levels.

Care should be exercised in relating the parameters measured to different safety levels in actual cable installations as the actual installed configuration of the cables could be a major determinant in the level of flame spread, heat release and smoke production occurring in an actual fire. These parameters depend upon several features, such as:

- a) the volume of combustible material exposed to the fire and to any flaming or heat which could be produced by the combustion of the cables.
- b) the geometrical configuration of the cables and their relationship to an enclosure.
- c) the temperature at which it is possible to ignite the gases emitted from the cables.
- d) the quantity of combustible gas released from the cables for a given temperature rise.
- e) the volume of air passing through the cable installation.
- f) the construction of the cable e.g. armoured or unarmoured, multi- or single core.

All the foregoing assumes that the cables can be ignited when involved in an external fire.

The conditions of cable mounting, including volume of material exposed and geometrical configuration of the cables on the test ladder, and volume of airflow through the chamber have been chosen to be in accordance with that required by the Commission Decision 2006/751/EC [6]. CENELEC has not been

EN 50399:2022 (E)

involved in the definition of these parameters. These standardized conditions provide the basis for classification, as detailed in EN 13501-6 [7] and EN 50575 [2], but do not necessarily correspond to conditions found in a particular cable installation.

EN 50399 gives the detailed description of the test apparatus and details of the test procedures, which are used.

1 Scope

This document specifies the apparatus and methods of test for the assessment of vertical flame spread, heat release, smoke production and occurrence of flaming droplets/particles of vertically mounted electric cables under defined conditions.

NOTE For the purpose of this document, the term “electric cable” covers all power, control and communication cables, including optical fibre cables and hybrid cables used for the conveyance of energy and/or signals.

This document details the apparatus for the fire propagation testing and the arrangement and calibration of the instrumentation to be installed to measure the heat release and the smoke production during the test. The combustion gases are collected in a hood above the test chamber and conveyed through an exhaust system, which allows the measurement of heat release rate and smoke production. Test procedures to be used for type approval testing for classification of cables in classes [2, 7] B1_{ca}, B2_{ca}, C_{ca} and D_{ca} are given. Cable installation on the test ladder and the volume of air passing through the chamber are in accordance with the Commission Decision 2006/751/EC [6], which is reflected in the requirements of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60584-1, *Thermocouples - Part 1: EMF specifications and tolerances (IEC 60584-1)*

EN 60811-203, *Electric and optical fibre cables - Test methods for non-metallic materials - Part 203: General tests - Measurement of overall dimensions (IEC 60811-203)*

EN ISO 13943, *Fire safety - Vocabulary (ISO 13943)*

koniec náhľadu – text ďalej pokračuje v platenej verzii STN