

STN	Rozšírené digitálne bezšnúrové telekomunikácie (DECT) Špecifikácia skúšky Časť 1: Rádio	STN EN 300 176-1 V2.4.1 87 0176
------------	--	---

Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 03/23

Obsahuje: EN 300 176-1 V2.4.1:2022

136423



ETSI EN 300 176-1 V2.4.1 (2022-11)



Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio

Reference

REN/DECT-00365

Keywords

DECT, radio, regulation, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	12
1 Scope	13
2 References	13
2.1 Normative references	13
2.2 Informative references.....	14
3 Definition of terms, symbols and abbreviations.....	15
3.1 Terms.....	15
3.2 Symbols.....	18
3.3 Abbreviations	18
4 General	20
4.1 Document layout	20
4.1.1 Test suites	20
4.1.2 Test groups.....	20
4.1.3 Test cases.....	21
4.2 Presentation of equipment for testing purposes.....	21
4.2.0 General.....	21
4.2.1 Choice of model for testing (if applicable).....	21
4.2.2 Description of equipment.....	22
4.2.2.0 General	22
4.2.2.1 Protocol Implementation Conformance Statement (PICS)	22
4.2.2.2 Protocol Implementation eXtra Information for Testing (PIXIT).....	22
4.2.2.3 Environmental test conditions.....	22
4.2.3 Host connected equipment.....	22
4.2.4 Manufacturer's declaration.....	23
4.3 Applicability of tests	23
4.3.0 General.....	23
4.3.1 Equipment that includes only a DECT RF receiver.....	23
4.3.2 Equipment that includes a radio transmitter	23
4.3.3 CTAs.....	23
4.3.4 Equipment with a synchronization port	23
4.3.5 Equipment incorporating the IPEI (PPs only).....	23
4.3.6 All FP equipment.....	23
4.3.7 PPs with direct PP to PP communication option	23
4.3.8 Installation related issues	24
4.3.9 Equipment with combined FT and PT functionality.....	24
4.3.9.0 General.....	24
4.3.9.1 Wireless Relay Station	24
4.3.9.2 Direct PP to PP communication	24
4.3.9.3 Distributed communications	24
4.3.10 Equipment that is capable of using higher level modulation	25
4.3.11 Equipment supporting additional carriers	25
4.4 Interpretation of the measurement results	25
5 General test requirements.....	25
5.1 Test philosophy	25
5.2 Test site	26
5.2.1 Open air test site	26
5.2.1.1 Description	26
5.2.1.2 Calibration.....	27
5.2.2 Anechoic chamber	28
5.2.2.1 General	28
5.2.2.2 Description	28
5.2.2.3 Influence of parasitic reflections	31

5.2.2.4	Calibration and mode of use.....	31
5.2.3	Stripline coupler.....	31
5.2.3.0	General.....	31
5.2.3.1	Description.....	31
5.2.3.2	Calibration.....	31
5.2.3.3	Mode of use.....	31
5.3	Standard position.....	32
5.4	Test antenna of the LT.....	32
5.5	Substitution antenna.....	32
5.6	Test fixture.....	32
5.6.1	Description.....	32
5.6.1.0	General.....	32
5.6.1.1	Calibration of the test fixture for the measurement of transmitter characteristics.....	33
5.6.1.2	Calibration of the test fixture for the measurement of receiver characteristics.....	33
5.6.1.3	Mode of use.....	34
5.6.2	Equipment with a temporary or internal permanent antenna connector.....	34
5.6.2.0	General.....	34
5.6.2.1	Equipment with a temporary antenna connector.....	34
5.7	Indoor test site.....	35
5.7.0	General.....	35
5.7.1	Description.....	35
5.7.2	Test for parasitic reflections.....	36
5.7.3	Calibration and mode of use.....	36
5.8	Lower Tester (LT).....	36
5.8.1	Description.....	36
5.8.2	Connections between the EUT and the LT.....	37
5.8.3	Functions and abilities.....	37
5.8.4	Signal generation uncertainty.....	38
5.8.4.0	General.....	38
5.8.4.1	Modulated DECT-like carrier.....	38
5.8.4.2	CW interferers.....	38
5.8.4.3	DECT RF signal.....	38
5.8.4.4	Test modulation signals.....	38
5.8.5	Measurement uncertainty.....	38
5.9	Upper Tester (UT).....	39
5.9.1	Description of the UT.....	39
5.9.2	The test standby mode.....	39
5.9.3	Test messages.....	39
5.9.4	Dummy setting when EUT is a RFP and it is in test stand-by mode.....	40
5.10	Description of the lower tester FT and PT.....	40
5.11	General test methods.....	40
5.11.1	General.....	40
5.11.2	Sampling the RF signal.....	40
5.11.2.1	Introduction.....	40
5.11.2.2	Sampling method.....	40
5.11.3	Determining the reference position.....	40
5.11.3.0	General.....	40
5.11.3.1	Case 1: EUTs that cannot transmit.....	41
5.11.3.2	Case 2: EUTs that can transmit.....	41
5.11.4	Bit Error Rate (BER) and Frame Error Ratio (FER) measurements.....	41
5.12	Test setup.....	41
5.12.0	General.....	41
5.12.1	Test setup 1.....	41
5.12.2	Test setup 2.....	41
5.12.3	Test setup 3.....	42
5.12.4	Test setup 4.....	43
5.12.5	Void.....	43
5.13	Test arrangements for intermodulation measurements.....	43
5.13.1	PT to PT arrangement.....	43
5.13.2	FT to FT arrangement.....	44
5.13.3	FT to PT arrangement.....	44

6	Test conditions, power sources and ambient temperatures	45
6.1	General	45
6.2	Nominal test conditions.....	45
6.3	Extreme test conditions	46
6.4	Test power source - general requirements.....	47
6.5	Nominal test power source	47
6.5.1	Mains voltage.....	47
6.5.2	Regulated lead acid battery power sources.....	47
6.5.3	Nickel cadmium or nickel metal hydride battery	47
6.5.4	Other power sources	47
6.6	Extreme test power source.....	48
6.6.1	Mains voltage.....	48
6.6.2	Regulated lead acid battery power sources.....	48
6.6.3	Nickel cadmium or nickel metal hydride battery	48
6.6.4	Other power sources	48
6.7	Testing of host connected equipment and plug-in cards.....	48
6.7.0	Approaches	48
6.7.1	Alternative A: composite equipment	48
6.7.2	Alternative B: use of a test jig and three hosts.....	49
7	Accuracy and stability of RF carriers.....	49
7.0	Requirements.....	49
7.1	Definition	49
7.2	Test environment.....	50
7.3	Method of measurement	50
7.4	Verdict criteria when the EUT is a RFP	51
7.5	Verdict criteria when the EUT is a PP.....	51
8	Accuracy and stability of timing parameters.....	51
8.0	Requirements.....	51
8.0.1	General.....	51
8.0.2	Limits.....	51
8.0.2.1	Reference timer accuracy and stability	51
8.0.2.2	RFP transmission jitter	51
8.0.2.3	PP reference timer synchronization.....	52
8.1	Slot structure definitions	52
8.2	Definition of the position of p0	52
8.3	Measurement of packet timing jitter.....	52
8.3.1	Test environment	52
8.3.2	Method of measurement	53
8.3.3	Verdict criteria	53
8.4	Measurement of the reference timing accuracy of a RFP.....	53
8.4.1	Test environment	53
8.4.2	Method of measurement	53
8.4.3	Verdict criteria	54
8.5	Measurement of packet transmission accuracy of a PP	54
8.5.1	Test environment	54
8.5.2	Method of measurement	54
8.5.3	Verdict criteria	55
9	Transmission burst	55
9.0	Requirements.....	55
9.0.1	General.....	55
9.0.2	Limits.....	55
9.0.2.1	Transmitter attack time	55
9.0.2.2	Transmitter release time	55
9.0.2.3	Minimum power.....	55
9.0.2.4	Maximum power	56
9.0.2.5	Maintenance of transmission after packet end	56
9.0.2.6	Transmitter idle power output.....	56
9.1	Definitions	56
9.1.0	Introduction.....	56
9.1.1	Physical packets.....	56

9.1.2	Transmitted power	56
9.1.3	Normal Transmitted Power (NTP).....	56
9.1.4	Transmitter attack time	57
9.1.5	Transmitter release time.....	57
9.1.6	Minimum power	57
9.1.7	Maximum power.....	57
9.1.8	Maintenance of transmission after packet end.....	57
9.1.9	Transmitter idle power output.....	57
9.1.10	Nominal transceiver definition	57
9.1.11	P _{NTP} definition.....	58
9.1.12	Multi-transceiver systems	58
9.2	Test environment.....	58
9.3	Method of measurement	58
9.4	Verdict criteria.....	58
10	Transmitted power.....	59
10.0	Requirements.....	59
10.0.1	General.....	59
10.0.2	Limits.....	59
10.0.3	Conformance.....	59
10.0.4	Multi-transceiver systems	59
10.1	Definitions	59
10.1.1	PP and RFP with an integral antenna.....	59
10.1.2	PP and RFP with external connections for all antennas.....	60
10.1.3	PP and RFP with both integral and external antennas	60
10.2	PP and RFP with an integral antenna	60
10.2.1	Test environment	60
10.2.2	Method of measurement	60
10.2.2.0	General.....	60
10.2.2.1	Measurement of NTP	60
10.2.2.2	Measurement of antenna gain	60
10.2.2.3	Determination of EIRP.....	61
10.2.3	Verdict criteria for all EUTs	61
10.3	PP and RFP with external antenna connection(s).....	61
10.3.1	Test environment	61
10.3.2	Method of measurement	62
10.3.3	Verdict criteria for all EUTs	62
11	RF carrier modulation	62
11.0	Requirements.....	62
11.0.1	General.....	62
11.0.2	Limits.....	62
11.1	Test environment.....	63
11.2	Method of measurement, parts 1 and 2.....	63
11.2.0	General.....	63
11.2.1	Part 1.....	63
11.2.2	Part 2.....	64
11.3	Method of measurement, parts 3 and 4.....	64
11.3.0	General.....	64
11.3.1	Part 3.....	64
11.3.2	Part 4.....	65
11.4	Verdict criteria for part 1.....	65
11.5	Verdict criteria for part 2.....	65
11.6	Verdict criteria for part 3.....	65
11.7	Verdict criteria for part 4.....	65
12	Unwanted RF power radiation	67
12.1	General test conditions	67
12.2	Emissions due to modulation.....	67
12.2.0	Definition.....	67
12.2.1	Requirements	67
12.2.2	Test environment	67
12.2.3	Method of measurement	67

12.2.4	Verdict criteria	68
12.3	Emissions due to transmitter transients	68
12.3.0	Requirements	68
12.3.0.1	General	68
12.3.0.2	Limits	68
12.3.1	Definition	69
12.3.2	Test environment	69
12.3.3	Method of measurement	69
12.3.4	Verdict criteria	70
12.4	Emissions due to intermodulation	70
12.4.0	Requirements	70
12.4.0.1	General	70
12.4.0.2	Limits	70
12.4.1	Definition	70
12.4.2	Test environment	70
12.4.3	Method of measurement	70
12.4.4	Verdict criteria	71
12.5	Spurious emissions when allocated a transmit channel	71
12.5.0	Requirements	71
12.5.0.1	General	71
12.5.0.2	Limits	71
12.5.1	Definition	72
12.5.2	Radiated emissions	72
12.5.2.1	Test environment	72
12.5.2.2	Method of measurement	72
12.5.2.3	Verdict criteria	73
12.5.3	Conducted spurious emissions when the EUT has a permanent external antenna connector	73
12.5.3.1	Test environment	73
12.5.3.2	Method of measurement	73
12.5.3.3	Verdict criteria	73
13	Radio receiver testing	74
13.1	Radio receiver sensitivity	74
13.1.0	Requirements	74
13.1.0.1	General	74
13.1.0.2	Limits	74
13.1.1	Definition	74
13.1.2	Test environment	74
13.1.3	Method of measurement	74
13.1.4	Verdict criteria	75
13.2	Radio receiver reference BER and FER	75
13.2.0	Requirements	75
13.2.0.1	General	75
13.2.0.2	Limits	75
13.2.1	Definition	75
13.2.2	Test environment	75
13.2.3	Method of measurement	75
13.2.4	Verdict criteria	76
13.3	Radio receiver interference performance	76
13.3.0	Requirements	76
13.3.0.1	General	76
13.3.0.2	Limits	76
13.3.1	Definition	76
13.3.2	Test environment	76
13.3.3	Method of measurement	76
13.3.4	Verdict criteria	77
13.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	77
13.4.0	Requirements	77
13.4.0.1	General	77
13.4.0.2	Limits	77
13.4.1	Definition	77
13.4.2	Test environment	77

13.4.3	Method of measurement	78
13.4.4	Verdict criteria	79
13.5	Radio receiver blocking case 2: owing to signals occurring at a different time	79
13.5.0	Requirements	79
13.5.0.1	General	79
13.5.0.2	Limits	79
13.5.1	Definition	79
13.5.2	Test environment	79
13.5.3	Method of measurement	80
13.5.4	Verdict criteria	80
13.6	Receiver intermodulation performance	80
13.6.0	Requirements	80
13.6.0.1	General	80
13.6.0.2	Limits	80
13.6.1	Definition	81
13.6.2	Test environment	81
13.6.3	Method of measurement	81
13.6.4	Verdict criteria	81
13.7	Spurious emissions when the PP has no allocated transmit channel	82
13.7.0	Requirements	82
13.7.0.1	General	82
13.7.0.2	Limits	82
13.7.0.2.1	Out of band	82
13.7.0.2.2	In the DECT band	82
13.7.1	Definition	82
13.7.2	Test environment	82
13.7.3	Method of measurement	82
13.7.4	Verdict criteria (outside the DECT band)	83
13.7.5	Verdict criteria (inside the DECT band)	83
14	Intersystem synchronization (FP only)	83
14.0	Requirements	83
14.1	Description	83
14.2	Test environment	83
14.3	Wired synchronization ports	83
14.3.1	FP as a master	83
14.3.1.1	Method of measurement	83
14.3.1.2	Verdict criteria	84
14.3.2	FP as a slave	84
14.3.2.1	Method of measurement	84
14.3.2.2	Verdict criteria	85
14.4	GPS synchronization	85
14.4.1	FP with integrated Global Positioning System (GPS) synchronization	85
14.4.1.1	Method of measurement	85
14.4.1.2	Verdict criteria	85
14.4.2	External GPS synchronization device	86
14.4.2.1	Method of measurement	86
14.4.2.2	Verdict criteria	86
15	EMC	86
16	Equipment identity testing	86
16.0	General	86
16.1	PP	86
16.2	FP	87
17	Efficient use of the radio spectrum	87
17.1	Channel selection	87
17.2	Channel confirmation	87
17.2.1	For the PT	87
17.2.2	For the FT	87
17.3	Channel release	88
17.4	General	88

17.5	Channel selection and confirmation for DECT ULE	88
17.5.1	General.....	88
17.5.2	For the PT	88
17.5.3	For the FT	89
17.6	Test Methods for channel selection.....	89
17.6.1	Test environment	89
17.6.2	FT Test Setup.....	89
17.6.2.1	General	89
17.6.2.2	FT Method of Measurement.....	90
17.6.2.3	FT Verdict Criteria.....	90
17.6.3	PT Test Setup.....	90
17.6.3.1	General	90
17.6.3.2	PT Method of Measurement.....	91
17.6.3.3	PT Verdict Criteria.....	91
17.6.4	Channel Release.....	91
17.6.4.1	General	91
17.6.4.2	Method of Measurement	92
17.6.4.3	Channel Release Verdict Criteria	92
18	WRS testing.....	93
18.0	General	93
18.1	Testing as a PP	93
18.2	Testing as an RFP.....	93
18.3	Additional requirements	94
18.3.1	General.....	94
18.3.2	Conformance.....	98
18.3.2.1	General	98
18.3.2.2	Testing as a PP	98
18.3.2.3	Testing as an RFP	98
18.3.2.4	Additional requirements.....	98
19	Requirements for PPs with direct PP to PP communication mode	99
19.0	General	99
19.1	Setting the EUT in direct communications mode.....	99
19.2	When the EUT has not initiated a call.....	99
19.3	When the EUT initiates a call.....	99
19.4	Manufacturer's declarations.....	100
20	Distributed communications.....	100
20.0	General	100
20.1	Testing as a PP	100
20.2	Testing as an RFP.....	100
20.3	Conformance	101
21	Higher level modulation options	101
21.0	Requirements.....	101
21.1	Activation of higher level modulations when EUT is in test stand-by mode	102
21.2	Conformance	102
Annex A (informative):	Procedures for test fixture calibration and for measurement of radiated spurious emissions	103
A.1	Calibration of test fixture for receiver measurements	103
A.1.0	General	103
A.1.1	Method of measurement.....	103
A.2	Radiated measurements.....	105
A.2.1	General	105
A.2.2	Radiated spurious emissions.....	105
A.2.2.1	Definition.....	105
A.2.2.2	Method of measurement	106
A.2.3	Cabinet radiation	107
A.2.3.1	Definition.....	107
A.2.3.2	Method of measurement	108

Annex B (informative):	Procedure for measurement of conducted spurious emissions	109
B.1	Conducted spurious emissions	109
B.1.1	Definition	109
B.1.2	Method of measurement	109
Annex C (normative):	Test Support Profile (TSP).....	110
C.1	Introduction	110
C.2	Standardized symbols for the status column	110
C.3	Capabilities of PP (EUT) under test	111
C.3.1	Services	111
C.3.2	Messages	111
C.3.3	Message parameters	113
C.3.4	Procedure support.....	117
C.3.5	CSF multiplexing functions.....	117
C.3.6	Timer and counter support.....	118
C.4	Capabilities of FP (EUT) under test	119
C.4.1	Services	119
C.4.2	Messages	119
C.4.3	Message parameters	121
C.4.4	Procedure support.....	125
C.4.5	CSF multiplexing functions.....	125
C.4.6	Timer and counter support.....	126
Annex D (normative):	Measurement of BER and FER.....	127
Annex E (informative):	Procedures for the measurement of synchronization loss at the EUT by the LT	128
E.1	Description	128
E.2	Method	128
Annex F (informative):	Guidelines for installation related issues	129
F.0	General	129
F.1	Antennas with directivity	129
F.2	DECT frame synchronization.....	129
F.2.0	General	129
F.2.1	Guidance for installation of frame synchronized DECT systems.....	130
F.2.1.1	GPS synchronization.....	130
F.2.1.2	Wired synch port synchronization	130
F.2.1.3	Requirements for DECT air synchronization.....	131
Annex G (informative):	Maximum measurement uncertainty	132
Annex H (informative):	Bibliography.....	133
Annex I (informative):	Change History	134
History		135

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document contains text pertaining to testing of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface [1] to [4] and [i.11] to [i.14]. Such text should be considered as guidance to approval (or licensing) authorities.

The present document covers DECT, DECT Evolution and DECT ULE as defined by the multi-part technical specification ETSI EN 300 175 (see [1] to [4] and [i.11] to [i.14]) and by the multi-part specification ETSI TS 102 939 (see [i.20] and [i.21]).

The present document is part 1 of a multi-part deliverable covering the test specification for Digital Enhanced Cordless Telecommunications (DECT), as identified below:

Part 1: "Radio";

Part 2: "Audio and speech".

National transposition dates	
Date of adoption of this EN:	31 October 2022
Date of latest announcement of this EN (doa):	31 January 2023
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2023
Date of withdrawal of any conflicting National Standard (dow):	31 July 2023

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies tests applicable to all Digital Enhanced Cordless Telecommunications (DECT) equipment accessing the DECT frequency band 1 880 MHz to 1 900 MHz and including provisions for testing other or extended frequency bands as described in ETSI EN 300 175-1 [i.11] and ETSI EN 300 175-2 [1]. Part 2 of the present multi-part deliverable [i.15] specifies tests applicable to DECT speech and audio transmission using a collection of speech codecs, including Recommendation ITU-T G.726 [i.7] ADPCM codec, Recommendation ITU-T G.722 [i.8] "7 kHz codec", "MPEG-4 codec" [i.10], LC3plus [i.24] and others.

The aims of the present document are to ensure:

- efficient use of frequency spectrum;
- no harm done to any connected network and its services;
- no harm done to other radio networks and services;
- no harm done to other DECT equipment or its services;
- interworking of terminal equipment via the public network.

The tests of ETSI EN 300 176 are split into two parts:

- the present document (part 1) covers testing of radio frequency parameters, security elements and those DECT protocols that facilitate the radio frequency tests and efficient use of frequency spectrum;
- part 2 [i.15] describes testing of speech and audio requirements between network interface and DECT PT, or between a DECT CI air interface and alternatively a DECT PT or FT. Part 2 is not applicable to terminal equipment specially designed for the disabled (e.g. with amplification of received speech as an aid for the hard-of-hearing).

DECT terminal equipment consists of the following elements:

- a) Fixed Part (FP);
- b) Portable Part (PP);
- c) Cordless Terminal Adapter (CTA);
- d) Wireless Relay Station (WRS) (FP and PP combined);
- e) Hybrid Part (HyP) (a PP with capability to act as a FP to provide PP to PP communication).

Details of the DECT Common Interface may be found in ETSI EN 300 175-1 [i.11], ETSI EN 300 175 parts 2 to 3 [1] to [2], ETSI EN 300 175-4 [i.12], ETSI EN 300 175 parts 5 to 6 [3] to [4], and ETSI EN 300 175 parts 7 to 8 [i.13] to [i.14]. Further details of the DECT system may be found in the ETSI Technical Report ETSI TR 101 178 [i.1]. Information about ULE may be found in the ETSI Technical Specifications ETSI TS 102 939-1 [i.20] and ETSI TS 102 939-2 [i.21].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [2] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [3] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [4] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [5] Recommendation ITU-T V.11: "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [6] Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [7] ETSI EN 300 700: "Digital Enhanced Cordless Telecommunications (DECT); Wireless Relay Station (WRS)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 178: "Digital Enhanced Cordless Telecommunications (DECT); A High Level Guide to the DECT Standardization".
- [i.2] Void.
- [i.3] ETSI EN 301 649: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)".
- [i.4] ETSI TS 102 527-1: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 1: Wideband speech".
- [i.5] ETSI TS 102 527-2: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 2: Support of transparent IP packet data".
- [i.6] ETSI TS 102 527-3: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 3: Extended Wideband speech services".
- [i.7] Recommendation ITU-T G.726 (1990): "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
- [i.8] Recommendation ITU-T G.722: "7 kHz audio - coding within 64 kbit/s".
- [i.9] ETSI TS 102 527-4: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 4: Light Data Services; Software Update Over The Air (SUOTA), content downloading and HTTP based applications".

- [i.10] ISO/IEC JTC1/SC29/WG11 (MPEG): International Standard ISO/IEC 14496-3:2005/AMD 1:2007: "Information Technology - Coding of audio-visual objects - Part 3: Audio; AMENDMENT 1: Low Delay AAC profile".
- [i.11] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [i.12] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [i.13] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [i.14] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [i.15] ETSI EN 300 176-2: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech".
- [i.16] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [i.17] Void.
- [i.18] Council Directive 2004/108/EC of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC.
- [i.19] ETSI EN 301 406-1: "Digital Enhanced Cordless Telecommunications (DECT); Harmonised Standard for access to radio spectrum; Part 1: DECT, DECT Evolution and DECT ULE".
- [i.20] ETSI TS 102 939-1: "Digital Enhanced Cordless Telecommunications (DECT); Ultra Low Energy (ULE); Machine to Machine Communications; Part 1: Home Automation Network (phase 1)".
- [i.21] ETSI TS 102 939-2: "Digital Enhanced Cordless Telecommunications (DECT); Ultra Low Energy (ULE); Machine to Machine Communications; Part 2: Home Automation Network (phase 2)".
- [i.22] ETSI TR 100 028: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.23] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.24] ETSI TS 103 634: "Digital Enhanced Cordless Telecommunications (DECT); Low Complexity Communication Codec plus (LC3plus)".

koniec náhľadu – text ďalej pokračuje v platenej verzii STN