

# Železnice Manažérstvo trenia medzi kolesom a koľajnicou Časť 1-2: Zariadenie a aplikácia Povrch koľajníc

STN P CEN/TS 15427-1-2

28 2237

Railway applications - Wheel/rail friction management - Part 1-2: Equipment and application - Top of rail

Táto norma obsahuje anglickú verziu európskej normy. This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 12/23

Táto predbežná slovenská technická norma je určená na overenie. Prípadné pripomienky pošlite do septembra 2025 Úradu pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky.

Obsahuje: CEN/TS 15427-1-2:2023

Oznámením tejto normy sa ruší STN P CEN/TS 15427-1-2 (28 2237) z augusta 2021

#### 137807

# TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

**CEN/TS 15427-1-2** 

October 2023

ICS 21.260; 45.080; 45.120

Supersedes CEN/TS 15427-1-2:2021

## **English Version**

# Railway applications - Wheel/rail friction management - Part 1-2: Equipment and application - Top of rail

Applications ferroviaries - Gestion du Frottement Roue/Rail - Partie 1-2 : Équipements et application -Tête de Rail Bahnanwendungen - Reibungsmanagement zwischen Rad und Schiene - Teil 1-2: Vorrichtungen und Anwendung - Kraftschlussmodifikatoren

This Technical Specification (CEN/TS) was approved by CEN on 9 July 2023 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

tents	Page
ean foreword	4
Scope	6
Normative references	6
Terms and definitions	6
Application	8
Requirements for trainborne equipment	9
* *	
Poquiroments for trackside equipment	12
General	12
Installation of trackside equipment	14
4 4	
Trainborne equipment	16
General	16
Fluid top of rail material application to the active interface	16
Solid top of rail material application to the wheel	16
Trackside equipment	16
General	16
Mechanically activated	16
Hydraulically activated	16
Electrically activated	16
<b>B</b> (informative) <b>Guidance on approvals testing and verification</b>	17
General	17
Process for system verification	17
Baselining	17
Approval and safety trials	18
	Scope

<b>B.2.3</b>	Measure effectiveness	18
B.2.4	Monitoring	19
B.2.5	Outcome of trial	19
Annex	c C (informative) Good practice for trainborne equipment	20
<b>C.1</b>	Reasons for installing trainborne equipment	20
<b>C.2</b>	Determination of equipment position	20
<b>C.3</b>	Inspection and maintenance	20
Annex	D (informative) Installation and maintenance good practice for trackside equip	
		25
D.1	Selecting locations for trackside equipment	25
D.2	Determination of equipment position	25
D.3	Inspection and maintenance	26
<b>D.4</b>	Records	26
Annex	E (informative) Guideline braking tests for top of rail friction management	
	(trainborne and trackside equipment)	27
<b>E.1</b>	General	27
<b>E.2</b>	Choosing the right test vehicle	27
E.3	Trainborne equipment	27
<b>E.4</b>	Test conditions	27
E.5	Brake tests	28
E.6	Test parameters	28
Biblio	graphy	29

# **European foreword**

This document (CEN/TS 15427-1-2:2023) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 15427-1-2:2021.

The 2023 edition has been updated with editorial changes following the feedback from the CEN/TS 15427-1-2:2021 edition. This mainly consists of corrections and clarifications and improved consistency with the other standards and technical specifications in the 15427 suite.

This document is part of the following series:

- EN 15427-1-1, Railway applications Wheel/Rail friction management Part 1-1: Equipment and Application Flange lubrication;
- CEN/TS 15427-1-2, Railway applications Wheel/rail friction management Part 1-2: Equipment and application - Top of rail materials;
- CEN/TS 15427-1-3, Railway applications Wheel/rail friction management Part 1-3: Equipment and application – Adhesion materials;
- EN 15427-2-1, Railway applications Wheel/Rail friction management Part 2-1: Properties and Characteristics Flange lubricants;
- CEN/TS 15427-2-2, Railway applications Wheel/rail friction management Part 2-2: Properties and characteristics Top of rail materials;
- CEN/TS 15427-2-3, Railway applications Wheel/Rail friction management Part 2-3: Properties and Characteristics Adhesion materials;
- CEN/prTR 15427-3, Railway applications Wheel/Rail friction management Part 3: Rationale for requirements and further background information.

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

#### Introduction

Friction management using solid or fluid (oil, grease, etc.) substances at the wheel-rail interface is a complex subject and includes:

- lubrication of the wheel flange / rail gauge corner interface, commonly referred to as "flange or rail lubrication";
- lubrication of the back of wheel / check rail face interface, commonly referred to as "check rail lubrication";
- controlling the level of friction at the interface between the top of rail and the wheel tread, commonly referred to as "top of rail friction management";
- applying materials to the wheel rail contact to increase (improve/enhance/recover) adhesion.

This document sets out the requirements for the equipment and application of the top of rail wheel/rail friction management. It describes systems fitted on board trains and on the track, as both systems may need to be deployed to achieve effective friction management of the wheel-rail interface. This document should always be used in conjunction with the accompanying document: CEN/TS 15427-2-2 *Railway applications - Wheel/rail friction management -* Part 2-2: Properties and characteristics - Top of rail materials.

Managing the wheel-rail interface effectively will reduce wear and other damage to both wheel and rail. When friction is managed effectively, noise levels, wear levels and the risk of flange climbing are reduced. Conversely, where not managed effectively, assets may require replacement prematurely before reaching their full economic potential.

There needs to be control in the application of top of rail materials such that there is:

- no loss of traction or braking performance;
- no adverse effect on signalling systems or track circuits;
- understanding of the increased risk of fire;
- no harmful environmental effect;
- no incompatibility between the different lubricants/ materials in use, particularly, between solid and fluid systems.

# 1 Scope

This document is limited to specifying the requirements when applying material to the active interface between the wheel tread and the crown of the rail and includes trainborne and track side equipment.

This document only covers the equipment and application of material to the active interface.

This document specifies:

- the characteristics of top of rail equipment for wheel-rail interface, together with applicable inspection and test methods to be carried out for verification;
- all relevant terminology which is specific to the application of top of rail materials at the wheelrail interface.

This document applies to the mainline railway.

NOTE This document can also be used for other railways, e.g. urban rail.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13749, Railway applications — Wheelsets and bogies — Method of specifying the structural requirements of bogie frames

CEN/TS 15427-2-2:2023, Railway applications — Wheel/rail friction management — Part 2-2: Properties and characteristics — Top of rail materials

EN 50125-1, Railway applications — Environmental conditions for equipment — Part 1: Rolling stock and on-board equipment

EN 50238-1, Railway applications — Compatibility between rolling stock and train detection systems — Part 1: General

EN 61373, Railway applications — Rolling stock equipment — Shock and vibration tests

EN 62621, Railway applications — Fixed installations — Electric traction — Specific requirements for composite insulators used for overhead contact line systems

# koniec náhľadu – text ďalej pokračuje v platenej verzii STN