| S | STN | Environmentálne inžinierstvo (EE) Rozhranie napájania na vstupe zariadení informačných a komunikačných technológií (ICT) Časť 2: Napájanie jednosmerným | STN EN 300 132-2 V2.8.1 |
|---|-----|---|-------------------------------|
| | | napätím (DC) -48 V | 87 0132 |

Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 2: -48 V Direct Current (DC)

Táto norma obsahuje anglickú verziu európskej normy. This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 02/25

Obsahuje: EN 300 132-2 V2.8.1:2024



140082

Úrad pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky, 2025

Slovenská technická norma a technická normalizačná informácia je chránená zákonom č. 60/2018 Z. z. o technickej normalizácii v znení neskorších predpisov.

STN EN 300 132-2 V2.8.1: 2025

Úrad pre normalizáciu, metrológiu a skúšobníctvo Slovenskej republiky

ETSI EN 300 132-2 V2.8.1 (2024-10)



Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 2: -48 V Direct Current (DC)

ETSI EN 300 132-2 V2.8.1 (2024-10)

Reference

REN/EE-02109

Keywords

interface, power supply

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the ETSI <u>Search & Browse Standards</u> application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on ETSI deliver.

Users should be aware that the present document may be revised or have its status changed, this information is available in the <u>Milestones listing</u>.

If you find errors in the present document, please send your comments to the relevant service listed under <u>Committee Support Staff</u>.

If you find a security vulnerability in the present document, please report it through our <u>Coordinated Vulnerability Disclosure (CVD)</u> program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI. The copyright and the foregoing restriction extend to reproduction in all media.

> © ETSI 2024. All rights reserved.

Contents

| Intell | Intellectual Property Rights | | | | | |
|--|------------------------------|--|----|--|--|--|
| Forev | vord | | 5 | | | |
| Moda | Modal verbs terminology | | | | | |
| 1 | | | | | | |
| 2 | Ĩ | | | | | |
| 2.1 | | · · · · · · · · · · · · · · · · · · · | | | | |
| 2.2 | | 25 | | | | |
| 3 | | mbols and abbreviations | | | | |
| 3.1 | | | | | | |
| 3.2 3.3 | • | | | | | |
| | | | | | | |
| 4 4.0 | | | | | | |
| 4.0 | | | | | | |
| 4.2 | | ge range at interface "A" | | | | |
| 4.3 | Abnormal service vol | Itage range at interface "A" | 13 | | | |
| 4.3.1 | | voltage range under steady state conditions | | | | |
| 4.3.2 4.3.3 | | ons: voltage variations, dips and short interruptions | | | | |
| 4.3.3 | | ent due to short-circuit and protective device clearance | | | | |
| 4.3.3.2 | | transient due to switching and lightning | | | | |
| 4.3.4 | Recovery from vo | oltage transients | 16 | | | |
| 4.4 | | to the regulation of the power supply | | | | |
| 4.5 | | ion at interface "A"ain | | | | |
| 4.6 4.7 | | nnection of interface "A" | | | | |
| 4.7.1 | | | | | | |
| 4.7.2 | Measurements | | 19 | | | |
| 4.8 | | requirements of the ICT equipment at interface "A": narrowband noise | | | | |
| 4.9 | Conducted emissions | requirements of the ICT equipment at interface "A" | 22 | | | |
| 5 | Earthing and bonding. | | 23 | | | |
| Annex A (informative): Identification of interface "A" | | | | | | |
| Anne | x B (informative). | -60 VDC systems | 25 | | | |
| | | • | | | | |
| Anne | ex C (informative): | Guide for measuring inrush current and for transferring the recorded pulses onto the limit chart | | | | |
| C.1 | Measurement | • | | | | |
| C.2 | | ormation | | | | |
| C.3 | | a current with filter capacitor current pulses | | | | |
| | | | | | | |
| Anne | x D (informative): | Test arrangements for the injection of electrical noise at interface | | | | |
| Anne | x E (informative): | Wideband noise | | | | |
| E.0 | · · · · · | | | | | |
| | | | | | | |
| E.1 Emission of wideband noiseE.1.0 General | | | | | | |
| E.1.0 E.1.1 | | and noise | | | | |
| | | | | | | |

ETSI EN 300 132-2 V2.8.1 (2024-10)

4

| E.2 How to calculate wide | band emission |
|---------------------------|---|
| Annex F (informative): | Protection dimensioning |
| Annex G (informative): | Effects of protective device operation transients in the power distribution |
| Annex H (normative): | Verification of measurement network defined in clause 4.9 |
| Annex I (informative): | Bibliography40 |
| Annex J (informative): | Change history41 |
| History | |

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECTTM, **PLUGTESTSTM**, **UMTSTM** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPPTM** and **LTETM** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2MTM** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE).

The present document concerns the requirements for the interface between ICT equipment and its power supply, and includes requirements relating to its stability and measurement. Various other references and detailed measurement and test arrangements are contained in informative annexes.

The present document is part 2 of a multi-part deliverable covering Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment, as identified below:

Part 1: "Alternating Current (AC)";

Part 2: "-48 V Direct Current (DC)";

Part 3: "Up to 400 V Direct Current (DC)".

| National transposition dates | | |
|---|-----------------|--|
| Date of adoption of this EN: | 3 October 2024 | |
| Date of latest announcement of this EN (doa): | 31 January 2025 | |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 July 2025 | |
| Date of withdrawal of any conflicting National Standard (dow): | 31 July 2025 | |

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document contains requirements and measurements methods for the physical interface "A" that is situated between the power supply system(s) and the power consuming ICT equipment.

The nominal voltage at power interface "A" of ICT equipment defined in the present document is DC voltage -48 V.

The DC power can be supplied by a DC output power system (e.g. based on AC rectifiers on grid or DC/DC converters on solar system, fuel cell, DC engine or fuel cell generator) and also directly supplied by a battery backup in this DC power system. The purpose of the present document is to be able to use a power supply system with the same characteristics for all ICT equipment defined in the area of application:

- to facilitate inter working of different types of load units;
- to facilitate the standardization of ICT equipment;
- to facilitate the installation, operation and maintenance in the same network of ICT equipment and systems from different origins.

The present document aims at providing electrical compatibility between the power supply equipment and the power consuming ICT equipment, between different system blocks and loads connected to the same power supply feeding the interface "A" (e.g. control/monitoring, cooling system, etc.).

The requirements are defined for:

- the power supply input of any type of ICT equipment installed at telecommunication centres that are connected to interface "A" powered by DC;
- any type of ICT equipment, installed in access networks and customers' premises, the DC interface "A" of which is also used by equipment requiring a DC supply source;
- any type of ICT equipment powered by DC, used in the fixed and mobile networks installed in different locations such as buildings, shelters, street cabinets, outdoor installations.

Disturbances on the power supply interface "A" relating to the continuous wave phenomena below 20 kHz are covered within the present document.

The present document does not cover safety requirements, they are covered by relevant safety standards.

The present document does not cover EMC requirements, they are covered by relevant EMC standards.

NOTE: Annex B gives guidance on -60 VDC supply systems.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference/.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] <u>ETSI EN 300 253</u>: "Environmental Engineering (EE); Earthing and bonding of ICT equipment powered by -48 VDC in telecom and data centres".

Void.

[3] Void.

[2]

[4] Void.

- [5] <u>EN 61000-4-5</u>: "Electromagnetic compatibility (EMC) Part 4-5: Testing and measurement techniques Surge immunity test" (produced by CENELEC).
- [6] Void.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

| [i.1] | Recommendation ITU-T Q.551: "Transmission characteristics of digital exchanges". |
|--------|--|
| [i.2] | Recommendation ITU-T Q.552: "Transmission characteristics at 2-wire analogue interfaces of digital exchanges". |
| [i.3] | Recommendation ITU-T Q.553: "Transmission characteristics at 4-wire analogue interfaces of digital exchanges". |
| [i.4] | Recommendation ITU-T Q.554: "Transmission characteristics at digital interfaces of digital exchanges". |
| [i.5] | ETSI TR 100 283: "Environmental Engineering (EE); Transient voltages at Interface "A" on telecommunications direct current (dc) power distributions". |
| [i.6] | US Department of Defence MIL-STD-461E: "Requirements for the control of electromagnetic interference characteristics of subsystems and equipment". |
| [i.7] | Void. |
| [i.8] | Recommendation ITU-T O.41: "Psophometer for use on telephone-type circuits". |
| [i.9] | IEC 60050-601: "International Electrotechnical Vocabulary. Chapter 601: Generation, transmission and distribution of electricity - General" (Area 826 "Electrical installations", section 826-11 "Voltages and currents"). |
| [i.10] | EN 60269-1: "Low-voltage fuses - Part 1: General requirements" (produced by CENELEC). |
| [i.11] | EN 60934: "Circuit-breakers for equipment (CBE)" (produced by CENELEC). |
| [i.12] | IEC 60050-351: 2013: "International Electrotechnical Vocabulary. Part 351: Control technology". |
| | |

koniec náhľadu – text ďalej pokračuje v platenej verzii STN

^{[7] &}lt;u>EN 61000-4-29</u>: "Electromagnetic compatibility (EMC) - Part 4-29: Testing and measurement techniques -Voltage dips, short interruptions and voltage variations on d.c. input power port immunity tests" (produced by CENELEC).