

<b>STN</b>	<b>Bunkové siete IMT</b> <b>Harmonizovaná norma pre prístup</b> <b>k rádiovému spektru</b> <b>Časť 13: Používateľské zariadenia (UE)</b> <b>zdokonaleného univerzálneho pozemského</b> <b>rádiového prístupu (E-UTRA)</b>	<b>STN</b> <b>EN 301 908-13</b> <b>V13.3.1</b>  87 1908
------------	--	---

IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)

Táto norma obsahuje anglickú verziu európskej normy.  
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 02/25

Obsahuje: EN 301 908-13 V13.3.1:2024

**140085**





# ETSI EN 301 908-13 V13.3.1 (2024-10)



**IMT cellular networks;  
Harmonised Standard for access to radio spectrum;  
Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA)  
User Equipment (UE)**

---

**Reference**

REN/MSG-TFES-1504

---

**Keywords**3G, 3GPP, cellular, digital, E-UTRA, IMT,  
IMT-2000, IMT-Advanced, LTE, LTE-Advanced,  
mobile, radio, regulation, UMTS**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**The present document can be downloaded from the  
ETSI [Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.  
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.  
All rights reserved.

# Contents

Intellectual Property Rights .....	11
Foreword.....	11
Modal verbs terminology.....	12
Introduction .....	12
1 Scope .....	13
2 References .....	16
2.1 Normative references .....	16
2.2 Informative references.....	16
3 Definition of terms, symbols and abbreviations.....	18
3.1 Terms.....	18
3.2 Symbols.....	21
3.3 Abbreviations .....	23
4 Technical requirements specifications .....	25
4.1 Environmental profile.....	25
4.2 Conformance requirements .....	25
4.2.0 General.....	25
4.2.1 Introduction.....	25
4.2.2 Transmitter Maximum Output Power .....	26
4.2.2.1 Transmitter maximum output power for Single Carrier .....	26
4.2.2.1.1 Definition.....	26
4.2.2.1.2 Limits .....	26
4.2.2.1.3 Conformance .....	26
4.2.2.2 Transmitter output power for Carrier Aggregation (DL CA and UL CA) .....	26
4.2.2.2.1 Definition.....	26
4.2.2.2.2 Limits .....	27
4.2.2.2.3 Conformance .....	28
4.2.2.3 Transmitter output power for UL-MIMO .....	28
4.2.2.3.1 Definition.....	28
4.2.2.3.2 Limits .....	28
4.2.2.3.3 Conformance .....	28
4.2.2.4 Transmitter output power for category NB1 .....	29
4.2.2.4.1 Definition.....	29
4.2.2.4.2 Limits .....	29
4.2.2.4.3 Conformance .....	29
4.2.2.5 Transmitter output power for UE category M1 .....	29
4.2.2.5.1 Definition.....	29
4.2.2.5.2 Limits .....	29
4.2.2.5.3 Conformance .....	30
4.2.3 Transmitter Spectrum Emission Mask .....	30
4.2.3.1 Transmitter spectrum emission mask for Single Carrier .....	30
4.2.3.1.1 Definition.....	30
4.2.3.1.2 Limits .....	30
4.2.3.1.3 Conformance .....	31
4.2.3.2 Transmitter spectrum emission mask for Carrier Aggregation (DL CA and UL CA) .....	31
4.2.3.2.1 Definition.....	31
4.2.3.2.2 Limits .....	31
4.2.3.2.3 Conformance .....	33
4.2.3.3 Transmitter spectrum emission mask for UL-MIMO .....	33
4.2.3.3.1 Definition.....	33
4.2.3.3.2 Limits .....	34
4.2.3.3.3 Conformance .....	34
4.2.3.4 Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier .....	34
4.2.3.4.1 Definition.....	34
4.2.3.4.2 Limits .....	34

4.2.3.4.3	Conformance .....	34
4.2.3.5	Transmitter spectrum emission mask for category NB1 .....	34
4.2.3.5.1	Definition.....	34
4.2.3.5.2	Limits .....	34
4.2.3.5.3	Conformance .....	34
4.2.4	Transmitter Spurious Emissions .....	35
4.2.4.1	Transmitter spurious emissions for Single Carrier .....	35
4.2.4.1.1	Definition.....	35
4.2.4.1.2	Limits .....	35
4.2.4.1.3	Conformance .....	39
4.2.4.2	Transmitter spurious emissions for Carrier Aggregation (DL CA and UL CA) .....	40
4.2.4.2.1	Definition.....	40
4.2.4.2.2	Limits .....	40
4.2.4.2.3	Conformance .....	45
4.2.4.3	Transmitter spurious emissions for UL-MIMO .....	45
4.2.4.3.1	Definition.....	45
4.2.4.3.2	Limits .....	45
4.2.4.3.3	Conformance .....	45
4.2.4.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier .....	45
4.2.4.4.1	Definition.....	45
4.2.4.4.2	Limits .....	45
4.2.4.4.3	Conformance .....	46
4.2.4.5	Transmitter spurious emissions for category NB1 .....	46
4.2.4.5.1	Definition.....	46
4.2.4.5.2	Limits .....	46
4.2.4.5.3	Conformance .....	46
4.2.5	Transmitter Minimum Output Power.....	46
4.2.5.1	Transmitter minimum output power for Single Carrier.....	46
4.2.5.1.1	Definition.....	46
4.2.5.1.2	Limits .....	46
4.2.5.1.3	Conformance .....	46
4.2.5.2	Transmitter minimum output power for Carrier Aggregation (DL CA and UL CA) .....	47
4.2.5.2.1	Definition.....	47
4.2.5.2.2	Limits .....	47
4.2.5.2.3	Conformance .....	47
4.2.5.3	Transmitter minimum output power for UL-MIMO .....	47
4.2.5.3.1	Definition.....	47
4.2.5.3.2	Limits .....	47
4.2.5.3.3	Conformance .....	48
4.2.5.4	Transmitter minimum output power for category NB1 .....	48
4.2.5.4.1	Definition.....	48
4.2.5.4.2	Limits .....	48
4.2.5.4.3	Conformance .....	48
4.2.6	Receiver Adjacent Channel Selectivity (ACS) .....	48
4.2.6.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier .....	48
4.2.6.1.1	Definition.....	48
4.2.6.1.2	Limits .....	48
4.2.6.1.3	Conformance .....	49
4.2.6.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands .....	49
4.2.6.2.1	Definition.....	49
4.2.6.2.2	Limits .....	50
4.2.6.2.3	Conformance .....	50
4.2.6.3	Receiver Adjacent Channel Selectivity (ACS) for category NB1 .....	51
4.2.6.3.1	Definition.....	51
4.2.6.3.2	Limits .....	51
4.2.6.3.3	Conformance .....	51
4.2.7	Receiver Blocking Characteristics .....	51
4.2.7.1	Receiver Blocking Characteristics for Single Carrier .....	51
4.2.7.1.1	Definition.....	51
4.2.7.1.2	Limits .....	51
4.2.7.1.3	Conformance .....	53
4.2.7.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands.....	53

4.2.7.2.1	Definition.....	53
4.2.7.2.2	Limits .....	54
4.2.7.2.3	Conformance .....	56
4.2.7.3	Receiver Blocking Characteristics for category NB1 .....	57
4.2.7.3.1	Definition.....	57
4.2.7.3.2	Limits .....	57
4.2.7.3.3	Conformance .....	58
4.2.8	Receiver Spurious Response.....	58
4.2.8.1	Receiver Spurious Response for Single Carrier .....	58
4.2.8.1.1	Definition.....	58
4.2.8.1.2	Limits .....	59
4.2.8.1.3	Conformance .....	59
4.2.8.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands .....	59
4.2.8.2.1	Definition.....	59
4.2.8.2.2	Limits .....	59
4.2.8.2.3	Conformance .....	59
4.2.8.3	Receiver Spurious Response for category NB1 .....	59
4.2.8.3.1	Definition.....	59
4.2.8.3.2	Limits .....	60
4.2.8.3.3	Conformance .....	60
4.2.9	Receiver Intermodulation Characteristic .....	60
4.2.9.1	Receiver Intermodulation Characteristics for Single Carrier .....	60
4.2.9.1.1	Definition.....	60
4.2.9.1.2	Limits .....	60
4.2.9.1.3	Conformance .....	61
4.2.9.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	61
4.2.9.2.1	Definition.....	61
4.2.9.2.2	Limits .....	61
4.2.9.2.3	Conformance .....	62
4.2.9.3	Receiver Intermodulation Characteristics for category NB1 .....	62
4.2.9.3.1	Definition.....	62
4.2.9.3.2	Limits .....	62
4.2.9.3.3	Conformance .....	62
4.2.10	Receiver Spurious Emissions.....	63
4.2.10.1	Receiver Spurious Emissions for Single Carrier .....	63
4.2.10.1.1	Definition.....	63
4.2.10.1.2	Limits .....	63
4.2.10.1.3	Conformance .....	63
4.2.10.2	Receiver Spurious Emissions in DL-only bands .....	63
4.2.10.2.1	Definition.....	63
4.2.10.2.2	Limits .....	63
4.2.10.2.3	Conformance .....	63
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio .....	64
4.2.11.1	Transmitter adjacent channel leakage power ratio for Single Carrier .....	64
4.2.11.1.1	Definition.....	64
4.2.11.1.2	Limits .....	64
4.2.11.1.3	Conformance .....	65
4.2.11.2	Transmitter adjacent channel leakage power ratio for Carrier Aggregation (DL CA and UL CA).....	65
4.2.11.2.1	Definition.....	65
4.2.11.2.2	Limits for CA UTRA.....	66
4.2.11.2.3	Limits for CA EUTRA .....	67
4.2.11.2.4	Conformance .....	68
4.2.11.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	68
4.2.11.3.1	Definition.....	68
4.2.11.3.2	Limits .....	68
4.2.11.3.3	Conformance .....	69
4.2.11.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier .....	69
4.2.11.4.1	Definition.....	69
4.2.11.4.2	Limits .....	70
4.2.11.4.3	Conformance .....	70
4.2.11.5	Transmitter adjacent channel leakage power ratio for category NB1 .....	70

4.2.11.5.1	Definition.....	70
4.2.11.5.2	Limits .....	70
4.2.11.5.3	Conformance .....	70
4.2.12	Receiver Reference Sensitivity Level .....	71
4.2.12.0	General .....	71
4.2.12.1	Receiver Reference Sensitivity Level for Single Carrier .....	71
4.2.12.1.1	Definition.....	71
4.2.12.1.2	Limits .....	71
4.2.12.1.3	Conformance .....	72
4.2.12.2	Receiver Reference Sensitivity Level for Carrier Aggregation in DL-only bands.....	72
4.2.12.2.1	Definition.....	72
4.2.12.2.2	Limits .....	72
4.2.12.2.3	Conformance .....	73
4.2.12.3	Receiver Reference Sensitivity Level for category NB1.....	73
4.2.12.3.1	Definition.....	73
4.2.12.3.2	Limits .....	73
4.2.12.3.3	Conformance .....	73
4.2.12.4	Receiver Reference Sensitivity Level for UE category 0.....	73
4.2.12.4.1	Definition.....	73
4.2.12.4.2	Limits .....	73
4.2.12.4.3	Conformance .....	74
4.2.12.5	Receiver Reference Sensitivity Level for UE category M1 .....	74
4.2.12.5.1	Definition.....	74
4.2.12.5.2	Limits .....	74
4.2.12.5.3	Conformance .....	75
4.2.13	Receiver Total Radiated Sensitivity (TRS).....	76
4.2.13.0	Applicability.....	76
4.2.13.1	Definition .....	76
4.2.13.2	Limits .....	77
4.2.13.3	Conformance.....	77
4.2.14	Total Radiated Power (TRP).....	77
4.2.14.0	Applicability.....	77
4.2.14.1	Definition .....	77
4.2.14.2	Limits .....	78
5	Testing for compliance with technical requirements.....	79
5.1	Environmental conditions for testing .....	79
5.2	Void.....	79
5.3	Essential radio test suites.....	79
5.3.0	General.....	79
5.3.1	Transmitter Maximum Output Power .....	80
5.3.1.1	Transmitter maximum output power for Single Carrier .....	80
5.3.1.1.1	Method of test.....	80
5.3.1.1.2	Test requirements .....	80
5.3.1.2	Transmitter maximum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	81
5.3.1.2.1	Method of test.....	81
5.3.1.2.2	Test requirements .....	81
5.3.1.2A	Transmitter maximum output power for inter-band Carrier Aggregation (DL CA and UL CA) .....	82
5.3.1.2A.1	Method of test.....	82
5.3.1.2A.2	Test requirements .....	82
5.3.1.3	Transmitter maximum output power for UL-MIMO .....	83
5.3.1.3.1	Method of test.....	83
5.3.1.3.2	Test requirements .....	83
5.3.1.4	Transmitter maximum output power for category NB1 .....	83
5.3.1.4.1	Method of Test .....	83
5.3.1.4.2	Test requirements .....	84
5.3.1.5	Transmitter maximum output power for UE category 0 .....	84
5.3.1.5.1	Method of test.....	84
5.3.1.5.2	Test requirements .....	85
5.3.1.6	Transmitter maximum output power for UE category M1 .....	85
5.3.1.6.1	Method of test.....	85

5.3.1.6.2	Test requirements .....	85
5.3.2	Transmitter Spectrum Emission Mask .....	86
5.3.2.1	Transmitter spectrum emission mask for Single Carrier .....	86
5.3.2.1.1	Method of test.....	86
5.3.2.1.2	Test requirements .....	86
5.3.2.2	Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	87
5.3.2.2.1	Method of test.....	87
5.3.2.2.2	Test requirements .....	87
5.3.2.2A	Transmitter spectrum emission mask for inter-band Carrier Aggregation (DL CA and UL CA) .....	88
5.3.2.2A.1	Method of test.....	88
5.3.2.2A.2	Test requirements .....	89
5.3.2.3	Transmitter spectrum emission mask for UL-MIMO .....	89
5.3.2.3.1	Method of test.....	89
5.3.2.3.2	Test requirements .....	89
5.3.2.4	Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier .....	90
5.3.2.4.1	Method of test.....	90
5.3.2.4.2	Test requirements .....	90
5.3.2.5	Transmitter spectrum emission mask for category NB1 .....	91
5.3.2.5.1	Method of test.....	91
5.3.2.5.2	Test requirements .....	91
5.3.2.6	Transmitter spectrum emission mask for UE category 0 .....	92
5.3.2.6.1	Method of test.....	92
5.3.2.6.2	Test requirements .....	92
5.3.2.7	Transmitter spectrum emission mask for UE category M1 .....	92
5.3.2.7.1	Method of test.....	92
5.3.2.7.2	Test requirements .....	93
5.3.3	Transmitter Spurious Emissions .....	93
5.3.3.1	Transmitter spurious emissions for Single Carrier .....	93
5.3.3.1.1	Method of test.....	93
5.3.3.1.2	Test requirements .....	94
5.3.3.2	Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	94
5.3.3.2.1	Method of test.....	94
5.3.3.2.2	Test requirements .....	95
5.3.3.2A	Transmitter spurious emissions for inter-band Carrier Aggregation (DL CA and UL CA) .....	95
5.3.3.2A.1	Method of test.....	95
5.3.3.2A.2	Test requirements .....	96
5.3.3.3	Transmitter spurious emissions for UL-MIMO .....	96
5.3.3.3.1	Method of test.....	96
5.3.3.3.2	Test requirements .....	97
5.3.3.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier .....	97
5.3.3.4.1	Method of test.....	97
5.3.3.4.2	Test requirements .....	97
5.3.3.5	Transmitter spurious emissions for category NB1 .....	98
5.3.3.5.1	Method of test.....	98
5.3.3.5.2	Test requirements .....	98
5.3.3.6	Transmitter spurious emissions for UE category 0 .....	99
5.3.3.6.1	Method of test.....	99
5.3.3.6.2	Test requirements .....	99
5.3.3.7	Transmitter spurious emissions for UE category M1 .....	99
5.3.3.7.1	Method of test.....	99
5.3.3.7.2	Test requirements .....	100
5.3.4	Transmitter Minimum Output Power.....	100
5.3.4.1	Transmitter minimum output power for Single Carrier.....	100
5.3.4.1.1	Method of test.....	100
5.3.4.1.2	Test requirements .....	101
5.3.4.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	101
5.3.4.2.1	Method of test.....	101
5.3.4.2.2	Test requirements .....	102
5.3.4.2A	Transmitter minimum output power for inter-band Carrier Aggregation (DL CA and UL CA).....	102

5.3.4.2A.1	Method of test.....	102
5.3.4.2A.2	Test requirements .....	103
5.3.4.3	Transmitter minimum output power for UL-MIMO .....	103
5.3.4.3.1	Method of test.....	103
5.3.4.3.2	Test requirements .....	104
5.3.4.4	Transmitter minimum output power for category NB1 .....	104
5.3.4.4.1	Method of test.....	104
5.3.4.4.2	Test requirements .....	104
5.3.4.5	Transmitter minimum output power for UE category 0 .....	105
5.3.4.5.1	Method of test.....	105
5.3.4.5.2	Test requirements .....	105
5.3.4.6	Transmitter minimum output power for UE category M1 .....	105
5.3.4.6.1	Method of test.....	105
5.3.4.6.2	Test requirements .....	106
5.3.5	Receiver Adjacent Channel Selectivity (ACS) .....	106
5.3.5.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier .....	106
5.3.5.1.1	Method of test.....	106
5.3.5.1.2	Test requirements .....	107
5.3.5.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands .....	107
5.3.5.2.1	Method of test.....	107
5.3.5.2.2	Test requirements .....	108
5.3.5.3	Receiver Adjacent Channel Selectivity (ACS) for category NB1 .....	108
5.3.5.3.1	Method of test.....	108
5.3.5.3.2	Test requirements .....	110
5.3.5.4	Receiver Adjacent Channel Selectivity (ACS) for UE category 0 .....	110
5.3.5.4.1	Method of test.....	110
5.3.5.4.2	Test requirements .....	110
5.3.5.5	Receiver Adjacent Channel Selectivity (ACS) for UE category M1 .....	110
5.3.5.5.1	Method of test.....	110
5.3.5.5.2	Test requirements .....	111
5.3.6	Receiver Blocking Characteristics .....	112
5.3.6.1	Receiver Blocking Characteristics for Single Carrier .....	112
5.3.6.1.1	Method of test.....	112
5.3.6.1.2	Test requirements .....	113
5.3.6.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands.....	114
5.3.6.2.1	Method of test.....	114
5.3.6.2.2	Test requirements .....	116
5.3.6.3	Receiver Blocking Characteristics for category NB1 .....	116
5.3.6.3.1	Method of test.....	116
5.3.6.3.2	Test requirements .....	117
5.3.6.4	Receiver Blocking Characteristics for UE category 0.....	117
5.3.6.4.1	Method of test.....	117
5.3.6.4.2	Test requirements .....	118
5.3.6.5	Receiver Blocking Characteristics for UE category M1 .....	118
5.3.6.5.1	Method of test.....	118
5.3.6.5.2	Test requirements .....	120
5.3.7	Receiver Spurious Response.....	120
5.3.7.1	Receiver Spurious Response for Single Carrier .....	120
5.3.7.1.1	Method of test.....	120
5.3.7.1.2	Test requirements .....	120
5.3.7.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands .....	120
5.3.7.2.1	Method of test.....	120
5.3.7.2.2	Test requirements .....	121
5.3.7.3	Receiver Spurious Response for category NB1 .....	121
5.3.7.3.1	Method of test.....	121
5.3.7.3.2	Test requirements .....	121
5.3.7.4	Receiver Spurious Response for UE category 0.....	122
5.3.7.4.1	Method of test.....	122
5.3.7.4.2	Test requirements .....	122
5.3.7.5	Receiver Spurious Response for UE category M1 .....	122
5.3.7.5.1	Method of test.....	122
5.3.7.5.2	Test requirements .....	122

5.3.8	Receiver Intermodulation Characteristics .....	123
5.3.8.1	Receiver Intermodulation Characteristics for Single Carrier .....	123
5.3.8.1.1	Method of test.....	123
5.3.8.1.2	Test requirements .....	123
5.3.8.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	124
5.3.8.2.1	Method of test.....	124
5.3.8.2.2	Test requirements .....	125
5.3.8.3	Receiver Intermodulation Characteristics for category NB1 .....	125
5.3.8.3.1	Test requirements .....	125
5.3.8.3.2	Test requirements .....	125
5.3.8.4	Receiver Intermodulation Characteristics for UE category 0.....	126
5.3.8.4.1	Method of test.....	126
5.3.8.4.2	Test requirements .....	126
5.3.8.5	Receiver Intermodulation Characteristics for UE category M1 .....	126
5.3.8.5.1	Method of test.....	126
5.3.8.5.2	Test requirements .....	127
5.3.9	Receiver Spurious Emissions.....	127
5.3.9.1	Receiver Spurious Emissions for Single Carrier .....	127
5.3.9.1.1	Method of test.....	127
5.3.9.1.2	Test requirements .....	128
5.3.9.2	Receiver Spurious Emissions in DL-only bands .....	128
5.3.9.2.1	Method of test.....	128
5.3.9.2.2	Test requirements .....	129
5.3.9.3	Receiver Spurious Emissions for UE category 0 .....	129
5.3.9.3.1	Method of test.....	129
5.3.9.3.2	Test requirements .....	129
5.3.9.4	Receiver Spurious Emissions for UE category M1 .....	129
5.3.9.4.1	Method of test.....	129
5.3.9.4.2	Test requirements .....	130
5.3.9.5	Receiver Spurious Emissions for UE category NB1 .....	130
5.3.9.5.1	Method of test.....	130
5.3.9.5.2	Test requirements .....	130
5.3.10	Transmitter Adjacent Channel Leakage Power Ratio .....	130
5.3.10.1	Transmitter adjacent channel leakage power ratio for Single Carrier .....	130
5.3.10.1.1	Method of test.....	130
5.3.10.1.2	Test requirements .....	131
5.3.10.2	Transmitter adjacent channel leakage power ratio for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	132
5.3.10.2.1	Method of test.....	132
5.3.10.2.2	Test requirements .....	133
5.3.10.2A	Transmitter adjacent channel leakage power ratio for inter-band Carrier Aggregation (DL CA and UL CA).....	133
5.3.10.2A.1	Method of test.....	133
5.3.10.2A.2	Test requirements .....	134
5.3.10.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	134
5.3.10.3.1	Method of test.....	134
5.3.10.3.2	Test requirements .....	135
5.3.10.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier .....	135
5.3.10.4.1	Method of test.....	135
5.3.10.4.2	Test requirements .....	136
5.3.10.5	Transmitter adjacent channel leakage power ratio for category NB1 .....	136
5.3.10.5.1	Method of test.....	136
5.3.10.5.2	Test requirements .....	137
5.3.10.6	Transmitter adjacent channel leakage power ratio for UE category 0.....	137
5.3.10.6.1	Method of test.....	137
5.3.10.6.2	Test requirements .....	138
5.3.10.7	Transmitter adjacent channel leakage power ratio for UE category M1 .....	138
5.3.10.7.1	Method of test.....	138
5.3.10.7.2	Test requirements .....	139
5.3.11	Receiver Reference Sensitivity Level .....	139
5.3.11.1	Receiver Reference Sensitivity Level for Single Carrier .....	139

5.3.11.1.1	Method of test.....	139
5.3.11.1.2	Test requirements .....	139
5.3.11.2	Receiver Reference Sensitivity Level for Carrier Aggregation in DL-only bands.....	140
5.3.11.2.1	Method of test.....	140
5.3.11.2.2	Test requirements .....	141
5.3.11.3	Receiver Reference Sensitivity Level for category NB1.....	141
5.3.11.3.1	Method of test.....	141
5.3.11.3.2	Test requirements .....	141
5.3.11.4	Receiver Reference Sensitivity Level for UE category 0.....	141
5.3.11.4.1	Method of test.....	141
5.3.11.4.2	Test requirements .....	142
5.3.11.5	Receiver Reference Sensitivity Level for UE category M1 .....	142
5.3.11.5.1	Method of test.....	142
5.3.11.5.2	Test requirements .....	143
5.3.12	Receiver Total Radiated Sensitivity (TRS).....	143
5.3.12.1	Method of test .....	143
5.3.12.1.1	Initial conditions.....	143
5.3.12.1.2	Procedure.....	143
5.3.12.1.3	Procedure, reverberation chamber method .....	143
5.3.12.2	Test requirements .....	143
5.3.13	Total Radiated Power (TRP).....	143
5.3.13.1	Method of test .....	143
5.3.13.1.1	Initial conditions .....	143
5.3.13.1.2	Procedure.....	143
5.3.13.1.3	Procedure, reverberation chamber method .....	144
5.3.13.2	Test requirements.....	144
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>145</b>
<b>Annex B (normative):</b>	<b>Environmental profile .....</b>	<b>147</b>
B.1	General .....	147
B.1.1	Introduction .....	147
B.1.2	Temperature .....	147
B.1.3	Voltage .....	147
B.1.4	Test environment.....	148
<b>Annex C (informative):</b>	<b>Maximum Measurement Uncertainty.....</b>	<b>149</b>
<b>Annex D (informative):</b>	<b>Bibliography.....</b>	<b>150</b>
<b>Annex E (informative):</b>	<b>Change history .....</b>	<b>151</b>
History .....		152

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

For non-EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 13 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.12].

This version of the harmonized standard includes the following revisions:

- Revision of the maximum output power requirements outlined in clause 4.2.2.
- Inclusion of requirements for band 41.
- Inclusion of Additional spurious emissions limits for frequency range 470 to 694 MHz to protect Broadband Public Protection and Disaster Relief (BB-PPDR) and Digital Terrestrial Television (DTT) operations.
- Inclusion of specific requirements for bands 72, 87, and 88 to protect Broadband Public Protection and Disaster Relief (BB-PPDR) and Digital Terrestrial Television (DTT) operations.

National transposition dates	
Date of adoption of this EN:	1 October 2024
Date of latest announcement of this EN (doa):	31 January 2025
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2025
Date of withdrawal of any conflicting National Standard (dow):	31 July 2026

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

# 1 Scope

The present document applies to the following radio equipment type:

- User Equipment for Evolved Universal Terrestrial Radio Access (E-UTRA).

This radio equipment type is capable of operating in all or any part of the frequency bands given in tables from 1-1 through 1-5.

**Table 1-1: E-UTRA UE operating bands**

E-UTRA Band	Direction of UE transmission	E-UTRA operating bands	Related EC/ECC decision
1	Transmit	1 920 MHz to 1 980 MHz	[i.21] and [i.22]
	Receive	2 110 MHz to 2 170 MHz	
3	Transmit	1 710 MHz to 1 785 MHz	[i.19] and [i.20]
	Receive	1 805 MHz to 1 880 MHz	
7	Transmit	2 500 MHz to 2 570 MHz	[i.24] and [i.25]
	Receive	2 620 MHz to 2 690 MHz	
8	Transmit	880 MHz to 915 MHz	[i.19] and [i.20]
	Receive	925 MHz to 960 MHz	
20	Transmit	832 MHz to 862 MHz	[i.6] and [i.7]
	Receive	791 MHz to 821 MHz	
22	Transmit	3 410 MHz to 3 490 MHz	[i.26] and [i.27]
	Receive	3 510 MHz to 3 590 MHz	
28 (see note 6)	Transmit	703 MHz to 748 MHz	[i.14] and [i.15]
	Receive	758 MHz to 803 MHz	
31	Transmit	452,5 MHz to 457,5 MHz	[i.16]
	Receive	462,5 MHz to 467,5 MHz	
32 (see note 1) (see note 2)	Transmit	N/A	[i.17] and [i.18]
	Receive	1 452 MHz to 1 496 MHz	
33	Transmit and Receive	1 900 MHz to 1 920 MHz	[i.22]
34	Transmit and Receive	2 010 MHz to 2 025 MHz	[i.22]
38	Transmit and Receive	2 570 MHz to 2 620 MHz	[i.24] and [i.25]
40	Transmit and Receive	2 300 MHz to 2 400 MHz	[i.23]
41 (note 7)	Transmit and Receive	2 496 MHz to 2 690 MHz	[i.24] and [i.25]
42	Transmit and Receive	3 400 MHz to 3 600 MHz	[i.26] and [i.27]
43	Transmit and Receive	3 600 MHz to 3 800 MHz	[i.26] and [i.27]
46 (see note 3) (see note 4)	Transmit and Receive	5 150 MHz to 5 925 MHz	[i.29] and [i.30]
65 (see note 5)	Transmit	1 920 MHz to 2 010 MHz	[i.21], [i.22] and [i.28]
	Receive	2 110 MHz to 2 200 MHz	
67	Transmit	N/A	[i.14] and [i.15]
	Receive	738 MHz to 758 MHz	
68	Transmit	698 MHz to 728 MHz	[i.14] and [i.15]
	Receive	753 MHz to 783 MHz	
69 (see note 1)	Transmit	N/A	[i.24] and [i.25]
	Receive	2 570 MHz to 2 620 MHz	
72	Transmit	451 MHz to 456 MHz	[i.16]
	Receive	461 MHz to 466 MHz	
87	Transmit	410 MHz to 415 MHz	[i.16]
	Receive	420 MHz to 425 MHz	
88	Transmit	412 MHz to 417 MHz	[i.16]
	Receive	422 MHz to 427 MHz	

NOTE 1:	Restricted to E-UTRA operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.
NOTE 2:	In Europe, according to [i.17] and [i.18], radio equipment in band 32 operates between 1 452 MHz and 1 492 MHz.
NOTE 3:	This band is an unlicensed band restricted to licensed-assisted operation using Frame Structure Type 3. In Europe according to [i.29] and [i.30], radio equipment in band 46 operates between 5 150 MHz and 5 725 MHz as in table 1-1A.
NOTE 4:	In this version of the present document, restricted to E-UTRA DL operation when carrier aggregation is configured.
NOTE 5:	A UE that complies with the E-UTRA Band 65 minimum requirements in the present document also complies with the E-UTRA Band 1 minimum requirements. This band includes two frequency ranges that are harmonised in Europe: <ol style="list-style-type: none"> <li>According to [i.21] and [i.22], radio equipment in band n65 operates between 2 110 MHz and 2 170 MHz for the transmitter (<math>F_{DL\_low} = 2\ 110\ \text{MHz}</math> and <math>F_{DL\_high} = 2\ 170\ \text{MHz}</math>), and between 1 920 MHz and 1 980 MHz for the receiver (<math>F_{UL\_low} = 1\ 920\ \text{MHz}</math> and <math>F_{UL\_high} = 1\ 980\ \text{MHz}</math>).</li> <li>Based on [i.29], radio equipment in band n65 operates between 2 170 MHz and 2 200 MHz for the transmitter (<math>F_{DL\_low} = 2\ 170\ \text{MHz}</math> and <math>F_{DL\_high} = 2\ 200\ \text{MHz}</math>) and between 1 980 MHz and 2 010 MHz for the receiver (<math>F_{UL\_low} = 1\ 980\ \text{MHz}</math> and <math>F_{UL\_high} = 2\ 010\ \text{MHz}</math>) as the Complementary Ground Component (CGC) of a Mobile-satellite service by reference to the present Harmonised Standard.</li> </ol>
NOTE 6:	In Europe, according to [i.14], [i.15] and [i.16], radio equipment in band 28 operates between 703 MHz to 736 MHz for the transmitter ( $F_{UL\_low} = 703\ \text{MHz}$ and $F_{UL\_high} = 736\ \text{MHz}$ ) and between 758 MHz to 791 MHz for the receiver ( $F_{DL\_low} = 758\ \text{MHz}$ and $F_{DL\_high} = 791\ \text{MHz}$ ).
NOTE 7:	In Europe according to [i.24] and [i.25], radio equipment in band 41 operates between 2 500 MHz and 2 570 MHz ( $F_{DL\_low} = 2\ 500\ \text{MHz}$ and $F_{DL\_high} = 2\ 570\ \text{MHz}$ ).

NOTE 1: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

**Table 1-1A: Sub-bands for band 46**

E-UTRA Band	
	46a
	46b
	46c
NOTE:	The sub-bands 46a and 46b are restricted to indoor use only.

**Table 1-2: E-UTRA UE Intra-band contiguous CA operating bands**

E-UTRA CA Band
CA_1
CA_3
CA_7
CA_38
CA_40
CA_41
CA_42

**Table 1-3: E-UTRA UE Inter-band CA operating bands (two bands)**

<b>E-UTRA CA Band</b>
CA_1-3
CA_1-7
CA_1-8
CA_1-20
CA_1-41
CA_1-42
CA_1-46
CA_3-7
CA_3-8
CA_3-20
CA_3-28
CA_3-41
CA_3-42
CA_3-46
CA_7-20
CA_7-28
CA_7-46
CA_8-20
CA_8-40
CA_8-41
CA_20-32
CA_41-42
CA_41-46
CA_42-46
CA_20-67

**Table 1-4: E-UTRA UE Inter-band CA operating bands (three bands)**

<b>E-UTRA CA Band</b>
CA_1-3-8
CA_1-3-20
CA_1-7-20
CA_3-7-20
CA_3-41-42

**Table 1-5: Intra-band non-contiguous CA operating bands (with two sub-blocks)**

<b>E-UTRA CA Band</b>
CA_3-3
CA_7-7
CA_41-41
CA_42-42

E-UTRA NB-IoT is designed to operate in the E-UTRA operating bands 1, 3, 8, 20, 28 and 65 defined in table 1-1. The present document covers requirements for E-UTRA FDD and E-UTRA TDD User Equipment from 3GPP™ Releases 8, 9, 10, 11, 12, and 13 defined in ETSI TS 136 101 [3]. This includes the requirements for E-UTRA UE operating bands and E-UTRA CA operating bands from 3GPP™ Release 13 defined in ETSI TS 136 101 [3].

NOTE 2: For Band 20:

- For user equipment designed to be mobile or nomadic, the requirements in the present document measured at the antenna port also show conformity to the corresponding requirement defined as Total Radiated Power (TRP), as described in Commission Decision 2010/267/EU [i.6] and ECC Decision (09)03 [i.7].
- For user equipment designed to be fixed or installed, the present document does not address the requirements described in Commission Decision 2010/267/EU [i.6] and ECC Decision (09)03 [i.7].

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI TS 136 521-1 \(V17.7.0\) \(07-2023\)](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing (3GPP TS 36.521-1 version 17.7.0 Release 17)".
- [2] [ETSI TS 136 508 \(V17.6.0\) \(07-2023\)](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); Common test environments for User Equipment (UE) conformance testing (3GPP TS 36.508 version 17.6.0 Release 17)".
- [3] [ETSI TS 136 101 \(V13.25.0\) \(07-2023\)](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception (3GPP TS 36.101 version 13.25.0 Release 13)".
- [4] [IEC 60068-2-1:2007 ED 6.0](#): "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [5] [IEC 60068-2-2:2007 ED 5.0](#): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
- [6] [ETSI TS 137 544 \(V16.3.0\) \(05-2024\)](#): "Universal Mobile Telecommunications System (UMTS); LTE; Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA); User Equipment (UE) Over The Air (OTA) performance; Conformance testing (3GPP TS 37.544 version 16.3.0 Release 16)".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

- [i.4] Recommendation ITU-R SM.329-12 (2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] [Commission Decision 2010/267/EU of 6 May 2010](#) on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.7] [ECC Decision \(09\)03 of 30 October 2009](#) on harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz.
- [i.8] Void.
- [i.9] [Commission Implementing Decision C\(2015\) 5376 final of 4.8.2015](#) on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.10] ETSI TS 136 509 (V10.3.0) (09-2014): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Packet Core (EPC); Special conformance testing functions for User Equipment (UE) (3GPP TS 36.509 version 10.3.0 Release 10)".
- [i.11] Void.
- [i.12] ETSI EN 301 908-1 (V13.1.1): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements".
- [i.13] ETSI TR 125 914 (V15.0.1) (09-2018): "Universal Mobile Telecommunications System (UMTS); Measurements of radio performances for UMTS terminals in speech mode (3GPP TR 25.914 version 15.0.1 Release 15)".
- [i.14] [Commission Implementing Decision \(EU\) 2016/687 of 28 April 2016](#) on the harmonisation of the 694-790 MHz frequency band for terrestrial systems capable of providing wireless broadband electronic communications services and for flexible national use in the Union.
- [i.15] [ECC Decision \(15\)01](#): "Harmonised technical conditions for mobile/fixed communications networks (MFCN) in the band 694-790 MHz including a paired frequency arrangement (Frequency Division Duplex 2x30 MHz) and an optional unpaired frequency arrangement (Supplemental Downlink)", Approved 06 March 2015.
- [i.16] [ECC Decision \(19\)02](#): "Land mobile systems in the frequency ranges 68-87.5 MHz, 146-174 MHz, 406.1-410 MHz, 410-430 MHz, 440-450 MHz and 450-470 MHz", approved 8 March 2019.
- [i.17] [Commission Implementing Decision \(EU\) 2018/661 of 26 April 2018](#) amending Implementing Decision (EU) 2015/750 on the harmonisation of the 1452-1492 MHz frequency band for terrestrial systems capable of providing electronic communications services in the Union as regards its extension in the harmonised 1427-1452 MHz and 1492-1517 MHz frequency bands.
- [i.18] [ECC Decision \(13\)03](#): "The harmonised use of the frequency band 1 452-1 492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [i.19] [Commission Implementing Decision \(EU\) 2022/173 of 7 February 2022](#) on the harmonisation of the 900 MHz and 1800 MHz frequency bands for terrestrial systems capable of providing electronic communications services in the Union and repealing Decision 2009/766/EC.
- [i.20] [ECC Decision \(06\)13](#): "Designation of the bands 880-915 MHz, 925-960 MHz, 1710-1785 MHz and 1805-1880 MHz for terrestrial UMTS, LTE, WiMAX and IoT cellular systems", Approved 01 December 2006, Amended 8 March 2019.
- [i.21] [Commission Implementing Decision \(EU\) 2020/667 of 6 May 2020](#) amending Decision 2012/688/EU as regards an update of relevant technical conditions applicable to the frequency bands 1 920-1 980 MHz and 2 110-2 170 MHz.

- [i.22] [ECC Decision \(06\)01](#): The harmonised utilisation of the bands 1920-1980 MHz and 2110-2170 MHz for mobile/fixed communications networks (MFCN) including terrestrial IMT systems, Approved 24 March 2006, Amended 8 March 2019. .
- [i.23] [ECC Decision \(14\)02](#): "Harmonised technical and regulatory conditions for the use of the band 2300-2400 MHz for Mobile/Fixed Communications Networks (MFCN)", Approved 27 June 2014.
- [i.24] [Commission Implementing Decision \(EU\) 2020/636 of 8 May 2020](#) amending Decision 2008/477/EC as regards an update of relevant technical conditions applicable to the 2 500-2 690 MHz frequency band.
- [i.25] [ECC Decision \(05\)05](#): "Harmonised utilization of spectrum for Mobile/Fixed Communications Networks (MFCN) operating within the band 2500-2690 MHz", Approved 18 March 2005, Amended 05 July 2019.
- [i.26] [Commission implementing Decision \(EU\) 2019/235 of 24 January 2019](#) on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3 400-3 800 MHz frequency band.
- [i.27] [ECC Decision \(11\)06](#): "Harmonised frequency arrangements and least restrictive technical conditions (LRTC) for mobile/fixed communications networks (MFCN) operating in the band 3400-3800 MHz" Approved 09 December 2011, Amended 26 October 2018.
- [i.28] [ECC Decision \(06\)09](#): "Designation of the bands 1980-2010 MHz and 2170-2200 MHz for use by systems in the Mobile-Satellite Service including those supplemented by a Complementary Ground Component (CGC)", Approved 01 December 2006, Amended 05 September 2007.
- [i.29] [Commission Implementing Decision \(EU\) 2022/179 of 8 February 2022](#) on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of wireless access systems including radio local area networks and repealing Decision 2005/513/EC.
- [i.30] [ECC Decision \(04\)08](#): "On the harmonised use of the 5 GHz frequency bands for Wireless Access Systems including Radio Local Area Networks (WAS/RLAN)". Approved 09 July 2004, latest amended 1 July 2022.

---

**koniec náhľadu – text ďalej pokračuje v platenej verzii STN**