

| | | |
|------------|---|--|
| STN | Rozhrania univerzálnej sériovej zbernice pre dáta a napájanie Časť 1-2: Spoločné súčasti Špecifikácia napájania elektrickou energiou cez USB | STN EN IEC 62680-1-2 36 8365 |
|------------|---|--|

Universal serial bus interfaces for data and power - Part 1-2: Common components - USB Power Delivery specification

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 04/25

Obsahuje: EN IEC 62680-1-2:2025, IEC 62680-1-2:2024

Oznámením tejto normy sa od 31.01.2028 ruší
STN EN IEC 62680-1-2 (36 8365) z januára 2023

140370



EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN IEC 62680-1-2

January 2025

ICS 29.220; 33.120; 35.200

Supersedes EN IEC 62680-1-2:2022

English Version

**Universal serial bus interfaces for data and power - Part 1-2:
Common components - USB Power Delivery specification
(IEC 62680-1-2:2024)**

Interfaces de bus universel en série pour les données et
l'alimentation électrique - Partie 1-2: Composants communs
- Spécification de l'alimentation électrique par port USB
(IEC 62680-1-2:2024)

Universelle Bus-Schnittstellen für Daten und Energie - Teil
1-2: Gemeinsame Komponenten - Festlegung für die
Energieübertragung über USB
(IEC 62680-1-2:2024)

This European Standard was approved by CENELEC on 2025-01-17. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN IEC 62680-1-2:2025 (E)**European foreword**

The text of document 100/4138/CDV, future edition 7 of IEC 62680-1-2, prepared by TC 100/Technical Area 18 "Multimedia home systems and applications for end-user networks" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62680-1-2:2025.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2026-01-31
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2028-01-31

This document supersedes EN IEC 62680-1-2:2022 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 62680-1-2:2024 was approved by CENELEC as a European Standard without any modification.



IEC 62680-1-2

Edition 7.0 2024-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Universal serial bus interfaces for data and power –
Part 1-2: Common components – USB Power Delivery specification**

**Interfaces de bus universel en série pour les données et l'alimentation
électrique –
Partie 1-2: Composants communs – Spécification de l'alimentation électrique
par port USB**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
 3, rue de Varembe
 CH-1211 Geneva 20
 Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



IEC 62680-1-2

Edition 7.0 2024-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Universal serial bus interfaces for data and power –
Part 1-2: Common components – USB Power Delivery specification**

**Interfaces de bus universel en série pour les données et l'alimentation
électrique –
Partie 1-2: Composants communs – Spécification de l'alimentation électrique
par port USB**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.220, 33.120, 35.200

ISBN 978-2-8327-0040-2

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

Part 1-2: Common components – USB Power Delivery specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62680-1-2 has been prepared by technical area 18: Multimedia home systems and applications for end-user networks, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this International Standard is based on the following documents:

| Draft | Report on voting |
|--------------|------------------|
| 100/4138/CDV | 100/4176/RVC |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Universal Serial Bus

Power Delivery Specification

| | |
|-----------------------------|-----------------------|
| <i>Revision:</i> | <i>3.2</i> |
| <i>Version:</i> | <i>1.0</i> |
| <i>Release date:</i> | <i>2023-10</i> |

LIMITED COPYRIGHT LICENSE

THE USB 3.0 PROMOTERS GRANT A CONDITIONAL COPYRIGHT LICENSE UNDER THE COPYRIGHTS EMBODIED IN THE USB POWER DELIVERY SPECIFICATION TO USE AND REPRODUCE THE SPECIFICATION FOR THE SOLE PURPOSE OF, AND SOLELY TO THE EXTENT NECESSARY FOR, EVALUATING WHETHER TO IMPLEMENT THE SPECIFICATION IN PRODUCTS THAT WOULD COMPLY WITH THE SPECIFICATION. WITHOUT LIMITING THE FOREGOING, USE THE OF SPECIFICATION FOR THE PURPOSE OF FILING OR MODIFYING ANY PATENT APPLICATION TO TARGET THE SPECIFICATION OR USB COMPLIANT PRODUCTS IS NOT AUTHORIZED. EXCEPT FOR THIS EXPRESS COPYRIGHT LICENSE, NO OTHER RIGHTS OR LICENSES ARE GRANTED, INCLUDING WITHOUT LIMITATION ANY PATENT LICENSES. IN ORDER TO OBTAIN ANY ADDITIONALLY INTELLECTUAL PROPERTY LICENSES OR LICENSING COMMITMENTS ASSOCIATED WITH THE SPECIFICATION A PARTY MUST EXECUTE THE USB 3.0 ADOPTERS AGREEMENT. NOTE: BY USING THE SPECIFICATION, YOU ACCEPT THESE LICENSE TERMS ON YOUR OWN BEHALF AND, IN THE CASE WHERE YOU ARE DOING THIS AS AN EMPLOYEE, ON BEHALF OF YOUR EMPLOYER.

INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Please send comments via electronic mail to techsup@usb.org.

For industry information, refer to the USB Implementers Forum web page at <http://www.usb.org>.

USB Type-C® and USB4® are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). Thunderbolt™ is a trademark of Intel Corporation.

You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and executing a Thunderbolt™ trademark license – see <http://usb.org/compliance> for further information.

All product names are trademarks, registered trademarks, or service marks of their respective owners.

Copyright © 2010-2023, USB 3.0 Promoter Group: Apple Inc., Hewlett-Packard Inc., Intel Corporation, Microsoft Corporation, Renesas, STMicroelectronics, and Texas Instruments.
All rights reserved.

Editors

Bob Dunstan

Richard Petrie

Contributors

| | | | |
|---------------------------|--------------------------------|-----------------------|------------------------------|
| Charles Wang | ACON, Advanced-Connectek, Inc. | Sameer Kelkar | Apple |
| Conrad Choy | ACON, Advanced-Connectek, Inc. | Sasha Tietz | Apple |
| Dennis Chuang | ACON, Advanced-Connectek, Inc. | Scott Jackson | Apple |
| Steve Sedio | ACON, Advanced-Connectek, Inc. | Sree Raman | Apple |
| Sunney Yang | ACON, Advanced-Connectek, Inc. | William Ferry | Apple |
| Vicky Chuang | ACON, Advanced-Connectek, Inc. | Zaki Moussaoui | Apple |
| Joseph Scanlon | Advanced Micro Devices | Jeff Liu | ASMedia Technology Inc. |
| Sujan Thomas | Advanced Micro Devices | Kuo Lung Li | ASMedia Technology Inc. |
| Caspar Lin | Allion Labs, Inc. | Ming-Wei Hsu | ASMedia Technology Inc. |
| Casper Lee | Allion Labs, Inc. | PS Tseng | ASMedia Technology Inc. |
| Danny Shih | Allion Labs, Inc. | Sam Tzeng | ASMedia Technology Inc. |
| Howard Chang | Allion Labs, Inc. | Thomas Hsu | ASMedia Technology Inc. |
| Greg Stewart | Analogix Semiconductor, Inc. | Weikao Chang | ASMedia Technology Inc. |
| Mehran Badii | Analogix Semiconductor, Inc. | Yang Cheng | ASMedia Technology Inc. |
| Alexei Kosut | Apple | Aaron Hou | Bizlink Technology Inc. |
| Bill Cornelius | Apple | Shawn Meng | Bizlink Technology Inc. |
| Carlos Corderon | Apple | Bernard Shyu | Bizlink Technology, Inc. |
| Chris Uiterwijk | Apple | Eric Wu | Bizlink Technology, Inc. |
| Colin Whitby-Stevens | Apple | Morphy Hsieh | Bizlink Technology, Inc. |
| Corey Axelowitz | Apple | Sean O'Neal | Bizlink Technology, Inc. |
| Corey Lange | Apple | Tiffany Hsiao | Bizlink Technology, Inc. |
| Dave Conroy | Apple | Weichung Ooi | Bizlink Technology, Inc. |
| David Sekowski | Apple | Rahul Bhushan | Broadcom Corp. |
| Girault Jones | Apple | Asila nahas | Cadence Design Systems, Inc. |
| James Orr | Apple | Claire Ying | Cadence Design Systems, Inc. |
| Jason Chung | Apple | Jie min | Cadence Design Systems, Inc. |
| Jay Kim | Apple | Mark Summers | Cadence Design Systems, Inc. |
| Jeff Wilcox | Apple | Michal Staworko | Cadence Design Systems, Inc. |
| Jennifer Tsai | Apple | Sathish Kumar Ganesan | Cadence Design Systems, Inc. |
| Karl Bowers | Apple | Alessandro Ingrassia | Canova Tech |
| Keith Porthouse | Apple | Andrea Colognese | Canova Tech |
| Kevin Hsiue | Apple | Antonio Orzelli | Canova Tech |
| Matt Mora | Apple | Davide Ghedin | Canova Tech |
| Paul Baker | Apple | Matteo Casalin | Canova Tech |
| Reese Schreiber | Apple | Michael Marioli | Canova Tech |
| Ricardo Janezic Pregitzer | Apple | Nicola Scantamburlo | Canova Tech |
| Ruchi Chaturvedi | Apple | Paolo Pilla | Canova Tech |

| | | | |
|----------------------|-------------------------------|-----------------|-------------------------------------|
| Ray Huang | Canyon Semiconductor | KE Hong | Dialog Semiconductor (UK) Ltd |
| Yi-Feng Lin | Canyon Semiconductor | Kevin Mori | Dialog Semiconductor (UK) Ltd |
| YuHung Lin | Canyon Semiconductor | Larry Ping | Dialog Semiconductor (UK) Ltd |
| David Tsai | Chrontel, Inc. | Mengfei Liu | Dialog Semiconductor (UK) Ltd |
| Anshul Gulati | Cypress Semiconductor | Scott Brown | Dialog Semiconductor (UK) Ltd |
| Anup Nayak | Cypress Semiconductor | Yimin Chen | Dialog Semiconductor (UK) Ltd |
| Benjamin Kropf | Cypress Semiconductor | Yong Li | Dialog Semiconductor (UK) Ltd |
| Dhanraj Rajput | Cypress Semiconductor | Justin Lee | Diodes Incorporated |
| Ganesh Subramaniam | Cypress Semiconductor | Dan Ellis | DisplayLink (UK) Ltd. |
| Jagadeesan Raj | Cypress Semiconductor | Jason Young | DisplayLink (UK) Ltd. |
| Junjie cui | Cypress Semiconductor | Kevin Jacobs | DisplayLink (UK) Ltd. |
| Manu Kumar | Cypress Semiconductor | Paulo Alcobia | DisplayLink (UK) Ltd. |
| Muthu M | Cypress Semiconductor | Peter Burgers | DisplayLink (UK) Ltd. |
| Nicholas Bodnaruk | Cypress Semiconductor | Richard Petrie | DisplayLink (UK) Ltd. |
| Pradeep Bajpai | Cypress Semiconductor | Chien-Cheng Kuo | eEver Technology, Inc. |
| Rajaram R | Cypress Semiconductor | Shyanjia Chen | eEver Technology, Inc. |
| Rama Vakkantula | Cypress Semiconductor | Abel Astley | Ellisys |
| Rushil Kadakia | Cypress Semiconductor | Chuck Trefts | Ellisys |
| Simon Nguyen | Cypress Semiconductor | Emmanuel Durin | Ellisys |
| Steven Wong | Cypress Semiconductor | Mario Pasquali | Ellisys |
| Subu Sankaran | Cypress Semiconductor | Tim Wei | Ellisys |
| Sumeet Gupta | Cypress Semiconductor | Chien-Cheng Kuo | Etron Technology, Inc. |
| Tejender Sheoran | Cypress Semiconductor | Jack Yang | Etron Technology, Inc. |
| Venkat Mandagulathar | Cypress Semiconductor | Richard Crisp | Etron Technology, Inc. |
| Xiaofeng Shen | Cypress Semiconductor | Shyanjia Chen | Etron Technology, Inc. |
| Zeng Wei | Cypress Semiconductor | TsungTa Lu | Etron Technology, Inc. |
| Adie Tan | Dell Inc. | Christian Klein | Fairchild Semiconductor |
| Adolfo Montero | Dell Inc. | Oscar Freitas | Fairchild Semiconductor |
| Bruce Montag | Dell Inc. | Souhib Harb | Fairchild Semiconductor |
| Gary Verdun | Dell Inc. | Amanda Ying | Feature Integration Technology Inc. |
| Ken Nicholas | Dell Inc. | Jacky Chan | Feature Integration Technology Inc. |
| Marcin Nowak | Dell Inc. | Kenny Hsieh | Feature Integration Technology Inc. |
| Merle Wood | Dell Inc. | KungAn Lin | Feature Integration Technology Inc. |
| Mohammed Hijazi | Dell Inc. | Paul Yang | Feature Integration Technology Inc. |
| Siddhartha Reddy | Dell Inc. | Su Jaden | Feature Integration Technology Inc. |
| Terry Matula | Dell Inc. | Yu-Lin Chu | Feature Integration Technology Inc. |
| Jay Hu | Derun Semiconductor | Yulin Lan | Feature Integration Technology Inc. |
| Shelly Liu | Derun Semiconductor | AJ Yang | Foxconn / Hon Hai |
| Bindhu Vasu | Dialog Semiconductor (UK) Ltd | Bob Hall | Foxconn / Hon Hai |
| Chanchal Gupta | Dialog Semiconductor (UK) Ltd | Chihyin Kan | Foxconn / Hon Hai |
| Dipti Baheti | Dialog Semiconductor (UK) Ltd | Fred Fons | Foxconn / Hon Hai |
| Duc Doan | Dialog Semiconductor (UK) Ltd | Jie Zheng | Foxconn / Hon Hai |
| Holger Petersen | Dialog Semiconductor (UK) Ltd | Patrick Casher | Foxconn / Hon Hai |
| Jianming Yao | Dialog Semiconductor (UK) Ltd | Shruti Deore | Foxconn / Hon Hai |
| John Shi | Dialog Semiconductor (UK) Ltd | Steve Sedio | Foxconn / Hon Hai |

| | | | |
|-------------------------|--------------------|------------------------|--------------------------------|
| Terry Little | Foxconn / Hon Hai | Vishal Kakade | Granite River Labs |
| Bob McVay | Fresco Logic Inc. | Yogeshwaran Venkatesan | Granite River Labs |
| Christopher Meyers | Fresco Logic Inc. | Jerry Qin | GuangDong OPPO Mobile |
| Dian Kurniawan | Fresco Logic Inc. | Alan Berkema | Hewlett Packard |
| Tom Burton | Fresco Logic Inc. | Lee Atkinson | Hewlett Packard |
| Abraham Levkoy | Google Inc. | Rahul Lakdawala | Hewlett Packard |
| Adam Rodriguez | Google Inc. | Robin Castell | Hewlett Packard |
| Alec Berg | Google Inc. | Ron Schooley | Hewlett Packard |
| Benson Leung | Google Inc. | Steve Chen | Hewlett Packard |
| Chao Fei | Google Inc. | Suketa Partiwala | Hewlett Packard |
| Dave Bernard | Google Inc. | Vaibhav Malik | Hewlett Packard |
| David Schneider | Google Inc. | Walter Fry | Hewlett Packard |
| Diana Zigterman | Google Inc. | Hideyuki HAYAFUJI | Hosiden Corporation |
| Eric Herrmann | Google Inc. | Keiji Mine | Hosiden Corporation |
| Jameson Thies | Google Inc. | Masaki Yamaoka | Hosiden Corporation |
| Jim Guerin | Google Inc. | Takashi Muto | Hosiden Corporation |
| Juan Fantin | Google Inc. | Yasunori Nishikawa | Hosiden Corporation |
| Ken Wu | Google Inc. | Alan Berkema | HP Inc. |
| Kyle Tso | Google Inc. | Kenneth Chan | HP Inc. |
| Mark Hayter | Google Inc. | Lee Atkinson | HP Inc. |
| Nathan Kolluru | Google Inc. | Lee Leppo | HP Inc. |
| Nithya Jagannathan | Google Inc. | Rahul Lakdawala | HP Inc. |
| Srikanth Lakshmikanthan | Google Inc. | Robin Castell | HP Inc. |
| Todd Broch | Google Inc. | Roger Benson | HP Inc. |
| Toshak Singhal | Google Inc. | Steve Chen | HP Inc. |
| Vincent Palatin | Google Inc. | Bai Sean | Huawei Technologies Co., Ltd. |
| Xuelin Wu | Google Inc. | Chunjiang Zhao | Huawei Technologies Co., Ltd. |
| Zhenxue Xu | Google Inc. | JianQuan Wu | Huawei Technologies Co., Ltd. |
| Alan Kinningham | Granite River Labs | Li Zongjian | Huawei Technologies Co., Ltd. |
| Anand Murugan | Granite River Labs | Liansheng Zheng | Huawei Technologies Co., Ltd. |
| Balamurugan Manialagan | Granite River Labs | Lihua Duan | Huawei Technologies Co., Ltd. |
| Medipalli Sowmya | Granite River Labs | Min Chen | Huawei Technologies Co., Ltd. |
| Mike Engbretson | Granite River Labs | Wang Feng | Huawei Technologies Co., Ltd. |
| Mike Wu | Granite River Labs | Wei Haihong | Huawei Technologies Co., Ltd. |
| Mukesh Tatiya | Granite River Labs | Zhenning Shi | Huawei Technologies Co., Ltd. |
| Naresh Botsa | Granite River Labs | James Xie | Hynetek Semiconductor Co., Ltd |
| PoornaKumar M. | Granite River Labs | Yingyang Ou | Hynetek Semiconductor Co., Ltd |
| Prajwal Rathod | Granite River Labs | Robert Heaton | Indie Semiconductor |
| Rajaraman V | Granite River Labs | Vincent Wang | Indie Semiconductor |
| Saai Ghoutham Revathi | Granite River Labs | Benjamin Kropf | Infineon Technologies |
| Sivan Perumal | Granite River Labs | Sie Boo Chiang | Infineon Technologies |
| Sivaram Murugesan | Granite River Labs | Tue Fatt David Wee | Infineon Technologies |
| Tim Lin | Granite River Labs | Wee Tar Richard Ng | Infineon Technologies |
| Vijay S. | Granite River Labs | Wolfgang Furtner | Infineon Technologies |
| Vijayakumar P | Granite River Labs | Aruni Nelson | Intel Corporation |

IEC 62680-1-2:2024
© USB-IF 2023

– 9 –

| | | | |
|------------------------------|--|---------------------|----------------------------|
| Bob Dunstan | Intel Corporation | Babu Mailachalam | Lattice Semiconductor Corp |
| Brad Saunders | Intel Corporation | Gianluca Mariani | Lattice Semiconductor Corp |
| Chee Lim Nge | Intel Corporation | Joel Coplen | Lattice Semiconductor Corp |
| Christine Krause | Intel Corporation | Thomas Watz | Lattice Semiconductor Corp |
| Chuen Ming Tan | Intel Corporation | Vesa Lauri | Lattice Semiconductor Corp |
| Dan Froelich | Intel Corporation | Bruce Chuang | Leadtrend |
| David Harriman | Intel Corporation | Eilian Liu | Leadtrend |
| David Hines | Intel Corporation | Chetan Kopalle | LeCroy Corporation |
| David Thompson | Intel Corporation | Daniel H Jacobs | LeCroy Corporation |
| Guobin Liu | Intel Corporation | Jake Jacobs | LeCroy Corporation |
| Harry Skinner | Intel Corporation | Kimberley McKay | LeCroy Corporation |
| Henrik Leegaard | Intel Corporation | Mike Engbretson | LeCroy Corporation |
| Jenn Chuan Cheng | Intel Corporation | Mike Micheletti | LeCroy Corporation |
| Jervis Lin | Intel Corporation | Roy Chestnut | LeCroy Corporation |
| John Howard | Intel Corporation | Tyler Joe | LeCroy Corporation |
| Karthi Vadivelu | Intel Corporation | Phil Jakes | Lenovo |
| Leo Heiland | Intel Corporation | Do Kyun Kim | LG electronics |
| Maarit Harkonen | Intel Corporation | Won-Jong Choi | LG electronics |
| Nge Chee Lim | Intel Corporation | Won-Jong Choi | LG Electronics Ltd. |
| Paul Durley | Intel Corporation | Aaron Melgar | Lion Semiconductor |
| Rahman Ismail | Intel Corporation | Chris Zhou | Lion Semiconductor |
| Rajaram Regupathy | Intel Corporation | Sehyung Jeon | Lion Semiconductor |
| Ronald Swartz | Intel Corporation | Wonyoung Kim | Lion Semiconductor |
| Sarah Sharp | Intel Corporation | Yongho Kim | Lion Semiconductor |
| Scott Brenden | Intel Corporation | Dave Thompson | LSI Corporation |
| Sridharan Ranganathan | Intel Corporation | Alan Kinningham | Luxshare-ICT |
| Steve McGowan | Intel Corporation | Alan Liu | Luxshare-ICT |
| Tim McKee | Intel Corporation | Daniel Chen | Luxshare-ICT |
| Toby Opferman | Intel Corporation | Eric Wen | Luxshare-ICT |
| Uma Medepalli | Intel Corporation | James Kirk | Luxshare-ICT |
| Venkataramani Gopalakrishnan | Intel Corporation | James Stevens | Luxshare-ICT |
| Ziv Kabiry | Intel Corporation | Josue Castillo | Luxshare-ICT |
| Jia Wei | Intersil Corporation | Pat Young | Luxshare-ICT |
| Weijie Huang | iST - Integrated Service Technology Inc. | Scott Shuey | Luxshare-ICT |
| Al Hsiao | ITE Tech. Inc. | Stone Lin | Luxshare-ICT |
| Greg Song | ITE Tech. Inc. | Chikara Kakizawa | Maxim Integrated Products |
| Richard Guo | ITE Tech. Inc. | Jacob Scott | Maxim Integrated Products |
| Victor Lin | ITE Tech. Inc. | Ken Helfrich | Maxim Integrated Products |
| Y.C. Chou | ITE Tech. Inc. | Michael Miskho | Maxim Integrated Products |
| Kenta Minejima | Japan Aviation Electronics Industry Ltd. | Chris Yokum | MCCI Corporation |
| Mark Saubert | Japan Aviation Electronics Industry Ltd. | Geert Knapen | MCCI Corporation |
| Toshio Shimoyama | Japan Aviation Electronics Industry Ltd. | Terry Moore | MCCI Corporation |
| Brian Fetz | Keysight Technologies Inc. | Velmurugan Selvaraj | MCCI Corporation |
| Jit Lim | Keysight Technologies Inc. | Tung-Sheng Lin | MediaTek Inc. |
| Koji Asakawa | Kinetic Technologies Inc. | Tung-Sheng Lin | MediaTek Inc. |

| | | | |
|----------------------|-------------------------------|-------------------|-------------------------------------|
| Satoru Kumashiro | MegaChips Corporation | Ben Crowe | MQP Electronics Ltd. |
| Brian Marley | Microchip Technology Inc. | Pat Crowe | MQP Electronics Ltd. |
| Dave Perchlik | Microchip Technology Inc. | Sten Carlsen | MQP Electronics Ltd. |
| Don Perkins | Microchip Technology Inc. | Kenji Oguma | NEC Corporation |
| Fernando Gonzalez | Microchip Technology Inc. | ChinJui Lin | Nexperia B.V. |
| John Sisto | Microchip Technology Inc. | Max Guan | Nexperia B.V. |
| Josh Averyt | Microchip Technology Inc. | Frank Borngräber | Nokia Corporation |
| Kiet Tran | Microchip Technology Inc. | Kai Inha | Nokia Corporation |
| Mark Bohm | Microchip Technology Inc. | Pekka Leinonen | Nokia Corporation |
| Matthew Kalibat | Microchip Technology Inc. | Richard Petrie | Nokia Corporation |
| Mick Davis | Microchip Technology Inc. | Sten Carlsen | Nokia Corporation |
| Prasanna Vengateshan | Microchip Technology Inc. | Abhijeet Kulkarni | NXP Semiconductors |
| Rich Wahler | Microchip Technology Inc. | Ahmad Yazdi | NXP Semiconductors |
| Richard Petrie | Microchip Technology Inc. | Bart Vertenten | NXP Semiconductors |
| Ronald Kunin | Microchip Technology Inc. | Dennis Ha | NXP Semiconductors |
| Shannon Cash | Microchip Technology Inc. | Dong Nguyen | NXP Semiconductors |
| Thomas Farkas | Microchip Technology Inc. | Guru Prasad | NXP Semiconductors |
| Venkataraman | Microchip Technology Inc. | Ken Jaramillo | NXP Semiconductors |
| Andrew Yang | Microsoft Corporation | Krishnan TN | NXP Semiconductors |
| Anthony Chen | Microsoft Corporation | Michael Joehren | NXP Semiconductors |
| Arvind Murching | Microsoft Corporation | Robert de Nie | NXP Semiconductors |
| Dave Perchlik | Microsoft Corporation | Rod Whitby | NXP Semiconductors |
| David Voth | Microsoft Corporation | Vijendra Kuroodi | NXP Semiconductors |
| Geoff Shew | Microsoft Corporation | Winston Langeslag | NXP Semiconductors |
| Jayson Kastens | Microsoft Corporation | Robert Heaton | Obsidian Technology |
| Kai Inha | Microsoft Corporation | Andrew Yoo | ON Semiconductor |
| Marwan Kadado | Microsoft Corporation | Brady Maasen | ON Semiconductor |
| Michelle Bergeron | Microsoft Corporation | Bryan McCoy | ON Semiconductor |
| Nathan Sherman | Microsoft Corporation | Christian Klein | ON Semiconductor |
| Rahul Ramadas | Microsoft Corporation | Cor Voorwinden | ON Semiconductor |
| Randy Aull | Microsoft Corporation | Edward Berrios | ON Semiconductor |
| Shiu Ng | Microsoft Corporation | Michael Smith | ON Semiconductor |
| Tieyong Yin | Microsoft Corporation | Oscar Freitas | ON Semiconductor |
| Timo Toivola | Microsoft Corporation | Tom Duffy | ON Semiconductor |
| Toby Nixon | Microsoft Corporation | Brian Collins | Parade Technologies Inc. |
| Vahid Vassey | Microsoft Corporation | Craig Wiley | Parade Technologies Inc. |
| Vivek Gupta | Microsoft Corporation | Hung-Chih Chiu | Power Forest Technology Corporation |
| Yang You | Microsoft Corporation | Jay Tu | Power Forest Technology Corporation |
| Adib Al Abaji | Molex LLC | Adel Lahham | Power Integrations |
| Aaron Xu | Monolithic Power Systems Inc. | Aditya Kulkarni | Power Integrations |
| Bo Zhou | Monolithic Power Systems Inc. | Akshay Nayaknur | Power Integrations |
| Christian Sporck | Monolithic Power Systems Inc. | Amruta Patra | Power Integrations |
| Di Han | Monolithic Power Systems Inc. | K R Rahul Raj | Power Integrations |
| Zhihong Yu | Monolithic Power Systems Inc. | Kaushik Raam | Power Integrations |
| Dan Wagner | Motorola Mobility Inc. | Rahul Joshi | Power Integrations |

IEC 62680-1-2:2024
© USB-IF 2023

– 11 –

| | | | |
|-------------------|--------------------------------|-------------------------|-----------------------------------|
| Ricardo Pregiteer | Power Integrations | Hidenori Nishimoto | Rohm Co. Ltd. |
| Shruti Anand | Power Integrations | Kris Bahar | Rohm Co. Ltd. |
| Amit gupta | Qualcomm, Inc | Manabu Miyata | Rohm Co. Ltd. |
| George Paparrizos | Qualcomm, Inc | Ruben Balbuena | Rohm Co. Ltd. |
| Giovanni Garcea | Qualcomm, Inc | Takashi Sato | Rohm Co. Ltd. |
| Jack Pham | Qualcomm, Inc | Vijendra Kuroodi | Rohm Co. Ltd. |
| James Goel | Qualcomm, Inc | Yusuke Kondo | Rohm Co. Ltd. |
| Joshua Warner | Qualcomm, Inc | Kazuomi Nagai | ROHM Co., Ltd. |
| Karyn Vuong | Qualcomm, Inc | Matti Kulmala | Salcomp Plc |
| Lalan Mishra | Qualcomm, Inc | Toni Lehimo | Salcomp Plc |
| Nicholas Cadieux | Qualcomm, Inc | Edward Lee | Samsung Electronics Co. Ltd. |
| Vamsi Samavedam | Qualcomm, Inc | Tong Kim | Samsung Electronics Co. Ltd. |
| Vatsal Patel | Qualcomm, Inc | Amit Bouzaglo | Scosche Industries |
| Chris Sporck | Qualcomm, Inc. | Alvin Cox | Seagate Technology LLC |
| Craig Aiken | Qualcomm, Inc. | Emmanuel Lemay | Seagate Technology LLC |
| Narendra Mehta | Qualcomm, Inc. | John Hein | Seagate Technology LLC |
| Terry Remple | Qualcomm, Inc. | Marc Noblitt | Seagate Technology LLC |
| Will Kun | Qualcomm, Inc. | Michael Morgan | Seagate Technology LLC |
| Yoram Rimoni | Qualcomm, Inc. | Ronald Rueckert | Seagate Technology LLC |
| Fan-Hau Hsu | Realtek Semiconductor Corp. | Tony Priborsky | Seagate Technology LLC |
| Tsung-Peng Chuang | Realtek Semiconductor Corp. | Chin Chang | Semtech Corporation |
| Atsushi Mitamura | Renesas Electronics Corp. | Tom Farkas | Semtech Corporation |
| Bob Dunstan | Renesas Electronics Corp. | Ankit Garg | Siemens Industry Software Inc. |
| Brian Allen | Renesas Electronics Corp. | Ning Dai | Silergy Corp. |
| Dan Aoki | Renesas Electronics Corp. | Wanfeng Zhang | Silergy Corp. |
| Fengshuan Zhou | Renesas Electronics Corp. | Kafai Leung | Silicon Laboratories, Inc. |
| Hajime Nozaki | Renesas Electronics Corp. | Kok Hong Soh | Silicon Laboratories, Inc. |
| John Carpenter | Renesas Electronics Corp. | Sorin Badiu | Silicon Laboratories, Inc. |
| Kiichi Muto | Renesas Electronics Corp. | Steven Ghang | Silicon Laboratories, Inc. |
| Masami Katagiri | Renesas Electronics Corp. | Abhishek Sardeshpande | SiliConch Systems Private Limited |
| Nobuo Furuya | Renesas Electronics Corp. | Aniket Mathad | SiliConch Systems Private Limited |
| Patrick Yu | Renesas Electronics Corp. | Chandana N | SiliConch Systems Private Limited |
| Peter Teng | Renesas Electronics Corp. | Jaswanth Ammineni | SiliConch Systems Private Limited |
| Philip Leung | Renesas Electronics Corp. | Jinisha Patel | SiliConch Systems Private Limited |
| Steve Roux | Renesas Electronics Corp. | Kaustubh Kumar | SiliConch Systems Private Limited |
| Tetsu Sato | Renesas Electronics Corp. | Nitish | SiliConch Systems Private Limited |
| Toshifumi Yamaoka | Renesas Electronics Corp. | Pavitra Balasubramanian | SiliConch Systems Private Limited |
| Yimin Chen | Renesas Electronics Corp. | Rakesh Polasa | SiliConch Systems Private Limited |
| Chunan Kuo | Richtek Technology Corporation | Satish Anand Verkila | SiliConch Systems Private Limited |
| Heinz Wei | Richtek Technology Corporation | Shubham Paliwal | SiliConch Systems Private Limited |
| Max Huang | Richtek Technology Corporation | Vishnu Pusuluri | SiliConch Systems Private Limited |
| TZUHSIEN CHUANG | Richtek Technology Corporation | John Sisto | SMSC |
| Tatsuya Irisawa | Ricoh Company Ltd. | Ken Gay | SMSC |
| Akihiro Ono | Rohm Co. Ltd. | Mark Bohm | SMSC |
| Chris Lin | Rohm Co. Ltd. | Richard Wahler | SMSC |

| | | | |
|---------------------|--------------------|---------------------|--------------------------------------|
| Shannon Cash | SMSC | Javed Ahmad | Texas Instruments |
| Tim Knowlton | SMSC | Jean Picard | Texas Instruments |
| William Chiechi | SMSC | John Perry | Texas Instruments |
| Shigenori Tagami | Sony Corporation | Kasthuri Annamalai | Texas Instruments |
| Shinichi Hirata | Sony Corporation | Martin Patoka | Texas Instruments |
| Amanda Hosler | Specwerkz | Mike Campbell | Texas Instruments |
| Bob Dunstan | Specwerkz | Scott Jackson | Texas Instruments |
| Brad Saunders | Specwerkz | Shafiuddin Mohammed | Texas Instruments |
| Diane Lenox | Specwerkz | Srinath Hosur | Texas Instruments |
| Michael Munn | StarTech.com Ltd. | Steven Tom | Texas Instruments |
| Fabien Friess | ST-Ericsson | Yoon Lee | Texas Instruments |
| Giuseppe Platania | ST-Ericsson | Tim Wilhelm | The Silanna Group Pty. Ltd. |
| Jean-Francois Gatto | ST-Ericsson | Tod Wolf | The Silanna Group Pty. Ltd. |
| Milan Stamenkovic | ST-Ericsson | Chris Yokum | Total Phase |
| Nicolas Florenchie | ST-Ericsson | Dylan Su | UL LLC |
| Patrizia Milazzo | ST-Ericsson | Eric Wall | UL LLC |
| Christophe Cochard | STMICROELECTRONICS | Jason Smith | UL LLC |
| Christophe Lorin | STMICROELECTRONICS | Terry Kao | UL LLC |
| Filippo Bonaccorso | STMICROELECTRONICS | Steven Chen | Unigraf OY |
| Jessy Guilbot | STMICROELECTRONICS | Topi Lampiranta | Unigraf OY |
| Joel Huloux | STMICROELECTRONICS | Brad Cox | Ventev Mobile |
| John Bloomfield | STMICROELECTRONICS | Colin Vose | Ventev Mobile |
| Massimo Panzica | STMICROELECTRONICS | Dydron Lin | VIA Technologies, Inc. |
| Meriem Mersel | STMICROELECTRONICS | Fong-Jim Wang | VIA Technologies, Inc. |
| Nathalie Ballot | STMICROELECTRONICS | Jay Tseng | VIA Technologies, Inc. |
| Pascal Legrand | STMICROELECTRONICS | Rex Chang | VIA Technologies, Inc. |
| Patrizia Milazzo | STMICROELECTRONICS | Terrance Shih | VIA Technologies, Inc. |
| Richard O'Connor | STMICROELECTRONICS | Ho Wen Tsai | Weltrend Semiconductor |
| Morten Christiansen | Synopsys, Inc. | Hung Chiang | Weltrend Semiconductor |
| Nivin George | Synopsys, Inc. | Jeng Cheng Liu | Weltrend Semiconductor |
| Prishkit Abrol | Synopsys, Inc. | Priscilla Lee | Weltrend Semiconductor |
| Zongyao Wen | Synopsys, Inc. | Wayne Lo | Weltrend Semiconductor |
| Joan Marrinan | Tektronix | Charles Neumann | Western Digital Technologies, Inc. |
| Kimberley McKay | Teledyne-LeCroy | Curtis Stevens | Western Digital Technologies, Inc. |
| Matthew Dunn | Teledyne-LeCroy | John Maroney | Western Digital Technologies, Inc. |
| Tony Minchell | Teledyne-LeCroy | Joe O'Brien | Wilder Technologies |
| Anand Dabak | Texas Instruments | Will Miller | Wilder Technologies |
| Annamalai Kasthuri | Texas Instruments | Juejia Zhou | Xiaomi Communications Co., Ltd. |
| Bill Waters | Texas Instruments | Xiaoxing Yang | Xiaomi Communications Co., Ltd. |
| Bing Lu | Texas Instruments | Liu Qiong | Zuhai Smartware Technology Co., Ltd. |
| Deric Waters | Texas Instruments | Long Zhang | Zuhai Smartware Technology Co., Ltd. |
| Grant Ley | Texas Instruments | Yuanchao Liang | Zuhai Smartware Technology Co., Ltd. |
| Gregory Watkins | Texas Instruments | | |
| Ingolf Frank | Texas Instruments | | |
| Ivo Huber | Texas Instruments | | |

Revision History

| Revision | Version | Comments | Issue Date |
|----------|---------|---|------------------|
| 1.0 | 1.0 | Initial release Revision 1.0 | 5 July, 2012 |
| 1.0 | 1.1 | Including errata through 31-October-2012 | 31 October 2012 |
| 1.0 | 1.2 | Including errata through 26-June-2013 | 26 June, 2013 |
| 1.0 | 1.3 | Including errata through 11-March-2014 | 11 March 2014 |
| 2.0 | 1.0 | Initial release Revision 2.0 | 11 August 2014 |
| 2.0 | 1.1 | Including errata through 7-May 2015 | 7 May 2015 |
| 2.0 | 1.2 | Including errata through 25-March-2016 | 25 March 2016 |
| 2.0 | 1.3 | Including errata through 11-January-2017 | 11 January 2017 |
| 3.0 | 1.0 | Initial release Revision 3.0 | 11 December 2015 |
| 3.0 | 1.0a | Including errata through 25-March-2016 | 25 March 2016 |
| 3.0 | 1.1 | Including errata through 12-January-2017 | 12 January 2017 |
| 3.0 | 1.2 | Including errata through 21-June-2018 | 21 June 2018 |
| 3.0 | 2.0 | Including errata through 29-August-2019 | 29 August 2019 |
| 3.1 | 1.0 | Including errata through May 2021 | May 2021 |
| 3.1 | 1.1 | Including errata through July 2021 This version incorporates the following ECNs: <ul style="list-style-type: none"> EPR Clarifications Define AMS starting point | July 2021 |
| 3.1 | 1.2 | Including errata through October 2021 This version incorporates the following ECNs: <ul style="list-style-type: none"> Clarify use of Retries Battery Capabilities FRS timing problem PPS power rule clarifications Peak current support for EPR AVS APDO | October 2021 |
| 3.1 | 1.3 | This version incorporates the following ECNs: <ul style="list-style-type: none"> Robust EPR Source Operation EPR Source Caps Editorial SRC PPS behavior in low current request Enter USB | January 2022 |

| | | | |
|-----|-----|---|--------------|
| 3.1 | 1.4 | <p>Editorial changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> • Capabilities Mismatch Update • Chunking Timing Issue • OT Mitigation | April 2022 |
| 3.1 | 1.5 | <p>Editorial changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> • Timer Description Corrections • Change Source_Info Requirements • AMS Update | July 2022 |
| 3.1 | 1.6 | <p>Editorial changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> • USB4® V2 Updates • Data Reset Issues • Increase tSenderResponse • PPS Power Limit Bit Update • Support for Asymmetric Mode • Timer Description Corrections Revisited | October 2022 |
| 3.1 | 1.7 | <p>Editorial Changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> • Data Reset Invalid Reject Handling • Source request • Source Transition • EPR Entry | January 2023 |
| 3.1 | 1.8 | <p>Editorial Changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none"> • Slew rate exemption for Power Role Swap. • EUDO cable speed clarification. • Update to PPS Requirements. • Deprecate Interruptibility. • Section 7.3 restructure and update. | April 2023 |

| | | | |
|-----|-----|---|---------------|
| 3.2 | 1.0 | <p>Editorial Changes</p> <p>This version incorporates the following ECNs:</p> <ul style="list-style-type: none">• VDM use conditions• tTypeCSinkWaitCap• tFirstSourceCap clarification• Hard Reset clarification• Unrecognized Country Code• EPR Entry Process• SPR AVS Definition• EPR Power Rules Clarifications | October 2023. |
|-----|-----|---|---------------|

Table of Contents

Contents

| | |
|--|-----------|
| Universal Serial Bus | 2 |
| Power Delivery Specification..... | 4 |
| LIMITED COPYRIGHT LICENSE | 5 |
| INTELLECTUAL PROPERTY DISCLAIMER | 5 |
| Editors | 6 |
| Contributors | 6 |
| Revision History | 13 |
| Table of Contents..... | 16 |
| List of Tables..... | 23 |
| List of Figures | 30 |
| 1. Introduction..... | 38 |
| 1.1 Overview | 38 |
| 1.2 Purpose..... | 39 |
| 1.2.1 Scope..... | 40 |
| 1.3 Section Overview..... | 40 |
| 1.4 Conventions | 41 |
| 1.4.1 Precedence | 41 |
| 1.4.2 Keywords | 41 |
| 1.4.3 Numbering | 42 |
| 1.5 Related Documents..... | 43 |
| 1.6 Terms and Abbreviations..... | 45 |
| 1.7 Parameter Values..... | 55 |
| 1.8 Changes from Revision 3.0..... | 55 |
| 1.9 Compatibility with Revision 2.0..... | 55 |
| 2. Overview | 56 |
| 2.1 Introduction..... | 56 |
| 2.1.1 Power Delivery Source Operational Contracts..... | 56 |
| 2.1.2 Power Delivery Contracts..... | 56 |
| 2.1.3 Other Uses for Power Delivery | 57 |
| 2.2 Compatibility with Revision 2.0..... | 58 |
| 2.3 USB Power Delivery Capable Devices..... | 58 |
| 2.4 SOP* Communication | 60 |
| 2.4.1 Introduction..... | 60 |
| 2.4.2 SOP* Collision Avoidance..... | 60 |
| 2.4.3 SOP Communication..... | 60 |
| 2.4.4 SOP'/SOP'' Communication with Cable Plugs..... | 60 |
| 2.5 Operational Overview | 62 |
| 2.5.1 Source Operation..... | 62 |
| 2.5.2 Sink Operation | 65 |

| | | |
|-----------|--|------------|
| 2.5.3 | Cable Plugs | 68 |
| 2.6 | Architectural Overview | 69 |
| 2.6.1 | Policy | 72 |
| 2.6.2 | Message Formation and Transmission | 73 |
| 2.6.3 | Collision Avoidance | 74 |
| 2.6.4 | Power supply | 74 |
| 2.6.5 | DFP/UFP | 75 |
| 2.6.6 | Cable and Connectors | 75 |
| 2.6.7 | Interactions between Non-PD, BC, and PD devices | 75 |
| 2.6.8 | Power Rules | 76 |
| 2.7 | Extended Power Range (EPR) Operation | 77 |
| 2.8 | Charging Models | 79 |
| 2.8.1 | Fixed Voltage Charging Models | 79 |
| 2.8.2 | Programmable Power Supply (PPS) Charging Models | 79 |
| 2.8.3 | Adjustable Voltage Supply (AVS) Charging Models | 80 |
| 3. | USB Type-A and USB Type-B Cable Assemblies and Connectors | 81 |
| 4. | Electrical Requirements | 82 |
| 4.1 | Interoperability with other USB Specifications | 82 |
| 4.2 | Dead Battery Detection / Unpowered Port Detection | 82 |
| 4.3 | Cable IR Ground Drop (IR Drop) | 82 |
| 4.4 | Cable Type Detection | 82 |
| 5. | Physical Layer | 84 |
| 5.1 | Physical Layer Overview | 84 |
| 5.2 | Physical Layer Functions | 84 |
| 5.3 | Symbol Encoding | 85 |
| 5.4 | Ordered Sets | 86 |
| 5.5 | Transmitted Bit Ordering | 88 |
| 5.6 | Packet Format | 89 |
| 5.6.1 | Packet Framing | 89 |
| 5.6.2 | CRC | 92 |
| 5.6.3 | Packet Detection Errors | 94 |
| 5.6.4 | Hard Reset | 94 |
| 5.6.5 | Cable Reset | 95 |
| 5.7 | Collision Avoidance | 96 |
| 5.8 | Biphase Mark Coding (BMC) Signaling Scheme | 97 |
| 5.8.1 | Encoding and signaling | 97 |
| 5.8.2 | Transmit and Receive Masks | 101 |
| 5.8.3 | Transmitter Load Model | 109 |
| 5.8.4 | BMC Common specifications | 111 |
| 5.8.5 | BMC Transmitter Specifications | 111 |
| 5.8.6 | BMC Receiver Specifications | 116 |
| 5.9 | Built in Self-Test (BIST) | 119 |
| 5.9.1 | BIST Carrier Mode | 119 |
| 5.9.2 | BIST Test Data | 119 |
| 6. | Protocol Layer | 120 |
| 6.1 | Overview | 120 |
| 6.2 | Messages | 120 |
| 6.2.1 | Message Construction | 120 |
| 6.3 | Control Message | 134 |

| | | |
|--------|---|-----|
| 6.3.1 | GoodCRC Message..... | 135 |
| 6.3.2 | GotoMin Message..... | 135 |
| 6.3.3 | Accept Message..... | 136 |
| 6.3.4 | Reject Message..... | 136 |
| 6.3.5 | Ping Message..... | 137 |
| 6.3.6 | PS_RDY Message..... | 137 |
| 6.3.7 | Get_Source_Cap Message..... | 137 |
| 6.3.8 | Get_Sink_Cap Message..... | 137 |
| 6.3.9 | DR_Swap Message..... | 138 |
| 6.3.10 | PR_Swap Message..... | 138 |
| 6.3.11 | VCONN_Swap Message..... | 139 |
| 6.3.12 | Wait Message..... | 140 |
| 6.3.13 | Soft Reset Message..... | 141 |
| 6.3.14 | Data_Reset Message..... | 142 |
| 6.3.15 | Data_Reset_Complete Message..... | 142 |
| 6.3.16 | Not_Supported Message..... | 143 |
| 6.3.17 | Get_Source_Cap_Extended Message..... | 143 |
| 6.3.18 | Get_Status Message..... | 143 |
| 6.3.19 | FR_Swap Message..... | 143 |
| 6.3.20 | Get_PPS_Status..... | 144 |
| 6.3.21 | Get_Country_Codes..... | 144 |
| 6.3.22 | Get_Sink_Cap_Extended Message..... | 144 |
| 6.3.23 | Get_Source_Info Message..... | 144 |
| 6.3.24 | Get_Revision Message..... | 144 |
| 6.4 | Data Message..... | 145 |
| 6.4.1 | Capabilities Message..... | 146 |
| 6.4.2 | Request Message..... | 162 |
| 6.4.3 | BIST Message..... | 169 |
| 6.4.4 | Vendor Defined Message..... | 172 |
| 6.4.5 | Battery_Status Message..... | 213 |
| 6.4.6 | Alert Message..... | 215 |
| 6.4.7 | Get_Country_Info Message..... | 219 |
| 6.4.8 | Enter_USB Message..... | 220 |
| 6.4.9 | EPR_Request Message..... | 223 |
| 6.4.10 | EPR_Mode Message..... | 224 |
| 6.4.11 | Source_Info Message..... | 231 |
| 6.4.12 | Revision Message..... | 233 |
| 6.5 | Extended Message..... | 234 |
| 6.5.1 | Source_Capabilities_Extended Message..... | 236 |
| 6.5.2 | Status Message..... | 242 |
| 6.5.3 | Get_Battery_Cap Message..... | 248 |
| 6.5.4 | Get_Battery_Status Message..... | 249 |
| 6.5.5 | Battery_Capabilities Message..... | 250 |
| 6.5.6 | Get_Manufacturer_Info Message..... | 252 |
| 6.5.7 | Manufacturer_Info Message..... | 253 |
| 6.5.8 | Security Messages..... | 255 |
| 6.5.9 | Firmware Update Messages..... | 257 |
| 6.5.10 | PPS_Status Message..... | 258 |
| 6.5.11 | Country_Codes Message..... | 260 |
| 6.5.12 | Country_Info Message..... | 261 |
| 6.5.13 | Sink_Capabilities_Extended Message..... | 262 |

| | | |
|--------|---|-----|
| 6.5.14 | Extended_Control Message | 268 |
| 6.5.15 | EPR Capabilities Message | 270 |
| 6.5.16 | Vendor_Defined_Extended Message..... | 272 |
| 6.6 | Timers | 274 |
| 6.6.1 | CRCReceiveTimer | 274 |
| 6.6.2 | SenderResponseTimer..... | 274 |
| 6.6.3 | Capability Timers | 275 |
| 6.6.4 | Wait Timers and Times..... | 277 |
| 6.6.5 | Power Supply Timers | 278 |
| 6.6.6 | NoResponseTimer..... | 280 |
| 6.6.7 | BIST Timers | 281 |
| 6.6.8 | Power Role Swap Timers | 282 |
| 6.6.9 | Soft Reset Timers..... | 283 |
| 6.6.10 | Data Reset Timers..... | 284 |
| 6.6.11 | Hard Reset Timers | 285 |
| 6.6.12 | Structured VDM Timers..... | 286 |
| 6.6.13 | VCONN Timers | 288 |
| 6.6.14 | tCableMessage | 288 |
| 6.6.15 | DiscoverIdentityTimer..... | 288 |
| 6.6.16 | Collision Avoidance Timers | 289 |
| 6.6.17 | Fast Role Swap Timers..... | 290 |
| 6.6.18 | Chunking Timers | 291 |
| 6.6.19 | Programmable Power Supply Timers | 293 |
| 6.6.20 | tEnterUSB | 293 |
| 6.6.21 | EPR Timers..... | 294 |
| 6.6.22 | Time Values and Timers..... | 295 |
| 6.7 | Counters | 299 |
| 6.7.1 | MessageID Counter..... | 299 |
| 6.7.2 | Retry Counter..... | 300 |
| 6.7.3 | Hard Reset Counter | 300 |
| 6.7.4 | Capabilities Counter..... | 300 |
| 6.7.5 | Discover Identity Counter | 300 |
| 6.7.6 | VDMBusyCounter..... | 300 |
| 6.7.7 | Counter Values and Counters..... | 301 |
| 6.8 | Reset..... | 302 |
| 6.8.1 | Soft Reset and Protocol Error | 302 |
| 6.8.2 | Data Reset..... | 304 |
| 6.8.3 | Hard Reset | 304 |
| 6.8.4 | Cable Reset..... | 305 |
| 6.9 | Accept, Reject and Wait | 306 |
| 6.10 | Collision Avoidance | 306 |
| 6.11 | Message Discarding..... | 306 |
| 6.12 | State behavior | 308 |
| 6.12.1 | Introduction to state diagrams used in Chapter 6..... | 308 |
| 6.12.2 | State Operation..... | 309 |
| 6.12.3 | List of Protocol Layer States | 331 |
| 6.13 | Message Applicability..... | 333 |
| 6.13.1 | Applicability of Control Messages..... | 334 |
| 6.13.2 | Applicability of Data Messages..... | 336 |
| 6.13.3 | Applicability of Extended Messages..... | 338 |
| 6.13.4 | Applicability of Extended Control Messages..... | 340 |

| | | |
|-----------|--|------------|
| 6.13.5 | Applicability of Structured VDM Commands | 341 |
| 6.13.6 | Applicability of Reset Signaling..... | 342 |
| 6.13.7 | Applicability of Fast Role Swap signal..... | 342 |
| 6.14 | Value Parameters..... | 343 |
| 7. | Power Supply | 344 |
| 7.1 | Source Requirements | 344 |
| 7.1.1 | Behavioral Aspects | 344 |
| 7.1.2 | Source Bulk Capacitance | 344 |
| 7.1.3 | Types of Sources | 345 |
| 7.1.4 | Source Transitions | 346 |
| 7.1.5 | Response to Hard Resets..... | 359 |
| 7.1.6 | Changing the Output Power Capability | 360 |
| 7.1.7 | Robust Source Operation | 361 |
| 7.1.8 | Output Voltage Tolerance and Range..... | 363 |
| 7.1.9 | Charging and Discharging the Bulk Capacitance on V_{BUS} | 364 |
| 7.1.10 | Swap Standby for Sources | 364 |
| 7.1.11 | Source Peak Current Operation | 365 |
| 7.1.12 | Source Capabilities Extended Parameters | 366 |
| 7.1.13 | Fast Role Swap | 369 |
| 7.1.14 | Non-application of V_{BUS} Slew Rate Limits | 371 |
| 7.1.15 | V_{CONN} Power Cycle | 372 |
| 7.2 | Sink Requirements..... | 374 |
| 7.2.1 | Behavioral Aspects | 374 |
| 7.2.2 | Sink Bulk Capacitance | 374 |
| 7.2.3 | Sink Standby | 375 |
| 7.2.4 | Suspend Power Consumption..... | 375 |
| 7.2.5 | Zero Negotiated Current | 375 |
| 7.2.6 | Transient Load Behavior..... | 375 |
| 7.2.7 | Swap Standby for Sinks..... | 376 |
| 7.2.8 | Sink Peak Current Operation..... | 376 |
| 7.2.9 | Robust Sink Operation | 377 |
| 7.2.10 | Fast Role Swap | 379 |
| 7.3 | Transitions | 380 |
| 7.3.1 | Transitions caused by a Request Message | 382 |
| 7.3.2 | Transitions Caused by Power Role Swap..... | 418 |
| 7.3.3 | Transitions Caused by GotoMin | 424 |
| 7.3.4 | Transitions Caused by Hard Reset..... | 426 |
| 7.3.5 | Transitions Caused by Fast Role Swap..... | 430 |
| 7.4 | Electrical Parameters | 433 |
| 7.4.1 | Source Electrical Parameters | 433 |
| 7.4.2 | Sink Electrical Parameters | 441 |
| 7.4.3 | Common Electrical Parameters..... | 443 |
| 8. | Device Policy | 444 |
| 8.1 | Overview | 444 |
| 8.2 | Device Policy Manager | 444 |
| 8.2.1 | Capabilities..... | 445 |
| 8.2.2 | System Policy..... | 446 |
| 8.2.3 | Control of Source/Sink..... | 446 |
| 8.2.4 | Cable Detection | 446 |
| 8.2.5 | Managing Power Requirements..... | 447 |

| | | |
|------------|---|-------------|
| 8.2.6 | Use of “Unconstrained Power” bit with Batteries and AC supplies | 449 |
| 8.2.7 | Interface to the Policy Engine | 451 |
| 8.3 | Policy Engine | 453 |
| 8.3.1 | Introduction | 453 |
| 8.3.2 | Atomic Message Sequence Diagrams | 453 |
| 8.3.3 | State Diagrams | 865 |
| 9. | States and Status Reporting | 1021 |
| 9.1 | Overview | 1021 |
| 9.1.1 | PDUSB Device and Hub Requirements | 1023 |
| 9.1.2 | Mapping to USB Device States | 1024 |
| 9.1.3 | PD Software Stack | 1026 |
| 9.1.4 | PDUSB Device Enumeration | 1027 |
| 9.2 | PD Specific Descriptors | 1029 |
| 9.2.1 | USB Power Delivery Capability Descriptor | 1029 |
| 9.2.2 | Battery Info Capability Descriptor | 1031 |
| 9.2.3 | PD Consumer Port Capability Descriptor | 1032 |
| 9.2.4 | PD Provider Port Capability Descriptor | 1033 |
| 9.3 | PD Specific Requests and Events | 1034 |
| 9.3.1 | PD Specific Requests | 1034 |
| 9.4 | PDUSB Hub and PDUSB Peripheral Device Requests | 1035 |
| 9.4.1 | GetBatteryStatus | 1035 |
| 9.4.2 | SetPDFeature | 1036 |
| 10. | Power Rules | 1039 |
| 10.1 | Introduction | 1039 |
| 10.2 | Source Power Rules | 1039 |
| 10.2.1 | Source Power Rule Considerations | 1039 |
| 10.2.2 | Normative Voltages and Currents | 1041 |
| 10.2.3 | Optional Voltages/Currents | 1051 |
| 10.2.4 | Power sharing between ports | 1060 |
| 10.3 | Sink Power Rules | 1061 |
| 10.3.1 | Sink Power Rule Considerations | 1061 |
| 10.3.2 | Normative Sink Rules | 1061 |
| A. | CRC calculation | 1063 |
| A.1 | C code example | 1063 |
| B. | PD Message Sequence Examples | 1066 |
| B.1 | External power is supplied downstream | 1066 |
| B.2 | External power is supplied upstream | 1070 |
| B.3 | Giving back power | 1076 |
| C. | VDM Command Examples | 1086 |
| C.1 | Discover Identity Example | 1086 |
| C.1.1 | Discover Identity Command request | 1086 |
| C.1.2 | Discover Identity Command response – Active Cable | 1087 |
| C.1.3 | Discover Identity Command response – Hub. | 1089 |
| C.2 | Discover SVIDs Example | 1090 |
| C.2.1 | Discover SVIDs Command request | 1090 |
| C.2.2 | Discover SVIDs Command response | 1091 |
| C.3 | Discover Modes Example | 1092 |
| C.3.1 | Discover Modes Command request | 1092 |
| C.3.2 | Discover Modes Command response | 1093 |

| | | |
|-----------|---|-------------|
| C.4 | Enter Mode Example..... | 1094 |
| C.4.1 | Enter Mode Command request | 1094 |
| C.4.2 | Enter Mode Command response | 1095 |
| C.4.3 | Enter Mode Command request with additional VDO | 1096 |
| C.5 | Exit Mode Example | 1097 |
| C.5.1 | Exit Mode Command request..... | 1097 |
| C.5.2 | Exit Mode Command response..... | 1098 |
| C.6 | Attention Example | 1099 |
| C.6.1 | Attention Command request | 1099 |
| C.6.2 | Attention Command request with additional VDO..... | 1100 |
| D. | BMC Receiver Design Examples..... | 1101 |
| D.1 | Finite Difference Scheme | 1101 |
| D.1.1 | Sample Circuitry | 1101 |
| D.1.2 | Theory..... | 1101 |
| D.1.3 | Data Recovery | 1103 |
| D.1.4 | Noise Zone and Detection Zone | 1104 |
| D.2 | Subtraction Scheme..... | 1105 |
| D.2.1 | Sample Circuitry | 1105 |
| D.2.2 | Output of Each Circuit Block | 1105 |
| D.2.3 | Subtractor Output at Power Source and Power Sink..... | 1105 |
| D.2.4 | Noise Zone and Detection Zone | 1106 |
| E. | FRS System Level Example..... | 1107 |
| E.1 | Overview | 1107 |
| E.2 | FRS Initial Setup..... | 1110 |
| E.3 | FRS Process..... | 1113 |

List of Tables

| | |
|---|-----|
| Table 1.1 Section Overview | 40 |
| Table 1.2 Document References | 43 |
| Table 1.3 Terms and Abbreviations | 45 |
| Table 2.1 “Fixed Voltage Power Ranges” | 79 |
| Table 2.2 “PPS Voltage Power Ranges” | 80 |
| Table 2.3 “Adjustable Voltage Supply Voltage Ranges” | 80 |
| Table 5.1 “4b5b Symbol Encoding Table” | 85 |
| Table 5.2 “Ordered Sets” | 86 |
| Table 5.3 “Validation of Ordered Sets” | 87 |
| Table 5.4 “Data Size” | 88 |
| Table 5.5 “SOP ordered set” | 89 |
| Table 5.6 “SOP’ ordered set” | 90 |
| Table 5.7 “SOP” ordered set” | 90 |
| Table 5.8 “SOP’_Debug ordered set” | 91 |
| Table 5.9 “SOP”_Debug ordered set” | 91 |
| Table 5.10 “CRC-32 Mapping” | 93 |
| Table 5.11 “Hard Reset ordered set” | 94 |
| Table 5.12 “Cable Reset ordered set” | 95 |
| Table 5.13 “R _p values used for Collision Avoidance” | 96 |
| Table 5.14 “BMC Tx Mask Definition, X Values” | 102 |
| Table 5.15 “BMC Tx Mask Definition, Y Values” | 103 |
| Table 5.16 “BMC Rx Mask Definition” | 108 |
| Table 5.17 “BMC Common Normative Requirements” | 111 |
| Table 5.18 “BMC Transmitter Normative Requirements” | 112 |
| Table 5.19 “BMC Receiver Normative Requirements” | 116 |
| Table 6.1 “Message Header” | 122 |
| Table 6.2 “Revision Interoperability during an Explicit Contract” | 125 |
| Table 6.3 “Extended Message Header” | 126 |
| Table 6.4 “Use of Unchunked Message Supported bit” | 128 |
| Table 6.5 “Control Message Types” | 134 |
| Table 6.6 “Data Message Types” | 145 |
| Table 6.7 “Power Data Object” | 147 |
| Table 6.8 “Augmented Power Data Object” | 147 |
| Table 6.9 “Fixed Supply PDO – Source” | 150 |
| Table 6.10 “Fixed Power Source Peak Current Capability” | 152 |
| Table 6.11 “Variable Supply (non-Battery) PDO – Source” | 153 |
| Table 6.12 “Battery Supply PDO – Source” | 153 |
| Table 6.13 “SPR Programmable Power Supply APDO – Source” | 154 |
| Table 6.14 “EPR Adjustable Voltage Supply APDO – Source “ | 154 |
| Table 6.15 “EPR AVS Power Source Peak Current Capability” | 155 |
| Table 6.16 “SPR Adjustable Voltage Supply APDO – Source” | 156 |
| Table 6.17 “Fixed Supply PDO – Sink” | 158 |
| Table 6.18 “Variable Supply (non-Battery) PDO – Sink” | 159 |
| Table 6.19 “Battery Supply PDO – Sink” | 160 |
| Table 6.20 “Programmable Power Supply APDO – Sink” | 160 |
| Table 6.21 “EPR Adjustable Voltage Supply APDO – Sink” | 161 |
| Table 6.22 “Fixed and Variable Request Data Object” | 162 |
| Table 6.23 “Fixed and Variable Request Data Object with GiveBack Support” | 163 |
| Table 6.24 “Battery Request Data Object” | 163 |

| | |
|--|-----|
| Table 6.25 “Battery Request Data Object with GiveBack Support” | 163 |
| Table 6.26 “PPS Request Data Object” | 164 |
| Table 6.27 “AVS Request Data Object” | 164 |
| Table 6.28 “BIST Data Object” | 170 |
| Table 6.29 “Unstructured VDM Header” | 173 |
| Table 6.30 “Structured VDM Header” | 175 |
| Table 6.31 “Structured VDM Commands” | 176 |
| Table 6.32 “SVID Values” | 176 |
| Table 6.33 “Commands and Responses” | 179 |
| Table 6.34 “ID Header VDO” | 182 |
| Table 6.35 “Product Types (UFP)” | 183 |
| Table 6.36 “Product Types (Cable Plug/VPD)” | 183 |
| Table 6.37 “Product Types (DFP)” | 184 |
| Table 6.38 “Cert Stat VDO” | 184 |
| Table 6.39 “Product VDO” | 185 |
| Table 6.40 “UFP VDO” | 186 |
| Table 6.41 “DFP VDO” | 188 |
| Table 6.42 “Passive Cable VDO” | 190 |
| Table 6.43 “Active Cable VDO 1” | 193 |
| Table 6.44 “Active Cable VDO 2” | 195 |
| Table 6.45 “VPD VDO” | 199 |
| Table 6.46 “Discover SVIDs Responder VDO” | 201 |
| Table 6.47 “Battery Status Data Object (BSDO)” | 213 |
| Table 6.48 “Alert Data Object (ADO)” | 216 |
| Table 6.49 “Country Code Data Object (CCDO)” | 219 |
| Table 6.50 “Enter_USB Data Object (EUODO)” | 221 |
| Table 6.51 “EPR Mode Data Object (EPRMDO)” | 225 |
| Table 6.52 “Source_Info Data Object (SIDO)” | 231 |
| Table 6.53 “Revision Message Data Object (RMDO)” | 233 |
| Table 6.54 “Extended Message Types” | 235 |
| Table 6.55 “Source Capabilities Extended Data Block (SCEDB)” | 236 |
| Table 6.56 “SOP Status Data Block (SDB)” | 243 |
| Table 6.57 “SOP’/SOP” Status Data Block (SDB)” | 247 |
| Table 6.58 “Get Battery Cap Data Block (GBCDB)” | 248 |
| Table 6.59 “Get Battery Status Data Block (GBSDB)” | 249 |
| Table 6.60 “Battery Capability Data Block (BCDB)” | 250 |
| Table 6.61 “Get Manufacturer Info Data Block (GMIDB)” | 252 |
| Table 6.62 “Manufacturer Info Data Block (MIDB)” | 253 |
| Table 6.63 “PPS Status Data Block (PPSSDB)” | 258 |
| Table 6.64 “Country Codes Data Block (CCDB)” | 260 |
| Table 6.65 “Country Info Data Block (CIDB)” | 261 |
| Table 6.66 “Sink Capabilities Extended Data Block (SKEDB)” | 263 |
| Table 6.67 “Extended Control Data Block (ECDB)” | 268 |
| Table 6.68 “Extended Control Message Types” | 268 |
| Table 6.69 “Time Values” | 296 |
| Table 6.70 “Timers” | 298 |
| Table 6.71 “Counter parameters” | 301 |
| Table 6.72 “Counters” | 301 |
| Table 6.73 “Response to an incoming Message (except VDM)” | 303 |
| Table 6.74 “Response to an incoming VDM” | 303 |
| Table 6.75 “Message discarding” | 307 |

| | |
|--|-----|
| Table 6.76 “Protocol Layer States” | 331 |
| Table 6.77 “Message Applicability Abbreviations” | 333 |
| Table 6.78 “Applicability of Control Messages” | 334 |
| Table 6.79 “Applicability of Data Messages” | 336 |
| Table 6.80 “Applicability of Extended Messages” | 338 |
| Table 6.81 “Applicability of Extended Control Messages” | 340 |
| Table 6.82 “Applicability of Structured VDM Commands” | 341 |
| Table 6.83 “Applicability of Reset Signaling” | 342 |
| Table 6.84 “Applicability of Fast Role Swap signal” | 342 |
| Table 6.85 “Value Parameters” | 343 |
| Table 7.1 “Sequence Description for Changing the Source to another (A)PDO” | 384 |
| Table 7.2 “Sequence Description for Increasing the Voltage” | 386 |
| Table 7.3 “Sequence Diagram for Increasing the Voltage and Current” | 388 |
| Table 7.4 “Sequence Description for Increasing the Voltage and Decreasing the Current” | 390 |
| Table 7.5 “Sequence Description for Decreasing the Voltage and Increasing the Current” | 392 |
| Table 7.6 “Sequence Description for Decreasing the Voltage” | 394 |
| Table 7.7 “Sequence Description for Decreasing the Voltage and the Current” | 396 |
| Table 7.8 “Sequence Description for no change in Current or Voltage” | 398 |
| Table 7.9 “Sequence Description for Increasing the Current” | 400 |
| Table 7.10 “Sequence Description for Decreasing the Current” | 402 |
| Table 7.11 “Sequence Description for Increasing the Programmable Power Supply Voltage” | 404 |
| Table 7.12 “Sequence Description for Decreasing the Programmable Power Supply Voltage” | 406 |
| Table 7.13 “Sequence Description for increasing the Current in PPS mode” | 408 |
| Table 7.14 “Sequence Description for decreasing the Current in PPS mode” | 410 |
| Table 7.15 “Sequence Description for no change in Current or Voltage in PPS mode” | 412 |
| Table 7.16 “Sequence Description for Increasing the Adjustable Voltage Supply Voltage” | 414 |
| Table 7.17 “Sequence Description for Decreasing the Adjustable Voltage Supply Voltage” | 416 |
| Table 7.18 “Sequence Description for no change in Current or Voltage in AVS mode” | 417 |
| Table 7.19 “Sequence Description for a Sink Requested Power Role Swap” | 419 |
| Table 7.20 “Sequence Description for a Source Requested Power Role Swap” | 422 |
| Table 7.21 “Sequence Description for a GotoMin Current Decrease” | 425 |
| Table 7.22 “Sequence Description for a Source Initiated Hard Reset” | 427 |
| Table 7.23 “Sequence Description for a Sink Initiated Hard Reset” | 429 |
| Table 7.24 “Sequence Description for Fast Role Swap” | 431 |
| Table 7.25 “Source Electrical Parameters” | 433 |
| Table 7.26 “Sink Electrical Parameters” | 441 |
| Table 7.27 “Common Source/Sink Electrical Parameters” | 443 |
| Table 8.1 “Basic Message Flow” | 454 |
| Table 8.2 “Potential issues in Basic Message Flow” | 456 |
| Table 8.3 “Basic Message Flow with CRC failure” | 458 |
| Table 8.4 “Atomic Message Sequences” | 460 |
| Table 8.5 “AMS: Power Negotiation (SPR)” | 461 |
| Table 8.6 “AMS: Power Negotiation (EPR)” | 462 |
| Table 8.7 “AMS: Unsupported Message” | 463 |
| Table 8.8 “AMS: Ping” | 464 |
| Table 8.9 “AMS: Soft Reset” | 464 |
| Table 8.10 “AMS: Data Reset” | 465 |
| Table 8.11 “AMS: Power Role Swap” | 466 |
| Table 8.12 “AMS: Fast Role Swap” | 466 |
| Table 8.13 “AMS: Data Role Swap” | 467 |
| Table 8.14 “AMS: VCONN Swap” | 468 |

| | |
|---|-----|
| Table 8.15 “AMS: Alert” | 468 |
| Table 8.16 “AMS: Status” | 469 |
| Table 8.17 “AMS: Source/Sink Capabilities (SPR)” | 470 |
| Table 8.18 “AMS: Source/Sink Capabilities (EPR)” | 471 |
| Table 8.19 “AMS: Extended Capabilities” | 472 |
| Table 8.20 “AMS: Battery Capabilities” | 472 |
| Table 8.21 “AMS: Manufacturer Information” | 473 |
| Table 8.22 “AMS: Country Codes” | 473 |
| Table 8.23 “AMS: Country Information” | 474 |
| Table 8.24 “AMS: Revision Information” | 474 |
| Table 8.25 “AMS: Source Information” | 474 |
| Table 8.26 “AMS: Security” | 475 |
| Table 8.27 “AMS: Firmware Update” | 475 |
| Table 8.28 “AMS: Structured VDM” | 476 |
| Table 8.29 “AMS: Built-In Self-Test (BIST)” | 477 |
| Table 8.30 “AMS: Enter USB” | 477 |
| Table 8.31 “AMS: Unstructured VDM” | 477 |
| Table 8.32 “AMS: Hard Reset” | 478 |
| Table 8.33 “Steps for a successful Power Negotiation” | 481 |
| Table 8.34 “Steps for a rejected Power Negotiation” | 485 |
| Table 8.35 “Steps for a Wait response to a Power Negotiation” | 488 |
| Table 8.36 “Steps for a GotoMin Negotiation” | 491 |
| Table 8.37 “Steps for SPR PPS Keep Alive” | 494 |
| Table 8.38 “Steps for SPR Sink Makes Request (Accept)” | 498 |
| Table 8.39 “Steps for SPR Sink Makes Request (Reject)” | 501 |
| Table 8.40 “Steps for SPR Sink Makes Request (Wait)” | 504 |
| Table 8.41 “Steps for Entering EPR Mode (Success)” | 507 |
| Table 8.42 “Steps for Entering EPR Mode (Failure due to non-EPR cable)” | 510 |
| Table 8.43 “Steps for Entering EPR Mode (Failure of VCONN Swap)” | 513 |
| Table 8.44 “Steps for a successful EPR Power Negotiation” | 517 |
| Table 8.45 “Steps for a Rejected EPR Power Negotiation” | 521 |
| Table 8.46 “Steps for a Wait response to an EPR Power Negotiation” | 524 |
| Table 8.47 “Steps for EPR Keep Alive” | 527 |
| Table 8.48 “Steps for Exiting EPR Mode (Sink Initiated)” | 530 |
| Table 8.49 “Steps for Exiting EPR Mode (Source Initiated)” | 533 |
| Table 8.50 “Steps for EPR Sink Makes Request (Accept)” | 536 |
| Table 8.51 “Steps for EPR Sink Makes Request (Reject)” | 539 |
| Table 8.52 “Steps for EPR Sink Makes Request (Wait)” | 542 |
| Table 8.53 “Steps for an Unsupported Message” | 545 |
| Table 8.54 “Steps for a Ping” | 548 |
| Table 8.55 “Steps for a Soft Reset” | 550 |
| Table 8.56 “Steps for a DFP Initiated Data Reset where the DFP is the VCONN Source” | 553 |
| Table 8.57 “Steps for a DFP Receiving a Data Reset where the DFP is the VCONN Source” | 557 |
| Table 8.58 “Steps for a DFP Initiated Data Reset where the UFP is the VCONN Source” | 561 |
| Table 8.59 “Steps for a DFP Receiving a Data Reset where the UFP is the VCONN Source” | 566 |
| Table 8.60 “Steps for Source initiated Hard Reset” | 571 |
| Table 8.61 “Steps for Sink initiated Hard Reset” | 574 |
| Table 8.62 “Steps for Source initiated Hard Reset – Sink long reset” | 577 |
| Table 8.63 “Steps for a Successful Source Initiated Power Role Swap Sequence” | 581 |
| Table 8.64 “Steps for a Rejected Source Initiated Power Role Swap Sequence” | 585 |
| Table 8.65 “Steps for a Source Initiated Power Role Swap with Wait Sequence” | 588 |

| | |
|---|-----|
| Table 8.66 “Steps for a Successful Sink Initiated Power Role Swap Sequence” | 592 |
| Table 8.67 “Steps for a Rejected Sink Initiated Power Role Swap Sequence” | 596 |
| Table 8.68 “Steps for a Sink Initiated Power Role Swap with Wait Sequence” | 599 |
| Table 8.69 “Steps for a Successful Fast Role Swap Sequence” | 603 |
| Table 8.70 “Steps for Data Role Swap, UFP operating as Sink initiates” | 607 |
| Table 8.71 “Steps for Rejected Data Role Swap, UFP operating as Sink initiates” | 610 |
| Table 8.72 “Steps for Data Role Swap with Wait, UFP operating as Sink initiates” | 613 |
| Table 8.73 “Steps for Data Role Swap, UFP operating as Source initiates” | 616 |
| Table 8.74 “Steps for Rejected Data Role Swap, UFP operating as Source initiates” | 619 |
| Table 8.75 “Steps for Data Role Swap with Wait, UFP operating as Source initiates” | 622 |
| Table 8.76 “Steps for Data Role Swap, DFP operating as Source initiates” | 625 |
| Table 8.77 “Steps for Rejected Data Role Swap, DFP operating as Source initiates” | 628 |
| Table 8.78 “Steps for Data Role Swap with Wait, DFP operating as Source initiates” | 631 |
| Table 8.79 “Steps for Data Role Swap, DFP operating as Sink initiates” | 634 |
| Table 8.80 “Steps for Rejected Data Role Swap, DFP operating as Sink initiates” | 637 |
| Table 8.81 “Steps for Data Role Swap with Wait, DFP operating as Sink initiates” | 640 |
| Table 8.82 “Steps for Source to Sink VCONN Source Swap” | 643 |
| Table 8.83 “Steps for Rejected VCONN Source Swap” | 646 |
| Table 8.84 “Steps for VCONN Source Swap with Wait” | 649 |
| Table 8.85 “Steps for VCONN Source Swap, Initiated by non- VCONN Source” | 652 |
| Table 8.86 “Steps for Rejected VCONN Source Swap, Initiated by non- VCONN Source” | 655 |
| Table 8.87 “Steps for VCONN Source Swap with Wait, Initiated by non- VCONN Source” | 658 |
| Table 8.88 “Steps for Source Alert to Sink” | 661 |
| Table 8.89 “Steps for Sink Alert to Source” | 663 |
| Table 8.90 “Steps for a Sink getting Source Status Sequence” | 665 |
| Table 8.91 “Steps for a Source getting Sink Status Sequence” | 668 |
| Table 8.92 “Steps for a VCONN Source getting Cable Plug Status Sequence” | 671 |
| Table 8.93 “Steps for a Sink getting Source PPS status Sequence” | 674 |
| Table 8.94 “Steps for a Sink getting Source Capabilities Sequence” | 677 |
| Table 8.95 “Steps for a Dual-Role Source getting Dual-Role Sink’s capabilities as a Source Sequence” | 680 |
| Table 8.96 “Steps for a Source getting Sink Capabilities Sequence” | 683 |
| Table 8.97 “Steps for a Dual-Role Sink getting Dual-Role Source capabilities as a Sink Sequence” | 686 |
| Table 8.98 “Steps for a Sink getting EPR Source Capabilities Sequence” | 689 |
| Table 8.99 “Steps for a Dual-Role Source getting Dual-Role Sink’s capabilities as an EPR Source Sequence” | 692 |
| Table 8.100 “Steps for a Source getting Sink EPR Capabilities Sequence” | 695 |
| Table 8.101 “Steps for a Dual-Role Sink getting Dual-Role Source capabilities as an EPR Sink Sequence” | 698 |
| Table 8.102 “Steps for a Sink getting Source extended capabilities Sequence” | 701 |
| Table 8.103 “Steps for a Dual-Role Source getting Dual-Role Sink extended capabilities Sequence” | 704 |
| Table 8.104 “Steps for a Source getting Sink extended capabilities Sequence” | 707 |
| Table 8.105 “Steps for a Dual-Role Sink getting Dual-Role Source extended capabilities Sequence” | 710 |
| Table 8.106 “Steps for a Sink getting Source Battery capabilities Sequence” | 713 |
| Table 8.107 “Steps for a Source getting Sink Battery capabilities Sequence” | 716 |
| Table 8.108 “Steps for a Sink getting Source Battery status Sequence” | 719 |
| Table 8.109 “Steps for a Source getting Sink Battery status Sequence” | 722 |
| Table 8.110 “Steps for a Source getting Sink’s Port Manufacturer Information Sequence” | 725 |
| Table 8.111 “Steps for a Source getting Sink’s Port Manufacturer Information Sequence” | 728 |
| Table 8.112 “Steps for a Source getting Sink’s Battery Manufacturer Information Sequence” | 731 |
| Table 8.113 “Steps for a Source getting Sink’s Battery Manufacturer Information Sequence” | 734 |
| Table 8.114 “Steps for a VCONN Source getting Sink’s Port Manufacturer Information Sequence” | 737 |
| Table 8.115 “Steps for a Source getting Country Codes Sequence” | 740 |
| Table 8.116 “Steps for a Source getting Sink’s Country Codes Sequence” | 743 |

| | |
|---|------|
| Table 8.117 “Steps for a VCONN Source getting Sink’s Country Codes Sequence” | 746 |
| Table 8.118 “Steps for a Source getting Country Information Sequence” | 749 |
| Table 8.119 “Steps for a Source getting Sink’s Country Information Sequence” | 752 |
| Table 8.120 “Steps for a VCONN Source getting Sink’s Country Information Sequence” | 755 |
| Table 8.121 “Steps for a Source getting Revision Information Sequence” | 758 |
| Table 8.122 “Steps for a Source getting Sink’s Revision Information Sequence” | 761 |
| Table 8.123 “Steps for a VCONN Source getting Sink’s Revision Information Sequence” | 764 |
| Table 8.124 “Steps for a Sink getting Source Information Sequence” | 767 |
| Table 8.125 “Steps for a Dual-Role Source getting Dual-Role Sink’s Information as a Source Sequence” | 770 |
| Table 8.126 “Steps for a Source requesting a security exchange with a Sink Sequence” | 773 |
| Table 8.127 “Steps for a Sink requesting a security exchange with a Source Sequence” | 776 |
| Table 8.128 “Steps for a VCONN Source requesting a security exchange with a Cable Plug Sequence” | 779 |
| Table 8.129 “Steps for a Source requesting a firmware update exchange with a Sink Sequence” | 782 |
| Table 8.130 “Steps for a Sink requesting a firmware update exchange with a Source Sequence” | 785 |
| Table 8.131 “Steps for a VCONN Source requesting a firmware update exchange with a Cable Plug Sequence” | 788 |
| Table 8.132 “Steps for Initiator to UFP Discover Identity (ACK)” | 791 |
| Table 8.133 “Steps for Initiator to UFP Discover Identity (NAK)” | 794 |
| Table 8.134 “Steps for Initiator to UFP Discover Identity (BUSY)” | 797 |
| Table 8.135 “Steps for DFP to UFP Discover SVIDs (ACK)” | 800 |
| Table 8.136 “Steps for DFP to UFP Discover SVIDs (NAK)” | 803 |
| Table 8.137 “Steps for DFP to UFP Discover SVIDs (BUSY)” | 806 |
| Table 8.138 “Steps for DFP to UFP Discover Modes (ACK)” | 809 |
| Table 8.139 “Steps for DFP to UFP Discover Modes (NAK)” | 812 |
| Table 8.140 “Steps for DFP to UFP Discover Modes (BUSY)” | 815 |
| Table 8.141 “Steps for DFP to UFP Enter Mode” | 818 |
| Table 8.142 “Steps for DFP to UFP Exit Mode” | 821 |
| Table 8.143 “Steps for DFP to Cable Plug Enter Mode” | 824 |
| Table 8.144 “Steps for DFP to Cable Plug Exit Mode” | 827 |
| Table 8.145 “Steps for Initiator to Responder Attention” | 830 |
| Table 8.146 “Steps for BIST Carrier Mode Test” | 832 |
| Table 8.147 “Steps for BIST Test Data Test” | 835 |
| Table 8.148 “Steps for BIST Shared Capacity Test Mode Test” | 839 |
| Table 8.149 “Steps for UFP USB4® Mode Entry (Accept)” | 842 |
| Table 8.150 “Steps for UFP USB4® Mode Entry (Reject)” | 845 |
| Table 8.151 “Steps for UFP USB4® Mode Entry (Wait)” | 848 |
| Table 8.152 “Steps for Cable Plug USB4® Mode Entry (Accept)” | 851 |
| Table 8.153 “Steps for Cable Plug USB4® Mode Entry (Reject)” | 854 |
| Table 8.154 “Steps for Cable Plug USB4® Mode Entry (Wait)” | 857 |
| Table 8.155 “Steps for Unstructured VDM Message Sequence” | 860 |
| Table 8.156 “Steps for VDEM Message Sequence” | 863 |
| Table 8.157 Policy Engine States..... | 1013 |
| Table 9.1 “USB Power Delivery Type Codes” | 1029 |
| Table 9.2 USB Power Delivery Capability Descriptor..... | 1029 |
| Table 9.3 “Battery Info Capability Descriptor” | 1031 |
| Table 9.4 “PD Consumer Port Descriptor” | 1032 |
| Table 9.5 “PD Provider Port Descriptor” | 1033 |
| Table 9.6 “PD Requests” | 1034 |
| Table 9.7 “PD Request Codes” | 1034 |
| Table 9.8 “PD Feature Selectors” | 1034 |
| Table 9.9 “Get Battery Status Request” | 1035 |
| Table 9.10 “Battery Status Structure” | 1035 |

| | |
|--|------|
| Table 9.11 “Set PD Feature” | 1036 |
| Table 9.12 “Battery Wake Mask” | 1037 |
| Table 9.13 “Charging Policy Encoding” | 1038 |
| Table 10.1 “Considerations for Sources” | 1040 |
| Table 10.2 “SPR Normative Voltages and Minimum Currents” | 1041 |
| Table 10.3 “SPR Source Capabilities When Port Present PDP is less than Port Maximum PDP” | 1042 |
| Table 10.4 “SPR Source Port Present PDP less than Port Maximum PDP Examples” | 1043 |
| Table 10.5 “Fixed Supply PDO – Source 5V” | 1046 |
| Table 10.6 “Fixed Supply PDO – Source 9V” | 1046 |
| Table 10.7 “Fixed Supply PDO – Source 15V” | 1047 |
| Table 10.8 “Fixed Supply PDO – Source 20V” | 1047 |
| Table 10.9 “SPR Adjustable Voltage Supply (AVS) Voltage Ranges” | 1050 |
| Table 10.10 “SPR Programmable Power Supply PDOs and APDOs based on the Port Maximum PDP” | 1052 |
| Table 10.11 SPR “Programmable Power Supply Voltage Ranges” | 1052 |
| Table 10.12 “EPR Source Capabilities based on the Port Maximim PDP and using an EPR Capable Cable” | 1056 |
| Table 10.13 “EPR Source Capabilities when Port Present PDP is less than Port Maximum PDP and using an EPR-capable cable” | 1056 |
| Table 10.14 “EPR Source Examples when Port Present PDP is less than Port Maximum PDP” | 1058 |
| Table 10.15 “EPR Adjustable Voltage Supply (AVS) Voltage Ranges” | 1059 |
| Table A-1 “Table showing the full calculation over one Message” | 1065 |
| Table B-1 External power is supplied downstream..... | 1067 |
| Table B.2 External power is supplied upstream..... | 1070 |
| Table B.3 Giving back power. | 1077 |
| Table C-1 “Discover Identity Command request from Initiator Example” | 1086 |
| Table C.2 “Discover Identity Command response from Active Cable Responder Example” | 1087 |
| Table C-3 “Discover Identity Command response from Hub Responder Example” | 1089 |
| Table C-4 “Discover SVIDs Command request from Initiator Example” | 1090 |
| Table C-5 “Discover SVIDs Command response from Responder Example” | 1091 |
| Table C-6 “Discover Modes Command request from Initiator Example” | 1092 |
| Table C-7 “Discover Modes Command response from Responder Example” | 1093 |
| Table C-8 “Enter Mode Command request from Initiator Example” | 1094 |
| Table C-9 “Enter Mode Command response from Responder Example” | 1095 |
| Table C-10 “Enter Mode Command request from Initiator Example” | 1096 |
| Table C-11 “Exit Mode Command request from Initiator Example” | 1097 |
| Table C-12 “Exit Mode Command response from Responder Example” | 1098 |
| Table C-13 “Attention Command request from Initiator Example” | 1099 |
| Table C-14 “Attention Command request from Initiator with additional VDO Example” | 1100 |
| Table E-1 “Sequence Table for setup of a Fast Role Swap (Hub connected to Power Adapter first)” | 1111 |
| Table E-2 “Sequence Table for setup of a Fast Role Swap (Hub connected to Notebook before Power Adapter)” | 1112 |
| Table E-3 Sequence Table for slow Vbus discharge (it discharges after FR_Swap message is sent) | 1114 |
| Table E-4 “Vbus discharges quickly after adapter disconnected” | 1116 |

List of Figures

| | |
|--|-----|
| Figure 2-1 “Logical Structure of USB Power Delivery Capable Devices” | 58 |
| Figure 2-2 “Example SOP’ Communication between VCONN Source and Cable Plug(s)” | 61 |
| Figure 2-3 “USB Power Delivery Communications Stack” | 70 |
| Figure 2-4 “USB Power Delivery Communication Over USB” | 71 |
| Figure 2-5 “High Level Architecture View” | 72 |
| Figure 2-6 “Example of a Normal EPR Mode Operational Flow” | 78 |
| Figure 5-1 “Interpretation of ordered sets” | 86 |
| Figure 5-2 “Transmit Order for Various Sizes of Data” | 88 |
| Figure 5-3 “USB Power Delivery Packet Format” | 89 |
| Figure 5-4 “CRC 32 generation” | 92 |
| Figure 5-5 “Line format of Hard Reset” | 95 |
| Figure 5-6 “Line format of Cable Reset” | 95 |
| Figure 5-7 “BMC Example” | 97 |
| Figure 5-8 “BMC Transmitter Block Diagram” | 97 |
| Figure 5-9 “BMC Receiver Block Diagram” | 98 |
| Figure 5-10 “BMC Encoded Start of Preamble” | 98 |
| Figure 5-11 “Transmitting or Receiving BMC Encoded Frame Terminated by Zero with High-to-Low Last Transition” | 99 |
| Figure 5-12 “Transmitting or Receiving BMC Encoded Frame Terminated by One with High-to-Low Last Transition” | 99 |
| Figure 5-13 “Transmitting or Receiving BMC Encoded Frame Terminated by Zero with Low to High Last Transition” | 100 |
| Figure 5-14 “Transmitting or Receiving BMC Encoded Frame Terminated by One with Low to High Last Transition” | 100 |
| Figure 5-15 “BMC Tx ‘ONE’ Mask” | 101 |
| Figure 5-16 “BMC Tx ‘ZERO’ Mask” | 102 |
| Figure 5-17 “BMC Rx ‘ONE’ Mask when Sourcing Power” | 104 |
| Figure 5-18 “BMC Rx ‘ZERO’ Mask when Sourcing Power” | 105 |
| Figure 5-19 “BMC Rx ‘ONE’ Mask when Power neutral” | 105 |
| Figure 5-20 “BMC Rx ‘ZERO’ Mask when Power neutral” | 106 |
| Figure 5-21 “BMC Rx ‘ONE’ Mask when Sinking Power” | 106 |
| Figure 5-22 “BMC Rx ‘ZERO’ Mask when Sinking Power” | 107 |
| Figure 5-23 “Transmitter Load Model for BMC Tx from a Source” | 109 |
| Figure 5-24 “Transmitter Load Model for BMC Tx from a Sink” | 109 |
| Figure 5-25 Transmitter diagram illustrating zDriver | 113 |
| Figure 5-26 “Inter-Frame Gap Timings” | 114 |
| Figure 5-27 “Example Multi-Drop Configuration showing two DRPs” | 117 |
| Figure 5-28 “Example Multi-Drop Configuration showing a DFP and UFP” | 118 |
| Figure 5-29 “Test Data Frame” | 119 |
| Figure 6-1 “USB Power Delivery Packet Format including Control Message Payload” | 121 |
| Figure 6-2 “USB Power Delivery Packet Format including Data Message Payload” | 121 |
| Figure 6-3 “USB Power Delivery Packet Format including an Extended Message Header and Payload” | 121 |
| Figure 6-4 “Example Security_Request sequence Unchunked (Chunked bit = 0)” | 129 |
| Figure 6-5 “Example byte transmission for Security_Request Message of Data Size 7 (Chunked bit is set to zero)” | 129 |
| Figure 6-6 “Example byte transmission for Security_Response Message of Data Size 7 (Chunked bit is set to zero)” | 130 |
| Figure 6-7 “Example Security_Request sequence Chunked (Chunked bit = 1)” | 131 |
| Figure 6-8 “Example Security_Request Message of Data Size 7 (Chunked bit set to 1)” | 132 |
| Figure 6-9 “Example Chunk 0 of Security_Response Message of Data Size 30 (Chunked bit set to 1)” | 132 |

| | |
|---|-----|
| Figure 6-10 “Example byte transmission for a Security_Response Message Chunk request (Chunked bit is set to 1)” | 133 |
| Figure 6-11 “Example Chunk 1 of Security_Response Message of Data Size 30 (Chunked bit set to 1)” | 133 |
| Figure 6-12 “Example Capabilities Message with 2 Power Data Objects” | 146 |
| Figure 6-13 “BIST Message” | 169 |
| Figure 6-14 “Vendor Defined Message” | 172 |
| Figure 6-15 “Discover Identity Command response” | 181 |
| Figure 6-16 “Discover Identity Command response for a DRD” | 181 |
| Figure 6-17 “Example Discover SVIDs response with 3 SVIDs” | 202 |
| Figure 6-18 “Example Discover SVIDs response with 4 SVIDs” | 202 |
| Figure 6-19 “Example Discover SVIDs response with 12 SVIDs followed by an empty response” | 202 |
| Figure 6-20 “Example Discover Modes response for a given SVID with 3 Modes” | 203 |
| Figure 6-21 “Successful Enter Mode sequence” | 205 |
| Figure 6-22 “Unsuccessful Enter Mode sequence due to NAK” | 206 |
| Figure 6-23 “Exit Mode sequence” | 207 |
| Figure 6-24 “Attention Command request/response sequence” | 208 |
| Figure 6-25 “Command request/response sequence” | 209 |
| Figure 6-26 “Enter/Exit Mode Process” | 211 |
| Figure 6-27 “Battery_Status Message” | 213 |
| Figure 6-28 “Alert Message” | 215 |
| Figure 6-29 “Get_Country_Info Message” | 219 |
| Figure 6-30 “Enter_USB Message” | 220 |
| Figure 6-31 “EPR_Request Message” | 223 |
| Figure 6-32 “EPR Mode DO Message” | 224 |
| Figure 6-33 “Illustration of process to enter EPR Mode” | 227 |
| Figure 6-34 “Source_Info Message” | 231 |
| Figure 6-35 “Revision Message Data Object” | 233 |
| Figure 6-36 “Source_Capabilities_Extended Message” | 236 |
| Figure 6-37 “SOP Status Message” | 242 |
| Figure 6-38 “SOP’/SOP” Status Message” | 247 |
| Figure 6-39 “Get_Battery_Cap Message” | 248 |
| Figure 6-40 “Get_Battery_Status Message” | 249 |
| Figure 6-41 “Battery_Capabilities Message” | 250 |
| Figure 6-42 “Get_Manufacturer_Info Message” | 252 |
| Figure 6-43 “Manufacturer_Info Message” | 253 |
| Figure 6-44 “Security_Request Message” | 255 |
| Figure 6-45 “Security_Response Message” | 256 |
| Figure 6-46 “Firmware_Update_Request Message” | 257 |
| Figure 6-47 “Firmware_Update_Response Message” | 257 |
| Figure 6-48 “PPS_Status Message” | 258 |
| Figure 6-49 “Country_Codes Message” | 260 |
| Figure 6-50 “Country_Info Message” | 261 |
| Figure 6-51 “Sink_Capabilities_Extended Message” | 262 |
| Figure 6-52 “Extended_Control Message” | 268 |
| Figure 6-53 “Mapping SPR Capabilities to EPR Capabilities” | 270 |
| Figure 6-54 “Vendor_Defined_Extended Message” | 272 |
| Figure 6-55 “Outline of States” | 308 |
| Figure 6-56 “References to states” | 308 |
| Figure 6-57 “Chunking architecture Showing Message and Control Flow” | 310 |
| Figure 6-58 “Chunked Rx State Diagram” | 311 |
| Figure 6-59 “Chunked Tx State Diagram” | 314 |

| | |
|---|-----|
| Figure 6-60 “Chunked Message Router State Diagram” | 318 |
| Figure 6-61 “Common Protocol Layer Message Transmission State Diagram” | 320 |
| Figure 6-62 “Source Protocol Layer Message Transmission State Diagram” | 323 |
| Figure 6-63 “Sink Protocol Layer Message Transmission State Diagram” | 325 |
| Figure 6-64 “Protocol layer Message reception” | 326 |
| Figure 6-65 “Hard/Cable Reset” | 328 |
| Figure 7-1 “Placement of Source Bulk Capacitance” | 344 |
| Figure 7-2 “Transition Envelope for Positive Voltage Transitions” | 346 |
| Figure 7-3 “Transition Envelope for Negative Voltage Transitions” | 347 |
| Figure 7-4 “PPS Positive Voltage Transitions” | 349 |
| Figure 7-5 “PPS Negative Voltage Transitions” | 350 |
| Figure 7-6 “Expected PPS Ripple Relative to an LSB” | 350 |
| Figure 7-7 “Allowed DNL errors and tolerance of Voltage and Current in PPS mode” | 351 |
| Figure 7-8 “SPR PPS Programmable Voltage and Current Limit” | 353 |
| Figure 7-9 “SPR PPS Constant Power” | 354 |
| Figure 7-10 “AVS Positive Voltage Transitions” | 356 |
| Figure 7-11 “AVS Negative Voltage Transitions” | 357 |
| Figure 7-12 “Expected AVS Ripple Relative to an LSB” | 357 |
| Figure 7-13 “Source V_{BUS} and V_{CONN} Response to Hard Reset” | 359 |
| Figure 7-14 “Application of v_{SrcNew} and $v_{SrcValid}$ limits after $t_{SrcReady}$ ” | 363 |
| Figure 7-15 “Source Peak Current Overload” | 365 |
| Figure 7-16 “Holdup Time Measurement” | 367 |
| Figure 7-17 “ V_{BUS} Power during Fast Role Swap” | 369 |
| Figure 7-18 “ V_{BUS} detection and timing during Fast Role Swap, initial V_{BUS} (at new source) > $v_{Safe5V(min)}$ ” | 370 |
| Figure 7-19 “ V_{BUS} detection and timing during Fast Role Swap, initial V_{BUS} (at new source) < $v_{Safe5V(min)}$ ” | 370 |
| Figure 7-20 “Data Reset UFP V_{CONN} Power Cycle” | 372 |
| Figure 7-21 “Data Reset DFP V_{CONN} Power Cycle” | 373 |
| Figure 7-22 “Placement of Sink Bulk Capacitance” | 374 |
| Figure 7-23 “Generic Change for the Source to another (A)PDO” | 383 |
| Figure 7-24 “Transition Diagram for Increasing the Voltage” | 385 |
| Figure 7-25 “Transition Diagram for Increasing the Voltage and Current” | 387 |
| Figure 7-26 “Transition Diagram for Increasing the Voltage and Decreasing the Current” | 389 |
| Figure 7-27 “Transition Diagram for Decreasing the Voltage and Increasing the Current” | 391 |
| Figure 7-28 “Transition Diagram for Decreasing the Voltage” | 393 |
| Figure 7-29 “Transition Diagram for Decreasing the Voltage and the Current” | 395 |
| Figure 7-30 “Transition Diagram for no change in Current or Voltage” | 397 |
| Figure 7-31 “Transition Diagram for Increasing the Current” | 399 |
| Figure 7-32 “Transition Diagram for Decreasing the Current” | 401 |
| Figure 7-33 “Transition Diagram for Increasing the Programmable Power Supply Voltage” | 403 |
| Figure 7-34 “Transition Diagram for Decreasing the Programmable Power Supply Voltage” | 405 |
| Figure 7-35 “Transition Diagram for increasing the Current in PPS mode” | 407 |
| Figure 7-36 “Transition Diagram for decreasing the Current in PPS mode” | 409 |
| Figure 7-37 “Transition Diagram for no change in Current or Voltage in PPS mode” | 411 |
| Figure 7-38 “Transition Diagram for Increasing the Adjustable Power Supply Voltage” | 413 |
| Figure 7-39 “Transition Diagram for Decreasing the Adjustable Voltage Supply Voltage” | 415 |
| Figure 7-40 “Transition Diagram for no change in Current or Voltage in AVS mode” | 417 |
| Figure 7-41 “Transition Diagram for a Sink Requested Power Role Swap” | 418 |
| Figure 7-42 “Transition Diagram for a Source Requested Power Role Swap” | 421 |
| Figure 7-43 “Transition Diagram for a GotoMin Current Decrease” | 424 |
| Figure 7-44 “Transition Diagram for a Source Initiated Hard Reset” | 426 |
| Figure 7-45 “Transition Diagram for a Sink Initiated Hard Reset” | 428 |

| | |
|--|-----|
| Figure 7-46 “Transition Diagram for Fast Role Swap” | 430 |
| Figure 8-1 “Example of daisy chained displays” | 450 |
| Figure 8-2 “Basic Message Exchange (Successful)” | 454 |
| Figure 8-3 “Basic Message flow indicating possible errors” | 455 |
| Figure 8-4 “Basic Message Flow with Bad CRC followed by a Retry” | 457 |
| Figure 8-5 “Successful Fixed, Variable or Battery SPR Power Negotiation” | 480 |
| Figure 8-6 “Rejected Fixed, Variable or Battery SPR Power Negotiation” | 484 |
| Figure 8-7 “Wait response to Fixed, Variable or Battery SPR Power Negotiation” | 487 |
| Figure 8-8 “Successful GotoMin operation” | 490 |
| Figure 8-9 “SPR PPS Keep Alive” | 493 |
| Figure 8-10 “SPR Sink Makes Request (Accept)” | 497 |
| Figure 8-11 “SPR Sink Makes Request (Reject)” | 500 |
| Figure 8-12 “SPR Sink Makes Request (Wait)” | 503 |
| Figure 8-13 “Entering EPR Mode (Success)” | 506 |
| Figure 8-14 “Entering EPR Mode (Failure due to non-EPR cable)” | 509 |
| Figure 8-15 “Entering EPR Mode (Failure of VCONN Swap)” | 512 |
| Figure 8-16 “Successful Fixed EPR Power Negotiation” | 516 |
| Figure 8-17 “Rejected Fixed EPR Power Negotiation” | 520 |
| Figure 8-18 “Wait response to Fixed EPR Power Negotiation” | 523 |
| Figure 8-19 “EPR Keep Alive” | 526 |
| Figure 8-20 “Exiting EPR Mode (Sink Initiated)” | 529 |
| Figure 8-21 “Exiting EPR Mode (Source Initiated)” | 532 |
| Figure 8-22 “EPR Sink Makes Request (Accept)” | 535 |
| Figure 8-23 “EPR Sink Makes Request (Reject)” | 538 |
| Figure 8-24 “EPR Sink Makes Request (Wait)” | 541 |
| Figure 8-25 “Unsupported message” | 544 |
| Figure 8-26 “Ping” | 547 |
| Figure 8-27 “Soft Reset” | 549 |
| Figure 8-28 “DFP Initiated Data Reset where the DFP is the VCONN Source” | 552 |
| Figure 8-29 “DFP Receives Data Reset where the DFP is the VCONN Source” | 556 |
| Figure 8-30 “DFP Initiated Data Reset where the UFP is the Vconn Source” | 560 |
| Figure 8-31 “DFP Receives a Data Reset where the UFP is the VCONN Source” | 565 |
| Figure 8-32 “Source initiated Hard Reset” | 570 |
| Figure 8-33 “Sink Initiated Hard Reset” | 573 |
| Figure 8-34 “Source initiated reset - Sink long reset” | 576 |
| Figure 8-35 “Successful Power Role Swap Sequence Initiated by the Source” | 580 |
| Figure 8-36 “Rejected Power Role Swap Sequence Initiated by the Source” | 584 |
| Figure 8-37 “Power Role Swap Sequence with wait Initiated by the Source” | 587 |
| Figure 8-38 “Successful Power Role Swap Sequence Initiated by the Sink” | 591 |
| Figure 8-39 “Rejected Power Role Swap Sequence Initiated by the Sink” | 595 |
| Figure 8-40 “Power Role Swap Sequence with wait Initiated by the Sink” | 598 |
| Figure 8-41 “Successful Fast Role Swap Sequence” | 602 |
| Figure 8-42 “Data Role Swap, UFP operating as Sink initiates” | 606 |
| Figure 8-43 “Rejected Data Role Swap, UFP operating as Sink initiates” | 609 |
| Figure 8-44 “Data Role Swap with Wait, UFP operating as Sink initiates” | 612 |
| Figure 8-45 “Data Role Swap, UFP operating as Source initiates” | 615 |
| Figure 8-46 “Rejected Data Role Swap, UFP operating as Source initiates” | 618 |
| Figure 8-47 “Data Role Swap with Wait, UFP operating as Source initiates” | 621 |
| Figure 8-48 “Data Role Swap, DFP operating as Source initiates” | 624 |
| Figure 8-49 “Rejected Data Role Swap, DFP operating as Source initiates” | 627 |
| Figure 8-50 “Data Role Swap with Wait, DFP operating as Source initiates” | 630 |

| | |
|--|-----|
| Figure 8-51 “Data Role Swap, DFP operating as Sink initiates” | 633 |
| Figure 8-52 “Rejected Data Role Swap, DFP operating as Sink initiates” | 636 |
| Figure 8-53 “Data Role Swap with Wait, DFP operating as Sink initiates” | 639 |
| Figure 8-54 “Successful VCONN Source Swap, initiated by VCONN Source” | 642 |
| Figure 8-55 “Rejected VCONN Source Swap, initiated by VCONN Source” | 645 |
| Figure 8-56 “VCONN Source Swap with Wait, initiated by VCONN Source” | 648 |
| Figure 8-57 “VCONN Source Swap, initiated by non- VCONN Source” | 651 |
| Figure 8-58 “Rejected VCONN Source Swap, initiated by non- VCONN Source” | 654 |
| Figure 8-59 “VCONN Source Swap with Wait, initiated by non- VCONN Source” | 657 |
| Figure 8-60 “Source Alert to Sink” | 660 |
| Figure 8-61 “Sink Alert to Source” | 662 |
| Figure 8-62 “Sink Gets Source Status” | 664 |
| Figure 8-63 “Source Gets Sink Status” | 667 |
| Figure 8-64 “VCONN Source Gets Cable Plug Status” | 670 |
| Figure 8-65 “Sink Gets Source PPS Status” | 673 |
| Figure 8-66 “Sink Gets Source’s Capabilities” | 676 |
| Figure 8-67 “Dual-Role Source Gets Dual-Role Sink’s Capabilities as a Source” | 679 |
| Figure 8-68 “Source Gets Sink’s Capabilities” | 682 |
| Figure 8-69 “Dual-Role Sink Gets Dual-Role Source’s Capabilities as a Sink” | 685 |
| Figure 8-70 “Sink Gets Source’s EPR Capabilities” | 688 |
| Figure 8-71 “Dual-Role Source Gets Dual-Role Sink’s Capabilities as an EPR Source” | 691 |
| Figure 8-72 “Source Gets Sink’s EPR Capabilities” | 694 |
| Figure 8-73 “Dual-Role Sink Gets Dual-Role Source’s Capabilities as an EPR Sink” | 697 |
| Figure 8-74 “Sink Gets Source’s Extended Capabilities” | 700 |
| Figure 8-75 “Dual-Role Source Gets Dual-Role Sink’s Extended Capabilities” | 703 |
| Figure 8-76 “Source Gets Sink’s Extended Capabilities” | 706 |
| Figure 8-77 “Dual-Role Sink Gets Dual-Role Source’s Extended Capabilities” | 709 |
| Figure 8-78 “Sink Gets Source’s Battery Capabilities” | 712 |
| Figure 8-79 “Source Gets Sink’s Battery Capabilities” | 715 |
| Figure 8-80 “Sink Gets Source’s Battery Status” | 718 |
| Figure 8-81 “Source Gets Sink’s Battery Status” | 721 |
| Figure 8-82 “Source Gets Sink’s Port Manufacturer Information” | 724 |
| Figure 8-83 “Sink Gets Source’s Port Manufacturer Information” | 727 |
| Figure 8-84 “Source Gets Sink’s Battery Manufacturer Information” | 730 |
| Figure 8-85 “Sink Gets Source’s Battery Manufacturer Information” | 733 |
| Figure 8-86 “VCONN Source Gets Cable Plug’s Manufacturer Information” | 736 |
| Figure 8-87 “Source Gets Sink’s Country Codes” | 739 |
| Figure 8-88 “Sink Gets Source’s Country Codes” | 742 |
| Figure 8-89 “VCONN Source Gets Cable Plug’s Country Codes” | 745 |
| Figure 8-90 “Source Gets Sink’s Country Information” | 748 |
| Figure 8-91 “Sink Gets Source’s Country Information” | 751 |
| Figure 8-92 “VCONN Source Gets Cable Plug’s Country Information” | 754 |
| Figure 8-93 “Source Gets Sink’s Revision Information” | 757 |
| Figure 8-94 “Sink Gets Source’s Revision Information” | 760 |
| Figure 8-95 “VCONN Source Gets Cable Plug’s Revision Information” | 763 |
| Figure 8-96 “Sink Gets Source’s Information” | 766 |
| Figure 8-97 “Dual-Role Source Gets Dual-Role Sink’s Information as a Source” | 769 |
| Figure 8-98 “Source requests security exchange with Sink” | 772 |
| Figure 8-99 “Sink requests security exchange with Source” | 775 |
| Figure 8-100 “VCONN Source requests security exchange with Cable Plug” | 778 |
| Figure 8-101 “Source requests firmware update exchange with Sink” | 781 |

| | |
|---|-----|
| Figure 8-102 “Sink requests firmware update exchange with Source” | 784 |
| Figure 8-103 “VCONN Source requests firmware update exchange with Cable Plug” | 787 |
| Figure 8-104 “Initiator to Responder Discover Identity (ACK)” | 790 |
| Figure 8-105 “Initiator to Responder Discover Identity (NAK)” | 793 |
| Figure 8-106 “Initiator to Responder Discover Identity (BUSY)” | 796 |
| Figure 8-107 “Initiator to Responder Discover SVIDs (ACK)” | 799 |
| Figure 8-108 “Initiator to Responder Discover SVIDs (NAK)” | 802 |
| Figure 8-109 “Initiator to Responder Discover SVIDs (BUSY)” | 805 |
| Figure 8-110 “Initiator to Responder Discover Modes (ACK)” | 808 |
| Figure 8-111 “Initiator to Responder Discover Modes (NAK)” | 811 |
| Figure 8-112 “Initiator to Responder Discover Modes (BUSY)” | 814 |
| Figure 8-113 “DFP to UFP Enter Mode” | 817 |
| Figure 8-114 “DFP to UFP Exit Mode” | 820 |
| Figure 8-115 “DFP to Cable Plug Enter Mode” | 823 |
| Figure 8-116 “DFP to Cable Plug Exit Mode” | 826 |
| Figure 8-117 “Initiator to Responder Attention” | 829 |
| Figure 8-118 “BIST Carrier Mode Test” | 831 |
| Figure 8-119 “BIST Test Data Test” | 834 |
| Figure 8-120 “BIST Share Capacity Mode Test” | 838 |
| Figure 8-121 “UFP Entering USB4® Mode (Accept)” | 841 |
| Figure 8-122 “UFP Entering USB4® Mode (Reject)” | 844 |
| Figure 8-123 “UFP Entering USB4® Mode (Wait)” | 847 |
| Figure 8-124 “Cable Plug Entering USB4® Mode (Accept)” | 850 |
| Figure 8-125 “Cable Plug Entering USB4® Mode (Reject)” | 853 |
| Figure 8-126 “Cable Plug Entering USB4® Mode (Wait)” | 856 |
| Figure 8-127 “Unstructured VDM Message Sequence” | 859 |
| Figure 8-128 “VDEM Message Sequence” | 862 |
| Figure 8-129 “Outline of States” | 865 |
| Figure 8-130 “References to states” | 866 |
| Figure 8-131 “Example of state reference with conditions” | 866 |
| Figure 8-132 “Example of state reference with the same entry and exit” | 866 |
| Figure 8-133 “SenderResponseTimer Policy Engine State Diagram” | 868 |
| Figure 8-134 “Source Port State Diagram” | 870 |
| Figure 8-135 “Sink Port State Diagram” | 878 |
| Figure 8-136 “SOP Source Port Soft Reset and Protocol Error State Diagram” | 884 |
| Figure 8-137 “Sink Port Soft Reset and Protocol Error Diagram” | 886 |
| Figure 8-138 “DFP Data_Reset Message State Diagram” | 888 |
| Figure 8-139 “UFP Data_Reset Message State Diagram” | 891 |
| Figure 8-140 “Source Port Not Supported Message State Diagram” | 894 |
| Figure 8-141 “Sink Port Not Supported Message State Diagram” | 896 |
| Figure 8-142 “Source Port Ping State Diagram” | 898 |
| Figure 8-143 “Source Port Source Alert State Diagram” | 899 |
| Figure 8-144 “Sink Port Source Alert State Diagram” | 901 |
| Figure 8-145 “Sink Port Sink Alert State Diagram” | 902 |
| Figure 8-146 “Source Port Sink Alert State Diagram” | 904 |
| Figure 8-147 “Sink Port Get Source Capabilities Extended State Diagram” | 905 |
| Figure 8-148 “Source Give Source Capabilities Extended State Diagram” | 906 |
| Figure 8-149 “Source Port Get Sink Capabilities Extended State Diagram” | 907 |
| Figure 8-150 “Sink Give Sink Capabilities Extended State Diagram” | 908 |
| Figure 8-151 “Sink Port Get Source Information State Diagram” | 909 |
| Figure 8-152 “Source Give Source Information State Diagram” | 910 |

| | |
|--|-----|
| Figure 8-153 “Get Status State Diagram” | 911 |
| Figure 8-154 “Give Status State Diagram” | 912 |
| Figure 8-155 “Sink Port Get Source PPS Status State Diagram” | 913 |
| Figure 8-156 “Source Give Source PPS Status State Diagram” | 914 |
| Figure 8-157 “Get Battery Capabilities State Diagram” | 915 |
| Figure 8-158 “Give Battery Capabilities State Diagram” | 916 |
| Figure 8-159 “Get Battery Status State Diagram” | 917 |
| Figure 8-160 “Give Battery Status State Diagram” | 918 |
| Figure 8-161 “Get Manufacturer Information State Diagram” | 919 |
| Figure 8-162 “Give Manufacturer Information State Diagram” | 920 |
| Figure 8-163 “Get Country Codes State Diagram” | 921 |
| Figure 8-164 “Give Country Codes State Diagram” | 922 |
| Figure 8-165 “Get Country Information State Diagram” | 923 |
| Figure 8-166 “Give Country Information State Diagram” | 924 |
| Figure 8-167 “Get Revision State Diagram” | 925 |
| Figure 8-168 “Give Revision State Diagram” | 926 |
| Figure 8-169 “DFP Enter_USB Message State Diagram” | 927 |
| Figure 8-170 “UFP Enter_USB Message State Diagram” | 928 |
| Figure 8-171 “Send security request State Diagram” | 929 |
| Figure 8-172 “Send security response State Diagram” | 930 |
| Figure 8-173 “Security response received State Diagram” | 931 |
| Figure 8-174 “Send firmware update request State Diagram” | 932 |
| Figure 8-175 “Send firmware update response State Diagram” | 933 |
| Figure 8-176 “Firmware update response received State Diagram” | 934 |
| Figure 8-177: “DFP to UFP Data Role Swap State Diagram” | 935 |
| Figure 8-178: “UFP to DFP Data Role Swap State Diagram” | 938 |
| Figure 8-179: “Dual-Role Port in Source to Sink Power Role Swap State Diagram” | 941 |
| Figure 8-180: “Dual-role Port in Sink to Source Power Role Swap State Diagram” | 944 |
| Figure 8-181: “Dual-Role Port in Source to Sink Fast Role Swap State Diagram” | 947 |
| Figure 8-182: “Dual-role Port in Sink to Source Fast Role Swap State Diagram” | 950 |
| Figure 8-183 “Dual-Role (Source) Get Source Capabilities diagram” | 953 |
| Figure 8-184 “Dual-Role (Source) Give Sink Capabilities diagram” | 954 |
| Figure 8-185 “Dual-Role (Sink) Get Sink Capabilities State Diagram” | 955 |
| Figure 8-186 “Dual-Role (Sink) Give Source Capabilities State Diagram” | 956 |
| Figure 8-187 “Dual-Role (Source) Get Source Capabilities Extended State Diagram” | 956 |
| Figure 8-188 “Dual-Role (Sink) Give Source Capabilities Extended diagram” | 958 |
| Figure 8-189 “Dual-Role (Sink) Get Sink Capabilities Extended State Diagram” | 958 |
| Figure 8-190 “Dual-Role (Source) Give Sink Capabilities Extended diagram” | 959 |
| Figure 8-191 “Dual-Role (Source) Get Source Information State Diagram” | 960 |
| Figure 8-192 “Dual-Role (Source) Give Source Information diagram” | 961 |
| Figure 8-193 “VCONN Swap State Diagram” | 962 |
| Figure 8-194 “Initiator to Port VDM Discover Identity State Diagram” | 965 |
| Figure 8-195 “Initiator VDM Discover SVIDs State Diagram” | 967 |
| Figure 8-196 “Initiator VDM Discover Modes State Diagram” | 969 |
| Figure 8-197 “Initiator VDM Attention State Diagram” | 971 |
| Figure 8-198 “Responder Structured VDM Discover Identity State Diagram” | 972 |
| Figure 8-199 “Responder Structured VDM Discover SVIDs State Diagram” | 973 |
| Figure 8-200 “Responder Structured VDM Discover Modes State Diagram” | 974 |
| Figure 8-201 “Receiving a Structured VDM Attention State Diagram” | 975 |
| Figure 8-202 “DFP VDM Mode Entry State Diagram” | 976 |
| Figure 8-203 “DFP VDM Mode Exit State Diagram” | 978 |

| | |
|--|------|
| Figure 8-204 “UFP Structured VDM Enter Mode State Diagram” | 980 |
| Figure 8-205 “UFP Structured VDM Exit Mode State Diagram” | 982 |
| Figure 8-206 “Cable Ready State Diagram” | 984 |
| Figure 8-207 “Cable Plug Soft Reset State Diagram” | 985 |
| Figure 8-208 “Cable Plug Hard Reset State Diagram” | 986 |
| Figure 8-209 “DFP/VCONN Source Soft Reset or Cable Reset of a Cable Plug or VPD State Diagram” | 987 |
| Figure 8-210 “UFP/VCONN Source Soft Reset of a Cable Plug or VPD State Diagram” | 989 |
| Figure 8-211 “Source Startup Structured VDM Discover Identity State Diagram” | 991 |
| Figure 8-212 “Cable Plug Structured VDM Enter Mode State Diagram” | 993 |
| Figure 8-213 “Cable Plug Structured VDM Exit Mode State Diagram” | 995 |
| Figure 8-214 “Source EPR Mode Entry State Diagram” | 997 |
| Figure 8-215 “Sink EPR Mode Entry State Diagram” | 1000 |
| Figure 8-216 “Source EPR Mode Exit State Diagram” | 1002 |
| Figure 8-217 “Sink EPR Mode Exit State Diagram” | 1004 |
| Figure 8-218 “BIST Carrier Mode State Diagram” | 1006 |
| Figure 8-219 “BIST Test Mode State Diagram” | 1008 |
| Figure 8-220 “BIST Shared Capacity Test Mode State Diagram” | 1010 |
| Figure 9-1 “Example PD Topology” | 1022 |
| Figure 9-2 “Mapping of PD Topology to USB” | 1023 |
| Figure 9-3 “USB Attached to USB Powered State Transition” | 1024 |
| Figure 9-4 “Any USB State to USB Attached State Transition (When operating as a Consumer)” | 1025 |
| Figure 9-5 “Any USB State to USB Attached State Transition (When operating as a Provider)” | 1025 |
| Figure 9-6 “Any USB State to USB Attached State Transition (After a USB Type-C® Data Role Swap)” | 1026 |
| Figure 9-7 “Software stack on a PD aware OS” | 1026 |
| Figure 9-8 “Enumeration of a PDUSB Device” | 1027 |
| Figure 10-1 “SPR Source Power Rule Illustration for Fixed PDOs” | 1044 |
| Figure 10-2 “SPR Source Power Rule Example For Fixed PDOs” | 1045 |
| Figure 10-3 “Valid SPR AVS Operating Region for a Source advertising in the range of $27W < PDP \leq 45W$ ” | 1048 |
| Figure 10-4 “Valid SPR AVS Operating Region for a Source advertising in the range of $45W < PDP \leq 60W$ ” | 1049 |
| Figure 10-5 “Valid SPR AVS Operating Region for a Source advertising in the range of $60W < PDP \leq 100W$ ” | 1049 |
| Figure 10-6 “Valid EPR AVS Operating Region” | 1058 |
| Figure 10-7 “EPR Source Power Rule Illustration for Fixed PDOs” | 1059 |
| Figure B-1 “External Power supplied downstream” | 1066 |
| Figure B-2 External Power supplied upstream | 1070 |
| Figure B-3 “Giving Back Power” | 1076 |
| Figure D-1 “Circuit Block of BMC Finite Difference Receiver” | 1101 |
| Figure D-2 “BMC AC and DC noise from VBUS at Power Sink” | 1102 |
| Figure D-3 “Sample BMC Signals (a) without USB 2.0 SE0 Noise (b) with USB 2.0 SE0 Noise” | 1102 |
| Figure D-4 “Scaled BMC Signal Derivative with 50ns Sampling Rate” | 1103 |
| Figure D-5 “BMC Signal and Finite Difference Output with Various Time Steps” | 1103 |
| Figure D-6 “Output of Finite Difference in dash line and Edge Detector in solid line” | 1104 |
| Figure D-7 “Noise Zone and Detect Zone of BMC Receiver” | 1104 |
| Figure D-8 “Circuit Block of BMC Subtraction Receiver” | 1105 |
| Figure D-9 “(a) Output of LPF1 and LPF2 (b) Subtraction of LPF1 and LPF2 Output” | 1105 |
| Figure D-10 “Output of the BMC LPF1 in blue dash curve and the Subtractor in red solid curve” | 1106 |
| Figure E-1 “Example FRS Capable System” | 1107 |
| Figure E-2 “Slow V_{BUS} Discharge” | 1108 |
| Figure E-3 “Fast V_{BUS} Discharge” | 1109 |
| Figure E-4 “Sequence Diagram for slow V_{BUS} discharge (it discharges after FR_Swap message is sent)” | 1113 |
| Figure E-5 Sequence for Vbus discharges quickly (before FR_Swap message is sent) after adapter disconnected... .. | 1115 |

1. Introduction

USB has evolved from a data interface capable of supplying limited power to a primary provider of power with a data interface. Today many devices charge or get their power from USB ports contained in laptops, cars, aircraft or even wall sockets. USB has become a ubiquitous power socket for many small devices such as cell phones, MP3 players and other hand-held devices. Users need USB to fulfil their requirements not only in terms of data but also to provide power to, or charge, their devices simply, often without the need to load a driver, in order to carry out “traditional” USB functions.

There are, however, still many devices which either require an additional power connection to the wall, or exceed the USB rated current in order to operate. Increasingly, international regulations require better energy management due to ecological and practical concerns relating to the availability of power. Regulations limit the amount of power available from the wall which has led to a pressing need to optimize power usage. The USB Power Delivery Specification has the potential to minimize waste as it becomes a standard for charging devices that are not satisfied by [\[USBBC 1.2\]](#).

Wider usage of wireless solutions is an attempt to remove data cabling but the need for “tethered” charging remains. In addition, industrial design requirements drive wired connectivity to do much more over the same connector.

USB Power Delivery is designed to enable the maximum functionality of USB by providing more flexible power delivery along with data over a single cable. Its aim is to operate with and build on the existing USB ecosystem; increasing power levels from existing USB standards, for example Battery Charging, enabling new higher power use cases such as USB powered Hard Disk Drives (HDDs) and printers.

With USB Power Delivery the power direction is no longer fixed. This enables the product with the power (Host or Peripheral) to provide the power. For example, a display with a supply from the wall can power, or charge, a laptop. Alternatively, USB power bricks or chargers are able to supply power to laptops and other battery powered devices through their, traditionally power providing, USB ports.

USB Power Delivery enables hubs to become the means to optimize power management across multiple peripherals by allowing each device to take only the power it requires, and to get more power when required for a given application. For example, battery powered devices can get increased charging current and then give it back temporarily when the user’s HDD requires spinning up. **Optionally** the hubs can communicate with the PC to enable even more intelligent and flexible management of power either automatically or with some level of user intervention.

USB Power Delivery allows Low Power cases such as headsets to negotiate for only the power they require. This provides a simple solution that enables USB devices to operate at their optimal power levels.

The Power Delivery Specification, in addition to providing mechanisms to negotiate power also can be used as a side-band channel for standard and vendor defined messaging. Power Delivery enables alternative modes of operation by providing the mechanisms to discover, enter and exit Alternate Modes. The specification also enables discovery of cable capabilities such as supported speeds and current levels.

1.1 Overview

This specification defines how USB Devices can negotiate for more current and/or higher or lower Voltages over the USB cable (using the USB Type-C® CC wire as the communications channel) than are defined in the [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB4\]](#), [\[USB Type-C 2.3\]](#) or [\[USBBC 1.2\]](#) specifications. It allows Devices with greater power requirements than can be met with today’s specification to get the power they require to operate from V_{BUS} and negotiate with external power sources (e.g., Wall Warts). In addition, it allows a Source and Sink to swap power roles such that a Device could supply power to the Host. For example, a display could supply power to a notebook to charge its battery.

The USB Power Delivery Specification is guided by the following principles:

- Works seamlessly with legacy USB Devices
- Compatible with existing spec-compliant USB cables
- Minimizes potential damage from non-compliant cables (e.g., ‘Y’ cables etc.)
- Optimized for low-cost implementations.

This specification defines mechanisms to discover, enter and exit Modes defined either by a standard or by a particular vendor. These Modes can be supported either by the Port Partner or by a cable connecting the two Port Partners.

The specification defines mechanisms to discover the capabilities of cables which can communicate using Power Delivery.

This specification adds a mechanism to swap the data roles such that the upstream facing Port becomes the downstream facing Port and vice versa. It also enables a swap of the end supplying VCONN to a powered cable.

To facilitate optimum charging, the specification defines two mechanisms a USB Charger can Advertise for the Device to use:

- 1) A list of fixed Voltages each with a maximum current. The Device selects a Voltage and current from the list. This is the traditional model used by Devices that use internal electronics to manage the charging of their battery including modifying the Voltage and current actually supplied to the battery. The side-effect of this model is that the charging circuitry generates heat that can be problematic for small form factor devices.
- 2) A list of programmable Voltage ranges each with a maximum current (PPS). The Device requests a Voltage (in 20mV increments in SPR PPS Mode and in 100mV increments in EPR AVS Mode) that is within the Advertised range and a maximum current. The USB Charger delivers the requested Voltage until the maximum current is reached at which time the USB charger reduces its output Voltage so as not to supply more than the requested maximum current. During the high current portion of the charge cycle, the USB Charger can be directly connected (through an appropriate safety device) to the battery. This model is used by Devices that want to minimize the thermal impact of their internal charging circuitry.

1.2 Purpose

The USB Power Delivery specification defines a power delivery system covering all elements of a USB system including Hosts, Devices, Hubs, Chargers and cable assemblies. This specification describes the architecture, protocols, power supply behavior, connectors and cabling necessary for managing power delivery over USB at up to 100W. This specification is intended to be fully compatible and extend the existing USB infrastructure. It is intended that this specification will allow system OEMs, power supply and peripheral developers adequate flexibility for product versatility and market differentiation without losing backwards compatibility.

USB Power Delivery is designed to operate independently of the existing USB bus defined mechanisms used to negotiate power which are:

- [\[USB 2.0\]](#), [\[USB 3.2\]](#) in band requests for high power interfaces.
- [\[USBBC 1.2\]](#) mechanisms for supplying higher power (not mandated by this specification).
- [\[USB Type-C 2.3\]](#) mechanisms for supplying higher power.

Initial operating conditions remain the USB Default Operation as defined in [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 2.3\]](#) or [\[USBBC 1.2\]](#).

- The DFP sources *vSafe5V* over V_{BUS} .
- The UFP consumes power from V_{BUS} .

1.2.1 Scope

This specification is intended as an extension to the existing [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 2.3\]](#) and [\[USBBC 1.2\]](#) specifications. It addresses only the elements required to implement USB Power Delivery. It is targeted at power supply vendors, manufacturers of [\[USB 2.0\]](#), [\[USB 3.2\]](#), [\[USB Type-C 2.3\]](#) and [\[USBBC 1.2\]](#) Platforms, Devices and cable assemblies.

Normative information is provided to allow interoperability of components designed to this specification.

Informative information, when provided, illustrates possible design implementation.

1.3 Section Overview

This specification contains the following sections:

Table 1.1 Section Overview

| Section | Description |
|--|---|
| <i>Section 1 “Introduction”</i> | Introduction, conventions used in the document, list of terms and abbreviations, references, and details of parameter usage. |
| <i>Section 2 “Overview”</i> | Overview of the document including a description of the operation of PD and the architecture. |
| <i>Section 3 “USB Type-A and USB Type-B Cable Assemblies and Connectors”</i> | Mechanical and electrical characteristics of the cables and connectors used by PD. Section Deprecated . See [USBPD 2.0] for legacy PD connector specification. |
| <i>Section 4 “Electrical Requirements”</i> | Electrical requirements for Dead Battery operation and cable detection. |
| <i>Section 5 “Physical Layer”</i> | Details of the PD PHY Layer requirements |
| <i>Section 6 “Protocol Layer”</i> | Protocol Layer requirements including the Messages, timers, counters, and state operation. |
| <i>Section 7 “Power Supply”</i> | Power supply requirements for both Providers and Consumers. |
| <i>Section 8 “Device Policy”</i> | Device Policy Manager requirements. Policy Engine Message sequence diagrams and state diagrams |
| <i>Section 9 “States and Status Reporting”</i> | USBPD Device requirements including mapping of V_{BUS} to USB states. System Policy Manager requirements including descriptors, events, and requests. |
| <i>Section 10 “Power Rules”</i> | Rated Output Power definitions for PD. |
| <i>Appendix A “CRC calculation”</i> | Example CRC calculations. |
| <i>Appendix B “PD Message Sequence Examples”</i> | Scenarios illustrating Device Policy Manager operation. |
| <i>Appendix C “VDM Command Examples”</i> | Examples of Structured VDM usage. |
| <i>Appendix D “BMC Receiver Design Examples”</i> | BMC Receiver Design Examples. |
| <i>Appendix E “FRS System Level Example”</i> | FRS System Level Example. |

1.4 Conventions

1.4.1 Precedence

If there is a conflict between text, figures, and tables, the precedence **Shall** be tables, figures, and then text.

In there is a conflict between a generic statement and a more specific statement, the more specific statement **Shall** apply.

1.4.2 Keywords

The following keywords differentiate between the levels of requirements and options.

1.4.2.1 Conditional Normative

Conditional Normative is a keyword used to indicate a feature that is mandatory when another related feature has been implemented. Designers are mandated to implement all such requirements, when the dependent features have been implemented, to ensure interoperability with other compliant Devices.

1.4.2.2 Deprecated

Deprecated is a keyword used to indicate a feature, supported in previous releases of the specification, which is no longer supported.

1.4.2.3 Discarded

Discard, **Discards** and **Discarded** are equivalent keywords indicating that a Packet when received **Shall** be thrown away by the PHY Layer and not passed to the Protocol Layer for processing. No **GoodCRC** Message **Shall** be sent in response to the Packet.

1.4.2.4 Ignored

Ignore, **Ignores** and **Ignored** are equivalent keywords indicating Messages or Message fields which, when received, **Shall** result in no special action by the receiver. An **Ignored** Message **Shall** only result in returning a **GoodCRC** Message to acknowledge Message receipt. A Message with an **Ignored** field **Shall** be processed normally except for any actions relating to the **Ignored** field.

1.4.2.5 Informative

Informative is a keyword indicating text with no specific requirements, provided only to improve understanding.

1.4.2.6 Invalid

Invalid is a keyword when used in relation to a Packet indicates that the Packet's usage or fields fall outside of the defined specification usage. When **Invalid** is used in relation to an Explicit Contract it indicates that a previously established Explicit Contract which can no longer be maintained by the Source. When **Invalid** is used in relation to individual K-codes or K-code sequences indicates that the received Signaling falls outside of the defined specification.

1.4.2.7 May

May is a keyword that indicates a choice with no implied preference.

1.4.2.8 May Not

May Not is a keyword that is the inverse of **May**. Indicates a choice to not implement a given feature with no implied preference.

1.4.2.9 N/A

N/A is a keyword that indicates that a field or value is not applicable and has no defined value and **Shall Not** be checked or used by the recipient.

1.4.2.10 Optional/Optionally/Optional Normative

Optional, **Optionally** and **Optional Normative** are equivalent keywords that describe features not mandated by this specification. However, if an **Optional** feature is implemented, the feature **Shall** be implemented as defined by this specification.

1.4.2.10.1 Reserved

Reserved is a keyword indicating **Reserved** bits, bytes, words, fields, and code values that are set-aside for future standardization. Their use and interpretation **May** be specified by future extensions to this specification and **Shall Not** be utilized or adapted by vendor implementation. A **Reserved** bit, byte, word, or field **Shall** be set to zero by the sender and **Shall** be **Ignored** by the receiver. **Reserved** field values **Shall Not** be sent by the sender and **Shall** be **Ignored** by the receiver.

1.4.2.11 Shall/Normative

Shall and **Normative** are equivalent keywords indicating a mandatory requirement. Designers are mandated to implement all such requirements to ensure interoperability with other compliant Devices.

1.4.2.12 Shall Not

Shall Not is a keyword that is the inverse of **Shall** indicating non-compliant operation.

1.4.2.13 Should

Should is a keyword indicating flexibility of choice with a preferred alternative; equivalent to the phrase “it is recommended that...”.

1.4.2.14 Should Not

Should Not is a keyword is the inverse of **Should**; equivalent to the phrase “it is recommended that implementations do not...”.

1.4.2.15 Valid

Valid is a keyword that is the inverse of **Invalid** indicating either a Packet or Signaling that fall within the defined specification or an Explicit Contract that can be maintained by the Source.

1.4.3 Numbering

Numbers that are immediately followed by a lowercase "b" (e.g., 01b) are binary values. Numbers that are immediately followed by an uppercase "B" are byte values. Numbers that are immediately followed by a lowercase "h" (e.g., 3Ah) or are preceded by "0x" (e.g., 0xFF00) are hexadecimal values. Numbers not immediately followed by either a "b", "B", or "h" are decimal values.

1.5 Related Documents

Document references listed below are inclusive of all approved and published ECNs and Errata:

Table 1.2 Document References

| Bookmark Reference | Title | Revision and date |
|-----------------------------------|--|---|
| [DPTC2.1] | DisplayPort™ Alt Mode on USB Type-C® Standard www.vesa.org . | Version 2.1 2022-11 |
| [IEC 60950-1] | IEC 60950-1:2005 Information technology equipment – Safety – Part 1: General requirements: Amendment 1:2009, Amendment 2:2013. www.iec.ch . | 2005, 2009, 2013 |
| [IEC 60958-1] | IEC 60958-1:2021 Digital Audio Interface Part:1 General. www.iec.ch . | 2021-09-10 |
| [IEC 62368-1] | IEC 62368-1:2018 Audio/Video, information, and communication technology equipment – Part 1: Safety requirements. www.iec.ch . | 2018-10-04 |
| [IEC 62368-3] | IEC 62368-3:2017 Audio/video, information, and communication technology equipment - Part 3: Safety aspects for DC power transfer through communication cables and ports www.iec.ch . | 2017-12-07 |
| [IEC 63002] | IEC 63002:2021 Interoperability specifications and communication method for external power supplies used with computing and consumer electronics devices www.iec.ch . | 2021-05-27 |
| [ISO 3166] | ISO 3166 international Standard for country codes and codes for their subdivisions. http://www.iso.org/iso/home/standards/country_codes.htm . | |
| [TBT3] | see [USB4] Chapter 13 for Thunderbolt™ 3 device operation. | |
| [UCSI] | USB Type-C® Connector System Software Interface (UCSI) Specification https://www.usb.org/documents . | 2023-06-23 |
| [USB 2.0] | Universal Serial Bus 2.0 Specification, , https://www.usb.org/documents . | Revision 2.0 |
| [USB 3.2] | Universal Serial Bus 3.2 Specification https://www.usb.org/documents . | Revision 1.1 June 2022 |
| [USB Type-C 2.3] | Universal Serial Bus Type-C® Cable and Connector Specification, https://www.usb.org/documents . | Release 2.3 October 2023 |
| [USB4] | Universal Serial Bus 4 Specification (USB4®), https://www.usb.org/documents . | Version 2.0 October 2022 |
| [USBBC 1.2] | Universal Serial Bus Battery Charging Specification plus Errata (referred to in this document as the Battery Charging specification). https://www.usb.org/documents . | Revision 1.2 |
| [USBPD 2.0] | Universal Serial Bus Power Delivery Specification, https://www.usb.org/documents . | Revision 2 Version 1.2 March 25, 2016 |
| [USBPDCompliance] | USB Power Delivery Compliance Test Specification, https://www.usb.org/documents . | Revision Q2, 2023 OR April 2023 |

| | | |
|--|--|----------------------------------|
| <i>[USBPD Firmware Update 1.0]</i> | Universal Serial Bus Power Delivery Firmware Update Specification, https://www.usb.org/documents . | Revision 1.0, September 15, 2016 |
| <i>[USB Type-C Authentication 1.0]</i> | Universal Serial Bus Type-C® Authentication Specification, https://www.usb.org/documents . | Revision 1.0, March 25, 2016 |
| <i>[USB Type-C Bridge 1.1]</i> | Universal Serial Bus Type-C® Bridge Specification, https://www.usb.org/documents . | Revision 1.1 September 2017 |

koniec náhľadu – text ďalej pokračuje v platenej verzii STN