

STN	Stanovenie intenzity vysokofrekvenčných polí, hustoty výkonu a špecifickej miery absorpcie (SAR) v okolí rádiokomunikačných základňových staníc na účely hodnotenia expozície osôb	STN EN IEC 62232 36 7087
------------	---	--

Determination of RF field strength, power density and SAR in the vicinity of base stations for the purpose of evaluating human exposure

Táto norma obsahuje anglickú verziu európskej normy.
This standard includes the English version of the European Standard.

Táto norma bola oznámená vo Vestníku ÚNMS SR č. 08/25

Obsahuje: EN IEC 62232:2025, IEC 62232:2025

Oznámením tejto normy sa od 30.06.2028 ruší
STN EN IEC 62232 (36 7087) z februára 2023

140923



EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN IEC 62232

June 2025

ICS 13.280; 17.240

Supersedes EN IEC 62232:2022

English Version

**Determination of RF field strength, power density and SAR in the vicinity of base stations for the purpose of evaluating human exposure
(IEC 62232:2025)**

Détermination de l'intensité du champ de radiofréquences, de la densité de puissance et du DAS à proximité des stations de base dans le but d'évaluer l'exposition humaine
(IEC 62232:2025)

Bestimmung der HF-Feldstärke, der Leistungsdichte und der spezifischen Absorptionsrate (SAR) in der Nachbarschaft von Funkkommunikations-Basisstationen zur Ermittlung der menschlichen Exposition
(IEC 62232:2025)

This European Standard was approved by CENELEC on 2025-06-03. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN IEC 62232:2025 (E)**European foreword**

The text of document 106/626/CDV, future edition 4 of IEC 62232, prepared by TC 106 "Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62232:2025.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2026-06-30 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2028-06-30 document have to be withdrawn

This document supersedes EN IEC 62232:2022 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 62232:2025 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

- | | |
|-------------------|---|
| ISO/IEC 17025 | NOTE Approved as EN ISO/IEC 17025 |
| CISPR 16-4-2:2011 | NOTE Approved as EN 55016-4-2:2011 (not modified) |

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC/IEEE 62209-1528	-	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-worn wireless communication devices - Part 1528: Human models, instrumentation and procedures (Frequency range of 4 MHz to 10 GHz)	EN IEC/IEEE 62209-1528	-
IEC 62209-3	-	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)	EN IEC 62209-3	-
IEC 62311	-	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz to 300 GHz)	EN IEC 62311	-
IEC 62479	-	Assessment of the compliance of low-power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)	EN 62479	-
IEC/IEEE 62704-1	-	Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz - Part 1: General requirements for using the finite difference time-domain (FDTD) method for SAR calculations	-	-

EN IEC 62232:2025 (E)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC/IEEE 62704-2	-	Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz - Part 2: Specific requirements for finite difference time domain (FDTD) modelling of exposure from vehicle mounted antennas	-	-
IEC/IEEE 62704-3	-	Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz - Part 3: Specific requirements for using the finite difference time domain (FDTD) method for SAR calculations of mobile phones	-	-
IEC/IEEE 62704-4	-	Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communication devices, 30 MHz to 6 GHz - Part 4: General requirements for using the finite element method for SAR calculations	-	-
IEC/IEEE 63195-1	-	Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz) - Part 2: Computational procedure	EN IEC/IEEE 63195-1	-
IEC/IEEE 63195-2	-	Évaluation de la densité de puissance de l'exposition humaine aux champs radiofréquences provenant de dispositifs sans fil à proximité immédiate de la tête et du corps (plage de fréquences de 6 GHz à 300 GHz) - Partie 2: Procédure de calcul	EN IEC/IEEE 63195-2	-



IEC 62232

Edition 4.0 2025-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Determination of RF field strength, power density and SAR in the vicinity of base stations for the purpose of evaluating human exposure

Détermination de l'intensité du champ de radiofréquences, de la densité de puissance et du DAS à proximité des stations de base dans le but d'évaluer l'exposition humaine

**THIS PUBLICATION IS COPYRIGHT PROTECTED****Copyright © 2025 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -**webstore.iec.ch/advsearchform**

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



IEC 62232

Edition 4.0 2025-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Determination of RF field strength, power density and SAR in the vicinity of base stations for the purpose of evaluating human exposure

Détermination de l'intensité du champ de radiofréquences, de la densité de puissance et du DAS à proximité des stations de base dans le but d'évaluer l'exposition humaine

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 13.280, 17.240

ISBN 978-2-8327-0316-8

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	16
INTRODUCTION	18
1 Scope.....	19
2 Normative references	20
3 Terms and definitions.....	21
4 Symbols and abbreviated terms	37
4.1 Physical quantities.....	37
4.2 Constants	37
4.3 Abbreviated terms.....	38
5 How to use this document.....	41
5.1 Quick start guide	41
5.2 RF evaluation purpose categories	43
5.3 Implementation case studies.....	43
6 Evaluation processes for product compliance, product installation compliance and in-situ RF exposure assessments	43
6.1 Evaluation process for product compliance.....	43
6.1.1 General.....	43
6.1.2 Establishing compliance boundaries	44
6.1.3 Iso-surface compliance boundary definition	44
6.1.4 Simple compliance boundaries	44
6.1.5 Methods for establishing the compliance boundary	46
6.1.6 Uncertainty.....	50
6.1.7 Reporting for product compliance	51
6.2 Evaluation process used for product installation compliance	52
6.2.1 General.....	52
6.2.2 General evaluation procedure for product installations	52
6.2.3 Product installation compliance based on the actual maximum transmitted power or EIRP	53
6.2.4 Product installation data collection.....	57
6.2.5 Simplified product installation evaluation process.....	57
6.2.6 Assessment area selection	61
6.2.7 Measurements.....	62
6.2.8 Computations	64
6.2.9 Uncertainty.....	65
6.2.10 Reporting for product installation compliance	65
6.3 In-situ RF exposure evaluation or assessment process.....	66
6.3.1 General.....	66
6.3.2 In-situ measurement process	66
6.3.3 Site analysis.....	67
6.3.4 Case A evaluation	68
6.3.5 Case B evaluation	68
6.3.6 Uncertainty.....	69
6.3.7 Reporting	69
6.4 Averaging procedures	70
6.4.1 Spatial averaging.....	70
6.4.2 Time averaging.....	70
7 Determining the evaluation method.....	70

7.1	Overview	70
7.2	Process to determine the evaluation method	70
7.2.1	General.....	70
7.2.2	Establishing the evaluation points in relation to the source-environment plane	71
7.2.3	Exposure metric selection	73
8	Evaluation methods	74
8.1	General	74
8.2	Measurement methods	74
8.2.1	General.....	74
8.2.2	RF field strength and power density measurements	75
8.2.3	SAR measurements	76
8.3	Computation methods	76
8.4	Methods for assessment based on actual maximum approach	78
8.4.1	General requirements.....	78
8.4.2	Actual transmitted power or EIRP monitoring	79
8.4.3	Actual transmitted power or EIRP control	79
8.5	Methods for the assessment of RF exposure to multiple sources	80
8.6	Methods for establishing the BS transmitted power or EIRP	82
9	Uncertainty	82
10	Reporting.....	83
10.1	General requirements.....	83
10.2	Report format.....	83
10.3	Opinions and interpretations	84
Annex A (informative) Source-environment plane and guidance on the evaluation method selection		85
A.1	Guidance on the source-environment plane.....	85
A.1.1	General.....	85
A.1.2	Source-environment plane example	85
A.1.3	Source regions	86
A.2	Select between computation or measurement approaches	92
A.3	Select measurement method.....	93
A.3.1	Selection stages	93
A.3.2	Selecting between RF field strength, power density and SAR measurement approaches.....	93
A.3.3	Selecting between broadband and frequency selective measurement	94
A.3.4	Selecting RF field strength measurement procedures	95
A.4	Select computation method.....	96
A.5	Additional considerations.....	97
A.5.1	Simplicity	97
A.5.2	Evaluation method ranking.....	97
A.5.3	Applying multiple methods for RF exposure evaluation	97
Annex B (normative) Evaluation methods		98
B.1	Overview	98
B.2	General	98
B.2.1	Coordinate systems and reference points	98
B.2.2	Variables	99
B.3	RF exposure evaluation principles	100
B.3.1	Simple calculation of RF field strength and power density	100

B.3.2	Measurement of RF field strength and power density	104
B.3.3	Spatial averaging	106
B.3.4	Time averaging	109
B.3.5	Comparing measured and computed values	111
B.3.6	Personal RF monitors	111
B.4	RF field strength and power density measurements	111
B.4.1	Applicability of RF field strength and power density measurements	111
B.4.2	In-situ RF exposure measurements	111
B.4.3	Laboratory based RF field strength and power density measurements	123
B.4.4	RF field strength and power density measurement uncertainty	133
B.5	SAR measurements	138
B.5.1	Overview of SAR measurements	138
B.5.2	SAR measurement requirements	138
B.5.3	SAR measurement description	140
B.5.4	SAR measurement uncertainty	146
B.6	Basic computation methods	148
B.6.1	General	148
B.6.2	Basic computation formulas for RF field strength or power density evaluation	149
B.6.3	Basic wbSAR and psSAR evaluation formulas	155
B.6.4	Basic compliance boundary assessment method for BS using parabolic dish antennas	162
B.6.5	Basic compliance boundary assessment method for intentionally radiating cables	165
B.7	Advanced computation methods	166
B.7.1	General	166
B.7.2	Synthetic model and ray tracing algorithms	166
B.7.3	Full wave RF exposure computation	173
B.7.4	Full wave SAR computation	182
B.8	Extrapolation from the evaluated values to the maximum or actual values	187
B.8.1	Extrapolation method	187
B.8.2	Extrapolation to maximum in-situ RF field strength or power density using broadband measurements	189
B.8.3	Extrapolation to maximum in-situ RF field strength / power density using frequency or code selective measurements	189
B.8.4	Influence of traffic in real operating network	190
B.8.5	Extrapolation for massive MIMO and beamforming BS	191
B.8.6	Maximum exposure extrapolation with dynamic spectrum sharing (DSS)	193
B.9	Guidance for implementing the actual maximum approach	194
B.9.1	BS actual EIRP evaluation assumptions	194
B.9.2	Technology duty-cycle factor description	195
B.9.3	CDF evaluation using modelling studies	197
B.9.4	CDF evaluation using measurement studies on operational BS sites	198
B.9.5	Actual transmitted power or EIRP monitoring counters	200
B.9.6	Configurations with multiple transmitters	200
B.10	Transmitted power or EIRP evaluation	202
B.10.1	General	202
B.10.2	Measurement of the transmitted power in conducted mode	202
B.10.3	Measurement of the transmitted power in OTA conditions	203
B.10.4	Measurement of the EIRP in OTA and laboratory conditions	203

B.10.5	Measurement of the EIRP in OTA and in-situ conditions.....	204
Annex C (informative) Guidelines for the validation of power or EIRP control features and monitoring counter(s) related to the actual maximum approach		
C.1	Overview	205
C.2	Guidelines for validating control feature(s) and monitoring counters.....	205
C.3	Validation of power or EIRP monitoring counter in laboratory conditions	206
C.3.1	Validation of power or EIRP monitoring counter in conducted mode – test procedure	206
C.3.2	Validation of power or EIRP monitoring counter in OTA mode – test procedure	208
C.3.3	Validation of control feature(s) in laboratory conditions	211
C.3.4	Validation of control features using in-situ measurements	214
C.4	Validation test report.....	216
C.5	Case studies	217
C.5.1	Case study A – In-situ validation.....	217
C.5.2	Case study B – In-situ validation.....	221
C.5.3	Case study C – In-situ validation	224
Annex D (informative) Rationale supporting simplified product installation criteria		
D.1	General	230
D.2	Class E2.....	230
D.3	Class E10	231
D.4	Class E100	232
D.5	Class E+.....	234
D.6	Simplified formulas for millimetre-wave antennas using massive MIMO or beam steering	235
Annex E (informative) Technology-specific exposure evaluation guidance		
E.1	Overview to guidance on specific technologies	237
E.2	Summary of technology-specific information	237
E.3	Guidance on spectrum analyser settings	238
E.3.1	Overview of spectrum analyser settings.....	238
E.3.2	Detection algorithms	239
E.3.3	Resolution bandwidth and channel power processing	239
E.3.4	Integration per service.....	242
E.4	Stable transmitted power signals	242
E.4.1	TDMA/FDMA technology.....	242
E.4.2	WCDMA/UMTS technology	243
E.4.3	OFDM technology	244
E.5	WCDMA measurement and calibration using a code domain analyser	244
E.5.1	WCDMA measurements – General.....	244
E.5.2	WCDMA decoder characteristics.....	244
E.5.3	Calibration	245
E.6	Wi-Fi measurements	247
E.6.1	General.....	247
E.6.2	Integration time for reproducible measurements	248
E.6.3	Channel occupation.....	248
E.6.4	Some considerations	249
E.6.5	Measurement configuration and steps	249
E.6.6	Influence of the application layers.....	250
E.6.7	Power control	250

E.7	LTE measurements.....	251
E.7.1	Overview.....	251
E.7.2	LTE transmission modes.....	251
E.7.3	LTE-FDD frame structure.....	252
E.7.4	LTE-TDD frame structure.....	253
E.7.5	Maximum LTE exposure evaluation.....	255
E.7.6	Instantaneous LTE exposure evaluation	260
E.7.7	MIMO multiplexing of LTE BS.....	260
E.8	NR BS measurements	261
E.8.1	General.....	261
E.8.2	Maximum NR exposure evaluation	261
E.9	Establishing compliance boundaries using numerical simulations of MIMO array antennas emitting correlated waveforms	270
E.9.1	General.....	270
E.9.2	Field combining near base stations for correlated exposure with the purpose of establishing compliance boundaries.....	271
E.9.3	Numerical simulations of MIMO array antennas with densely packed columns	272
E.9.4	Numerical simulations of large MIMO array antennas.....	272
E.10	Massive MIMO antennas	273
E.10.1	Overview.....	273
E.10.2	Deterministic conservative approach.....	273
E.10.3	Statistical conservative approach.....	273
E.10.4	Example approaches	274
Annex F (informative)	Guidelines for the assessment of BS compliance with ICNIRP- 2020 brief exposure limits	291
F.1	General	291
F.2	Brief exposure limits	291
F.3	Implications of brief exposure limits on signal modulation and TDD duty cycle	293
F.4	Implications of brief exposure limits on the actual maximum approach	293
Annex G (informative)	Uncertainty.....	298
G.1	Background.....	298
G.2	Requirement to estimate uncertainty.....	298
G.3	How to estimate uncertainty.....	299
G.4	Guidance on uncertainty and assessment schemes.....	299
G.4.1	General.....	299
G.4.2	Overview of assessment schemes	299
G.4.3	Examples of assessment schemes.....	300
G.4.4	Assessment schemes and compliance probabilities	303
G.5	Guidance on uncertainty.....	305
G.5.1	Overview.....	305
G.5.2	Measurement uncertainty and confidence levels.....	306
G.6	Applying uncertainty for compliance assessments.....	307
G.7	Example influence quantities for field measurements.....	308
G.7.1	General.....	308
G.7.2	Calibration uncertainty of measurement antenna or field probe	308
G.7.3	Frequency response of the measurement antenna or field probe.....	308
G.7.4	Isotropy of the measurement antenna or field probe	310
G.7.5	Frequency response of the spectrum analyser	310

G.7.6	Temperature response of a broadband field probe.....	310
G.7.7	Linearity deviation of a broadband field probe	311
G.7.8	Mismatch uncertainty	311
G.7.9	Deviation of the experimental source from numerical source.....	311
G.7.10	Meter fluctuation uncertainty for time-varying signals.....	311
G.7.11	Uncertainty due to power variation in the RF source	312
G.7.12	Uncertainty due to field gradients	312
G.7.13	Mutual coupling between measurement antenna or isotropic probe and object	313
G.7.14	Uncertainty due to field scattering from the surveyor's body	314
G.7.15	Measurement device	316
G.7.16	Fields out of measurement range.....	316
G.7.17	Noise.....	317
G.7.18	Integration time.....	317
G.7.19	Power chain	317
G.7.20	Positioning system	317
G.7.21	Matching between probe and the EUT.....	317
G.7.22	Drifts in output power of the EUT, probe, temperature, and humidity	317
G.7.23	Perturbation by the environment.....	317
G.8	Example influence quantities for RF field strength computations by ray tracing or full wave methods	318
G.8.1	General.....	318
G.8.2	System	318
G.8.3	Technique uncertainties.....	319
G.8.4	Environmental uncertainties	319
G.9	Influence quantities for SAR measurements	320
G.9.1	General.....	320
G.9.2	Post-processing.....	320
G.9.3	EUT holder.....	320
G.9.4	EUT positioning	321
G.9.5	Phantom shell uncertainty.....	322
G.9.6	SAR correction depending on target liquid permittivity and conductivity	322
G.9.7	Liquid permittivity and conductivity measurements	323
G.9.8	Liquid temperature	323
G.10	Influence quantities for SAR calculations.....	323
G.11	Spatial averaging.....	323
G.11.1	General.....	323
G.11.2	Small-scale fading variations.....	324
G.11.3	Error on the estimation of local average power density	324
G.11.4	Characterization of environment statistical properties	325
G.11.5	Characterization of different spatial averaging schemes.....	326
G.12	Influence of human body on measurements of the electric RF field strength.....	330
G.12.1	Simulations of the influence of human body on measurements based on the method of moments (surface equivalence principle)	330
G.12.2	Comparison with measurements	332
G.12.3	Conclusions	333
Annex H (informative)	Guidance on comparing evaluated parameters with a limit value.....	334
H.1	Overview	334
H.2	Information recommended to compare evaluated value against limit value.....	334

H.3 Performing a limit comparison at a given confidence level.....	334
H.4 Performing a limit comparison using a process-based assessment scheme	335
Bibliography.....	336
Figure 1 – Quick start guide to the evaluation process.....	41
Figure 2 – Example of iso-surface compliance boundary.....	44
Figure 3 – Example of cylindrical and half-pipe compliance boundaries.....	45
Figure 4 – Example of box shaped compliance boundary.....	46
Figure 5 – Example of truncated box shaped compliance boundary	46
Figure 6 – Example illustrating the linear scaling procedure.....	47
Figure 7 – Example of massive MIMO antenna and corresponding beams and envelope patterns.....	49
Figure 8 – Example of compliance boundary shape for BS antennas with beam steering.....	50
Figure 9 – Example of dish antenna compliance boundary.....	50
Figure 10 – Flowchart describing the product installation evaluation process	53
Figure 11 – Example of a CDF curve representing the normalized actual transmitted power or EIRP.....	55
Figure 12 – Flow chart for product installation compliance based on the actual maximum transmitted power or EIRP threshold(s).....	56
Figure 13 – Simplified compliance assessment process using installation classes.....	58
Figure 14 – Example of DI within a square-shaped assessment domain boundary (ADB) with dimension L_{ADB}	62
Figure 15 – In-situ RF exposure evaluation or assessment process flow chart	67
Figure 16 – Source-environment plane concept	72
Figure 17 – Flow chart of the measurement methods.....	75
Figure 18 – Flow chart of the relevant computation methods.....	77
Figure 19 – Example of segments used for monitoring and control of BS using mMIMO or beam steering	79
Figure A.1 – Example source-environment plane regions near a base station antenna on a tower	85
Figure A.2 – Example source-environment plane regions near a roof-top antenna that has a narrow vertical (elevation plane) beamwidth (not to scale)	86
Figure A.3 – Geometry of an antenna with largest linear dimension L_{eff} and largest end dimension L_{end}	87
Figure A.4 – Maximum path difference for an antenna with largest linear dimension L	91
Figure B.1 – Cartesian, cylindrical and spherical coordinate systems relative to the BS antenna (view from the rear panel).....	99
Figure B.2 – Typical RF exposure assessment case.....	101
Figure B.3 – Reflection due to the presence of a ground plane.....	102
Figure B.4 – Reflections due to the presence of internal walls of the housing and surrounding asphalt and soil configuring a base station installed underground.....	103
Figure B.5 – General representation of RF field strength or power density measurements	104
Figure B.6 – Practical examples of measurement equipment installation	105

Figure B.7 – Spatial averaging schemes relative to walking or standing surface and in the vertical plane oriented to offer maximum area in the direction of the source being evaluated	107
Figure B.8 – Spatial averaging relative to spatial-peak field strength point height.....	109
Figure B.9 – Evaluation points	121
Figure B.10 – Relationship of separation of remote radio source and evaluation area to separation of evaluation points	122
Figure B.11 – Outline of the surface scanning methodology	125
Figure B.12 – Block diagram of the antenna measurement system.....	126
Figure B.13 – Minimum radius constraint, where a denotes the minimum radius of a sphere, centred at the reference point, that encompasses the EUT.....	127
Figure B.14 – Maximum angular sampling spacing constraint.....	127
Figure B.15 – Outline of the volume/surface scanning methodology.....	130
Figure B.16 – Block diagram of typical near-field EUT measurement system.....	131
Figure B.17 – Examples of positioning of the EUT relative to the relevant phantom	138
Figure B.18 – Phantom liquid volume and measurement volume used for wbSAR measurements with the box-shaped phantoms.....	145
Figure B.19 – Reference frame employed for cylindrical formulas for RF field strength computation at a point P (left), and on a line perpendicular to boresight (right)	149
Figure B.20 – Views illustrating the three valid zones for field strength computation around an antenna	151
Figure B.21 – Enclosed cylinder around collinear array antennas, with and without electrical downtilt.....	152
Figure B.22 – Spherical formulas reference results	155
Figure B.23 – Cylindrical formulas reference results.....	155
Figure B.24 – Directions for which SAR estimation expressions are provided.....	156
Figure B.25 – Description of SAR estimation formulas physical parameters	157
Figure B.26 – Flow chart for the simplified assessment of RF compliance boundary in the line of sight of a parabolic dish antenna.....	164
Figure B.27 – Radiating cable geometry.....	165
Figure B.28 – Synthetic model and ray tracing algorithms geometry and parameters	169
Figure B.29 – Line 4 far-field positions for synthetic model and ray tracing validation example	171
Figure B.30 – Antenna parameters for synthetic model and ray tracing algorithms validation example.....	172
Figure B.31 – Generic 900 MHz BS antenna with nine dipole radiators.....	179
Figure B.32 – Line 1, 2 and 3 near-field positions for full wave and ray tracing validation.....	180
Figure B.33 – Generic 1 800 MHz BS antenna with five slot radiators	181
Figure B.34 – BS antenna placed in front of a multi-layered lossy cylinder.....	187
Figure B.35 – Time variation over 24 h of the exposure induced by NR, GSM and FM, each normalized to the mean value	191
Figure B.36– Generic structure of a base station transmitted RF signal frame.....	196
Figure B.37 – Example of setup for the direct power level measurement for BS equipped with direct access conducted output ports.....	203
Figure C.1 – Example of a laboratory test setup for validation of an actual power control feature intended for use with a 5G BS.....	212

Figure C.2 – Example of a test setup for validation of an actual power control feature implemented in a 5G BS.....	215
Figure C.3 – Ground based in-situ validation setup	219
Figure C.4 – In-situ validation measurement setup near the general public compliance boundary in front of the 5G massive MIMO antenna (bore sight position).....	219
Figure C.5 – Comparison between measured time-averaged EMF and power control feature (5G counter data) for the ground-based measurements	220
Figure C.6 – Measured exposure adaptation in time expressed as a percentage of ICNIRP exposure limits [1], [2] for the measurements near the general public compliance boundary	221
Figure C.7 – Overview of the measurement site.....	223
Figure C.8 – Ground view of the validation site and measurement setup, located 60 m from the 5G BS, in the line of sight.....	223
Figure C.9 – Power transmitted by the massive MIMO antenna (top trace), channel power (ChP) measurements (middle trace) and transmitted resource blocks (RBs) (bottom trace)	224
Figure C.10 – Overview of the test platform.....	225
Figure C.11 – Example of synthetic model simulation of the test area	225
Figure C.12 – Examples of traffic load profiles.....	226
Figure C.13 – Example of testing in different segments in the test area.....	227
Figure C.14 – Results of the monitoring validation and baseline test in phase 1	227
Figure C.15 – Example of power density measurements and power density derived from counters.....	228
Figure C.16 – Measured power density and power density derived from counters.....	228
Figure C.17 – Comparisons of both counters and measurements.....	229
Figure D.1 – Measured ER as a function of distance for a BS ($G = 5$ dBi, $f = 2100$ MHz) transmitting with an EIRP of 2 W (installation class E2) and 10 W (installation class E10)	230
Figure D.2 – Minimum installation height as a function of transmitting power corresponding to installation class E10	231
Figure D.3 – Compliance distance in the main lobe as a function of EIRP established in accordance with the far-field formula corresponding to installation class E100	232
Figure D.4 – Minimum installation height as a function of transmitting power corresponding to installation class E100	233
Figure D.5 – Averaged power density at ground level for various installation configurations of equipment with 100 W EIRP (installation class E100)	234
Figure D.6 – Compliance distance in the main lobe CD_m as a function of EIRP established in accordance with the far-field formula corresponding to installation class E+	235
Figure D.7 – Minimum installation height h_m as a function of EIRP corresponding to installation class E+	235
Figure D.8 – Power density distribution in watts per square metre in a vertical cut plane for an 8×8 antenna array at 28 GHz (grid step of 10 cm).....	236
Figure D.9 – Power density distribution in watts per square metre in a vertical cut plane for an 8×8 antenna array at 39 GHz (grid step of 10 cm).....	236
Figure E.1 – Spectral occupancy for GMSK.....	240
Figure E.2 – Spectral occupancy for CDMA.....	241
Figure E.3 – Channel allocation for a WCDMA signal	244
Figure E.4 – Example of Wi-Fi frames.....	247

Figure E.5 – Channel occupation versus the integration time for IEEE 802.11b standard	248
Figure E.6 – Channel occupation versus nominal throughput rate for IEEE 802.11b/g standards	249
Figure E.7 – Wi-Fi spectrum trace snapshot	249
Figure E.8 – Frame structure of transmission signal for LTE-FDD downlink	253
Figure E.9 – Frame structure LTE-TDD type 2 (for 5 ms switch-point periodicity)	254
Figure E.10 – Frame structure of transmission signal for LTE-TDD	254
Figure E.11 – LTE-TDD PBCH measurement example.....	256
Figure E.12 – Example of VBW setting for LTE-FDD and LTE-TDD to avoid underestimation.....	258
Figure E.13 – Examples of received waves from LTE-FDD downlink signals using a spectrum analyser using zero span mode.....	259
Figure E.14 – LTE-TDD PBCH measurement example spectrum analyser using zero span mode.....	259
Figure E.15 – Example of VBW setting for NR to avoid underestimation.....	263
Figure E.16 – Examples of measurement accuracy results according to the ratio of VBW and RBW for NR SCS 30 kHz and 1 MHz RBW using various SA types (A to D).....	264
Figure E.17 – Waterfall reconstruction plot of a 1 s long measurement trace of an NR signal with subcarrier spacing (SCS) 30 kHz (along one component of the electric field)	264
Figure E.18 – Example of NR signal frame measured on SA with SSB signal above PDSCH (data).....	265
Figure E.19 – Example of NR signal frame measured on SA with SSB signal below or equal to PDSCH (data).....	266
Figure E.20 – Time gating of SS burst signal.....	266
Figure E.21 – Representation of the channel bandwidth (CBW).....	267
Figure E.22 – An example for one port CSI-RS beam design.....	269
Figure E.23 – Plan view representation of statistical conservative model.....	275
Figure E.24 – Binomial cumulative probability function for $N = 24$, $PR = 0,125$	283
Figure E.25 – Binomial cumulative probability function for $N = 18$, $PR = 2/7$	284
Figure E.26 – Binomial cumulative probability function for $N = 100$, $PR = 0,125$	288
Figure E.27 – Binomial cumulative probability function for $N = 82$, $PR = 2/7$	288
Figure F.1 – Limits for brief exposure ($t < 360$ s), see Table F.1, divided by the corresponding time interval t and normalized with the value obtained for t up to 360 s.....	292
Figure F.2 – F_{PR_min} as a function of the pulse duration assuming a whole-body averaging time of 30 min	296
Figure F.3 – F_{PR_min} as a function of the pulse duration assuming an averaging time of 6 min.....	296
Figure G.1 – Examples of general assessment schemes	301
Figure G.2 – Target uncertainty scheme overview.....	302
Figure G.3 – Probability of the true value being above (respectively below) the evaluated value depending on the confidence level assuming a normal distribution	306
Figure G.4 – Plot of the calibration factors for E (not E^2) provided from an example calibration report for an electric field probe	309
Figure G.5 – Computational model used for the variational analysis of reflected RF fields from the front of a surveyor	315

Figure G.6 – EUT positioning equipment and different positioning errors	321
Figure G.7 – Physical model of small-scale fading variations	323
Figure G.8 – Example of electric field strength variations in line of sight of an antenna operating at 2,2 GHz.....	324
Figure G.9 – Error at 95 % on average power estimation	325
Figure G.10 – 343 measurement points building a cube (centre) and different templates consisting of a different number of positions	326
Figure G.11 – Moving a template (Line 3) through the cube	327
Figure G.12 – Standard deviations for GSM 900, DCS 1800 and UMTS	329
Figure G.13 – Simulation arrangement.....	331
Figure G.14 – Body influence.....	331
Figure G.15 – Simulation arrangement.....	332
 Table 1 – Quick start guide evaluation steps	 42
Table 2 – Example of product installation classes where a simplified evaluation process is applicable (based on ICNIRP general public limits [1] and [2])	59
Table 3 – Exposure metrics validity for evaluation points in each source region	73
Table 4 – Requirements for RF field strength and power density measurements	75
Table 5 – wbSAR exclusions based on RF power levels	76
Table 6 – Requirements for SAR measurements.....	76
Table 7 – Applicability of computation methods for source-environment regions of Figure 16.....	78
Table 8 – Requirements for computation methods.....	78
Table A.1 – Definition of source regions.....	88
Table A.2 – Default source region boundaries	88
Table A.3 – Source region boundaries for antennas with maximum dimension less than 2,5 λ	89
Table A.4 – Source region boundaries for linear/planar antenna arrays with a maximum dimension greater than or equal to 2,5 λ	89
Table A.5 – Source region boundaries for equiphase radiation aperture (e.g. dish) antennas with maximum reflector dimension much greater than a wavelength.....	90
Table A.6 – Source region boundaries for radiating cables.....	90
Table A.7 – Far-field distance r measured in metres as a function of angle β	92
Table A.8 – Guidance on selecting between computation and measurement approaches.....	92
Table A.9 – Guidance on selecting between broadband and frequency selective measurement.....	94
Table A.10 – Guidance on selecting RF field strength measurement procedures	95
Table A.11 – Guidance on selecting computation methods.....	96
Table A.12 – Guidance on specific evaluation method ranking	97
Table B.1 – Dimension variables	99
Table B.2 – RF power variables	99
Table B.3 – Antenna variables	100
Table B.4 – Exposure metric variables.....	100
Table B.5 – Broadband measurement system minimum requirements	113
Table B.6 – Frequency selective measurement system minimum requirements	114

Table B.7 – Example template for estimating the expanded uncertainty of an in-situ RF field strength measurement that used a frequency selective equipment.....	134
Table B.8 – Example template for estimating the expanded uncertainty of an in-situ RF field strength measurement that used a broadband equipment	135
Table B.9 – Example template for estimating the expanded uncertainty of a laboratory-based RF field strength or power density measurement using the surface scanning method.....	136
Table B.10 – Example template for estimating the expanded uncertainty of a laboratory-based RF field strength or power density measurement using the volume scanning method	137
Table B.11 – Numerical reference SAR values for reference dipoles and flat phantom – All values are normalized to a forward power of 1 W	142
Table B.12 – Phantom liquid volume and measurement volume used for wbSAR measurements [61], [77].....	145
Table B.13 – Correction factor to compensate for a possible bias in the obtained general public wbSAR when assessed using the large box-shaped phantom for child exposure configurations [72].....	145
Table B.14 – Measurement uncertainty evaluation template for EUT wbSAR test	146
Table B.15 – Measurement uncertainty evaluation template for wbSAR system validation.....	147
Table B.16 – Definition of boundaries for selecting the zone of computation	151
Table B.17 – Input parameters for cylindrical and spherical formulas validation.....	154
Table B.18 – Applicability of SAR estimation formulas	156
Table B.19 – Calculation of $A(f, d)$	159
Table B.20 – Antenna parameters for SAR estimation formulas verification	161
Table B.21 – Verification data for SAR estimation formulas - front	161
Table B.22 – Verification data for SAR estimation formulas – axial and back	161
Table B.23 – Example template for estimating the expanded uncertainty of a synthetic model and ray tracing RF field strength computation	170
Table B.24 – Synthetic model and ray tracing power density reference results	173
Table B.25 – Example template for estimating the expanded uncertainty of a full wave RF field strength / power density computation	178
Table B.26 – Validation 1 full wave field reference results.....	180
Table B.27 – Validation 2 full wave field reference results.....	181
Table B.28 – Example template for estimating the expanded uncertainty of a full wave SAR computation.....	185
Table B.29 – Validation reference SAR results for computation method.....	187
Table B.30 – Relevant parameters for performing RF exposure modelling studies of a massive MIMO site or site cluster	197
Table B.31 – Measurement campaign parameters for performing RF exposure assessment of a massive MIMO site or site cluster	199
Table B.32 – Power combination factors applicable to the normalized actual transmitted power CDF in case of combination of multiple independent identical transmitters	201
Table B.33 – Power combination factors applicable to two independent transmitters with a ratio p in amplitude.....	202
Table C.1 – Example of relative difference between the measured averaged transmitted power and actual power counter value for systems that allow direct power level measurements.....	206

Table C.2 – Example of correlation between the configured maximum power level and the level reported by actual power counters for BS that allow direct power level measurements	207
Table C.3 – Example of correlation between the configured time-averaged load levels and the actual power counter value for systems that allow direct power level measurements	207
Table C.4 – Example of relative difference between the configured maximum power, measured averaged transmitted power, and actual power counters for systems that do not support direct power level measurements	209
Table C.5 – Example of correlation between the configured power level and the level reported by power counters for BS that do not support direct power level measurements	210
Table C.6 – Example of correlation between time linearity of the configured maximum power level and the level reported by actual power counters for BS that do not support direct power level measurements	211
Table E.1 – Technology-specific information	237
Table E.2 – Example of spectrum analyser settings for an integration per service	242
Table E.3 – Example constant power components for specific TDMA/FDMA technologies	243
Table E.4 – WCDMA decoder characteristics	245
Table E.5 – Signal configurations	245
Table E.6 – WCDMA generator setting for power linearity	246
Table E.7 – WCDMA generator setting for decoder calibration	246
Table E.8 – WCDMA generator setting for reflection coefficient measurement	247
Table E.9 – Uplink-downlink configurations	254
Table E.10 – Theoretical extrapolation factor, N_{RS} , based on frame structure given in 3GPP TS 36.104 [21]	256
Table E.11 – F_{BW} for each combination of BS channel bandwidth and SSB subcarrier spacing (SCS) for sub-6 GHz signals	262
Table E.12 – F_{BW} for each combination of BS channel bandwidth and SSB subcarrier spacing (SCS) for mm-wave signals	262
Table E.13 – List of variables in the case study	287
Table F.1 – Brief exposure limits for the general public integrated over intervals of between 0 min and 6 min as specified by ICNIRP-2020 [1]	292
Table F.2 – Minimum F_{PR} , F_{PR_min} , for which compliance with the time-averaged whole-body limits ICNIRP-2020 [1] inherently ensures compliance with the brief exposure limits specified by ICNIRP-2020 [1]	297
Table G.1 – Determining target uncertainty	302
Table G.2 – Monte Carlo simulation of 10 000 trials, both surveyor and auditor using best estimate	304
Table G.3 – Monte Carlo simulation of 10 000 trials, both surveyor and auditor using target uncertainty of 4 dB	304
Table G.4 – Monte Carlo simulation of 10 000 trials where surveyor uses upper 95 % CI and auditor uses lower 95 % CI	305
Table G.5 – Guidance on minimum separation distances for some dipole lengths such that the uncertainty does not exceed 5 % or 10 % in a measurement of E	313
Table G.6 – Guidance on minimum separation distances for some loop diameters such that the uncertainty does not exceed 5 % or 10 % in a measurement of H	313

Table G.7 – Example minimum separation conditions for selected dipole lengths for 10 % uncertainty in E	314
Table G.8 – Standard estimates of dB variation for the perturbations in front of a surveyor due to body reflected fields as described in Figure G.5	316
Table G.9 – Standard uncertainty (u) estimates for E and H due to body reflections from the surveyor for common radio services derived from estimates provided in Table G.8	316
Table G.10 – Maximum sensitivity coefficients for liquid permittivity and conductivity over the frequency range 300 MHz to 6 GHz for various SAR measurement procedures	323
Table G.11 – Uncertainty at 95 % for different fading models	326
Table G.12 – Correlation coefficients for GSM 900 and DCS 1800	328
Table G.13 – Variations of the standard deviations for the GSM 900, DCS 1800 and UMTS frequency bands	329
Table G.14 – Examples of total uncertainty calculation	330
Table G.15 – Maximum simulated error due to the influence of a human body on the measurement values of an omnidirectional probe	332
Table G.16 – Measured influence of a human body on omnidirectional probe measurements	332

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**DETERMINATION OF RF FIELD STRENGTH, POWER DENSITY
AND SAR IN THE VICINITY OF BASE STATIONS FOR
THE PURPOSE OF EVALUATING HUMAN EXPOSURE**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62232 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2022. It includes corrections of obvious errors and text improvements on the third edition in order to bring more clarity in the description of the assessment methods and avoid misinterpretations. This edition has the same technical content as the third edition.

This document contains attached files that are cited in Figure B.30, G.4.4.3 and bibliography reference [67]. These files can be downloaded from <https://www.iec.ch/tc106/supportingdocuments>.

The text of this International Standard is based on the following documents:

Draft	Report on voting
106/626/CDV	106/672/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at http://www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at <http://www.iec.ch/standardsdev/publications>.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- amended.

INTRODUCTION

This document addresses the evaluation of RF field strength, power density and specific absorption rate (SAR) levels in the vicinity of base stations (BS), also called products or equipment under test (EUT), intentionally radiating in the radio frequency (RF) range 110 MHz to 300 GHz in accordance with the scope, see Clause 1. It does not address the evaluation of current density.

RF exposure evaluation methods to be used for product compliance, product installation compliance and in-situ RF exposure assessments are specified in this document. Exposure limits are not specified in this document. The entity conducting RF exposure assessments refers to the set of exposure limits applicable where exposure takes place. Examples of applicable exposure limits considered in this document are provided in the Bibliography, for example ICNIRP-2020 [1]¹, ICNIRP-1998 [2], IEEE Std C95.1™-2019 [3] and Safety Code 6 [4].

NOTE In this document, “ICNIRP” used without “-1998 or “-2020” applies to both [1] and [2].

This document is based on IEC 62232:2017 leveraging guidelines and lessons learned from the implementation guide IEC TR 62669:2019 [5]. In particular, it specifies how to implement the actual maximum approach. It also includes corrections of obvious errors and text improvements on IEC 62232:2022 in order to bring more clarity in the description of the assessment methods and avoid misinterpretations. It has the same technical content as IEC 62232:2022.

Clause 2, Clause 3 and Clause 4 address normative references, terms and definitions, symbols, and abbreviated terms, respectively.

Clause 5 provides advice on how to use this document, including a quick-start guide.

Clause 6 describes the three main application areas of this document: RF exposure evaluation methods for product compliance, product installation compliance, and in-situ RF exposure assessments. It includes the key requirements for assessing RF exposure based on using the actual maximum approach. It also includes simplified criteria for putting BS into operation. Further details are provided in Annex C, Annex D and Annex E.

Clause 7 provides guidelines on how to select the evaluation method. Further details are provided in Annex A.

Clause 8 specifies the RF exposure evaluation methods to be used and refers to further details in Annex B, Annex C, Annex F and Annex H.

Clause 9 addresses the estimation of uncertainty and refers to Annex G and Annex H for further details.

Clause 10 describes reporting requirements for the evaluation or assessment.

Annexes and the bibliography are referenced extensively to provide useful clarifications or guidance.

Additional guidance can be found in IEC TR 62669 [5], which includes a set of case studies providing practical examples of the application of this document.

¹ Numbers in square brackets refer to the Bibliography.

DETERMINATION OF RF FIELD STRENGTH, POWER DENSITY AND SAR IN THE VICINITY OF BASE STATIONS FOR THE PURPOSE OF EVALUATING HUMAN EXPOSURE

1 Scope

This document provides methods for the determination of RF field strength, power density and specific absorption rate (SAR) in the vicinity of base stations (BS) for the purpose of evaluating human exposure.

This document:

- a) considers intentionally radiating BS which transmit on one or more antennas using one or more frequencies in the range 110 MHz to 300 GHz;
- b) considers the impact of ambient sources on RF exposure at least in the 100 kHz to 300 GHz frequency range;
- c) specifies the methods to be used for RF exposure evaluation for compliance assessment applications, namely:
 - 1) product compliance – determination of compliance boundary information for a BS product before it is placed on the market;
 - 2) product installation compliance – determination of the total RF exposure levels in accessible areas from a BS product and other relevant sources before the product is put into operation;
 - 3) in-situ RF exposure assessment – measurement of in-situ RF exposure levels in the vicinity of a BS installation after the product has been taken into operation;
- d) specifies how to perform RF exposure assessment based on the actual maximum approach;
- e) describes several RF field strength, power density, and SAR measurement and computation methodologies with guidance on their applicability to address both the in-situ evaluation of installed BS and laboratory-based evaluations;
- f) describes how surveyors establish their specific evaluation procedures appropriate for their evaluation purpose;
- g) provides guidance on how to report, interpret and compare results from different evaluation methodologies and, where the evaluation purpose requires it, determine a justified decision against a limit value;
- h) provides methods for the RF exposure assessment of BS using time-varying beam-steering technologies such as new radio (NR) BS using massive multiple input multiple output (MIMO).

NOTE 1 Practical implementation case studies are provided as examples in the companion Technical Report IEC TR 62669 [5].

NOTE 2 Although the current BS product types have been specified to operate up to 200 GHz (see, for example, [6] and [7]), the upper frequency of 300 GHz is consistent with applicable exposure limits.

NOTE 3 The lower frequency considered for ambient sources, 100 kHz, is derived from ICNIRP-1998 [2] and ICNIRP-2020 [1]. However, some applicable exposure guidelines require ambient fields to be evaluated as low as 3 kHz, e.g. Safety Code 6 [4] and IEEE Std C95.1-2019 [3].

NOTE 4 Specification of appropriate RF exposure mitigation measures such as signage, access control, and training are beyond the scope of this document. It is possible to refer to the applicable regulations or recommended practices on these topics.

NOTE 5 While this document is based on the current international consensus about the best engineering practice for assessing the compliance of RF exposure with the applicable exposure limits, it is possible that national regulatory agencies specify different requirements. The entity conducting an RF exposure assessment needs to be aware of the applicable regulations.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC/IEEE 62209-1528, *Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures: Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-worn wireless communication devices (Frequency range of 4 MHz to 10 GHz)*

IEC 62209-3, *Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)*

IEC 62311, *Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz)*

IEC 62479, *Assessment of the compliance of low power electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (10 MHz – 300 GHz)*

IEC/IEEE 62704-1, *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz – Part 1: General requirements for using the finite difference time-domain (FDTD) method for SAR calculations*

IEC/IEEE 62704-2, *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz – Part 2: Specific requirements for finite difference time domain (FDTD) modelling of exposure from vehicle mounted antennas*

IEC/IEEE 62704-3, *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz – Part 3: Specific requirements for using the finite difference time domain (FDTD) method for SAR calculations of mobile phones*

IEC/IEEE 62704-4, *Recommended practise for determining the Peak Spatial Average Specific Absorption Rate (SAR) in the human body from wireless communications devices, 30 MHz – 6 GHz: General requirements for using the Finite-Element Method (FEM) for SAR calculations and specific requirements for modelling vehicle-mounted antennas and personal wireless devices*

IEC/IEEE 63195-1, *Measurement procedure for the assessment of power density of human exposure to radio frequency fields from wireless devices operating in close proximity to the head and body – Frequency range of 6 GHz to 300 GHz*

IEC/IEEE 63195-2, *Determining the power density of the electromagnetic field associated with human exposure to wireless devices operating in close proximity to the head and body using computational techniques, 6 GHz to 300 GHz*

koniec náhl'adu – text ďalej pokračuje v platenej verzii STN